

The diagram shows a circuit with a +BATT supply and a GND connection. A TP9 pin is connected to +BATT, and a TP8 pin is connected to GND. A red 'X' is drawn over the connection, indicating an error or a crossed connection.

FLASH_SS 2 1 BTN_SEL

Diagram of the Conn_01x05_Socket J7 pin connections:

- Pin 5: +3V3
- Pin 4: ANA_X
- Pin 3: ANA_SW
- Pin 2: ANA_Y
- Pin 1: GND

NB: X and Y are swapped because the analog stick is rotated by 90 deg

Diagram 2: Wiring for the second button (BTN_R). The button is connected to TP3 (BTN_R 3.3V) and TP4 (BTN_R). The common ground connection is to ND.

The schematic diagram illustrates the electrical connection between a microcontroller (MCU) and an SD card module. The MCU pins and their connections are as follows:

- SD_VDD**: Connected to the VDD pin (pin 4) of the SD card module and the VSS pin (pin 6) of the SD card module.
- SWCLK**: Connected to the CLK pin (pin 5) of the SD card module.
- SD_CS**: Connected to the DATA/CD pin (pin 2) of the SD card module.
- SPI_MOSI**: Connected to the DAT2 pin (pin 1) of the SD card module.
- SPI_SCK**: Connected to the CMD pin (pin 3) of the SD card module.
- SPI_MISO**: Connected to the DAT0 pin (pin 7) of the SD card module.
- SWD**: Connected to the DAT1 pin (pin 8) of the SD card module.
- SD_DET**: Connected to the DET pin (pin 9) of the SD card module.
- GND**: Connected to the SHIELD pin (pin 10) of the SD card module.

The SD card module is labeled **Micro_SD_Card_Det1** and **J2**. The resistors **R13**, **R14**, and **R15** are all 10kΩ.

NB: Pulling SD_DET_MCU hi powers down the SD card
 Making SD_DET_MCU hi-z powers up the SD card
 (This way you can reset an already inserted card)

Pinout diagram for LCD_SPL_MOSI_MCU showing connections for a 32-pin connector. The diagram shows a green wire connected to pins 1, 5, 9, 13, 17, 21, 25, 29, and 33. A red wire is connected to pins 2, 6, 10, 14, 18, 22, 26, 30, 34, and 38. A blue wire is connected to pins 3, 7, 11, 15, 19, 23, 27, 31, 35, and 39. A yellow wire is connected to pins 4, 8, 12, 16, 20, 24, 28, 32, 36, and 40. A black wire is connected to pins 37, 38, 39, and 40. The diagram also shows a GND symbol at the bottom left.

Pin	Signal
1	LCD_R5
2	LCD_R4
3	LCD_R3
4	LCD_R2
5	LCD_R1
6	LCD_G5
7	LCD_G4
8	LCD_G3
9	LCD_G2
10	LCD_G1
11	LCD_G0
12	LCD_B5
13	LCD_B4
14	LCD_B3
15	LCD_B2
16	LCD_B1
17	LCD_HS
18	LCD_VS
19	LCD_DE
20	LCD_PCLK
21	LCD_CS
22	SPI_SCK
23	LCD_SPL_MOSI
24	LCD_RST
25	LED_K
26	LED_K
27	LED_A
28	LED_A
29	LED_A
30	LED_A
31	LED_A
32	LED_A
33	LED_A
34	LED_A
35	LED_A
36	LED_A
37	LED_A
38	LED_A
39	LED_A
40	LED_A

GND

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

32

31

30

29

28

27

26

25

The diagram shows the following connections:

- LED_A** (green wire) is connected to **GND/TP11**.
- LED_K** (blue wire) is connected to **+3V3/TP12 (3.3V)**.
- ANA_Y** (green wire) is connected to **+5V/TP7 (5V)**.
- ANA_X** (blue wire) is connected to **+5V/TP7 (5V)**.

- H1 MountingHole
- H2 MountingHole