

Lab 11 Arrays (one dimension) I

Objective

- To practically familiarize student with the concept of array and related operations performed on array.

Current Lab Learning Outcomes (LLO)

By completion of the lab the students should be able to

1. understand the concept of arrays
2. create and access an array element, or a part of the array
3. enter elements to array and print its elements how a method may return a value
4. find maximum and minimum element in array
5. other operations on the array

Lab Requirements

NetBeans IDE 8.0.1 or higher


Lab Assessment/Activities

Practice Activity with Lab Instructor (10 minutes)

(Reverse the numbers entered) Write a program that reads ten integers and displays them in the reverse of the order in which they were read.

Solution:

1. Open NetBeans and create a new project
2. Create a new java main class and write its name as **ReverseEnteredNumbers**
3. Write the following code inside the class, Figure (1).



```
1 import java.util.Scanner;
2 public class ReverseEnteredNumbers {
3     public static void main(String[] args) {
4         Scanner input = new Scanner(System.in);
5         int[] numbers = new int[10];
6         System.out.print("Enter " + numbers.length + " integer numbers: ");
7         for (int i = 0; i < numbers.length; i++) {
8             numbers[i] = input.nextInt();
9         }
10
11         System.out.print("\nThe reverse of entered numbers : ");
12         for (int i = numbers.length-1; i >= 0; i--) {
13             System.out.print(numbers[i] + " ");
14         }
15         System.out.println("");
16     }
17 }
18
```

Output - LabManualsprogramms (run) x

run:
Enter 10 integer numbers: 10 20 25 30 40 45 55 60 70 80

The reverse of entered numbers : 80 70 60 55 45 40 30 25 20 10

BUILD SUCCESSFUL (total time: 4 seconds)

Figure 1: The program to read 10 numbers and displays them in reverse order

Short Exercise (5 minutes)

(Display even numbers) Rewrite the above program to display the even numbers.

Individual Activities: (60 minutes)

1. **(Analyze scores)** Write a program that reads an unspecified number of scores and determines how many scores are above or equal to the average and how many scores are below the average. Enter a negative number to signify the end of the input. Assume that the maximum number of scores is 100.
2. **(Count single digits)** Write a program that generates 100 random integers between 0 and 9 and displays the count for each number. (Hint: Use an array of ten integers, say counts, to store the counts for the number of 0s, 1s, ..., 9s.)
3. **(Assign grades)** Write a program that reads student scores, gets the best score, and then assigns grades based on the following scheme:
Grade is A if score is $\geq$ best - 10
Grade is B if score is $\geq$ best - 20;
Grade is C if score is $\geq$ best - 30;
Grade is D if score is $\geq$ best - 40;
Grade is F otherwise.

The program prompts the user to enter the total number of students, then prompts the user to enter all of the scores, and concludes by displaying the grades. Here is a sample run:

```
Enter the number of students: 4 Enter
Enter 4 scores: 40 55 70 58 Enter
Student 0 score is 40 and grade is C
Student 1 score is 55 and grade is B
Student 2 score is 70 and grade is A
Student 3 score is 58 and grade is B
```

4. **(Print distinct numbers)** Write a program that reads in ten numbers and displays the number of distinct numbers and the distinct numbers separated by exactly one space (i.e., if a number appears multiple times, it is displayed only once). (Hint: Read a number and store it to an array if it is new. If the number is already in the array, ignore it.) After the input, the array contains the distinct numbers. Here is the sample run of the program:

```
Enter ten numbers: 1 2 3 2 1 6 3 4 5 2 Enter
The number of distinct number is 6
The distinct numbers are: 1 2 3 6 4 5
```

5. (**Strictly Identical arrays**) The arrays `list1` and `list2` are strictly identical if their corresponding elements are equal. Write a program that prompts the user to enter two lists of integers and displays whether the two are strictly identical. Here are the sample runs. Note that the first number in the input indicates the number of the elements in the list. This number is not part of the list.

```
Enter list1: 5 2 5 6 1 6 → Enter
Enter list2: 5 2 5 6 1 6 → Enter
Two lists are strictly identical
```

```
Enter list1: 5 2 5 6 6 1 → Enter
Enter list2: 5 2 5 6 1 6 → Enter
Two lists are not strictly identical
```

Lab Description

An array is a collection of data values of the same data type.

Array declaration

To use an array in a program, you must declare it.

Syntax: `dataType [] arrayName;` Or `dataType arrayName [];`

`dataType`: can be any data type

Example: `double [] studentsMarks;` or `double studentsMarks[];`

Array Creation

Array declaration does not create an array. So you must create the array using `new` operator.

Syntax: `arrayName= new dataType[arraySize]`

Example: `studentsMarks=new double[20];`

You can declare and create an array in one step.

Syntax: `dataType [] arrayName= new dataType[arraySize];` Or

`dataType arrayName[]= new dataType[arraySize];`

Example: `double []studentsMarks=new double[20];` Or

`double studentsMarks[]=new double[20];`

The array `studentsMarks` has **20** elements of `double` type. The elements are saved from index 0 to index 19.

You can get the size of array using the following syntax: `arrayName.length`;

Example: `studentsMarks.length`; // return 20

Accessing array elements

Array elements are accessed through their index. First index is **0** and the last index is

`arrayName.length-1`

Array Initialization

Java has a shorthand notation known as the array initializer which allows you to declare, create and initialize the array in one step.

Syntax: `dataType [] arrayName= {value0, value1, .....valuek};`

Example `double []studentsMarks= {90.0,85.5,88.5,95.0};`

Reading array elements

The following code use to read array elements:

```
System.out.println("Enter  "+ arrayName.length + " values");
for(iint var=0;var<arrayName.length;var++)
{
    System.out.print("Enter value  "+(var+1)+" :  ");
    arrayName[var]=scannerName.nextMethod();
}
```

`nextMethod()` : any methods used in previous labs. {`next()`, `nextInt()`,} based on the data type of the array.

Displaying array elements

The following code use to display array elements:

```
System.out.println("The values of array are as follows");
System.out.println("-----");
for(iint var=0;var<arrayName.length;var++)
{
    System.out.println(arrayName[var]);
}
```

Extra (supplementary) Materials (if any)

None
