

COMP3231/9201/3891/9283 **Operating Systems 2021/T1**

UNSW

Administration

- Notices
- Course Outline
- UNSW Timetable
- Consultations
- Survey Results!!

Work

- Lectures
- Tutorials

Support

- Ed Forums
- Wiki

Assignments

- Submission Guide
- Assignment 0 Warm-up

Resources **OS/161**

- General
- Man Pages
- Sys161 Pages

C coding

- Info Sheet

Debugging

- Learn Debugging

General

- "Hardware" Guide
- R3000 Reference Manual
- Intro. to Prog. Threads

Previous years

- 2020 T2
- 2020 T1
- 2019 T1

Tutorial Week 9

Questions

Assignment 3 Exercises

By now you should be familiar enough with navigating the kernel source that you can find the answers to the questions below by yourself (Hint: use a source code browser or the grep utility). You may also find the MIPS r3000 reference useful.

- 1. What is the difference between the different MIPS address space segments? What is the use of each segment?
- 2. What functions exist to help you manage the TLB? Describe their use. (Hint: look in kern/arch/mips/include/tlb.h)
- 3. What macros are used to convert from a physical address to a kernel virtual address?
- 4. What address should the initial user stack pointer be?
- 5. What are the entryli and entrylo co-processor registers? Describe their contents.
- 6. What do the as * functions do? Why do we need as prepare load() and as complete load()?
- 7. What does vm fault() do? When is it called?
- 8. Assuming a 2-level hierarchical page table (4k pages), show for the following virtual addresses:
 - 1. The page number and offset;
 - 2. the translated address (after any page allocation); and
 - 3. the contents of the page table after the TLB miss.

Staff

- Kevin Elphinstone (LiC)
- TBD (Admin)

Grievances

- Student Reps



The page table is initially empty, with no L2 pages. You may assume that the allocator returns frames in order, so that the first frame allocated is frame 1, then frames 2, 3, 4, etc.

- o 0x100008
- o 0x101008
- o 0x1000f0
- o 0x41000
- o 0x41b00
- o 0x410000

C bitwise operations refresher

Given the following constants from the source code:

And a 32-bit page table entry and 32-bit virtual address is defined as

```
uint32_t pte;
vaddr t vaddr;
```

- 9. What C expressions would you use to set or reset the valid bit in a page table entry?
- 10. What C expression would you use to test if the valid bit is set?
- 11. How would you extract the 12-bit offset (bits 0 11) from the virtual address?
- 12. How would you convert the 10 most significant bits (22–31) of a virtual address into an index?
- 13. How would you convert the next 10 most significant bits (12–21) into an index?
- 14. How would you round down a virtual address to the base of the page?

Page last modified: 4:49pm on Saturday, 23rd of May, 2020

Print Version

CRICOS Provider Number: 00098G