Computer Networks and Applications

COMP 3331/COMP 9331

Week 4

Transport Layer Part 1

Reading Guide:
Chapter 3, Sections 3.1 – 3.4

Transport Layer

our goals:

- understand principles behind transport layer services:
  - multiplexing, demultiplexing
  - reliable data transfer
  - flow control
  - congestion control
- learn about Internet transport layer protocols:
  - UDP: connectionless transport
  - TCP: connection-oriented reliable transport

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP
- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

Transport layer

- Moving "down" a layer

- Current perspective:
  - Application is the boss….
  - Usually executing within the OS Kernel
  - The network layer is ours to command !!



Network layer (context)

- What it does: finds paths through network
  - Routing from one end host to another

- What it doesn't:
  - Reliable transfer: "best effort delivery"
  - Guarantee paths
  - Arbitrate transfer rates

- For now, think of the network layer as giving us an "API" with one function: *sendtohost(data, host)*
  - Promise: the data will go to that (usually!!)

Transport services and protocols

- provide *logical communication* between app processes running on different hosts
- transport protocols run in end systems
  - send side: breaks app messages into *segments*, passes to network layer
  - rcv side: reassembles segments into messages, passes to app layer
  - Exports services to application that network layer does not provide



Why a transport layer?



Why a transport layer?



Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP

- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

Multiplexing/demultiplexing

multiplexing at sender:
handle data from multiple sockets, add transport header (later used for demultiplexing)

demultiplexing at receiver:
use header info to deliver received segments to correct socket



Note: The network is a shared resource. It does not care about your applications, sockets, etc.

Connectionless demultiplexing

- *recall:* created socket has host-local port #:

```
DatagramSocket mySocket1
= new DatagramSocket(12534);
```

- *recall:* when creating datagram to send into UDP socket, must specify
  - destination IP address
  - destination port #

- when host receives UDP segment:
  - checks destination port # in segment
  - directs UDP segment to socket with that port #

→ IP datagrams with *same dest. port #,* but different source IP addresses and/or source port numbers will be directed to *same socket* at dest

Connectionless demux: example



Connection-oriented demux

- TCP socket identified by 4-tuple:
  - source IP address
  - source port number
  - dest IP address
  - dest port number
- demux: receiver uses all four values to direct segment to appropriate socket
- server host may support many simultaneous TCP sockets:
  - each socket identified by its own 4-tuple
- web servers have different sockets for each connecting client
  - non-persistent HTTP will have different socket for each request

Revisiting TCP Sockets



Connection-oriented demux: example



three segments, all destined to IP address: B,
dest port: 80 are demultiplexed to *different* sockets

May I scan your ports?

http://netsecurity.about.com/cs/hackertools/a/aa121303.htm

- Servers wait at open ports for client requests
- Hackers often perform *port scans* to determine open, closed and unreachable ports on candidate victims
- Several ports are well-known
  - <1024 are reserved for well-known apps
  - Other apps also use known ports
    - MS SQL server uses port 1434 (udp)
    - Sun Network File System (NFS) 2049 (tcp/udp)
- Hackers can exploit known flaws with these known apps
  - Example: Slammer worm exploited buffer overflow flaw in the SQL server
- How do you scan ports?
  - Nmap, Superscan, etc

http://www.auditmypc.com/

https://www.grc.com/shieldsup

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP
- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

UDP: User Datagram Protocol [RFC 768]

- "no frills," "bare bones" Internet transport protocol
- "best effort" service, UDP segments may be:
  - lost
  - delivered out-of-order to app

- *connectionless:*
  - no handshaking between UDP sender, receiver
  - each UDP segment handled independently of others

UDP: segment header



UDP segment format

why is there a UDP?

- no connection establishment (which can add delay)
- simple: no connection state at sender, receiver
- small header size
- no congestion control: UDP can blast away as fast as desired

UDP checksum

- *Goal:* detect "errors" (e.g., flipped bits) in transmitted segment
  - Router memory errors
  - Driver bugs
  - Electromagnetic interference

sender:

- treat segment contents, including header fields, as sequence of 16-bit integers
- checksum: addition (one's complement sum) of segment contents
- sender puts checksum value into UDP checksum field

receiver:

- Add all the received bits together as 16-bit integers
- Add that to the checksum
- If the result is not 1111 1111 1111 1111, there are errors !

Internet checksum: example

example: add two 16-bit integers

	1 1 1 0 0 1 1 0 0 1 1 0 0 1 1 0
	1 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1
wraparound	1 1 0 1 1 1 0 1 1 1 0 1 1 1 0 1 1
	+1
sum	1 0 1 1 1 0 1 1 1 0 1 1 1 1 0 0
checksum	0 1 0 0 0 1 0 0 0 1 0 0 0 0 1 1

1's complement

Checksum is 1's complement of *sum*

Note: when adding numbers, a carryout from the most significant bit needs to be added to the result (wraparound)

UDP Applications

- Latency sensitive/time critical
  - Quick request/response (DNS, DHCP)
  - Network management (SNMP)
  - Routing updates (RIP)
  - Voice/video chat
  - Gaming (especially FPS)

- Error correction unnecessary (periodic messages)

QUIC: Quick UDP Internet Connections
A Google Experiment

Outside the scope of exams

- Core idea: HTTP/2 over UDP
  - Faster connection establishment
  - Overcomes HoL blocking due to lost packets
  - Improved congestion control
  - Forward error correction
  - Connection migration



https://www.chromium.org/quic

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP
- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

Reliable Transport

- In a perfect world, reliable transport is easy
- All the bad things best-effort can do
  - a packet is corrupted (bit errors)
  - a packet is lost (*why?*)
  - a packet is delayed (*why?*)
  - packets are reordered (*why?*)
  - a packet is duplicated (*why?*)

The Two Generals Problem



- Two army divisions (blue) surround enemy (red)
  - Each division led by a general
  - Both must agree when to simultaneously attack
  - If either side attacks alone, defeat
- Generals can only communicate via messengers
  - Messengers may get captured (unreliable channel)

The Two Generals Problem



- How to coordinate?
  - Send messenger: “Attack at dawn”
  - What if messenger doesn’t make it?

The Two Generals Problem



- How to be sure messenger made it?
  - Send acknowledgement: “We received message”

Principles of reliable data transfer

- important in application, transport, link layers
  - top-10 list of important networking topics!



No bits are corrupted, lost or arrive out-of-order at the receiver

(a) provided service

- characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

Principles of reliable data transfer

- important in application, transport, link layers
  - top-10 list of important networking topics!



- characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

Principles of reliable data transfer

- important in application, transport, link layers
  - top-10 list of important networking topics!



- characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

Reliable data transfer: getting started

We' ll:

- Incrementally develop sender, receiver sides of reliable data transfer protocol (rdt)
- Consider only unidirectional data transfer
  - but control info will flow on both directions!
- Channel will not re-order packets

rdt1.0: reliable transfer over a reliable channel

- Underlying channel perfectly reliable
  - no bit errors
  - no loss of packets
- Transport layer does nothing !

Global Picture of rdt1.0



Solid line: error-free transmission

rdt2.0: channel with bit errors

- underlying channel may flip bits in packet
  - checksum to detect bit errors
- *the* question: how to recover from errors:

How do humans recover from "errors"
during conversation?

rdt2.0: channel with bit errors

- underlying channel may flip bits in packet
  - checksum to detect bit errors
- *the* question: how to recover from errors:
  - *acknowledgements (ACKs):* receiver explicitly tells sender that pkt received OK
  - *negative acknowledgements (NAKs):* receiver explicitly tells sender that pkt had errors
  - sender retransmits pkt on receipt of NAK
- new mechanisms in **`rdt2.0`** (beyond **`rdt1.0`**):
  - error detection
  - feedback: control msgs (ACK,NAK) from receiver to sender
  - retransmission

Global Picture of rdt2.0



Dotted line: erroneous transmission
Solid line: error-free transmission

rdt2.0 has a fatal flaw!

what happens if ACK/NAK corrupted?

- sender doesn't know what happened at receiver!
- can't just retransmit: possible duplicate

handling duplicates:

- sender retransmits current pkt if ACK/NAK corrupted
- sender adds *sequence number* to each pkt
- receiver discards (doesn't deliver up) duplicate pkt

stop and wait

sender sends one packet, then waits for receiver response

rdt2.1: discussion

sender:

- seq # added to pkt
- two seq. #'s (0,1) will suffice. Why?
- must check if received ACK/NAK corrupted
- twice as many states
  - state must "remember" whether "expected" pkt should have seq # of 0 or 1

receiver:

- must check if received packet is duplicate
  - state indicates whether 0 or 1 is expected pkt seq #
- note: receiver can *not* know if its last ACK/NAK received OK at sender

New Measures: Sequence Numbers, Checksum for ACK/NACK, Duplicate detection

Another Look at rdt2.1

Dotted line: erroneous transmission
Solid line: error-free transmission



rdt2.2: a NAK-free protocol

- same functionality as rdt2.1, using ACKs only
- instead of NAK, receiver sends ACK for last pkt received OK
  - receiver must *explicitly* include seq # of pkt being ACKed
- duplicate ACK at sender results in same action as NAK: *retransmit current pkt*

rdt2.2: Example

Dotted line: erroneous transmission
Solid line: error-free transmission



rdt3.0: channels with errors *and* loss

new assumption: underlying channel can also loose packets (data, ACKs)

- checksum, seq. #, ACKs, retransmissions will be of help … but not enough

approach: sender waits "reasonable" amount of time for ACK

- retransmits if no ACK received in this time
- if pkt (or ACK) just delayed (not lost):
  - retransmission will be duplicate, but seq. #'s already handles this
  - receiver must specify seq # of pkt being ACKed
- requires countdown timer

rdt3.0 in action



(a) no loss



(b) packet loss

rdt3.0 in action



(c) ACK loss



(d) premature timeout/ delayed ACK

rdt3.0: stop-and-wait operation



$$U_{sender} = \frac{L / R}{RTT + L / R}$$

Performance of rdt3.0

- rdt3.0 is correct, but performance stinks
- e.g.: 1 Gbps link, 8000 bit packet and 30msec RTT:

$$D_{trans} = \frac{L}{R} = \frac{8000 \text{ bits}}{10^9 \text{ bits/sec}} = 8 \text{ microsecs}$$

- U_{sender}: *utilization* – fraction of time sender busy sending

$$U_{sender} = \frac{L / R}{RTT + L / R} = \frac{.008}{30.008} = 0.00027$$

- RTT=30 msec, 1KB pkt every 30.008 msec: 33kB/sec thruput over 1 Gbps link

- Network protocol limits use of physical resources!

Pipelined protocols

pipelining: sender allows multiple, “in-flight”, yet-to-be-acknowledged pkts

- range of sequence numbers must be increased
- buffering at sender and/or receiver



(a) a stop-and-wait protocol in operation (b) a pipelined protocol in operation

- two generic forms of pipelined (sliding window) protocols: *go-Back-N, selective repeat*

Pipelining: increased utilization



3-packet pipelining increases utilization by a factor of 3!

$$U_{sender} = \frac{3L / R}{RTT + L / R}$$

Pipelined protocols: overview

Go-Back-N:

- Sender can have up to N unacked packets in pipeline
- Sender has single timer for oldest unacked packet, when timer expires, retransmit *all* unacked packets
- There is no buffer available at Receiver, out of order packets are discarded
- Receiver only sends *cumulative ack,* doesn't ack new packet if there's a gap

Selective Repeat:

- Sender can have up to N unacked packets in pipeline
- Sender maintains timer for each unacked packet, when timer expires, retransmit only that unacked packet
- Receiver has buffer, can accept out of order packets
- Receiver sends *individual ack* for each packet

Go-Back-N: sender

- k-bit seq # in pkt header
- "window" of up to N, consecutive unack'ed pkts allowed



- ACK(n): ACKs all pkts up to, including seq # n - *"cumulative ACK"*
  - may receive duplicate ACKs (see receiver)
- timer for oldest in-flight pkt
- *timeout(n):* retransmit packet n and all higher seq # pkts in window

Applets: http://media.pearsoncmg.com/aw/aw_kurose_network_2/applets/go-back-n/go-back-n.html
http://www.ccs-labs.org/teaching/rn/animations/gbn_sr/

GBN in action

GBN Window size restrictions:
Receiver Window Size = 1
Sender Window Size (N) < 2^m (why not 2^m)Hint: what if all ACKs are lost!
m is the number of bits in sequence number field
i.e., sequence number space = 0 to (2^m-1)



Selective repeat

- receiver *individually* acknowledges all correctly received pkts
  - buffers pkts, as needed, for eventual in-order delivery to upper layer
- sender only resends pkts for which ACK not received
  - sender timer for each unACKed pkt
- sender window
  - *N* consecutive seq #'s
  - limits seq #s of sent, unACKed pkts

Applet: http://media.pearsoncmg.com/aw/aw_kurose_network_3/applets/SelectRepeat/SR.html

Selective repeat: sender, receiver windows



(a) sender view of sequence numbers



(b) receiver view of sequence numbers

Selective repeat

sender

data from above:

- if next available seq # in window, send pkt

timeout(n):

- resend pkt n, restart timer

ACK(n) in [sendbase,sendbase+N]:

- mark pkt n as received
- if n smallest unACKed pkt, advance window base to next unACKed seq #

receiver

pkt n in [rcvbase, rcvbase+N-1]

- send ACK(n)
- out-of-order: buffer
- in-order: deliver (also deliver buffered, in-order pkts), advance window to next not-yet-received pkt

pkt n in [rcvbase-N,rcvbase-1]

- ACK(n)

otherwise:

- ignore

Selective repeat in action



SR sender window size = receiver window size <=(2^{m-1})

Selective repeat: dilemma

example:

- seq #'s: 0, 1, 2, 3
- window size=3
- receiver sees no difference in two scenarios!
- duplicate data accepted as new in (b)

Q: what relationship between seq # size and window size to avoid problem in (b)?

A: Sender window size <= ½ of Sequence number space



receiver can't see sender side.
receiver behavior identical in both cases!
something's (very) wrong!



Recap: components of a solution

- Checksums (for error detection)
- Timers (for loss detection)
- Acknowledgments
  - cumulative
  - selective
- Sequence numbers (duplicates, windows)
- Sliding Windows (for efficiency)

- Reliability protocols use the above to decide when and what to retransmit or acknowledge

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP

- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control