

Resources / Lab Exercises (/COMP3331/20T2/resources/44913)

/ Lab Exercise 2: HTTP & Socket Programming

Lab Exercise 2: HTTP & Socket Programming

[Specification](#)[Make Submission](#)[Check Submission](#)[Collect Submission](#)

There are 6 labs during this course. For each student, the 5 best performing labs will contribute to your final lab mark.

Objectives:

- Gain insights into operation of HTTP
- Get familiar with the basic socket programming
- Preparation for programming assignment

Prerequisites:

- Week 2 Lectures
- Relevant Parts of Chapter 2 of the textbook (Sections 2.2 on HTTP and 2.7 on Socket Programming)
- Basic understanding of Linux. A good resource is here (<http://www.ee.surrey.ac.uk/Teaching/Unix/>) but there are several other resources online
- Several socket programming resources and sample codes for all 3 programming languages are available at this page (<https://webcms3.cse.unsw.edu.au/COMP3331/20T2/resources/45218>)
- PingServer.java (<https://webcms3.cse.unsw.edu.au/COMP3331/20T2/resources/45189>)
- http-wireshark-trace-1 (<https://webcms3.cse.unsw.edu.au/COMP3331/20T2/resources/45203>)
- http-wireshark-trace-2 (<https://webcms3.cse.unsw.edu.au/COMP3331/20T2/resources/45188>)

Marks: 10 marks

- This lab comprises of a number of exercises. Pl note that not all the exercises for this lab are marked. You have to submit a report containing answers to selected exercises only.
- Please attend the lab in your allocated lab time slot.
- We expect the students to go through as much of the lab exercises as they can at home and come to the lab for clarifying any doubts in procedure/specifications.

Deadline:

09:45 am Tuesday 23/06/2020 . You can submit as many times as you wish before the deadline. A later submission will override the earlier submission, so make sure you submit the correct file. Do not leave until the last moment to submit, as there may be technical or communications error and you will not have time to

rectify it.

Late Report Submission Penalty:

Late penalty will be applied as follows:

- 1 day after deadline: 20% reduction
- 2 days after deadline: 40% reduction
- 3 or more days late: NOT accepted

Note that the above penalty is applied to your final mark in report. For example, if you submit your lab report 2 days late and your score on the lab is 8, then your final mark will be $8 - 3.2$ (40% penalty) = 4.8.

Submission Instructions:

Submit a PDF document Lab2.pdf with answers to Exercises 3, 4 and 5. Your client should be named PingClient.c or PingClient.java or PingClient.py. Create a tar archive of all the files (e.g. if you have additional header or helper files) called **Lab2.tar**. Submit the archive using give. You can submit from a lab machine or ssh into the CSE login server. Instructions to ssh into CSE login servers are here (https://taggi.cse.unsw.edu.au/FAQ/Logging_In_With_SSH/) . Max file size for submission is **3MB** .

IMPORTANT: IF YOU ARE USING PYTHON THEN PLEASE ADD A COMMENT AT THE TOP OF YOUR CODE TO INDICATE THE CORRECT VERSION OF PYTHON. THIS WILL ALLOW US TO USE THIS VERSION OF PYTHON FOR TESTING YOUR CODE.

Original Work Only:

You are strongly encouraged to discuss the questions with other students in your lab. However, each student must submit his or her own work. You may need to refer to the material indicated above (particularly socket programming links) and also conduct your own research to answer the questions.

System Compatibility (Very Important):

We will test your code on CSE machines via the command line interface. Note that CSE machines support the following: **gcc version 8.2, Java 11, Python 2.7 and 3.7**. It is thus imperative that you test your code on CSE machines before submitting. This is particularly important if you write your code on your own machine and use an IDE. You **MUST** test your code on CSE machines (via command line) before submitting. If we cannot get your code to work on CSE machines, then we can't mark it and unfortunately you won't receive any marks. This point is also relevant for the assignment.

Exercise 1: Using Telnet to interact with a Web Server (Unmarked, not to be included in report)

Follow the steps described below. You will notice certain questions as you attempt the exercise. Write down the answers and discuss them with your lab partner to enable him/her to assess your performance. If you have any questions or are experiencing difficulty with executing the lab please consult your tutor.

Step 1: Open an *xterm* window. Enlarge the size of your *xterm* window so that it is reasonably large and covers almost the entire screen.

Step 2: Telnet to the vision.ucla.edu web server by typing:

```
$ telnet vision.ucla.edu 80
```

Note that the port number for all web servers is "80".

Step 3: Retrieve the main webpage by typing:

GET / HTTP/1.1

host: www.vision.ucla.edu (http://www.vision.ucla.edu)

Important Note : You will have to press the carriage return twice after typing the last line.

Question 1: What is the content type of the response? What is the size of the response? When was the webpage last modified? Do you see an "Accept-Ranges" header field? What may this be used for?

Step 4: Now execute the HEAD method. When a server receives a request with the HEAD method, it responds with only the message header lines (i.e. the response to the GET method minus the actual requested object).

HEAD / HTTP/1.1

host: www.vision.ucla.edu (http://www.vision.ucla.edu)

Question 2: What is the content type of the response? What is the size of the response?

Question 3: Using telnet, find a way to get the people.html webpage from vision.ucla.edu

Question 4: Why is there the need to include the host in the GET (and HEAD) HTTP 1.1 request messages?

Exercise 2: Understanding Internet Cookies (unmarked, not to be included in the report)

Question 1. Repeat steps 1-3 in the previous experiment for www.google.com.au (http://www.google.com.au) . Does the site set a cookie in your browser? How can you tell by purely examining the HTTP response message received using telnet? How about www.vision.ucla.edu? Do you think this site will set a cookie in your browser?

Question 2. Open a web browser (Firefox/IceWeasel/Mozilla preferred). Go to the browser preferences and remove all existing cookies. Open the google webpage and then view the cookies. How many cookies are stored on your machine? Which sites installed the cookies?

Question 3. Repeat the above steps for the vision.ucla.edu website. How many cookies are stored on your machine? Which sites installed the cookies? Is the answer inconsistent with the answer for Question 1? Explain why.

Exercise 3: Using Wireshark to understand basic HTTP request/response messages (marked, include in your report)

We will not be running Wireshark on a live network connection (You are strongly encouraged to try this on your own machine. Pointers provided at the end of this exercise). The CSE network administrators do not permit live traffic monitoring for security reasons. Instead, for all our lab exercises we will make use of several trace files, which were collected by running Wireshark by one of the textbook's authors. For this particular experiment download the following trace file: http-wireshark-trace-1 (https://webcms3.cse.unsw.edu.au/COMP3331/20T2/resources/45203)

NOTE: IT IS NOT POSSIBLE TO RUN WIRESHARK VIA SSH. IT IS A RESOURCE INTENSIVE PROGRAM AND IT WOULD SLOW DOWN THE CSE LOGIN SERVERS. IF YOU WANT TO WORK REMOTELY, THEN YOU CAN DOWNLOAD AND INSTALL WIRESHARK (https://www.wireshark.org/download.html) ON YOUR PERSONAL MACHINE. WIRESHARK IS AVAILABLE ON ALL LAB MACHINES.

The following indicate the steps involved:

Step 1: Start Wireshark by typing *wireshark* at the command prompt.

Step 2: Load the trace file *http-wireshark-trace-1* by using the *File* pull down menu, choosing *Open* and selecting the appropriate trace file. This trace file captures a simple request/response interaction between a browser and a web server.

Step 3: You will see a large number of packets in the packet-listing window. Since we are currently only interested in HTTP we will filter out all the other packets by typing “http” in lower-case in the *Filter* field and press Enter. You should now see only HTTP packets in the packet-listing window.

Step 4: Select the first HTTP message in the packet-listing window and observe the data in the packet-header detail window. Recall that since each HTTP message was carried inside a TCP segment, which was carried inside an IP datagram, which was carried within an Ethernet frame, Wireshark displays the Frame, Ethernet, IP, and TCP packet information as well. We want to minimize the amount of non-HTTP data displayed (we’re interested in HTTP here, and will be investigating these other protocols in later labs), so make sure the boxes at the far left of the Frame, Ethernet, IP and TCP information have a right-pointing arrowhead (which means there is hidden, undisplayed information), and the HTTP line has a down-pointing arrowhead (which means that all information about the HTTP message is displayed).

NOTE: Please neglect the HTTP GET and response for favicon.ico, (the third and fourth HTTP messages in the trace file. Most browsers automatically ask the server if the server has a small icon file that should be displayed next to the displayed URL in the browser. We will ignore references to this pesky file in this lab.)

By looking at the information in the HTTP GET and response messages (the first two messages), answer the following questions:

Question 1: What is the status code and phrase returned from the server to the client browser?

Question 2: When was the HTML file that the browser is retrieving last modified at the server? Does the response also contain a DATE header? How are these two fields different?

Question 3: Is the connection established between the browser and the server persistent or non-persistent? How can you infer this?

Question 4: How many bytes of content are being returned to the browser?

Question 5: What is the data contained inside the HTTP response packet?

Note: Students are strongly encouraged to use wireshark to capture real network traffic on their own machines. Check <https://www.wireshark.org/download.html> (<https://www.wireshark.org/download.html>) for details. Once you have wireshark installed, do the following. Clear the cache of your web browser (Firefox->Tools->Clear Recent History). Launch the wireshark tool by typing wireshark in the command line. Start wireshark capture by clicking on: capture -> interfaces -> click Start on the interface eth0. Run the Web browser and enter an url for a website (e.g. www.bbc.co.uk (<http://www.bbc.co.uk>)). Stop capturing packets when the web page is fully loaded. Examine the captured trace and answer the questions as above.

Exercise 4: Using Wireshark to understand the HTTP CONDITIONAL GET/response interaction (marked, include in your report)

For this particular experiment download the second trace file: *http-wireshark-trace-2* (<https://webcms3.cse.unsw.edu.au/COMP3331/20T2/resources/45188>)

(<https://webcms3.cse.unsw.edu.au/COMP3331/18s2/resources/17311>) The following indicate the steps for this experiment:

Step 1: Start Wireshark by typing *wireshark* at the command prompt.

Step 2: Load the trace file *http-wireshark-trace-2* by using the *File* pull down menu, choosing *Open* and selecting the appropriate trace file. This trace file captures a request response between a client browser and web server where the client requests the same file from the server within a span of a few seconds.

Step 3: Filter out all the non-HTTP packets and focus on the HTTP header information in the packet-header detail window.

By looking at the information in the HTTP GET and response messages (the first two messages), answer the following questions:

Question 1: Inspect the contents of the first HTTP GET request from the browser to the server. Do you see an "IF-MODIFIED-SINCE" line in the HTTP GET?

Question 2: Does the response indicate the last time that the requested file was modified?

Question 3: Now inspect the contents of the second HTTP GET request from the browser to the server. Do you see an "IF-MODIFIED-SINCE:" and "IF-NONE-MATCH" lines in the HTTP GET? If so, what information is contained in these header lines?

Question 4: What is the HTTP status code and phrase returned from the server in response to this second HTTP GET? Did the server explicitly return the contents of the file? Explain.

Question 5: What is the value of the Etag field in the 2nd response message and how it is used? Has this value changed since the 1st response message was received?

Exercise 5: Ping Client (marked, submit source code as a separate file, include sample output in the report)

In this exercise, you will study a simple Internet ping server (written in Java), and implement a corresponding client. The functionality provided by these programs are similar to the standard ping programs available in modern operating systems, except that they use UDP rather than Internet Control Message Protocol (ICMP) to communicate with each other. Note that, we will study ICMP later in the course. (Most programming languages do not provide a straightforward means to interact with ICMP)

The ping protocol allows a client machine to send a packet of data to a remote machine and have the remote machine return the data back to the client unchanged (an action referred to as echoing). Among other uses, the ping protocol allows hosts to determine round-trip times to other machines.

Ping Server (provided)

You are given the complete code for the Ping server: `PingServer.java`.

(<https://webcms3.cse.unsw.edu.au/COMP3331/20T2/resources/45189>) The server sits in an infinite loop listening for incoming UDP packets. When a packet comes in, the server simply sends the encapsulated data back to the client.

Your task is to write the corresponding Ping client. You can use either C, Java or Python to write your client. You should read through the server code thoroughly, as it will help you with the development of your client program.

Packet Loss & Delay

UDP provides applications with an unreliable transport service, because messages may get lost in the network due to router queue overflows or other reasons. In contrast, TCP provides applications with a reliable transport service and takes care of any lost packets by retransmitting them until they are successfully received. Applications using UDP for communication must therefore implement any reliability they need separately in the application level (each application can implement a different policy, according to its specific needs). Because packet loss is rare or even non-existent in typical campus networks, the server in this lab

injects artificial loss to simulate the effects of network packet loss. The server has a parameter `LOSS_RATE` that specifies the percentage of packets that are lost (i.e. dropped). The server also has another parameter `AVERAGE_DELAY` that is used to simulate the delay incurred by packets in the Internet. You should set `AVERAGE_DELAY` to a positive value when testing your client and server on the same machine, or when machines are close by on the network. You can set `AVERAGE_DELAY` to 0 to find out the true round-trip time between the client and server.

Compiling and Running Server

To compile the server, type the following at the command prompt:

```
$javac PingServer.java
```

To run the server, type the following:

```
$java PingServer port
```

where *port* is the port number the server listens on. Remember that you should pick a port number greater than 1024, because only processes running with root (administrator) privilege can bind to ports less than 1024. If you get a message that the port is in use, try a different port number as the one you chose may be in use.

Note: if you get a class not found error when running the above command, then you may need to tell Java to look in the current directory in order to resolve class references. In this case, the commands will be as follows:

```
$java -classpath . PingServer port
```

Your Task: Implementing Ping Client

You should write the client (called `PingClient.java` or `PingClient.c` or `PingClient.py`) such that it sends 15 ping requests to the server. Each message contains a payload of data that includes the keyword `PING`, a sequence number starting from 3,331, and a timestamp. After sending each packet, the client waits up to 600 ms to receive a reply. If 600 ms goes by without a reply from the server, then the client assumes that its packet or the server's reply packet has been lost in the network.

You should write the client so that it executes with the following command:

```
$java PingClient host port (for Java)
```

or

```
$PingClient host port (for C)
```

or

```
$python PingClient.py host port (for Python)
```

where *host* is the IP address of the computer the server is running on and *port* is the port number it is listening to. In your lab you will be running the client and server on the same machine. So just use 127.0.0.1 (i.e., localhost) for *host* when running your client. In practice, you can run the client and server on different machines.

The client should send 15 pings to the server. Because UDP is an unreliable protocol, some of the packets sent to the server may be lost, or some of the packets sent from server to client may be lost. For this reason, the client cannot wait indefinitely for a reply to a ping message. You should have the client wait up to 600 ms

for a reply; if no reply is received, then the client should assume that the packet was lost during transmission across the network. It is important that you choose a reasonably large value, which is greater than the expected RTT (Note that the server artificially delays the response using the `AVERAGE_DELAY` parameter). In order to achieve this your socket will need to be non-blocking (i.e. it must not just wait indefinitely for a response from the server). If you are using Java, you will need to research the API for `DatagramSocket` to find out how to set the timeout value on a datagram socket (Check: <http://java.sun.com/javase/6/docs/api/java/net/Socket.html>

(<http://java.sun.com/javase/6/docs/api/java/net/Socket.html>)). If you are using C, you can find information here: <http://www.beej.us> (<http://www.beej.us/guide/bgnet/html/multi/index.html>) . Note that, the `fcntl()` function is the simplest way to achieve this.

Note that, your client should not send all 15 ping messages back-to-back, but rather sequentially. The client should send one ping and then wait either for the reply from the server or a timeout before transmitting the next ping. Upon receiving a reply from the server, your client should compute the RTT, i.e. the difference between when the packet was sent and the reply was received. There are functions in Java Python and C that will allow you to read the system time in milliseconds. The RTT value should be printed to the standard output (similar to the output printed by ping; have a look at the output of ping for yourself). An example output could be:

```
ping to 127.0.0.1, seq = 1, rtt = 120 ms
```

We prefer that you show the timeout requests in the out put. Only replace the 'rtt=120ms' in the above example with 'time out'. You will also need to report the minimum, maximum and the average RTTs of all packets received successfully at the end of your program's output.

Message Format

The ping messages in this lab are formatted in a simple way. Each message contains a sequence of characters terminated by a carriage return (CR) character (`\r`) and a line feed (LF) character (`\n`). The message contains the following string:

PING sequence_number time CRLF

where *sequence_number* starts at 3,331 and progresses to 3,345 for each successive ping message sent by the client, *time* is the time when the client sent the message, and CRLF represent the carriage return and line feed characters that terminate the line.

Hint: Cut and paste PingServer, rename the code PingClient, and then modify the code, if you are using Java.

Optional Extensions (For students keen to take up a challenge. THESE ARE NOT MARKED)

When you are finished writing the client, you may wish to try one of the following exercises:

- 1) The basic program sends a new ping immediately when it receives a reply. Modify the program so that it sends exactly 1 ping per second, similar to how the standard ping program works (difficult).
- 2) Develop two new classes *ReliableUdpSender* and *ReliableUdpReceiver* , which are used to send and receive data reliably over UDP. To do this, you will need to devise a protocol (such as TCP) in which the recipient of data sends acknowledgements back to the sender to indicate that the data has arrived. You can simplify the problem by only providing one-way transport of application data from sender to recipient. Because your experiments may be in a network environment with little or no loss of IP packets, you should simulate packet loss (difficult).

Resource created 4 months ago (Wednesday 29 April 2020, 03:56:57 PM), last modified 2 months ago (Thursday 18 June 2020, 05:03:11 PM).

Comments

🔍 (/COMP3331/20T2/forums/search?forum_choice=resource/44921)

💬 (/COMP3331/20T2/forums/resource/44921)

💬 Add a comment



Simon Sillitoe (/users/z3188123) 2 months ago (Tue Jun 30 2020 18:27:26 GMT+0800 (China Standard Time))

My tutor confirmed that Lab2 was marked but it is unavailable in both the 'grades' section (shows N/A) and under Lab2 Collect submission it says "not yet marked" - is there an error?

Reply



Ayda Valinezhad Orang (/users/z5195667) 2 months ago (Thu Jul 02 2020 10:39:40 GMT+0800 (China Standard Time))

Dear Simon,

The SMS was blocked. However, now you can see your grade.

Regards,

Ayda

Reply



Hao Wu (/users/z5287049) 2 months ago (Tue Jun 23 2020 07:29:19 GMT+0800 (China Standard Time))

Hi,

Homework submission:

I just stupidly submitted the lab2 homework at lab1 webpage this morning after checking how to make a tar archive and of course it is overdue. Will I get a penalty for that or what should I do?

Reply



Saksham Yadav (/users/z5164624) 2 months ago (Thu Jun 25 2020 12:44:46 GMT+0800 (China Standard Time))

I nearly did this just minutes AFTER reading your post haha.

Reply



Wei Song (/users/z5198433) 2 months ago (Tue Jun 23 2020 10:03:53 GMT+0800 (China Standard Time))

Hi

Please contact your tutor and send the lab1 report file with last-modified time within the lab1 ddl.

Reply



Xuehua Ma (/users/z5262637) 2 months ago (Tue Jun 23 2020 03:06:34 GMT+0800 (China Standard Time))

Hi,

I want to know the output of average RTT is not integer, is something look like 110.12334ms, does it matter?

Reply



Wei Song (/users/z5198433) 2 months ago (Tue Jun 23 2020 10:01:47 GMT+0800 (China Standard Time))

Hi Xuehua,

That's fine.

Reply



Zihe Wang (/users/z5242160) 2 months ago (Mon Jun 22 2020 21:15:03 GMT+0800 (China Standard Time))

Hi,

I am wondering if the deadline of the people who go to the lab on Monday is Thursday, coz I saw in the Specificatinon, the deadline of us is on Tuesday. I always thought that the deadline for us is Thursday so that I have not started doing the lab and suddenly I saw that made me feel nervous..

Reply



Wen Hu (/users/z2260468) 2 months ago (Mon Jun 22 2020 21:35:18 GMT+0800 (China Standard Time))

Hi Zihe,

It will be Thursdays for Monday labs as shown in

<https://webcms3.cse.unsw.edu.au/COMP3331/20T2/reso...>

(<https://webcms3.cse.unsw.edu.au/COMP3331/20T2/resources/45214>) . You tutors will take this into account automatically.

Reply



Zihe Wang (/users/z5242160) 2 months ago (Mon Jun 22 2020 22:44:10 GMT+0800 (China Standard Time))

Okay, thank you so much

Reply



Sameer Mahmud (/users/z5257706) 2 months ago (Mon Jun 22 2020 20:45:11 GMT+0800 (China Standard Time))

How do I know the client is connected to the server. At the moment, when I try running the client I always get back the same output despite if the server is running or not?

Round-trip min/avg/max = 0/1.4888888888888888/21

Reply



Wei Song (/users/z5198433) 2 months ago (Mon Jun 22 2020 21:11:48 GMT+0800 (China Standard Time))

Hi Sameer,

After you run the PingServer.java then the server should be running.

And the protocol used is UDP which is NO connection. Every ping message is a datagram which is directly sent to the server, sometimes your datagram will be lost while sometimes your datagram will arrive the server. This exercise is trying to simulate the UDP protocol communication.

Reply



Sasha Carlisle (/users/z5207478) 2 months ago (Mon Jun 22 2020 19:39:54 GMT+0800 (China Standard Time))

Submitting files:

When submitting, should the pdf and PingClient be in a tar archive? Or can we just upload them as two separate files?

Reply



Wei Song (/users/z5198433) 2 months ago (Mon Jun 22 2020 20:01:05 GMT+0800 (China Standard Time))

Hi Sasha,

PDF and the PingClient should be two separate files, and tar them together as one tar file and submit.

Reply



Cavinash Chelliah (/users/z3417347) 2 months ago (Sun Jun 21 2020 23:47:25 GMT+0800 (China Standard Time))

Hi, I just wanted to find out whether for implementation of the PingClient whether it is ok for the client to establish a new connection each Ping or whether there should only be a single connection established and ongoing?

Reply



Wei Song (/users/z5198433) 2 months ago (Mon Jun 22 2020 14:41:03 GMT+0800 (China Standard Time))

Hi Cavinash,

The protocol used is UDP which is NO connection. Every ping message is a datagram which is directly sent to the server, sometimes your datagram will be lost while sometimes your datagram will arrive the server. This exercise is trying to simulate the UDP protocol communication.

Reply



Cavinash Chelliah (/users/z3417347) 2 months ago (Mon Jun 22 2020 20:59:02 GMT+0800 (China Standard Time))

Thank you Wei

Reply



Xuehua Ma (/users/z5262637) 2 months ago (Sun Jun 21 2020 19:09:23 GMT+0800 (China Standard Time))

Hello,

I want to know when we write the ping message, the time should be accurate to millisecond or second is enough?

Reply



Nipuna Shanthidewa (/users/z5175209) 2 months ago (Sun Jun 21 2020 19:27:01 GMT+0800 (China Standard Time))

we are testing both client and server on same computer, therefore delay is very small, hence time should be accurate to milliseconds

Reply



Michael Gysel (/users/z5251938) 2 months ago (Sun Jun 21 2020 18:15:56 GMT+0800 (China Standard Time))

Hello,

Is the data technically everything after the line break (everything shown below)? Or would the data just be considered the Line-based text data section?

```
\r\n
[HTTP response 1/2]
[Time since request: 0.024143000 seconds]
[Request in frame: 10]
[Next request in frame: 13]
[Next response in frame: 14]
[Request URI: http://gaia.cs.umass.edu/ethereal-labs/lab2-1.html]
File Data: 73 bytes
▼ Line-based text data: text/html (3 lines)
<html>\n
Congratulations. You've downloaded the file lab2-1.html!\n
</html>\n
```

Reply



Nipuna Shanthidewa (/users/z5175209) 2 months ago (Sun Jun 21 2020 19:23:48 GMT+0800 (China Standard Time))

Data contained inside the HTTP response packet should be things inside "Line-based text data"

Reply



Yuyang Zheng (/users/z5227468) 2 months ago (Sun Jun 21 2020 16:16:59 GMT+0800 (China Standard Time))

Hello, should I print the loss rate at the bottom of the client?

Reply



Nipuna Shanthidewa (/users/z5175209) 2 months ago (Sun Jun 21 2020 19:21:35 GMT+0800 (China Standard Time))

yes , you can print the loss rate at the bottom of the client, but not mandatory

Reply

Load More Comments