

How to go from partial to full retroactivity in detail

Cristina Gomes Fernandes, Felipe Castro de Noronha

IME-USP – Brazil

LAGOS 25 – November 10-14, 2025

1. Hello everyone. My name is Felipe Noronha, and today I'll be presenting the work done by Professor Cristina Fernandes and I at IME-USP.
2. Our paper details a method for transforming partially retroactive data structures into fully retroactive ones.
3. This work is motivated by a practical limitation in the well-known 2007 transformation by Demaine, Iacono, and Langerman and it also builds upon a 2022 solution by Junior and Seabra.
4. Our key contribution is a method to achieve this transformation with the same time complexity, but **without** the need for complex persistent data structures.
5. To illustrate our approach, we'll use the minimum spanning forest problem as our main example. So, let's start by defining what that is.

2025-10-26

Partial to full retroactivity

└─What is a spanning tree?

What is a spanning tree?

- Let $G = (V, E)$ be a connected graph
- **Spanning tree:** A tree with all vertices of G

1. Lets start of by defining what is a spanning tree on a graph G with a set of vertices and edges
2. A spanning tree will be a tree will all the vertices of G
3. ——— SKIP SLIDE ———
4. It will have 3 main properties: it is connected (path between any two vertices), acyclic (no cycles), contains exactly $n-1$ edges for n vertices
5. ——— SKIP SLIDE ———
6. Show visual example with graph G (blue edges) and spanning tree T (red wavy edges)
7. In the example: 8 vertices, so spanning tree has exactly 7 edges
8. Emphasize that spanning trees are not unique - there can be many valid spanning trees

└─What is a spanning tree?

What is a spanning tree?

- Let $G = (V, E)$ be a connected graph
- **Spanning tree:** A tree with all vertices of G
- **Properties:**
 - ▶ Connected (path between any two vertices)
 - ▶ Acyclic (no cycles)
 - ▶ Contains exactly $n - 1$ edges for n vertices

1. Lets start of by defining what is a spanning tree on a graph G with a set of vertices and edges
2. A spanning tree will be a tree will all the vertices of G
3. _____ SKIP SLIDE _____
4. It will have 3 main properties: it is connected (path between any two vertices), acyclic (no cycles), contains exactly $n-1$ edges for n vertices
5. _____ SKIP SLIDE _____
6. Show visual example with graph G (blue edges) and spanning tree T (red wavy edges)
7. In the example: 8 vertices, so spanning tree has exactly 7 edges
8. Emphasize that spanning trees are not unique - there can be many valid spanning trees

What is a spanning tree?

- Let $G = (V, E)$ be a connected graph
- Spanning tree:** A tree with all vertices of G
- Properties:**
 - Connected (path between any two vertices)
 - Acyclic (no cycles)
 - Contains exactly $n - 1$ edges for n vertices





Figure: Graph G (blue edges) and spanning tree T (red wavy edges)

2025-10-26

Partial to full retroactivity

└ What is a spanning tree?



- Let's start by defining what is a spanning tree on a graph G with a set of vertices and edges
- A spanning tree will be a tree with all the vertices of G
- SKIP SLIDE ——
- It will have 3 main properties: it is connected (path between any two vertices), acyclic (no cycles), contains exactly $n-1$ edges for n vertices
- SKIP SLIDE ——
- Show visual example with graph G (blue edges) and spanning tree T (red wavy edges)
- In the example: 8 vertices, so spanning tree has exactly 7 edges
- Emphasize that spanning trees are not unique - there can be many valid spanning trees

2025-10-26

Partial to full retroactivity

Minimum Spanning Tree and Forest

Minimum Spanning Tree and Forest

- **Minimum Spanning Tree (MST):** spanning tree in a weighted graph with minimum total cost

1. Now, let's add weights or costs to the edges. In a weighted graph, a Minimum Spanning Tree, or MST, is a spanning tree that has the minimum possible total cost. It's an optimization problem.
2. ——— SKIP SLIDE ———
3. This concept generalizes to disconnected graphs as well. We call this a Minimum Spanning Forest, or MSF, which is simply the collection of MSTs for each connected component.
4. ——— SKIP SLIDE ———
5. In the visual example, you can see the same graph as before, but now with costs on the edges. The red edges again show the tree, but this time, they've been chosen to be the MST.
6. If we sum the costs of the red edges, we get a total of 14. Any other spanning tree you could build for this graph would have a total cost greater than or equal to 14.
7. This idea of maintaining an optimal-cost forest is central to our problem. Specifically, how to maintain this optimality as the graph changes.

Minimum Spanning Tree and Forest

Minimum Spanning Tree and Forest

- **Minimum Spanning Tree (MST)**: spanning tree in a weighted graph with minimum total cost
- **Minimum Spanning Forest (MSF)**: generalization for disconnected graphs

1. Now, let's add weights or costs to the edges. In a weighted graph, a Minimum Spanning Tree, or MST, is a spanning tree that has the minimum possible total cost. It's an optimization problem.
2. ——— SKIP SLIDE ———
3. This concept generalizes to disconnected graphs as well. We call this a Minimum Spanning Forest, or MSF, which is simply the collection of MSTs for each connected component.
4. ——— SKIP SLIDE ———
5. In the visual example, you can see the same graph as before, but now with costs on the edges. The red edges again show the tree, but this time, they've been chosen to be the MST.
6. If we sum the costs of the red edges, we get a total of 14. Any other spanning tree you could build for this graph would have a total cost greater than or equal to 14.
7. This idea of maintaining an optimal-cost forest is central to our problem. Specifically, how to maintain this optimality as the graph changes.

Minimum Spanning Tree and Forest

- **Minimum Spanning Tree (MST):** spanning tree in a weighted graph with minimum total cost
- **Minimum Spanning Forest (MSF):** generalization for disconnected graphs





Figure: Graph G (blue edges) and Minimum Spanning Tree (red wavy edges)

2025-10-26

Partial to full retroactivity

└ Minimum Spanning Tree and Forest



1. Now, let's add weights or costs to the edges. In a weighted graph, a Minimum Spanning Tree, or MST, is a spanning tree that has the minimum possible total cost. It's an optimization problem.
2. — SKIP SLIDE —
3. This concept generalizes to disconnected graphs as well. We call this a Minimum Spanning Forest, or MSF, which is simply the collection of MSTs for each connected component.
4. — SKIP SLIDE —
5. In the visual example, you can see the same graph as before, but now with costs on the edges. The red edges again show the tree, but this time, they've been chosen to be the MST.
6. If we sum the costs of the red edges, we get a total of 14. Any other spanning tree you could build for this graph would have a total cost greater than or equal to 14.
7. This idea of maintaining an optimal-cost forest is central to our problem. Specifically, how to maintain this optimality as the graph changes.

Incremental MSF problem

- **Problem:** Keep track of an MSF in a graph that grows over time
- Graph starts empty, edges are added one by one

2025-10-26

Partial to full retroactivity

└ Incremental MSF problem

Incremental MSF problem

• Problem: Keep track of an MSF in a graph that grows over time

• Graph starts empty, edges are added one by one

1. So, this brings us to the Incremental MSF problem. The goal is to maintain a Minimum Spanning Forest in a graph that grows over time.
2. Crucially, the graph starts empty, and edges are only added one by one.
3. ——— SKIP SLIDE ———
4. This problem is defined by two operations: *add_edge*, which inserts a new weighted edge, and *get_msf*, which returns the current minimum spanning forest.
5. ——— SKIP SLIDE ———
6. The solution to this was given by Frederickson in 1983. He used a dynamic data structure called link-cut trees which achieves a $O(\log n)$ amortized time per edge addition, where n is the number of vertices.

Incremental MSF problem

- **Problem:** Keep track of an MSF in a graph that grows over time
- Graph starts empty, edges are added one by one
- **Operations:**
 - ▶ `add_edge(u, v, w)`: add edge with cost w between vertices u and v
 - ▶ `get_msf()`: return a list with the edges of an MSF of G

2025-10-26

Partial to full retroactivity

└ Incremental MSF problem

Incremental MSF problem

- **Problem:** Keep track of an MSF in a graph that grows over time
- Graph starts empty, edges are added one by one
- **Operations:**
 - ▶ `add_edge(u, v, w)`: add edge with cost w between vertices u and v
 - ▶ `get_msf()`: return a list with the edges of an MSF of G

1. So, this brings us to the Incremental MSF problem. The goal is to maintain a Minimum Spanning Forest in a graph that grows over time.
2. Crucially, the graph starts empty, and edges are only added one by one.
3. ——— SKIP SLIDE ———
4. This problem is defined by two operations: `add_edge`, which inserts a new weighted edge, and `get_msf`, which returns the current minimum spanning forest.
5. ——— SKIP SLIDE ———
6. The solution to this was given by Frederickson in 1983. He used a dynamic data structure called link-cut trees which achieves a $O(\log n)$ amortized time per edge addition, where n is the number of vertices.

Incremental MSF problem

- **Problem:** Keep track of an MSF in a graph that grows over time
- Graph starts empty, edges are added one by one
- **Operations:**
 - ▶ `add_edge(u, v, w)`: add edge with cost w between vertices u and v
 - ▶ `get_msf()`: return a list with the edges of an MSF of G
- **Solution:** Frederickson (1983) using link-cut trees

2025-10-26

Partial to full retroactivity

└ Incremental MSF problem

1. So, this brings us to the Incremental MSF problem. The goal is to maintain a Minimum Spanning Forest in a graph that grows over time.
2. Crucially, the graph starts empty, and edges are only added one by one.
3. ——— SKIP SLIDE ———
4. This problem is defined by two operations: `add_edge`, which inserts a new weighted edge, and `get_msf`, which returns the current minimum spanning forest.
5. ——— SKIP SLIDE ———
6. The solution to this was given by Frederickson in 1983. He used a dynamic data structure called link-cut trees which achieves a $O(\log n)$ amortized time per edge addition, where n is the number of vertices.

Incremental MSF problem

- **Problem:** Keep track of an MSF in a graph that grows over time
- Graph starts empty, edges are added one by one
- **Operations:**
 - ▶ `add_edge(u, v, w)`: add edge with cost w between vertices u and v
 - ▶ `get_msf()`: return a list with the edges of an MSF of G
- **Solution:** Frederickson (1983) using link-cut trees

2025-10-26

Partial to full retroactivity

└ Frederickson's link-cut tree solution

- **Key insight:** Use link-cut trees to maintain MSF dynamically

1. So, what was Frederickson's solution? He showed that link-cut trees can efficiently maintain this incrementing forest.
2. — SKIP SLIDE —
3. Link-cut trees provide all the operations we need, all in $O(\log n)$ amortized time: *find_max* to find the most expensive edge on a path, *link* to add a weighted edge, and *cut* to remove one.
4. — SKIP SLIDE —
5. With this, we can construct a straightforward algorithm that supports adding a new edge (u, v, w) :
6. First, we check if u and v are already connected. If they're not, the new edge can't create a cycle, so we just add it to the forest using *link*.
7. If they *are* connected, adding this new edge creates a cycle. We find the most expensive edge on the path in that cycle using *find_max*.
8. If our new edge's cost w is cheaper than that maximum cost, we swap them: we *cut* the old, expensive edge and *link* our new, cheaper edge.
9. — SKIP SLIDE —
10. With these steps using LCT operations, the time per edge addition is $O(\log n)$ amortized.

- ♦ **Key insight:** Use link-cut trees to maintain MSF dynamically
- ♦ **Link-cut tree operations:**
 - $\text{find_max}(u, v)$: $O(\log n)$ amortized
 - $\text{link}(u, v, w)$: $O(\log n)$ amortized
 - $\text{cut}(u, v)$: $O(\log n)$ amortized

2025-10-26

Partial to full retroactivity

└ Frederickson's link-cut tree solution

Frederickson's link-cut tree solution

- ♦ **Key insight:** Use link-cut trees to maintain MSF dynamically
- ♦ **Link-cut tree operations:**
 - ▶ $\text{find_max}(u, v)$: $O(\log n)$ amortized
 - ▶ $\text{link}(u, v, w)$: $O(\log n)$ amortized
 - ▶ $\text{cut}(u, v)$: $O(\log n)$ amortized

1. So, what was Frederickson's solution? He showed that link-cut trees can efficiently maintain this incrementing forest.
2. ——— SKIP SLIDE ———
3. Link-cut trees provide all the operations we need, all in $O(\log n)$ amortized time: *find_max* to find the most expensive edge on a path, *link* to add a weighted edge, and *cut* to remove one.
4. ——— SKIP SLIDE ———
5. With this, we can construct a straightforward algorithm that supports adding a new edge (u, v, w) :
6. First, we check if u and v are already connected. If they're not, the new edge can't create a cycle, so we just add it to the forest using *link*.
7. If they *are* connected, adding this new edge creates a cycle. We find the most expensive edge on the path in that cycle using *find_max*.
8. If our new edge's cost w is cheaper than that maximum cost, we swap them: we *cut* the old, expensive edge and *link* our new, cheaper edge.
9. ——— SKIP SLIDE ———
10. With these steps using LCT operations, the time per edge addition is $O(\log n)$ amortized.

Frederickson's link-cut tree solution

- **Key insight:** Use link-cut trees to maintain MSF dynamically

- **Link-cut tree operations:**

- ▶ $\text{find_max}(u, v)$: $\mathcal{O}(\log n)$ amortized
- ▶ $\text{link}(u, v, w)$: $\mathcal{O}(\log n)$ amortized
- ▶ $\text{cut}(u, v)$: $\mathcal{O}(\log n)$ amortized

- **Algorithm for adding edge (u, v, w) :**

- 1 Check if u and v are in same component
- 2 If not: add edge to forest
- 3 If yes: find max cost edge on u - v path
- 4 If $w < \text{max cost}$: replace max edge with new edge

Partial to full retroactivity

└ Frederickson's link-cut tree solution

Frederickson's link-cut tree solution

- **Key insight:** Use link-cut trees to maintain MSF dynamically
- **Link-cut tree operations:**
 - $\text{find_max}(u, v)$: $\mathcal{O}(\log n)$ amortized
 - $\text{link}(u, v, w)$: $\mathcal{O}(\log n)$ amortized
 - $\text{cut}(u, v)$: $\mathcal{O}(\log n)$ amortized
- **Algorithm for adding edge (u, v, w) :**
 - 1 Check if u and v are in same component
 - 2 If not: add edge to forest
 - 3 If yes: find max cost edge on u - v path
 - 4 If $w < \text{max cost}$: replace max edge with new edge

1. So, what was Frederickson's solution? He showed that link-cut trees can efficiently maintain this incrementing forest.
2. ——— SKIP SLIDE ———
3. Link-cut trees provide all the operations we need, all in $\mathcal{O}(\log n)$ amortized time: find_max to find the most expensive edge on a path, link to add a weighted edge, and cut to remove one.
4. ——— SKIP SLIDE ———
5. With this, we can construct a straightforward algorithm that supports adding a new edge (u, v, w) :
6. First, we check if u and v are already connected. If they're not, the new edge can't create a cycle, so we just add it to the forest using link .
7. If they *are* connected, adding this new edge creates a cycle. We find the most expensive edge on the path in that cycle using find_max .
8. If our new edge's cost w is cheaper than that maximum cost, we swap them: we cut the old, expensive edge and link our new, cheaper edge.
9. ——— SKIP SLIDE ———
10. With these steps using LCT operations, the time per edge addition is $\mathcal{O}(\log n)$ amortized.

Frederickson's link-cut tree solution

- **Key insight:** Use link-cut trees to maintain MSF dynamically
- **Link-cut tree operations:**
 - ▶ $\text{find_max}(u, v)$: $\mathcal{O}(\log n)$ amortized
 - ▶ $\text{link}(u, v, w)$: $\mathcal{O}(\log n)$ amortized
 - ▶ $\text{cut}(u, v)$: $\mathcal{O}(\log n)$ amortized
- **Algorithm for adding edge (u, v, w) :**
 - 1 Check if u and v are in same component
 - 2 If not: add edge to forest
 - 3 If yes: find max cost edge on u - v path
 - 4 If $w < \text{max cost}$: replace max edge with new edge
- **Total cost:** Amortized $\mathcal{O}(\log n)$ per edge addition

2025-10-26

Partial to full retroactivity

└ Frederickson's link-cut tree solution

Frederickson's link-cut tree solution

- **Key insight:** Use link-cut trees to maintain MSF dynamically
- **Link-cut tree operations:**
 - ▶ $\text{find_max}(u, v)$: $\mathcal{O}(\log n)$ amortized
 - ▶ $\text{link}(u, v, w)$: $\mathcal{O}(\log n)$ amortized
 - ▶ $\text{cut}(u, v)$: $\mathcal{O}(\log n)$ amortized
- **Algorithm for adding edge (u, v, w) :**
 - 1 Check if u and v are in same component
 - 2 If not: add edge to forest
 - 3 If yes: find max cost edge on u - v path
 - 4 If $w < \text{max cost}$: replace max edge with new edge
- **Total cost:** Amortized $\mathcal{O}(\log n)$ per edge addition

1. So, what was Frederickson's solution? He showed that link-cut trees can efficiently maintain this incrementing forest.
2. ——— SKIP SLIDE ———
3. Link-cut trees provide all the operations we need, all in $\mathcal{O}(\log n)$ amortized time: *find_max* to find the most expensive edge on a path, *link* to add a weighted edge, and *cut* to remove one.
4. ——— SKIP SLIDE ———
5. With this, we can construct a straightforward algorithm that supports adding a new edge (u, v, w) :
6. First, we check if u and v are already connected. If they're not, the new edge can't create a cycle, so we just add it to the forest using *link*.
7. If they *are* connected, adding this new edge creates a cycle. We find the most expensive edge on the path in that cycle using *find_max*.
8. If our new edge's cost w is cheaper than that maximum cost, we swap them: we *cut* the old, expensive edge and *link* our new, cheaper edge.
9. ——— SKIP SLIDE ———
10. With these steps using LCT operations, the time per edge addition is $\mathcal{O}(\log n)$ amortized.

Incremental MSF example - Step 1

- **add_edge(g, h, 4):** Add edge with cost 4





Figure: Step 1: Added edge (g,h) with cost 4

- **MSF:** {g-h}

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Step 1



1. Let's walk through a quick example. We start with an empty graph.
2. First, we add edge (g, h) with cost 4.
3. Are 'g' and 'h' connected? No. So, by step 2 of the algorithm, we simply add the edge to our MSF.
4. The MSF is now just {g-h}.

Incremental MSF example - Step 2

- **add_edge(c, a, 1):** Add edge with cost 1





Figure: Step 2: Added edge (c,a) with cost 1

- **MSF:** $\{g-h, c-a\}$

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Step 2



1. Next, we add (c, a) with cost 1.
2. Again, are 'c' and 'a' connected? No. They are in a different component from 'g' and 'h'.
3. So, we add it directly. The MSF now has two components: $\{g-h\}$ and $\{c-a\}$.

Incremental MSF example - Step 3

- **add_edge(f, g, 6):** Add edge with cost 6





Figure: Step 3: Added edge (f,g) with cost 6

- **MSF:** {g-h, c-a, f-g}

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Step 3



1. Now, add (f, g) with cost 6.
2. Are 'f' and 'g' connected? No. 'f' is isolated, and 'g' is in the {g-h} component.
3. We link them. The MSF now contains {c-a} and {f-g-h}.

Incremental MSF example - Step 4

- **add_edge(a, f, 2):** Add edge with cost 2





Figure: Step 4: Added edge (a,f) with cost 2

- **MSF:** $\{g-h, c-a, f-g, a-f\}$

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Step 4



1. Add (a, f) with cost 2.
2. Are 'a' and 'f' connected? No. 'a' is in the $\{c-a\}$ component and 'f' is in the $\{f-g-h\}$ component.
3. We link these two components. Our forest now becomes a single tree, and all vertices shown so far are connected.

Incremental MSF example - Step 5

- **add_edge(c, f, 5):** Add edge with cost 5





Figure: Step 5: Added edge (c,f) with cost 5

- **MSF:** {g-h, c-a, f-g, a-f}

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Step 5



1. Okay, now we add (c, f) with cost 5. This is our first interesting case.
2. Are 'c' and 'f' connected? Yes, they are. Adding this edge will create a cycle: c-a-f-c.
3. So, we go to step 3. We find the max-cost edge on the path c-a-f. The edges are (c,a) with cost 1 and (a,f) with cost 2. The max cost is 2.
4. Our new edge costs 5. Since 5 is **not** less than the max cost of 2, we **do not** add this edge. It's discarded.
5. The MSF remains unchanged.

Incremental MSF example - Step 6

- **add_edge(f, d, 7):** Add edge with cost 7





Figure: Step 6: Added edge (f,d) with cost 7

- **MSF:** {g-h, c-a, f-g, a-f, f-d}

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Step 6



1. Next, add (f, d) with cost 7.
2. Are 'f' and 'd' connected? No. 'f' is in the main tree, but 'd' is a new, isolated vertex.
3. Therefore, we simply add the edge. The MSF is updated.

Incremental MSF example - Step 7

- **add_edge(a, d, 3):** Add edge with cost 3





Figure: Step 7: Added edge (a,d) with cost 3

- **MSF:** {g-h, c-a, f-g, a-f, a-d}

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Step 7



1. Now, add (a, d) with cost 3.
2. Are 'a' and 'd' connected? Yes. This creates the cycle a-f-d-a.
3. We find the max-cost edge on the path a-f-d. The edges are (a,f) with cost 2 and (f,d) with cost 7. The max cost is 7.
4. Our new edge costs 3. Since 3 *is* less than 7, we swap them.
5. We 'cut' the expensive edge (f,d) and 'link' our new, cheaper edge (a,d).
6. The MSF is now {g-h, c-a, f-g, a-f, a-d} and its total cost has improved.

Incremental MSF example - Step 8

- **add_edge(d, g, 2):** Add edge with cost 2





Figure: Step 8: Added edge (d,g) with cost 2

- **MSF:** {g-h, c-a, a-f, a-d, d-g}

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Step 8



1. Finally, let's add (d, g) with cost 2.
2. Are 'd' and 'g' connected? Yes. This creates the cycle d-a-f-g-d.
3. We find the max-cost edge on the path d-a-f-g. The edges are (d,a) cost 3, (a,f) cost 2, and (f,g) cost 6. The max cost is 6, from edge (f,g).
4. Our new edge costs 2. Since 2 *is* less than 6, we swap them.
5. We 'cut' edge (f,g) and 'link' our new edge (d,g).
6. The MSF is updated again, and the total cost is now 12.

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Final Result

Incremental MSF example - Final Result

- Continue adding edges...

1. If we continue this process, adding all the remaining edges from our original graph...
2. ——— SKIP SLIDE ———
3. ...we would eventually arrive at the final, optimal Minimum Spanning Tree. The one shown here, for example, has a total cost of 12.
4. But this only answers queries about the *present*. What if we want to ask: "What did the MSF look like 10 updates ago?"
5. This is the core question of retroactivity. How do we efficiently query the past?

Incremental MSF example - Final Result

- Continue adding edges...
- **Final MSF:** Minimum spanning forest with optimal cost





Figure: Final MSF with optimal cost = 14

- **Solution:** Frederickson (1983) using link-cut trees

2025-10-26

Partial to full retroactivity

└ Incremental MSF example - Final Result



1. If we continue this process, adding all the remaining edges from our original graph...
2. ~~_____ SKIP SLIDE _____~~
3. ...we would eventually arrive at the final, optimal Minimum Spanning Tree. The one shown here, for example, has a total cost of 12.
4. But this only answers queries about the *present*. What if we want to ask: "What did the MSF look like 10 updates ago?"
5. This is the core question of retroactivity. How do we efficiently query the past?

What is retroactivity?

- **Problem:** Data structures usually support updates and queries
- The order of updates affects the state of the data structure

2025-10-26

Partial to full retroactivity

└─What is retroactivity?

1. In a normal data structure, the order of updates is important. Most of the time, the state of the structure, and thus the answers to queries, depends on this sequence.
2. This means we usually don't have a good way to go back and correct mistakes or insert operations we forgot.
3. ——— SKIP SLIDE ———
4. That's where retroactivity comes in. A retroactive data structure allows us to manipulate this sequence of updates.
5. ——— SKIP SLIDE ———
6. Specifically, it adds operations to: Insert a new update at some time t *in the past*...
7. ...Remove an update that *already happened* at time t
8. ...and, most importantly, Query the state of the structure at *any* time t , not just the present.
9. The key challenge is how to do this efficiently, maintaining the state for every possible time.

What is retroactivity?

• **Problem:** Data structures usually support updates and queries

• The order of updates affects the state of the data structure

What is retroactivity?

- **Problem:** Data structures usually support updates and queries
- The order of updates affects the state of the data structure
- **Retroactivity:** Manipulate the sequence of updates

2025-10-26

Partial to full retroactivity

└─What is retroactivity?

1. In a normal data structure, the order of updates is important. Most of the time, the state of the structure, and thus the answers to queries, depends on this sequence.
2. This means we usually don't have a good way to go back and correct mistakes or insert operations we forgot.
3. ——— SKIP SLIDE ———
4. That's where retroactivity comes in. A retroactive data structure allows us to manipulate this sequence of updates.
5. ——— SKIP SLIDE ———
6. Specifically, it adds operations to: Insert a new update at some time t^* in the past*...
7. ...Remove an update that *already happened* at time t
8. ...and, most importantly, Query the state of the structure at *any* time t , not just the present.
9. The key challenge is how to do this efficiently, maintaining the state for every possible time.

What is retroactivity?

• **Problem:** Data structures usually support updates and queries

• The order of updates affects the state of the data structure

• **Retroactivity:** Manipulate the sequence of updates

What is retroactivity?

- **Problem:** Data structures usually support updates and queries
- The order of updates affects the state of the data structure
- **Retroactivity:** Manipulate the sequence of updates
- **Operations:**
 - ▶ Insert update at time t (possibly in the past)
 - ▶ Remove update at time t
 - ▶ Query at time t (not just present)

Partial to full retroactivity

└─What is retroactivity?

1. In a normal data structure, the order of updates is important. Most of the time, the state of the structure, and thus the answers to queries, depends on this sequence.
2. This means we usually don't have a good way to go back and correct mistakes or insert operations we forgot.
3. ——— SKIP SLIDE ———
4. That's where retroactivity comes in. A retroactive data structure allows us to manipulate this sequence of updates.
5. ——— SKIP SLIDE ———
6. Specifically, it adds operations to: Insert a new update at some time t *in the past*...
7. ...Remove an update that *already happened* at time t
8. ...and, most importantly, Query the state of the structure at *any* time t , not just the present.
9. The key challenge is how to do this efficiently, maintaining the state for every possible time.

What is retroactivity?

- **Problem:** Data structures usually support updates and queries
- The order of updates affects the state of the data structure
- **Retroactivity:** Manipulate the sequence of updates
- **Operations:**
 - Insert update at time t (possibly in the past)
 - Remove update at time t
 - Query at time t (not just present)

2025-10-26

Partial vs Full retroactivity

Fully Retroactive

- Queries at **any** time t
- Insert/remove updates at any time

2025-10-26

Partial to full retroactivity

└ Partial vs Full retroactivity

Partial vs Full retroactivity

Fully Retroactive

- Queries at any time t
- Insert/remove updates at any time

1. There are a few different "flavors" of retroactivity. The most powerful is Fully Retroactivity, which supports all the operations we just saw: insert, remove, and query, all at any time t .
2. ——— SKIP SLIDE ———
3. Partially Retroactive is more limited. You can still insert or remove updates anywhere in the timeline, but you can only query the state of the structure at the **current** time, "now". This is a key limitation.
4. ——— SKIP SLIDE ———
5. And finally, there's Semi-Retroactive, which is a bit of a mix. You can query at any time t and insert updates at any time, but you are **not allowed** to remove updates.
6. Generally, partially retroactive structures are much simpler to design. And this leads to an interesting challenge...

Partial vs Full retroactivity

Fully Retroactive

- Queries at **any** time t
- Insert/remove updates at any time

Partially Retroactive

- Queries only on **current** state
- Insert/remove updates at any time

2025-10-26

Partial to full retroactivity

└ Partial vs Full retroactivity

1. There are a few different "flavors" of retroactivity. The most powerful is Fully Retroactivity, which supports all the operations we just saw: insert, remove, and query, all at any time t .
2. ——— SKIP SLIDE ———
3. Partially Retroactive is more limited. You can still insert or remove updates anywhere in the timeline, but you can only query the state of the structure at the **current** time, "now". This is a key limitation.
4. ——— SKIP SLIDE ———
5. And finally, there's Semi-Retroactive, which is a bit of a mix. You can query at any time t and insert updates at any time, but you are **not allowed** to remove updates.
6. Generally, partially retroactive structures are much simpler to design. And this leads to an interesting challenge...

Partial vs Full retroactivity

Fully Retroactive

- Queries at any time t
- Insert/remove updates at any time

Partially Retroactive

- Queries only on **current** state
- Insert/remove updates at any time

Partial vs Full retroactivity

Fully Retroactive

- Queries at **any** time t
- Insert/remove updates at any time

Partially Retroactive

- Queries only on **current** state
- Insert/remove updates at any time

Semi-Retroactive

- Queries at **any** time t
- Insert updates at any time
- **No removal** of updates

2025-10-26

Partial to full retroactivity

└ Partial vs Full retroactivity

Partial vs Full retroactivity
Fully Retroactive
• Queries at any time t
• Insert/remove updates at any time
Partially Retroactive
• Queries only on current state
• Insert/remove updates at any time
Semi-Retroactive
• Queries at any time t
• Insert updates at any time
• No removal of updates

1. There are a few different "flavors" of retroactivity. The most powerful is Fully Retroactivity, which supports all the operations we just saw: insert, remove, and query, all at any time t .
2. _____ SKIP SLIDE _____
3. Partially Retroactive is more limited. You can still insert or remove updates anywhere in the timeline, but you can only query the state of the structure at the *current* time, "now". This is a key limitation.
4. _____ SKIP SLIDE _____
5. And finally, there's Semi-Retroactive, which is a bit of a mix. You can query at any time t and insert updates at any time, but you are *not allowed* to remove updates.
6. Generally, partially retroactive structures are much simpler to design. And this leads to an interesting challenge...

The challenge

Challenge

How to transform partial \rightarrow full retroactivity?

2025-10-26

Partial to full retroactivity

└ The challenge

1. ...which is this: How can we transform a simple partially retroactive structure into a fully retroactive one?
2. ——— SKIP SLIDE ———
3. We **have** a structure that lets us query "now", but we **need** a structure that lets us query any time t in the past.
4. ——— SKIP SLIDE ———
5. A general solution for this was proposed by Demaine, Iacono, and Langerman in 2007.
6. Their approach uses a classic technique called square-root decomposition.
7. Let's see how that works.

The challenge

Challenge

How to transform partial \rightarrow full retroactivity?

- **Problem:** Need to support queries at any time t
- **Solution approach:** Square-root decomposition

2025-10-26

Partial to full retroactivity

└ The challenge

1. ...which is this: How can we transform a simple partially retroactive structure into a fully retroactive one?
2. ——— SKIP SLIDE ———
3. We **have** a structure that lets us query "now", but we **need** a structure that lets us query any time t in the past.
4. ——— SKIP SLIDE ———
5. A general solution for this was proposed by Demaine, Iacono, and Langerman in 2007.
6. Their approach uses a classic technique called square-root decomposition.
7. Let's see how that works.

The challenge

Challenge

How to transform partial \rightarrow full retroactivity?

- **Problem:** Need to support queries at any time t
- **Solution approach:** Square-root decomposition

The challenge

Challenge

How to transform partial \rightarrow full retroactivity?

- **Problem:** Need to support queries at any time t
- **Solution approach:** Square-root decomposition
- **Key insight:** Keep checkpoints with data structure states
- **Implementation:** Demaine, Iacono & Langerman (2007)

2025-10-26

Partial to full retroactivity

└ The challenge

1. ...which is this: How can we transform a simple partially retroactive structure into a fully retroactive one?
2. ——— SKIP SLIDE ———
3. We **have** a structure that lets us query "now", but we **need** a structure that lets us query any time t in the past.
4. ——— SKIP SLIDE ———
5. A general solution for this was proposed by Demaine, Iacono, and Langerman in 2007.
6. Their approach uses a classic technique called square-root decomposition.
7. Let's see how that works.

The challenge

Challenge

How to transform partial \rightarrow full retroactivity?

- **Problem:** Need to support queries at any time t
- **Solution approach:** Square-root decomposition
- **Key insight:** Keep checkpoints with data structure states
- **Implementation:** Demaine, Iacono & Langerman (2007)

- $O(\sqrt{m})$ slowdown per operation
- $O(m)$ space usage
- **Requirement:** Need persistent version of the data structure

2025-10-26

Partial to full retroactivity

└ Demaine, Iacono & Langerman's solution

Demaine, Iacono & Langerman's solution

Theorem (Theorem 05)

Any partially retroactive data structure can be transformed into a fully retroactive one with:

- $O(\sqrt{m})$ slowdown per operation
- $O(m)$ space usage
- **Requirement:** Need persistent version of the data structure

1. Their paper presented this theorem: any partially retroactive data structure can be made fully retroactive.
2. The cost is an $O(\sqrt{m})$ slowdown per operation and $O(m)$ space, where m is the number of updates.
3. But there's a catch: this transformation **requires** a persistent version of the data structure.
4. ——— SKIP SLIDE ———
5. So, how does it work? The idea is to break the m updates into \sqrt{m} blocks, each of size \sqrt{m} .
6. At the beginning of each block, we store a "checkpoint" of the data structure's state.
7. ——— SKIP SLIDE ———
8. Now, to query at some time t :
9. First, we find the closest checkpoint **before** t . We load this saved state.
10. Then, we "roll forward" by applying all the updates between that checkpoint and time t . There are at most \sqrt{m} of them.
11. We answer the query, and then we "roll back" the changes to restore the checkpoint, which is where persistence comes in handy.

- $O(\sqrt{m})$ slowdown per operation
- $O(m)$ space usage
- **Requirement:** Need persistent version of the data structure
- **Key idea:** Square-root decomposition
- Keep \sqrt{m} checkpoints with data structure states

2025-10-26

Partial to full retroactivity

└ Demaine, Iacono & Langerman's solution

Demaine, Iacono & Langerman's solution

Theorem (Theorem 05)

Any partially retroactive data structure can be transformed into a fully retroactive one with:

- $O(\sqrt{m})$ slowdown per operation
- $O(m)$ space usage
- **Requirement:** Need persistent version of the data structure
- **Key idea:** Square-root decomposition
- Keep \sqrt{m} checkpoints with data structure states

1. Their paper presented this theorem: any partially retroactive data structure can be made fully retroactive.
2. The cost is an $O(\sqrt{m})$ slowdown per operation and $O(m)$ space, where m is the number of updates.
3. But there's a catch: this transformation **requires** a persistent version of the data structure.
4. ——— SKIP SLIDE ———
5. So, how does it work? The idea is to break the m updates into \sqrt{m} blocks, each of size \sqrt{m} .
6. At the beginning of each block, we store a "checkpoint" of the data structure's state.
7. ——— SKIP SLIDE ———
8. Now, to query at some time t :
9. First, we find the closest checkpoint **before** t . We load this saved state.
10. Then, we "roll forward" by applying all the updates between that checkpoint and time t . There are at most \sqrt{m} of them.
11. We answer the query, and then we "roll back" the changes to restore the checkpoint, which is where persistence comes in handy.

- $O(\sqrt{m})$ slowdown per operation
- $O(m)$ space usage
- **Requirement:** Need persistent version of the data structure

▼ **Key idea:** Square-root decomposition

- Keep \sqrt{m} checkpoints with data structure states

▼ **Query at time t :**

- Find closest checkpoint before t
- Apply updates from checkpoint to t
- Answer query, then rollback

Partial to full retroactivity

└ Demaine, Iacono & Langerman's solution

2025-10-26

Demaine, Iacono & Langerman's solution

Theorem (Theorem 05)

Any partially retroactive data structure can be transformed into a fully retroactive one with:

- $O(\sqrt{m})$ slowdown per operation
- $O(m)$ space usage
- **Requirement:** Need persistent version of the data structure

- **Key idea:** Square-root decomposition
- Keep \sqrt{m} checkpoints with data structure states
- **Query at time t :**
 - 1 Find closest checkpoint before t
 - 2 Apply updates from checkpoint to t
 - 3 Answer query, then rollback

1. Their paper presented this theorem: any partially retroactive data structure can be made fully retroactive.
2. The cost is an $O(\sqrt{m})$ slowdown per operation and $O(m)$ space, where m is the number of updates.
3. But there's a catch: this transformation **requires** a persistent version of the data structure.
4. ——— SKIP SLIDE ———
5. So, how does it work? The idea is to break the m updates into \sqrt{m} blocks, each of size \sqrt{m} .
6. At the beginning of each block, we store a "checkpoint" of the data structure's state.
7. ——— SKIP SLIDE ———
8. Now, to query at some time t :
9. First, we find the closest checkpoint **before** t . We load this saved state.
10. Then, we "roll forward" by applying all the updates between that checkpoint and time t . There are at most \sqrt{m} of them.
11. We answer the query, and then we "roll back" the changes to restore the checkpoint, which is where persistence comes in handy.

The space problem

- **Naive approach:** Keep \sqrt{m} independent copies
- Space usage: $\Theta(m\sqrt{m})$

2025-10-26

Partial to full retroactivity

└ The space problem

The space problem

- Naive approach: Keep \sqrt{m} independent copies
- Space usage: $\Theta(m\sqrt{m})$

1. ...and that leads to the space problem. If we're naive and just store \sqrt{m} *independent copies* of the data structure, one for each checkpoint...
2. ...and each copy can have up to m updates, our space usage explodes to $\Theta(m\sqrt{m})$.
3. ——— SKIP SLIDE ———
4. This is why Demaine et al. use persistent data structures. A persistent structure cleverly shares memory between versions, so all \sqrt{m} checkpoints can be stored efficiently in just $O(m)$ total space.
5. ——— SKIP SLIDE ———
6. But this raises a practical problem: What if we don't have a persistent version of our data structure? Or what if it's just too complex to implement?
7. ——— SKIP SLIDE ———
8. This is our contribution. We propose a simple rebuilding strategy that *doesn't* require persistence.
9. We achieve the *same $O(\sqrt{m})$ time* per operation.
10. The trade-off is that we go back to using $\Theta(m\sqrt{m})$ space, but we argue this is a practical trade-off for a much, much simpler implementation.

The space problem

- **Naive approach:** Keep \sqrt{m} independent copies
- Space usage: $\Theta(m\sqrt{m})$
- **Demaine et al. solution:** Use persistent data structures
- Space usage: $\mathcal{O}(m)$

2025-10-26

Partial to full retroactivity

└ The space problem

The space problem

- **Naive approach:** Keep \sqrt{m} independent copies
- Space usage: $\Theta(m\sqrt{m})$
- **Demaine et al. solution:** Use persistent data structures
- Space usage: $\mathcal{O}(m)$

1. ...and that leads to the space problem. If we're naive and just store \sqrt{m} *independent copies* of the data structure, one for each checkpoint...
2. ...and each copy can have up to m updates, our space usage explodes to $\Theta(m\sqrt{m})$.
3. ——— SKIP SLIDE ———
4. This is why Demaine et al. use persistent data structures. A persistent structure cleverly shares memory between versions, so all \sqrt{m} checkpoints can be stored efficiently in just $\mathcal{O}(m)$ total space.
5. ——— SKIP SLIDE ———
6. But this raises a practical problem: What if we don't have a persistent version of our data structure? Or what if it's just too complex to implement?
7. ——— SKIP SLIDE ———
8. This is our contribution. We propose a simple rebuilding strategy that *doesn't* require persistence.
9. We achieve the *same $\mathcal{O}(\sqrt{m})$ time* per operation.
10. The trade-off is that we go back to using $\Theta(m\sqrt{m})$ space, but we argue this is a practical trade-off for a much, much simpler implementation.

The space problem

- **Naive approach:** Keep \sqrt{m} independent copies
- Space usage: $\Theta(m\sqrt{m})$
- **Demaine et al. solution:** Use persistent data structures
- Space usage: $\mathcal{O}(m)$

Problem

What if we don't have or don't want to use persistent data structures?

2025-10-26

Partial to full retroactivity

└ The space problem

1. ...and that leads to the space problem. If we're naive and just store \sqrt{m} *independent copies* of the data structure, one for each checkpoint...
2. ...and each copy can have up to m updates, our space usage explodes to $\Theta(m\sqrt{m})$.
3. ——— SKIP SLIDE ———
4. This is why Demaine et al. use persistent data structures. A persistent structure cleverly shares memory between versions, so all \sqrt{m} checkpoints can be stored efficiently in just $\mathcal{O}(m)$ total space.
5. ——— SKIP SLIDE ———
6. But this raises a practical problem: What if we don't have a persistent version of our data structure? Or what if it's just too complex to implement?
7. ——— SKIP SLIDE ———
8. This is our contribution. We propose a simple rebuilding strategy that *doesn't* require persistence.
9. We achieve the *same $\mathcal{O}(\sqrt{m})$ time* per operation.
10. The trade-off is that we go back to using $\Theta(m\sqrt{m})$ space, but we argue this is a practical trade-off for a much, much simpler implementation.

The space problem

- **Naive approach:** Keep \sqrt{m} independent copies
- Space usage: $\Theta(m\sqrt{m})$
- **Demaine et al. solution:** Use persistent data structures
- Space usage: $\mathcal{O}(m)$

Problem

What if we don't have or don't want to use persistent data structures?

└ The space problem

- **Naive approach:** Keep \sqrt{m} independent copies
- Space usage: $\Theta(m\sqrt{m})$
- **Demaine et al. solution:** Use persistent data structures
- Space usage: $\mathcal{O}(m)$

Problem

What if we don't have or don't want to use persistent data structures?

Our contribution

- Simple rebuilding strategy without persistent data structures
- Same time complexity: $\mathcal{O}(\sqrt{m})$ per operation
- Space usage: $\Theta(m\sqrt{m})$

The space problem

- **Naive approach:** Keep \sqrt{m} independent copies
- Space usage: $\Theta(m\sqrt{m})$
- **Demaine et al. solution:** Use persistent data structures
- Space usage: $\mathcal{O}(m)$

Problem

What if we don't have or don't want to use persistent data structures?

Our contribution

Simple rebuilding strategy without persistent data structures

- Same time complexity: $\mathcal{O}(\sqrt{m})$ per operation
- Space usage: $\Theta(m\sqrt{m})$

1. ...and that leads to the space problem. If we're naive and just store \sqrt{m} *independent copies* of the data structure, one for each checkpoint...
2. ...and each copy can have up to m updates, our space usage explodes to $\Theta(m\sqrt{m})$.
3. ——— SKIP SLIDE ———
4. This is why Demaine et al. use persistent data structures. A persistent structure cleverly shares memory between versions, so all \sqrt{m} checkpoints can be stored efficiently in just $\mathcal{O}(m)$ total space.
5. ——— SKIP SLIDE ———
6. But this raises a practical problem: What if we don't have a persistent version of our data structure? Or what if it's just too complex to implement?
7. ——— SKIP SLIDE ———
8. This is our contribution. We propose a simple rebuilding strategy that *doesn't* require persistence.
9. We achieve the *same $\mathcal{O}(\sqrt{m})$ time* per operation.
10. The trade-off is that we go back to using $\Theta(m\sqrt{m})$ space, but we argue this is a practical trade-off for a much, much simpler implementation.

Starting point

- **Junior & Seabra's solution:** Semi-retroactive incremental MSF

- **Operations:**

- ▶ `add_edge(u, v, w, t)`: add edge at time t
- ▶ `get_msf(t)`: get MSF at time t

2025-10-26

Partial to full retroactivity

└ Starting point

Starting point

• Junior & Seabra's solution: Semi-retroactive incremental MSF

• Operations:

- `add_edge(u, v, w, t)`: add edge at time t
- `get_msf(t)`: get MSF at time t

1. Our starting point was the 2022 work by Junior and Seabra on a semi-retroactive MSF.
2. Remember, "semi-retroactive" means they can add edges at any time t in the past, and query the MSF at any time t , but they cannot *remove* edges.
3. ——— SKIP SLIDE ———
4. They also use a square-root decomposition. They maintain \sqrt{m} checkpoints, t_i , spaced \sqrt{m} updates apart.
5. ——— SKIP SLIDE ———
6. They use a set of data structures, D_i , where each D_i stores the incremental MSF containing all edges added *before* its checkpoint time t_i .
7. This approach gives them a final time complexity of $O(\sqrt{m} \log n)$ per operation.
8. However, their solution has some significant practical limitations...

Starting point

- **Junior & Seabra's solution:** Semi-retroactive incremental MSF
- **Operations:**
 - ▶ `add_edge(u, v, w, t)`: add edge at time t
 - ▶ `get_msf(t)`: get MSF at time t
- **Implementation:** Square-root decomposition
- **Checkpoints:** $t_i = i\sqrt{m}$ for $i = 1, \dots, \sqrt{m}$

Partial to full retroactivity

└ Starting point

1. Our starting point was the 2022 work by Junior and Seabra on a semi-retroactive MSF.
2. Remember, "semi-retroactive" means they can add edges at any time t in the past, and query the MSF at any time t , but they cannot *remove* edges.
3. ——— SKIP SLIDE ———
4. They also use a square-root decomposition. They maintain \sqrt{m} checkpoints, t_i , spaced \sqrt{m} updates apart.
5. ——— SKIP SLIDE ———
6. They use a set of data structures, D_i , where each D_i stores the incremental MSF containing all edges added *before* its checkpoint time t_i .
7. This approach gives them a final time complexity of $O(\sqrt{m} \log n)$ per operation.
8. However, their solution has some significant practical limitations...

Starting point

- **Junior & Seabra's solution:** Semi-retroactive incremental MSF
- **Operations:**
 - ▶ `add_edge(u, v, w, t)`: add edge at time t
 - ▶ `get_msf(t)`: get MSF at time t
- **Implementation:** Square-root decomposition
- **Checkpoints:** $t_i = i\sqrt{m}$ for $i = 1, \dots, \sqrt{m}$

2025-10-26

Starting point

- **Junior & Seabra's solution:** Semi-retroactive incremental MSF
- **Operations:**
 - ▶ `add_edge(u, v, w, t)`: add edge at time t
 - ▶ `get_msf(t)`: get MSF at time t
- **Implementation:** Square-root decomposition
- **Checkpoints:** $t_i = i\sqrt{m}$ for $i = 1, \dots, \sqrt{m}$
- **Data structures:** D_i contains edges before time t_i
- **Time:** $\mathcal{O}(\sqrt{m} \log n)$ per operation

2025-10-26

Partial to full retroactivity

└ Starting point

1. Our starting point was the 2022 work by Junior and Seabra on a semi-retroactive MSF.
2. Remember, "semi-retroactive" means they can add edges at any time t in the past, and query the MSF at any time t , but they cannot *remove* edges.
3. _____ SKIP SLIDE _____
4. They also use a square-root decomposition. They maintain \sqrt{m} checkpoints, t_i , spaced \sqrt{m} updates apart.
5. _____ SKIP SLIDE _____
6. They use a set of data structures, D_i , where each D_i stores the incremental MSF containing all edges added *before* its checkpoint time t_i .
7. This approach gives them a final time complexity of $\mathcal{O}(\sqrt{m} \log n)$ per operation.
8. However, their solution has some significant practical limitations...

Starting point

- **Junior & Seabra's solution:** Semi-retroactive incremental MSF
- **Operations:**
 - ▶ `add_edge(u, v, w, t)`: add edge at time t
 - ▶ `get_msf(t)`: get MSF at time t
- **Implementation:** Square-root decomposition
- **Checkpoints:** $t_i = i\sqrt{m}$ for $i = 1, \dots, \sqrt{m}$
- **Data structures:** D_i contains edges before time t_i
- **Time:** $\mathcal{O}(\sqrt{m} \log n)$ per operation

Problems with the Existing Static Approach

- **Fixed m :** Requires knowing the maximum sequence length (m) beforehand. Meaning that it cannot handle arbitrary growth or dynamic operation counts.

Our Dynamic Goal and Solution

Goal: Remove the **Fixed m** dependency while preserving time complexity.

- **Key Insight:** Introduce a ****dynamic rebuilding process**** to handle arbitrary growth.
- **Challenge:** Rebuilding \sqrt{m} checkpoints must be fast, avoiding complex persistent data structures.
- **Solution:** ****Reuse**** the existing data structures to efficiently reconstruct new checkpoints.

2025-10-26

Partial to full retroactivity

└ Limitations → Key Insight

Limitations → Key Insight

Problems with the Existing Static Approach

- **Fixed m :** Requires knowing the maximum sequence length (m) beforehand. Meaning that it cannot handle arbitrary growth or dynamic operation counts.

Our Dynamic Goal and Solution

Goal: Remove the **Fixed m** dependency while preserving time complexity.

- **Key Insight:** Introduce a ****dynamic rebuilding process**** to handle arbitrary growth.
- **Challenge:** Rebuilding \sqrt{m} checkpoints must be fast, avoiding complex persistent data structures.
- **Solution:** ****Reuse**** the existing data structures to efficiently reconstruct new checkpoints.

1. The existing approach is based on a static constraint: we must assume a fixed m .
2. This means you have to know the total number of operations in advance.
3. Crucially, they lack a mechanism for ****rebuilding****, making them unable to handle a growing or unknown number of operations.
4. Our goal is simple: remove the dependence on a fixed m while keeping the time efficiency.
5. Our key insight is to introduce a ****dynamic rebuilding process**** to handle growth.
6. The challenge is doing this efficiently. Rebuilding \sqrt{m} checkpoints non-persistently usually takes too long.
7. Our solution is a clever trick: we ****reuse**** the data structures already present in our system to reconstruct new checkpoints quickly.

Partial to full retroactivity

2025-10-26

└ Our solution - Rebuilding strategy

- **Key idea:** Reuse existing data structures during rebuilding
- **Rebuilding moments:** When $m = k^2$ (perfect square)

1. Here's our strategy. The key idea is to reuse the existing structures.
2. We trigger a rebuild whenever the total number of operations, m , becomes a perfect square, say k^2 .
3. ——— SKIP SLIDE ———
4. When we rebuild, we're going from k checkpoints to $k + 1$ new ones. Our strategy is:
 1. We create two new, *empty* structures, D'_0 and D'_1 .
 2. Then, we *reuse* our old structures: the old D_0 becomes the new D'_2 , the old D_1 becomes the new D'_3 , and so on. We shift them over by two spots.
 3. Finally, we just apply the "missing" updates to each of these reused structures to get them up to date for their new checkpoint times.
8. ——— SKIP SLIDE ———
9. The reason this is efficient is based on a key lemma we prove: The updates needed for the new D'_{i+2} are just a continuation of the updates from the old D_i . We don't have to restart from scratch.
10. ——— SKIP SLIDE ———
11. This rebuilding process takes $O(m \log n)$ time in total.

- **Key idea:** Reuse existing data structures during rebuilding
- **Rebuilding moments:** When $m = k^2$ (perfect square)
- **Strategy:**
 - ① Create new empty structures D'_0, D'_1
 - ② Reuse $D_i \rightarrow D'_{i+2}$ for $i = 0, \dots, k-1$
 - ③ Apply missing updates to each D'_i

2025-10-26

Partial to full retroactivity

└ Our solution - Rebuilding strategy

Our solution - Rebuilding strategy

- **Key idea:** Reuse existing data structures during rebuilding
- **Rebuilding moments:** When $m = k^2$ (perfect square)
- **Strategy:**
 - ① Create new empty structures D'_0, D'_1
 - ② Reuse $D_i \rightarrow D'_{i+2}$ for $i = 0, \dots, k-1$
 - ③ Apply missing updates to each D'_i

1. Here's our strategy. The key idea is to reuse the existing structures.
2. We trigger a rebuild whenever the total number of operations, m , becomes a perfect square, say k^2 .
3. ——— SKIP SLIDE ———
4. When we rebuild, we're going from k checkpoints to $k+1$ new ones. Our strategy is:
 1. We create two new, *empty* structures, D'_0 and D'_1 .
 2. Then, we *reuse* our old structures: the old D_0 becomes the new D'_2 , the old D_1 becomes the new D'_3 , and so on. We shift them over by two spots.
 3. Finally, we just apply the "missing" updates to each of these reused structures to get them up to date for their new checkpoint times.
8. ——— SKIP SLIDE ———
9. The reason this is efficient is based on a key lemma we prove: The updates needed for the new D'_{i+2} are just a continuation of the updates from the old D_i . We don't have to restart from scratch.
10. ——— SKIP SLIDE ———
11. This rebuilding process takes $O(m \log n)$ time in total.

- **Key idea:** Reuse existing data structures during rebuilding
- **Rebuilding moments:** When $m = k^2$ (perfect square)
- **Strategy:**
 - ① Create new empty structures D'_0, D'_1
 - ② Reuse $D_i \rightarrow D'_{i+2}$ for $i = 0, \dots, k-1$
 - ③ Apply missing updates to each D'_i

Key Lemma

Every update in D_i is within the first $(i+2)(k+1)$ updates in the new sequence.

└ Our solution - Rebuilding strategy

- **Key idea:** Reuse existing data structures during rebuilding
- **Rebuilding moments:** When $m = k^2$ (perfect square)
- **Strategy:**
 - ① Create new empty structures D'_0, D'_1
 - ② Reuse $D_i \rightarrow D'_{i+2}$ for $i = 0, \dots, k-1$
 - ③ Apply missing updates to each D'_i

Key Lemma

Every update in D_i is within the first $(i+2)(k+1)$ updates in the new sequence.

1. Here's our strategy. The key idea is to reuse the existing structures.
2. We trigger a rebuild whenever the total number of operations, m , becomes a perfect square, say k^2 .
3. ——— SKIP SLIDE ———
4. When we rebuild, we're going from k checkpoints to $k+1$ new ones. Our strategy is:
 1. We create two new, *empty* structures, D'_0 and D'_1 .
 2. Then, we *reuse* our old structures: the old D_0 becomes the new D'_2 , the old D_1 becomes the new D'_3 , and so on. We shift them over by two spots.
 3. Finally, we just apply the "missing" updates to each of these reused structures to get them up to date for their new checkpoint times.
5. ——— SKIP SLIDE ———
6. The reason this is efficient is based on a key lemma we prove: The updates needed for the new D'_{i+2} are just a continuation of the updates from the old D_i . We don't have to restart from scratch.
7. ——— SKIP SLIDE ———
8. This rebuilding process takes $O(m \log n)$ time in total.

Our solution - Rebuilding strategy

- **Key idea:** Reuse existing data structures during rebuilding
- **Rebuilding moments:** When $m = k^2$ (perfect square)
- **Strategy:**
 - 1 Create new empty structures D'_0, D'_1
 - 2 Reuse $D_i \rightarrow D'_{i+2}$ for $i = 0, \dots, k-1$
 - 3 Apply missing updates to each D'_i

Key Lemma

Every update in D_i is within the first $(i+2)(k+1)$ updates in the new sequence.

- **Time per rebuilding:** $\mathcal{O}(m \log n)$
- **Amortized cost:** $\mathcal{O}(\sqrt{m} \log n)$ per operation

Partial to full retroactivity

└ Our solution - Rebuilding strategy

1. Here's our strategy. The key idea is to reuse the existing structures.
2. We trigger a rebuild whenever the total number of operations, m , becomes a perfect square, say k^2 .
3. ——— SKIP SLIDE ———
4. When we rebuild, we're going from k checkpoints to $k+1$ new ones. Our strategy is:
 1. We create two new, *empty* structures, D'_0 and D'_1 .
 2. Then, we *reuse* our old structures: the old D_0 becomes the new D'_2 , the old D_1 becomes the new D'_3 , and so on. We shift them over by two spots.
 3. Finally, we just apply the "missing" updates to each of these reused structures to get them up to date for their new checkpoint times.
8. ——— SKIP SLIDE ———
9. The reason this is efficient is based on a key lemma we prove: The updates needed for the new D'_{i+2} are just a continuation of the updates from the old D_i . We don't have to restart from scratch.
10. ——— SKIP SLIDE ———
11. This rebuilding process takes $\mathcal{O}(m \log n)$ time in total.

Our solution - Rebuilding strategy

- **Key idea:** Reuse existing data structures during rebuilding
- **Rebuilding moments:** When $m = k^2$ (perfect square)
- **Strategy:**
 - 1 Create new empty structures D'_0, D'_1
 - 2 Reuse $D_i \rightarrow D'_{i+2}$ for $i = 0, \dots, k-1$
 - 3 Apply missing updates to each D'_i

Key Lemma

Every update in D_i is within the first $(i+2)(k+1)$ updates in the new sequence.

- **Time per rebuilding:** $\mathcal{O}(m \log n)$
- **Amortized cost:** $\mathcal{O}(\sqrt{m} \log n)$ per operation

2025-10-26

Rebuilding algorithm

- 1 $D'_0 \leftarrow \text{NEWINCREMENTALMSF}()$
- 2 $D'_1 \leftarrow \text{NEWINCREMENTALMSF}()$
- 3 For $i = 2$ to $k + 1$: $D'_i \leftarrow D_{i-2}$ ▷ reuse existing
- 4 For $i = 1$ to $k + 1$:
 - ▷ $p \leftarrow \text{KTH}(S, i(k + 1))$ ▷ $i(k + 1)$ th edge
 - ▷ $t'_i \leftarrow p.\text{time}$
 - ▷ $\text{ADDEDGES}(S, t_{i-2}, t'_i, D'_i)$
- 5 Return $k + 1, D', t'$

2025-10-26

Partial to full retroactivity

└ Rebuilding algorithm

Rebuilding algorithm

```


1  $D'_0 \leftarrow \text{NEWINCREMENTALMSF}()$ 
2  $D'_1 \leftarrow \text{NEWINCREMENTALMSF}()$ 
3 For  $i = 2$  to  $k + 1$ :  $D'_i \leftarrow D_{i-2}$  ▷ reuse existing
4 For  $i = 1$  to  $k + 1$ :
    •  $p \leftarrow \text{KTH}(S, i(k + 1))$  ▷  $i(k + 1)$ th edge
    •  $t'_i \leftarrow p.\text{time}$ 
    •  $\text{ADDEDGES}(S, t_{i-2}, t'_i, D'_i)$ 
5 Return  $k + 1, D', t'$ 
    
```

1. This slide shows the algorithm in more detail.
2. Lines 1 and 2 create the two new empty structures, D'_0 and D'_1 .
3. Line 3 is the reuse: we loop from $i = 2$ up to $k + 1$, and simply assign the old D_{i-2} to be the new D'_i . This is just a pointer swap; it's instant.
4. Line 4 is where the work happens. We loop through our new structures and apply the missing updates to each one, from its old checkpoint time t_{i-2} to its new checkpoint time t'_i .
5. ——— SKIP SLIDE ———
6. The diagram at the bottom visualizes this reuse. The new D'_0 and D'_1 are built from scratch, but all the others, D'_2 through D'_{k+1} , are just the old D_0 through D_{k-1} , shifted over and updated.
7. Again, this gives us the $O(\sqrt{m} \log n)$ amortized time...
8. ...but it requires $\Theta(m\sqrt{m})$ space, because we are storing these \sqrt{m} independent copies.

Rebuilding algorithm

- 1 $D'_0 \leftarrow \text{NEWINCREMENTALMSF}()$
- 2 $D'_1 \leftarrow \text{NEWINCREMENTALMSF}()$
- 3 For $i = 2$ to $k + 1$: $D'_i \leftarrow D_{i-2}$ ▷ reuse existing
- 4 For $i = 1$ to $k + 1$:
 - ▷ $p \leftarrow \text{KTH}(S, i(k + 1))$ ▷ $i(k + 1)$ th edge
 - ▷ $t'_i \leftarrow p.\text{time}$
 - ▷ $\text{ADDEDGES}(S, t_{i-2}, t'_i, D'_i)$
- 5 Return $k + 1, D', t'$

Original




New

$$D_i \rightarrow D'_{i+2}$$

2025-10-26

Partial to full retroactivity

Rebuilding algorithm



1. This slide shows the algorithm in more detail.
2. Lines 1 and 2 create the two new empty structures, D'_0 and D'_1 .
3. Line 3 is the reuse: we loop from $i = 2$ up to $k + 1$, and simply assign the old D_{i-2} to be the new D'_i . This is just a pointer swap; it's instant.
4. Line 4 is where the work happens. We loop through our new structures and apply the missing updates to each one, from its old checkpoint time t_{i-2} to its new checkpoint time t'_i .
5. ——— SKIP SLIDE ———
6. The diagram at the bottom visualizes this reuse. The new D'_0 and D'_1 are built from scratch, but all the others, D'_2 through D'_{k+1} , are just the old D_0 through D_{k-1} , shifted over and updated.
7. Again, this gives us the $O(\sqrt{m} \log n)$ amortized time...
8. ...but it requires $\Theta(m\sqrt{m})$ space, because we are storing these \sqrt{m} independent copies.

Our contribution

- **General transformation:** Partial \rightarrow Full retroactivity
- **No persistent data structures needed**
- **Same time complexity:** $\mathcal{O}(\sqrt{m})$ per operation
- **Space trade-off:** $\Theta(m\sqrt{m})$ vs $\mathcal{O}(m)$

2025-10-26

Partial to full retroactivity

Results

Results

Our contribution

- General transformation: Partial \rightarrow Full retroactivity
- No persistent data structures needed
- Same time complexity: $\mathcal{O}(\sqrt{m})$ per operation
- Space trade-off: $\Theta(m\sqrt{m})$ vs $\mathcal{O}(m)$

1. So, to summarize our contributions:
2. We've developed a general transformation to take a partially retroactive data structure and make it fully retroactive.
3. Crucially, our method *does not require persistent data structures*.
4. We match the $\mathcal{O}(\sqrt{m})$ slowdown per operation from the Demaine et al. paper...
5. ...at the cost of $\Theta(m\sqrt{m})$ space, which we argue is a very practical trade-off for simplicity.
6. ——— SKIP SLIDE ———
7. Applying this to our test case, we get a semi-retroactive MSF implementation.
8. It supports adding edges and querying the MSF at any time t in $\mathcal{O}(\sqrt{m} \log n)$ amortized time.
9. And, we have successfully removed the limitations from the previous work: our structure works *without* a fixed m or a fixed time range.

Our contribution

- **General transformation:** Partial \rightarrow Full retroactivity
- **No persistent data structures needed**
- **Same time complexity:** $\mathcal{O}(\sqrt{m})$ per operation
- **Space trade-off:** $\Theta(m\sqrt{m})$ vs $\mathcal{O}(m)$

Semi-retroactive MSF implementation

- **Operations:** `add_edge(u, v, w, t)`, `get_msf(t)`
- **Time:** $\mathcal{O}(\sqrt{m} \log n)$ per operation
- **Space:** $\Theta(m\sqrt{m})$
- **No fixed m or time range restrictions**

Results

Our contribution

- General transformation: Partial \rightarrow Full retroactivity
- No persistent data structures needed
- Same time complexity: $\mathcal{O}(\sqrt{m})$ per operation
- Space trade-off: $\Theta(m\sqrt{m})$ vs $\mathcal{O}(m)$

Semi-retroactive MSF implementation

- Operations: `add_edge(u, v, w, t)`, `get_msf(t)`
- Time: $\mathcal{O}(\sqrt{m} \log n)$ per operation
- Space: $\Theta(m\sqrt{m})$
- No fixed m or time range restrictions

1. So, to summarize our contributions:
2. We've developed a general transformation to take a partially retroactive data structure and make it fully retroactive.
3. Crucially, our method **does not require persistent data structures**.
4. We match the $\mathcal{O}(\sqrt{m})$ slowdown per operation from the Demaine et al. paper...
5. ...at the cost of $\Theta(m\sqrt{m})$ space, which we argue is a very practical trade-off for simplicity.
6. ——— SKIP SLIDE ———
7. Applying this to our test case, we get a semi-retroactive MSF implementation.
8. It supports adding edges and querying the MSF at any time t in $\mathcal{O}(\sqrt{m} \log n)$ amortized time.
9. And, we have successfully removed the limitations from the previous work: our structure works **without** a fixed m or a fixed time range.

Thank you!

Questions?

2025-10-26

Partial to full retroactivity

Thank you!

Questions?

1. Invite questions from the audience
2. Be prepared to answer questions about:
 3. * The rebuilding algorithm details
 4. * Space vs time trade-offs
 5. * Implementation challenges
 6. * Comparison with persistent data structures
 7. * Applications beyond MSF
8. Key points to emphasize if asked:
 9. * Our approach is simpler to implement
10. * Same time complexity as Demaine et al.
11. * No persistent data structure requirement
12. * General applicability to any partially retroactive structure
13. Thank the audience for their attention