

## TOILET OVERSERVICING - CLEANING/PAINTING

*EFFECTIVITY: ACFT MODEL(S) EMB-145*

### 1. General

- A. This section gives the procedures to do a general cleaning after a toilet overservicing.
- B. The procedures in this section are given in the sequence below. The tasks identified with (◆) are part of the Scheduled Maintenance Requirements Document (SMRD).

TASK NUMBER	DESCRIPTION	EFFECTIVITY
05-50-12-100-801-A	TOILET OVERSERVICING - CLEANING	ACFT MODEL(S) EMB-145

TASK 05-50-12-100-801-A

EFFECTIVITY: ACFT MODEL(S) EMB-145

## 2. TOILET OVERSERVICING - CLEANING

### A. General

- (1) This task gives the procedures to do a toilet overservicing cleaning.
- (2) Overservicing can be detected by observing a "blue streak" on the vent line side of the fuselage.

### B. References

REFERENCE	DESIGNATION
AMM MPP 06-41-02/100	-

### C. Zones and Accesses

ZONE	PANEL/DOOR	LOCATION
261	261BF	Lavatory compartment floor

### D. Tools and Equipment

ITEM	DESCRIPTION	PURPOSE	QTY
Standard tool	Vacuum Cleaner	Wet vac moisture	

### E. Auxiliary Items

Not Applicable

### F. Consumable Materials

Not Applicable

### G. Expandable Parts

Not Applicable

### H. Persons Recommended

QTY	FUNCTION	PLACE
1	Does the task	Lavatory Compartment

### I. Toilet Overservicing - Cleaning

SUBTASK 160-005-B

**WARNING: PREVENT CONTACT WITH THE LAVATORY FLUIDS DURING MAINTENANCE OR SERVICE IN THE LAVATORY AREA.**

- PUT ON SAFETY GOGGLES.
- PUT ON SAFETY CLOTHES.

- (1) Wet vac the over serviced moisture fallen on the lavatory and passenger cabin floor.

- (2) Remove the carpet, floor path emergency light system and floor panel 261BF of lavatory compartment (AMM MPP 06-41-02/100).
- (3) Wet vac and make sure that all excess of overserviced moisture possibly fallen through the toilet and passenger cabin floor panel, was drained.
- (4) Install the floor panel 261BF (AMM MPP 06-41-02/100), floor path emergency light system and carpet of lavatory compartment.

