



AIRCRAFT  
MAINTENANCE MANUAL

COCKPIT SEAT TRACKS - CLEANING/PAINTING

EFFECTIVITY: ALL

1. General

- A. This section gives the procedures to clean the tracks of the pilot and copilot seats.
- B. The procedures in this section are given in the sequence below. The tasks identified with (♦) are part of the Scheduled Maintenance Requirements Document (SMRD).

TASK NUMBER	DESCRIPTION	EFFECTIVITY
53-01-05-100-801-A	COCKPIT SEAT TRACKS - CLEANING	ALL



AIRCRAFT  
MAINTENANCE MANUAL

TASK 53-01-05-100-801-A

EFFECTIVITY: ALL

2. COCKPIT SEAT TRACKS - CLEANING

A. General

- (1) This task gives the procedures to clean the tracks of the pilot and copilot seats.

B. References

REFERENCE	DESIGNATION
TASK 25-11-01-220-001-A	-

C. Zones and Accesses

Not Applicable

D. Tools and Equipment

Not Applicable

E. Auxiliary Items

ITEM	DESCRIPTION	PURPOSE	QTY
Commercially available	Soft lint-free cloth	To clean the seat track	AR

F. Consumable Materials

SPECIFICATION (BRAND)	DESCRIPTION	QTY
MEP 13-073	Rhodiasolve E-23	AR

G. Expandable Parts

Not Applicable

H. Persons Recommended

QTY	FUNCTION	PLACE
1	Does the task	Cockpit RH side/Cockpit LH side

I. Preparation

*SUBTASK 841-002-A*

- (1) Make sure that the aircraft is safe for maintenance.

J. Cleaning of the Pilot and Copilot Seat Tracks

*SUBTASK 212-002-A*

- (1) Move the pilot and copilot seats to the maximum forward position, to clean the aft region of the seat tracks.



EMB145 – EMB135

AIRCRAFT  
MAINTENANCE MANUAL

**WARNING: BE CAREFUL WHEN YOU USE SOLVENTS BECAUSE THEY ARE A HEALTH AND FIRE HAZARD. USE SAFETY GOGGLES AND PROTECTIVE CLOTHING. DO NOT BREATHE THE SOLVENT GASES AND WORK IN A WELL VENTILATED AREA.**

- (2) With a cloth moist with RHODIASOLVE, clean the seat track.
- (3) With a plastic spatula, remove any material that can be in the track holes. Refer to Figure 701.
- (4) Move the pilot and copilot seats to the maximum aft position, to clean the forward region of seat tracks. Repeat the steps (2) and (3).

K. Follow-on

**SUBTASK 842-002-A**

- (1) Do a detailed inspection on the pilot and copilot seats to make sure that their locking pins lock in the tracks. Refer to TASK 25-11-01-220-001-A item (2).

