

## OIL FILTER ELEMENT - MAINTENANCE PRACTICES

*EFFECTIVITY: ALL*

1. General

- A. This section gives the procedures to replace and discard the oil filter element of the engine.
- B. These procedures are applicable to the LH and RH engines.
- C. The procedures in this section are given in the sequence below. The tasks identified with (◆) are part of the Scheduled Maintenance Requirements Document (SMRD).

TASK NUMBER	DESCRIPTION	EFFECTIVITY
79-23-01-960-801-A	OIL FILTER ELEMENT - REPLACEMENT	ALL

TASK 79-23-01-960-801-A

EFFECTIVITY: ALL

## 2. OIL FILTER ELEMENT - REPLACEMENT

### A. General

(1) Replace and discard the oil filter element as follows.

### B. References

REFERENCE	DESIGNATION
AMM TASK 71-12-01-000-801-A/400	ENGINE LOWER COWLING - OPENING
AMM TASK 71-12-01-400-801-A/400	ENGINE LOWER COWLING - CLOSING
Rolls-Royce MM CSP 34022	-

### C. Zones and Accesses

ZONE	PANEL/DOOR	LOCATION
413		LH Engine Lower Cowling
423		RH Engine Lower Cowling

### D. Tools and Equipment

Not Applicable

### E. Auxiliary Items

ITEM	DESCRIPTION	PURPOSE	QTY
Commercially available	Workstand	To get access to the work area	01

### F. Consumable Materials

Not Applicable

### G. Expandable Parts

Not Applicable

### H. Persons Recommended

QTY	FUNCTION	PLACE
01	Does the task	Engine work area

### I. Preparation

#### SUBTASK 841-003-A

(1) On the circuit breaker panel, open these circuit breakers and attach DO-NOT-CLOSE tags to them:

- POWERPLANT START 1/2.

- (2) Open the engine lower cowling (LH or RH). Refer to ( [AMM TASK 71-12-01-000-801-A/400](#)).

J. Discard Oil Filter Element

*SUBTASK 960-003-A*

- (1) Remove the oil filter element. Refer to the latest revision of Rolls-Royce MM CSP 34022.
- (2) Discard the oil filter element.
- (3) Install a new oil filter element. Refer to the latest revision of Rolls-Royce MM CSP 34022.

K. Follow-on

*SUBTASK 842-003-A*

- (1) Remove the DO-NOT-CLOSE tags and close these circuit breakers.
  - POWERPLANT START 1/2.
- (2) Close the lower cowling. Refer to ( [AMM TASK 71-12-01-400-801-A/400](#)).

