

COMPRESSOR SHAFT CONE - MAINTENANCE PRACTICES

EFFECTIVITY: ALL

1. General

- A. This section gives the procedures to replace the compressor shaft cone.
- B. The procedures in this section are given in the sequence below. The tasks identified with (◆) are part of the Scheduled Maintenance Requirements Document (SMRD).

<i>TASK NUMBER</i>	<i>DESCRIPTION</i>	<i>EFFECTIVITY</i>
72-35-01-960-801-A	COMPRESSOR SHAFT CONE - RE-PLACEMENT	ALL

TASK 72-35-01-960-801-A

EFFECTIVITY: ALL

2. COMPRESSOR SHAFT CONE - REPLACEMENT

A. General

(1) To do this task, refer to the instructions given in Rolls-Royce Engine Manual CSP 31010.

B. References

REFERENCE	DESIGNATION
AMM TASK 71-00-00-000-801-A/400	ENGINE - REMOVAL
AMM TASK 71-00-00-400-801-A/400	ENGINE - INSTALLATION
Rolls-Royce Engine Manual CSP 31010	-

C. Zones and Accesses

Not Applicable

D. Tools and Equipment

Not Applicable

E. Auxiliary Items

Not Applicable

F. Consumable Materials

Not Applicable

G. Expandable Parts

Not Applicable

H. Persons Recommended

QTY	FUNCTION	PLACE
4	Do the task	In the engine

I. Preparation

SUBTASK 841-002-A

(1) Remove the engine. Refer to [AMM TASK 71-00-00-000-801-A/400](#).

J. Replace Compressor Shaft Cone

SUBTASK 960-002-A

(1) Disassemble the compressor shaft cone. Refer to the latest revision of Rolls-Royce Engine Manual CSP 31010 (72-35-01).

(2) Discard the old compressor shaft cone.

(3) Assemble the new compressor shaft cone. Refer to the latest revision of Rolls-Royce Engine Manual CSP 31010 (72-35-01).

K. Follow-on

SUBTASK 842-002-A

- (1) Install the engine. Refer to [AMM TASK 71-00-00-400-801-A/400](#).

