

## ENGINE FIRE EXTINGUISHING BOTTLE CARTRIDGE - MAINTENANCE PRACTICES

*EFFECTIVITY: ALL*

### 1. General

- A. This section gives the procedures to replace/discard the cartridges of the engine fire extinguishing bottle.
- B. The procedures in this section are given in the sequence below. The tasks identified with (♦) are part of the Scheduled Maintenance Requirements Document (SMRD).

TASK NUMBER	DESCRIPTION	EFFECTIVITY
26-21-04-960-801-A ♦	ENGINE-FIRE EXTINGUISHING BOTTLE CARTRIDGES - REPLACEMENT/ DISCARD	ALL

TASK 26-21-04-960-801-A

EFFECTIVITY: ALL

## 2. ENGINE-FIRE EXTINGUISHING BOTTLE CARTRIDGES - REPLACEMENT/DISCARD

### A. General

(1) To do the task, refer to the instructions in Pacific Scientific CMM 26-20-202.

### B. References

REFERENCE	DESIGNATION
<a href="#">AMM TASK 26-21-02-000-801-A/400</a>	ENGINE FIRE-EXTINGUISHING BOTTLE - REMOVAL
<a href="#">AMM TASK 26-21-02-400-801-A/400</a>	ENGINE FIRE-EXTINGUISHING BOTTLE - INSTALLATION
Pacific Scientific CMM 26-20-202	-

### C. Zones and Accesses

ZONE	PANEL/DOOR	LOCATION
312	312AR	Tail cone compartment

### D. Tools and Equipment

Not Applicable

### E. Auxiliary Items

ITEM	DESCRIPTION	PURPOSE	QTY
Commercially available	Ladder	To get access to the tail cone	1

### F. Consumable Materials

Not Applicable

### G. Expandable Parts

Not Applicable

### H. Persons Recommended

QTY	FUNCTION	PLACE
1	Does the task	Tail cone compartment

### I. Preparation

SUBTASK 841-002-A

(1) Remove the engine fire-extinguishing bottle ([AMM TASK 26-21-02-000-801-A/400](#)).

J. Discard Engine Fire Extinguishing Bottle Cartridges

*SUBTASK 960-002-A*

**WARNING: THE CARTRIDGES ARE EXPLOSIVE DEVICES. ACCIDENTAL DETONATION OF A CARTRIDGE CAN CAUSE INJURY. DURING THE TASK, OBEY ALL SAFETY PRECAUTIONS GIVEN IN THE PACIFIC SCIENTIFIC CMM.**

- (1) Remove and discard the cartridges. Refer to the last revision of Pacific Scientific CMM 26-20-202.
- (2) Install the new cartridges. Refer to the last revision of Pacific Scientific CMM 26-20-202.

K. Follow-on

*SUBTASK 842-002-A*

- (1) Install the engine fire-extinguishing bottle ( [AMM TASK 26-21-02-400-801-A/400](#)).

