

## CVG ACTUATOR - ADJUSTMENT/TEST

*EFFECTIVITY: ALL*

1. General

- A. This section gives the procedure to do the electrical check of the CVG actuator.
- B. These procedures are applicable to the LH and RH engines.
- C. The procedures in this section are given in the sequence below. The tasks identified with (◆) are part of the Scheduled Maintenance Requirements Document (SMRD).

TASK NUMBER	DESCRIPTION	EFFECTIVITY
75-33-01-700-801-A	CVG ACTUATOR - ELECTRICAL CHECK	ALL

TASK 75-33-01-700-801-A

EFFECTIVITY: ALL

## 2. CVG ACTUATOR - ELECTRICAL CHECK

### A. General

- (1) To do the electrical check of the CVG actuator, obey the instructions in Rolls-Royce MM CSP 34022.

### B. References

REFERENCE	DESIGNATION
AMM MPP 71-00-00/200	- MAINTENANCE PRACTICES
AMM TASK 71-11-01-000-801-A/400	ENGINE UPPER COWLING - REMOVAL
AMM TASK 71-11-01-400-801-A/400	ENGINE UPPER COWLING - INSTALLATION
AMM TASK 71-12-01-000-802-A/400	ENGINE LOWER COWLING - REMOVAL
AMM TASK 71-12-01-400-802-A/400	ENGINE LOWER COWLING - INSTALLATION

### C. Zones and Accesses

ZONE	PANEL/DOOR	LOCATION
413	Lower Cowling	LH Engine
423	Lower Cowling	RH Engine
414	Upper Cowling	LH Engine
424	Upper Cowling	RH Engine

### D. Tools and Equipment

Not Applicable

### E. Auxiliary Items

ITEM	DESCRIPTION	PURPOSE	QTY
Commercially available	Workstand	To get access to the engine	01

### F. Consumable Materials

Not Applicable

### G. Expandable Parts

Not Applicable

### H. Persons Recommended

QTY	FUNCTION	PLACE
01	Does the task	Engine work area

I. Preparation

*SUBTASK 841-002-A*

**WARNING: MAKE SURE THE ENGINE START/STOP SWITCH IS IN THE “OFF” POSITION TO PREVENT AN ACCIDENTAL ENGINE OPERATION.**

- (1) On the circuit breaker panel, open these circuit breakers and attach DO-NOT-CLOSE tags to them:
  - START 1/2.
- (2) Remove the engine lower cowling ([AMM TASK 71-12-01-000-802-A/400](#)).
- (3) Remove the upper cowling ([AMM TASK 71-11-01-000-801-A/400](#)).

J. Electrical Check

*SUBTASK 760-002-A*

**WARNING: BEFORE YOU DO THE TASK OBEY THE SAFETY PRECAUTIONS GIVEN IN ( [AMM MPP 71-00-00/200](#)) TO PREVENT INJURY TO THE PERSONS AND DAMAGE TO THE MATERIAL.**

- (1) Do the electrical check of the CVG actuator. Refer to the last revision of Rolls-Royce MM CSP 34022.

K. Follow-on

*SUBTASK 842-002-A*

- (1) Install the upper cowling ([AMM TASK 71-11-01-400-801-A/400](#)).
- (2) Install the lower cowling. Refer to ([AMM TASK 71-12-01-400-802-A/400](#)).
- (3) Remove the DO-NOT-CLOSE tags and close the applicable circuit breakers.
  - START 1/2.
- (4) Refer to the Rolls-Royce MM CSP 34022 to do the related check procedures after an engine LRU maintenance procedure, as applicable.

