



AIRCRAFT  
MAINTENANCE MANUAL

FUEL NOZZLES - CLEANING/PAINTING

EFFECTIVITY: ALL

1. General

- A. This section gives the procedures to clean the fuel nozzles.
- B. The procedures in this section are given in the sequence below. The tasks identified with (♦) are part of the Scheduled Maintenance Requirements Document (SMRD).

TASK NUMBER	DESCRIPTION	EFFECTIVITY
73-11-10-100-801-A ♦	FUEL NOZZLES - CLEANING	ALL



AIRCRAFT  
MAINTENANCE MANUAL

TASK 73-11-10-100-801-A

EFFECTIVITY: ALL

2. FUEL NOZZLES - CLEANING

A. General

- (1) To clean the fuel nozzles, obey the instructions given in Rolls-Royce CMM CSP 34023 and MM CSP 34022.

B. References

REFERENCE	DESIGNATION
AMM TASK 71-11-01-000-801-A/400	ENGINE UPPER COWLING - REMOVAL
AMM TASK 71-11-01-400-801-A/400	ENGINE UPPER COWLING - INSTALLATION
Rolls-Royce CMM CSP 34023 73-12-12	-
Rolls-Royce CMM CSP 34023 73-12-15	-
Rolls-Royce IPC CSP 33002 73-11-10	-
Rolls-Royce MM CSP 34022 Task 73-11-10-000-801	-
Rolls-Royce MM CSP 34022 Task 73-11-10-400-801	-

C. Zones and Accesses

ZONE	PANEL/DOOR	LOCATION
413		LH Engine Lower Cowling
423		RH Engine Lower Cowling
412		LH Engine Upper Cowling
422		RH Engine Upper Cowling

D. Tools and Equipment

Not Applicable

E. Auxiliary Items

ITEM	DESCRIPTION	PURPOSE	QTY
Commercially available	Workstand	To get access to the engine	1

F. Consumable Materials

Not Applicable

G. Expandable Parts

Not Applicable

H. Persons Recommended

QTY	FUNCTION	PLACE
1	Does the task	Engine



EMB145 – EMB135

AIRCRAFT  
MAINTENANCE MANUAL

I. Preparation

SUBTASK 841-002-A

- (1) On the circuit breaker panel, open these circuit breakers and attach a DO-NOT-CLOSE tag to them:
  - START 1/2.
- (2) Remove the upper cowling ([AMM TASK 71-11-01-000-801-A/400](#)) to get access to the fuel nozzles.
- (3) Remove the fuel nozzles. Refer to the latest revision of Rolls-Royce MM CSP 34022 Task 73-11-10-000-801.

J. Clean Fuel Nozzles

SUBTASK 130-002-A

- (1) Clean the fuel nozzles. Refer to the latest revision of Rolls-Royce CMM CSP 34023 73-12-12 or Rolls-Royce CMM CSP 34023 73-12-15.

NOTE: Refer to Rolls-Royce IPC CSP 33002 73-11-10 for configuration.

K. Follow-on

SUBTASK 842-002-A

- (1) Install the fuel nozzles. Refer to the latest revision of Rolls-Royce MM CSP 34022 Task 73-11-10-400-801.
- (2) Install the upper cowling ([AMM TASK 71-11-01-400-801-A/400](#)).
- (3) On the circuit breaker panel, close these circuit breakers and remove the DO-NOT-CLOSE tag from them:
  - START 1/2.

