

## DOME LIGHT REFLECTOR - REMOVAL/INSTALLATION

*EFFECTIVITY: ALL*

### 1. General

- A. This section gives the procedures to remove/install the pilot and copilot dome light reflectors.
- B. The pilot dome light is installed on the left side of the cockpit ceiling. The copilot dome light is installed on the right side of the cockpit ceiling.
- C. The procedures in this section are given in the sequence below. The tasks identified with (♦) are part of the Scheduled Maintenance Requirements Document (SMRD).

TASK NUMBER	DESCRIPTION	EFFECTIVITY
33-11-02-000-801-A	DOME LIGHT REFLECTOR - REMOVAL	ALL
33-11-02-400-801-A	DOME LIGHT REFLECTOR - INSTALLATION	ALL

TASK 33-11-02-000-801-A

*EFFECTIVITY: ALL*

## 2. DOME LIGHT REFLECTOR - REMOVAL

### A. General

(1) This task gives the procedures to remove the pilot and copilot dome light reflector.

### B. References

REFERENCE	DESIGNATION
<a href="#">AMM TASK 25-12-01-000-801-A/400</a>	COCKPIT LINING - REMOVAL

### C. Zones and Accesses

Not Applicable

### D. Tools and Equipment

Not Applicable

### E. Auxiliary Items

Not Applicable

### F. Consumable Materials

Not Applicable

### G. Expandable Parts

Not Applicable

### H. Persons Recommended

QTY	FUNCTION	PLACE
1	Does the task	Cockpit ceiling

### I. Preparation

*SUBTASK 841-002-A*

(1) Make sure the DOME switch, on the overhead panel, is in the OFF position.

### J. Removal ([Figure 401](#))


*SUBTASK 020-002-A*

- (1) Remove the ceiling lining panel ( [AMM TASK 25-12-01-000-801-A/400](#)).
- (2) Disconnect the electrical connections (2).
- (3) Release and remove the reflector protective lens (3).
- (4) Remove the screws (4), washers and nuts (5) that attach the reflector (6) to the ceiling lining panel (1).
- (5) Remove the reflector (6).

EFFECTIVITY: ALL

Dome Light Reflector - Removal/Installation

Figure 401



145AMM330058.MCE A

TASK 33-11-02-400-801-A

EFFECTIVITY: ALL

### 3. DOME LIGHT REFLECTOR - INSTALLATION

#### A. General

(1) This task gives the procedures to install the pilot and copilot dome light reflector.

#### B. References

REFERENCE	DESIGNATION
<a href="#">AMM TASK 33-11-00-700-801-A/500</a>	COCKPIT LIGHTS - OPERATIONAL TEST
<a href="#">AMM TASK 33-11-01-400-801-A/400</a>	DOME LIGHT LAMP - INSTALLATION

#### C. Zones and Accesses

Not Applicable

#### D. Tools and Equipment

Not Applicable

#### E. Auxiliary Items

Not Applicable

#### F. Consumable Materials

Not Applicable

#### G. Expandable Parts

Not Applicable

#### H. Persons Recommended

QTY	FUNCTION	PLACE
1	Does the task	Cockpit ceiling

#### I. Installation (Figure 401)

##### *SUBTASK 420-002-A*

- (1) Put the reflector (6) in position.
- (2) Tighten the screws (4), washers and nuts (5) which attach the reflector (6) to the ceiling lining panel (1).
- (3) Make the electrical connections (2) again.
- (4) Install a lamp (7) ([AMM TASK 33-11-01-400-801-A/400](#)), if it is not installed.
- (5) Install the reflector lens (3).

#### J. Follow-on

##### *SUBTASK 842-002-A*

- (1) Do the operational test of the light dome ( [AMM TASK 33-11-00-700-801-A/500](#)).