



**POLITECNICO**  
MILANO 1863

**Analysis and validation of spaceborne  
synthetic imagery using a Vision-Based pose  
initialization algorithm for non-cooperative  
spacecrafts**

**Francescodario Cuzzocrea**  
April 24, 2021



# Introduction

# Introduction

## Pose determination for close range proximity operations using monocular camera

Purposes:

- Formation Flying (FF)
- On-Orbit Servicing (OOS)
- Active Debris Removal (ADR)

Advantages:

- |               |              |
|---------------|--------------|
| • Reliability | • Low weight |
| • Simplicity  | • Low power  |

Challenge




Estimate the **pose** of an **uncooperative** target from a **monocular** image

# Problem Statement

## Monocular algorithm requirements


- Target 3D model availability
- On-Board real-time execution
- Robustness to illumination
- Robustness to background
- Robustness to variability of pose




- Need a **representative** data-set to develop image processing algorithms
- A lack of realism can lead to **wrong** assumptions and thus **incoherent** results

# Available Solutions


ESA PANGU



SPEED DATA-SET



AIRBUS SURRENDER



URSO DATA-SET



## Data-set requirements

- Emerges the need for a tool capable of rendering images for CV algorithms training which must:
  - be affordable for small research center or small companies
  - be capable of rendering different kinds S/C
  - be able to accomodate solar-system sized scenes
  - be able to also render composite background

**Aim of the thesis** → Develop a tool capable of producing a data-set of images **representative** of in-orbit real operative conditions and use them to implement and test a State-of-Art pose initialization algorithm


# Synthetic Image Generation

# Ray Tracing

## POV-Ray represents a viable solution

→ It simulates the physics of light!


- Support meshes for objects
- Customizable textures support
- Customizable optical properties
- Customizable light properties
- Customizable camera parameters
- Accepted by ESA in past studies



→ Noise can be modeled and added *a posteriori* to enhance fidelity.

## Earth and Light Modeling


- Use three different layers to differentiate optical parameters and textures for seasonality variations
- Include 25 km tick atmosphere with scattering properties




Terrain



Landmask



Clouds




- The Sun has been modeled using POV-Ray **area\_light** feature

## 3D Model of the Spacecraft


→ Based on the TANGO spacecraft from the PRISMA mission to perform comparison with SPEED



CAD



Blender



POV-Ray

- CAD is created using Autodesk Inventor
- Imported in Blender to exploit POV-Ray add-on
- Textures are applied
- Optical parameters are defined
- SDL code is refactored for MATLAB implementation

→ Process has to be carried out only one time per S/C

## Simulate a pin-hole camera


→ POV-Ray allows to set camera aperture angle  $\alpha$  and Aspect Ratio:

$$CCD_{size} = d_u \cdot N_u$$

$$A.R. = \frac{N_u}{N_v}$$

$$\alpha = 2 \cdot \arctan \left( \frac{CCD_{size}}{2 \cdot f_x} \right)$$


$N_u$	Number of horizontal pixels
$N_v$	Number of vertical pixels
$f_x$	Horizontal focal length
$d_u$	Horizontal pixel length




- Under the assumption of square CCD sensor having square pixels
- If camera model is known, distortion can be added in post-processing

## Add Gaussian white noise and speckle noise

→ To enhance the fidelity noise is added to the image



Normal



Noisy

Gaussian:  $\sigma^2 = 0.003$

Speckle:  $\sigma^2 = 0.004$

## Simulink Model




- Simulate uncontrolled behavior on LEO orbit
- Easily extendable to include controlled behavior too
- Chaser constrained to be between 3 to 18 meters far from the target
- Extendable to simulate precise chaser approach

## MATLAB Functions

- Write .pov SDL files for each image
- Annotate ground truth pose for each image
- Sets relevant POV-Ray options and run it
- Can re-parse ground truth pose for each image

# Results

## Samples




**WARNING:** Custom POV-Ray version needed to replicate results

# The SVD Architecture for Pose Initialization

# Introduction

## Solve the pose initialization problem

### → General architecture




### → Enhance current State-of-the-art

- Introduces WGE technique which allows to distinguish S/C from background and allows to determine a ROI
- Uses 2D/3D feature groups to solve feature correspondence problem


## Image processing subsystem - 1

### → Weak Gradient Eliminator

Most of the gradient intensities are weak and corresponds to the feature in the background or on the spacecraft surface → Threshold normalized gradient



Original image




Normal gradient



Histogram



Tresholding




Found by limiting CDFs of the vertical and horizontal gradient of WGE filtered image

# The SVD Architecture for Pose Initialization

## Feature-based pose estimation


15/28

### Image processing subsystem - 2



- Two streams of features are extracted using Hough transform:
  - WGE stream
  - S&H stream
- Multiple truncated edges are merged into one line

- The knowledge of the ROI allows to tune Hough hyperparameters adaptively to obtain desired behavior
- Edges outside the ROI are rejected



## Feature-based pose estimation

### Image processing subsystem - 3

#### → Custom implementation


- ROI it's enlarged by adding the 5% of the mean edge length of the detected ROI to not penalize images presenting a black background
- Prior applying Hough transform to the Sobel image, to eliminate the pixel chunks belonging to smaller reflective elements from the output of Hough, all connected components (objects) that have fewer than P pixels from the input binary image are removed
- The edge merging procedure is applied to both streams

# The SVD Architecture for Pose Initialization


## Feature-based pose estimation

17/28

### Image processing subsystem - 4




WGE stream




S&H stream




WGE merge



S&H merge



WGE + S&H





Merge stream

## Perceptual Grouping

→ Allows to reduce the search space of the correspondence problem

2D perceptual groups are defined on the basis of some geometrical constraints







Carried out on a wireframe model too by applying 3D geometry definitions instead of 2D ones

# Result

## Successful pose initialization

- Obtained using P3P solver coupled with a RANSAC algorithm for outlier rejection instead of ePnP




Figures are showing the map superposed to the image and the 3D camera pose in map coordinates

# Results

# Qualitative Assessment

## SPEED VS Implemented Tool


→ Speed



Unfiltered Image




Image Histogram



Sobel Image

→ Implemented Tool



Unfiltered Image





Image Histogram




Sobel Image

# Qualitative Assessment

## SPEED VS Implemented Tool

→ Speed



Unfiltered Image





Image Histogram



Sobel Image

→ Implemented Tool



Unfiltered Image





Image Histogram




Sobel Image

## Failures

ROI Detection → Due to composite background

Implemented Tool




Detected ROI



Thresholded Gradient

SPEED



Detected ROI




Thresholded Gradient

## Rotational and translational errors


### Translational Error

→ Mean error: 0.2506 m



### Rotational Error

→ Mean error: 0.0528°




# SVD Algorithm

## Errors WRT inter-spacecraft distance


### Translational Error

→ Increases with distance




### Rotational Error

→ No recognizable trend



## Camera axis error

→ No preferred axis



# Conclusions

## Image Generation Tool

- Image toolbox is fully automated
- Controlled and uncontrolled behavior can be simulated as well as well as approach
- Generated images are compatible with data-sets claimed to be representative by the scientific community

## SVD Algorithm

- Successfully tested SVD algorithm
- Results seems to be promising

## Image Generation Tool

- Use better textures for the S/C and the Earth
- Use a more rigorous method to set optical parameters
- Improve noise model
- Patch POV-Ray code to allow GPU cores usage for rendering

## SVD Algorithm

- Employ separated Hough transforms to detect different geometric shapes
- Improve edge detection procedure (solar panels, distance are an issue)
- Compare different pose solvers
- Hardware-in-the-loop experiments to evaluate the computational time on real H/W.

# The End




*Thanks for your attention!*

*If you have any question, feel free to ask!*

# Additional Material

## Earth Modeling

→ Binary image Comparison



## Light Modeling


→ The Sun can be modeled using POV-Ray **area\_light** feature:

- it creates a cluster of point-like light sources distributed on a disc
- the radius of the disc is set to the radius of the Sun, and placed at the exact distance which the Sun has from the Earth
- the **orient** option makes every object see the Sun's disc as oriented toward it, from any position around it

## 3D Model of the Spacecraft

→ Based on the TANGO spacecraft from the PRISMA mission:




- 570 mm x 759 mm solar panel
- 560 mm x 550 mm x 300 mm body
- 4x 204 mm antennas



## Reference Frames and Ground Truth Pose


→ POV-Ray by default works using a Left Handed Coordinate System

- Flip it to use a Right Handed Coordinate System
- Compute camera attitude by the knowledge of camera position and camera looking direction
- Compute ground truth pose by knowledge of camera attitude and target attitude




## Bounding issue

This system compartmentalizes all finite objects in a scene into invisible rectangular boxes that are arranged in a tree-like hierarchy. Before testing the objects within the bounding boxes the tree is descended and only those objects whose bounds are hit by a ray are tested.




Bounding on



Bounding off

## Pose Problem

## Pose estimation problem



2D/3D true perspective equations

$$\mathbf{r}_C = [x_C \quad y_C \quad z_C]^T = A_{TC} q_B + \mathbf{t}_C$$


$$\mathbf{p} = \left[ \frac{x_C}{z_C} f_x + C_x, \frac{y_C}{z_C} f_y + C_y \right]$$

→ (A<sub>TC</sub>, t<sub>C</sub>) ←


- Highly non linear and can have  $\infty$  solutions if underconstrained
- No *a priori* knowledge of the correspondence between q<sub>B</sub> and p
- Image has to be corrected for pixel's non-quadratism and lens distortion

## Image processing subsystem

ROI it's enlarged by adding the 5% of the mean edge length of the detected ROI to not penalize images having a black background from a too strict thresholding of the normalized gradient.



Detected ROI



Enlarged ROI

## Failures


Edge Detection → Due to solar panels or distance



WGE Stream



S&amp;H Stream



Merging streams



Thresholded Gradient



WGE Stream



S&amp;H Stream



Merging Streams