

## ch1: Markov Decision Process (static concepts)

state(S) - policy(pi) - action(A) - model(p) - state(S')

reward(R') from transition

return(G) from trajectory

value(V+Q)

策略与价值:

reward、return、value, 用来评估一个策略的好坏。

策略与价值一一对应。

价值比较, 策略比较, 策略改进定理。

强化学习的终极目标, 求取最优策略,

最优策略不唯一, 最优价值唯一。

r线性变换, V+Q线性变换, 改变最优价值, 不改变greedy最优策略。

最优动作价值, 意味着选取这个动作, 未来回报的期望最大。

迭代时, 最优策略可能已经稳定了, 但是对应的最优价值还没稳定。

从终止状态反向迭代更新价值, 速度更快。但是哪里是终止状态? 上帝视角。

$$p(s', r | s, a) = \Pr \{S_t = s', R_t = r | S_{t-1} = s, A_{t-1} = a\}$$

$$\sum_{s' \in S} \sum_{r \in R} p(s', r | s, a) = 1$$

$$p(s' | s, a) = \sum_{r \in R} p(s', r | s, a)$$

$$r(s, a) = \sum_{s' \in S} \sum_{r \in R} (p(s', r | s, a) * r)$$

## ch2: Bellman Equations (static relations)

实质：描述状态值之间的静态关系（单项形式、矩阵形式）

求解：（矩阵求逆、数值迭代）—（policy-evaluation）

$$\begin{aligned}v_{\pi}(s) &= E_{\pi}[G_t \mid S_t = s] \\&= E_{\pi}[R_{t+1} + \gamma G_{t+1} \mid S_t = s] \\&= \sum_{a \in A} \pi(a \mid s) \sum_{s', r} p(s', r \mid s, a) * [r + \gamma E_{\pi}[G_{t+1} \mid S_{t+1} = s']] \\&= \sum_{a \in A} \pi(a \mid s) \sum_{s', r} p(s', r \mid s, a) * [r + \gamma v_{\pi}(s')] \\&= \sum_{a \in A} (\pi(a \mid s) * q_{\pi}(s, a))\end{aligned}$$

$$\begin{aligned}q_{\pi}(s, a) &= E_{\pi}[G_t \mid S_t = s, A_t = a] \\&= E_{\pi}[R_{t+1} + \gamma G_{t+1} \mid S_t = s, A_t = a] \\&= \sum_{s', r} p(s', r \mid s, a) * [r + \gamma E_{\pi}[G_{t+1} \mid S_{t+1} = s']] \\&= \sum_{s', r} p(s', r \mid s, a) * [r + \gamma v_{\pi}(s')] \\&= \sum_{s', r} p(s', r \mid s, a) * \left[ r + \gamma \sum_{a' \in A} (\pi(a' \mid s') * q_{\pi}(s', a')) \right]\end{aligned}$$

policy-comparison:

$$\pi' \geq \pi \quad \longleftrightarrow \quad v_{\pi'}(s) \geq v_{\pi}(s) \quad \forall s \in S$$

policy-improvement:

$$E_{\pi'} [q_{\pi}(s, \pi'(s))] \geq v_{\pi}(s) = E_{\pi} [q_{\pi}(s, \pi(s))] \quad \forall s \in S$$

Bellman Optimal Equations:

$$\begin{aligned} v_*(s) &= \max_{\pi} v_{\pi}(s) \\ &= \max_{\pi} (r_{\pi} + \gamma P_{\pi} v) \\ &= \max_{a \in A} q_{\pi^*}(s, a) \quad \forall s \in S \end{aligned}$$

Contraction Mapping Theorem (迭代收敛至唯一不动点)  
贝尔曼最优方程的收缩迭代过程，即是value iteration算法

## ch3: Dynamic Programming (dynamics with model p)

(1) Value Iteration:

$$v_{k+1} = \max_{\pi} (r_{\pi} + \gamma P_{\pi} v_k)$$

Policy Update:

$$\pi_{k+1} = \arg \max_{\pi} (r_{\pi} + \gamma P_{\pi} v_k)$$

Value Update:

$$v_{k+1} = r_{\pi_{k+1}} + \gamma P_{\pi_{k+1}} v_k$$

(2) Policy Iteration:

Policy Evaluation: (matrix solution vs. iteration solution)

$$v_{\pi_k} = r_{\pi_k} + \gamma P_{\pi_k} v_{\pi_k}$$

Policy Improvement:

$$\pi_{k+1} = \arg \max_{\pi} (r_{\pi} + \gamma P_{\pi} v_k)$$

(3) Turncated Iteration:

## **1 Monte Carlo**

(1) 基于数据 trajectory 的价值估计、策略改进:

## **2 Temporal Difference**

(1) 基于数据 transition 的价值估计、策略改进: