

# Dynamics for Multi-Agent System Coordination in Noisy and Stochastic Environments



Francesco d'Amore  
COATI team

Based on joint work with [A. Clementi](#), [G. Giakkoupis](#), [E. Natale](#), and [I. Ziccardi](#)

Hamburg University  
09 May 2022

# Table of contents

1. Distributed computing tasks in biological systems
2. Lévy walks and the ANTS problem
3. Opinion dynamics for the consensus problem with uniform communication noise

# Table of contents

1. Distributed computing tasks in biological systems
2. Lévy walks and the ANTS problem
3. Opinion dynamics for the consensus problem with uniform communication noise

# Natural algorithms

Algorithms designed by **evolution** over millions of years [Chazelle, SODA 2009]

- migrating geese
- flocking cranes
- fish baitball
- prey-predator systems
- synchronously flashing fireflies



"Georgia Aquarium Fish" by Mike Johnston

# Natural algorithms

The **computational lens** help catching **behavioral properties** of biological systems

- bird flocking convergence time [Chazelle, SODA 2009]
- slime mold computing shortest paths [Bonifaci et al., Journal of Theoretical Biology 2012]



slime mold



flocking birds

"Flocking birds" by davepatten, CC BY-NC-SA 2.0.

# Natural algorithms

The **computational lens** help catching **behavioral properties** of biological systems

- bird flocking convergence time [Chazelle, SODA 2009]
- slime mold computing shortest paths [Bonifaci et al., Journal of Theoretical Biology 2012]

On the other hand, biological systems help **designing** new **algorithms** for well-known problems

- distributed **maximal independent set** from the fly's nervous system [Afek et al., SCIENCE 2011]



slime mold



flocking birds

"Flocking birds" by davepatten, CC BY-NC-SA 2.0.



# Distributed computing tasks

Often, systems of **interacting agents** performing **collective tasks**

Other than MIS and bird flocking:

- Information spreading: schooling fish [Rosenthal et al., PNAS 2015]
- Reaching agreement: molecules [Carrol, Nature Immunology 2004], bacteria [Bassler, Cell 2002], social insects [Franks et al., 2002] (e.g. bees [Reina et al., Physical Review E 2017])
- Collective search: ants and bees [Feinermant et Korman, Distributed Computing 2017]



foraging ants



"The Blueberry Hunters" by bob in swamp, CC BY 2.0.

# Table of contents

1. Distributed computing tasks in biological systems
2. Lévy walks and the ANTS problem
3. Opinion dynamics for the consensus problem with uniform communication noise



# The Lévy walk



## Lévy walk (informal):

*A Lévy walk is a random walk whose step-length density distribution is proportional to a power-law, namely, for each  $d \in \mathbb{R}^+$ ,  $f(d) \sim 1/d^\alpha$ , for some  $\alpha > 1$*

**Note:** the **speed** of the walk is **constant**

# Movement models and foraging theory

Lévy walks are used to model **movement patterns** [\[Reynolds, Biology Open 2018\]](#)

Examples:

- T cells within the brain
- swarming bacteria
- midge swarms
- termite broods
- schools of fish
- Australian desert ants
- a variety of molluscs



*Rhytidoponera mayri* workers. Credit: Associate Professor Heloise Gibb, La Trobe University

# Movement models and foraging theory

Lévy walks are used to model **movement patterns** [\[Reynolds, Biology Open 2018\]](#)

Examples:

- T cells within the brain
- swarming bacteria
- midge swarms
- termite broods
- schools of fish
- Australian desert ants
- a variety of molluscs



Rhytidoponera mayri workers. Credit: Associate Professor Heloise Gibb, La Trobe University


Widely employed in the **foraging theory**

# Lévy walk optimality

## Foraging theory

- distribution of food locations in  $\mathbb{R}^n$
- uninformed agent searching for food

[Viswanathan et al., Nature 1999]: Lévy walk with exponent  $\alpha = 2$  is optimal in any dimension, with some assumptions



*maximum expected food discovery rate*


# Lévy walk optimality

## Foraging theory

- distribution of **food locations** in  $\mathbb{R}^n$
- **uninformed agent** searching for food

[Viswanathan et al., Nature 1999]: Lévy walk with exponent  $\alpha = 2$  is **optimal** in **any dimension**, with some assumptions

*maximum expected food discovery rate*



## Other search problems

- a **target** in the bidimensional **thorus**  $\mathbb{T}$
- **uninformed agent** searching for it

[Guinard et Korman, Sciences Advances 2021]: (truncated) Lévy walk with exponent  $\alpha = 2$  is **optimal**

*as fast as possible*



# The Lévy flight foraging hypothesis

Formulation of an evolutionary hypothesis

**The Lévy flight foraging hypothesis** [Viswanathan et al., Physics of Life Reviews 2008]: since Lévy flights/walks **optimize random searches**, **biological organisms** must have therefore **evolved** to exploit Lévy flights/walks

# The Lévy flight foraging hypothesis

Formulation of an evolutionary hypothesis

**The Lévy flight foraging hypothesis** [Viswanathan et al., Physics of Life Reviews 2008]: since Lévy flights/walks **optimize random searches**, **biological organisms** must have therefore **evolved** to exploit Lévy flights/walks

Seems there is a **special exponent**  $\alpha = 2$



# The Lévy flight foraging hypothesis

Formulation of an evolutionary hypothesis

**The Lévy flight foraging hypothesis** [Viswanathan et al., Physics of Life Reviews 2008]: since Lévy flights/walks **optimize random searches**, **biological organisms** must have therefore **evolved** to exploit Lévy flights/walks

Seems there is a **special exponent**  $\alpha = 2$

We test **this hypothesis** by focusing on a **distributed search problem**:

- the **ANTS** (Ants Nearby Treasure Search) problem



# The ANTS problem

Introduced by [\[Feinerman et al., PODC 2012\]](#):

- Setting:
- $k$  (mutually) **independent agents** start moving on  $\mathbb{Z}^2$  from the origin
  - time is **synchronous** and marked by a global clock
  - one special node  $\mathcal{P} \in \mathbb{Z}^2$ , the **target**, placed by an **adversary** at unknown (Manhattan) distance  $\ell$  from the origin

# The ANTS problem

Introduced by [Feinerman et al., PODC 2012]:

- Setting:
- $k$  (mutually) **independent agents** start moving on  $\mathbb{Z}^2$  from the origin
  - time is **synchronous** and marked by a global clock
  - one special node  $\mathcal{P} \in \mathbb{Z}^2$ , the **target**, placed by an **adversary** at unknown (Manhattan) distance  $\ell$  from the origin

**Task:** **find** the target **as fast as possible**

**Lower bound:** for any  $k \geq 1$ , and for **any search algorithm**  $\mathcal{A}$ , the **hitting time** to find  $\mathcal{P}$  is  $\Omega(\ell^2/k + \ell)$  both with **constant probability** and in **expectation**




Image by OpenClipart-Vectors from Pixabay

# Our contributions

Based on the work [\[Clementi et al., PODC 2021\]](#)

(i) we give the **first definition** of Lévy walk in the **discrete setting** in  $\mathbb{Z}^2$ , which is **natural** and **time-homogeneous**

# Our contributions

Based on the work [\[Clementi et al., PODC 2021\]](#)

(i) we give the **first definition** of Lévy walk in the **discrete setting** in  $\mathbb{Z}^2$ , which is **natural** and **time-homogeneous**

(ii) to the best of our knowledge, we give the **first analysis** of the **hitting time** distribution of  $k$  parallel walks

# Our contributions

Based on the work [\[Clementi et al., PODC 2021\]](#)

- (i) we give the **first definition** of Lévy walk in the **discrete setting** in  $\mathbb{Z}^2$ , which is **natural** and **time-homogeneous**
- (ii) to the best of our knowledge, we give the **first analysis** of the **hitting time** distribution of  $k$  parallel walks
- (iii) we show how the Lévy walks can be employed to give a natural, **almost-optimal** solution to the **ANTS problem** (no advice, no communication)

# Our contributions

(i) DEFINITION OF DISCRETE LÉVY WALK

(ii) ANALYSIS OF THE PARALLEL HITTING TIME

(iii) ALGORITHM FOR THE ANTS PROBLEM



# Defining the discrete Lévy walk


Two choices to make:

- define the **jump-length** distribution
- define a **notion** of **approximating a line-segment**


**Jump length distribution**

- $d = 0$  with probability  $1/2$
- $d \geq 1$  with probability  $c_\alpha/d^\alpha$

**Approximation of a line-segment**



# Discrete Lévy walk



..... direction chosen  
— path performed

Six jumps of a discrete  
Lévy walk

Let  $\alpha > 1$  be a real value

**Lévy walk:** the agent

- chooses a **distance**  $d \in \mathbb{N}$  as follows:  $d = 0$  w.p.  $1/2$ , and  $d \geq 1$  w.p.  $c_\alpha/d^\alpha$
- chooses a **destination** u.a.r. among those at distance  $d$
- walks along an **approximating path** for  $d$  steps, one edge at a time, crossing  $d$  nodes
- repeats** the procedure

# Our contributions





(i) DEFINITION OF DISCRETE LÉVY WALK

(ii) ANALYSIS OF THE PARALLEL HITTING TIME

(iii) ALGORITHM FOR THE ANTS PROBLEM

# $\alpha$ -behavior of Lévy walks

- $1 < \alpha \leq 2$  ballistic diffusion (fig.s A and B)
- $2 < \alpha < 3$  super diffusion (fig. C)
- $3 \leq \alpha$  normal diffusion (fig. D)



# Intuitive explanation

## Expected jump-length

- $1 < \alpha \leq 2$ :  $\int_1^\infty x^{-\alpha+1} dx = \infty$
- $2 < \alpha$ :  $\int_1^\infty x^{-\alpha+1} dx = \Theta(1)$

## Jump-length second moment

- $1 < \alpha \leq 3$ :  $\int_1^\infty x^{-\alpha+2} dx = \infty$
- $3 < \alpha$ :  $\int_1^\infty x^{-\alpha+2} dx = \Theta(1)$

# Intuitive explanation

## Expected jump-length

- $1 < \alpha \leq 2$ :  $\int_1^\infty x^{-\alpha+1} dx = \infty$
- $2 < \alpha$ :  $\int_1^\infty x^{-\alpha+1} dx = \Theta(1)$

## Jump-length second moment

- $1 < \alpha \leq 3$ :  $\int_1^\infty x^{-\alpha+2} dx = \infty$
- $3 < \alpha$ :  $\int_1^\infty x^{-\alpha+1} dx = \Theta(1)$

The secret lies in the range  $2 < \alpha < 3$ ...

# Three ranges for $k$ and $\ell$

Recall:  $\ell$  target distance,  $k$  number of agents


Three different possible settings:

1. **close target**:  $\ell \leq k/\text{polylog}(k)$
2. **far target**:  $k/\text{polylog}(k) \leq \ell \leq \exp(k^{\Theta(1)})$
3. **very far target**:  $\exp(k^{\Theta(1)}) \leq \ell$



# Close target: $\ell \leq k/\text{polylog}(k)$


Best strategy = **ballistic walks**: any  $\alpha$  in  $(1, 2]$



# Close target: $\ell \leq k/\text{polylog}(k)$

Best strategy = **ballistic walks**: any  $\alpha$  in  $(1, 2]$

**With high probability** in  $\ell$ , the hitting time is  $\mathcal{O}(\ell \text{polylog}(\ell))$




# Close target: $\ell \leq k/\text{polylog}(k)$

Best strategy = **ballistic walks**: any  $\alpha$  in  $(1, 2]$

**With high probability** in  $\ell$ , the hitting time is  $\mathcal{O}(\ell \text{polylog}(\ell))$

**Recall:** an event  $E$  depending on a parameter  $\ell$  holds **with high probability** in  $\ell$  if  $\mathbb{P}(E) \geq 1 - \ell^{-\Theta(1)}$



Very far target:  $\exp(k^{\Theta(1)}) \leq \ell$


More problematic interval...

Vey far target:  $\exp(k^{\Theta(1)}) \leq \ell$

More problematic interval...

Best strategy = **diffusive walks**: any  $\alpha$  in  $[3, +\infty)$  (brownian-like behavior)

With probability 1, the walks will **eventually** find the target




Vey far target:  $\exp(k^{\Theta(1)}) \leq \ell$

More problematic interval...

Best strategy = **diffusive walks**: any  $\alpha$  in  $[3, +\infty)$  (brownian-like behavior)

With probability 1, the walks will **eventually** find the target



If  $\alpha = 3 - \epsilon$ , with high probability the target **is not found**

Far target:  $k/\text{polylog}(k) \leq \ell \leq \exp(k^{\Theta(1)})$


Best strategy: ... it depends!



Far target:  $k/\text{polylog}(k) \leq \ell \leq \exp(k^{\Theta(1)})$

Best strategy: ... it depends!

Fix  $\alpha^* = 3 - \log k / \log \ell$ : super-diffusive range



# Far target: $k/\text{polylog}(k) \leq \ell \leq \exp(k^{\Theta(1)})$

Best strategy: ... **it depends!**

Fix  $\alpha^* = 3 - \log k / \log \ell$ : **super-diffusive** range

The followings hold w.h.p. in  $\ell$

- if  $\alpha = \alpha^* + \mathcal{O}(\log \log \ell / \log \ell)$ , the hitting time is


$$\mathcal{O}((\ell^2/k + \ell) \text{polylog}(\ell))$$

- if  $\alpha = \alpha^* + \epsilon$ , the hitting time is

$$\Omega((\ell^2/k + \ell) \ell^c),$$

for some constant  $c > 0$

- if  $\alpha = \alpha^* - \epsilon$  the hitting time is **infinite**



# But... No advice, no communication!

How can we find  $\alpha^*$ ?

# Our contributions

(i) DEFINITION OF DISCRETE LÉVY WALK

(ii) ANALYSIS OF THE PARALLEL HITTING TIME

(iii) ALGORITHM FOR THE ANTS PROBLEM

# But... No advice, no communication!

How can we find  $\alpha^*$ ?

# But... No advice, no communication!

How can we find  $\alpha^*$ ?

**We don't have to!**

**Algorithm:** each agent  $u$  *samples* u.a.r. a real number  $\alpha_u \in (2, 3)$ . Then, it *performs* a discrete *Lévy walk* with *exponent*  $\alpha_u$

# But... No advice, no communication!

How can we find  $\alpha^*$ ?

**We don't have to!**

**Algorithm:** each agent  $u$  *samples* u.a.r. a real number  $\alpha_u \in (2, 3)$ . Then, it *performs* a discrete *Lévy walk* with *exponent*  $\alpha_u$

If  $\ell \leq \exp(k^{\Theta(1)})$ , the hitting time is  $\mathcal{O}((\ell^2/k + \ell) \text{polylog}(\ell))$  w.h.p.

# The idea behind the algorithm

Fix some  $\epsilon = \mathcal{O}(\log \log \ell / \log \ell)$

We use:  $\ell < \exp(k^{\Theta(1)})$  ( $\iff k \geq \text{polylog}(\ell)$ ) + Chernoff bound

$\implies$  at least  $\Theta(\epsilon k)$  agents sample an exponent in the range  $(\alpha^* - \epsilon, \alpha^* + \epsilon)$  w.h.p.

$\Theta(\epsilon k)$  agents are sufficient to ensure high probability to find the target fast enough



# Recap

In this work, we

- provide a **definition** of a discrete version of the **Lévy walk**
- analyze the **hitting time** of  $k$  parallel **Lévy walks**
- show that for any choices of  $k$  and  $\ell$  from a wide range, **Lévy walks** are an **almost-optimal search strategy** for the ANTS problem

# Recap

In this work, we

- provide a **definition** of a discrete version of the **Lévy walk**
- analyze the **hitting time** of  $k$  parallel **Lévy walks**
- show that for any choices of  $k$  and  $\ell$  from a wide range, **Lévy walks** are an **almost-optimal search strategy** for the ANTS problem
  - very **natural** and **time-homogeneous** random process
  - does **not improve** the **optimal** solution

# Recap

In this work, we

- provide a **definition** of a discrete version of the **Lévy walk**
- analyze the **hitting time** of  $k$  parallel **Lévy walks**
- show that for any choices of  $k$  and  $\ell$  from a wide range, **Lévy walks** are an **almost-optimal search strategy** for the ANTS problem
  - very **natural** and **time-homogeneous** random process
  - does **not improve** the **optimal** solution
- mathematically corroborate the **Lévy flight foraging hypothesis**
- argue the non (universal) optimality of exponent  $\alpha = 2$

# Table of contents

1. Distributed computing tasks in biological systems
2. Lévy walks and the ANTS problem
3. Opinion dynamics for the consensus problem with uniform communication noise

# The consensus problem

**Input:** system of  $n$  agents supporting opinions, with a communication network

**Task:** designing a protocol which brings the system in finite time to a configuration such that

1. all agents support the same opinion (AGREEMENT)
2. the final opinion is among the initial ones (VALIDITY)
3. the agreement keeps on unless external events occur (STABILITY)


# The consensus problem

**Input:** system of  $n$  agents supporting opinions, with a communication network

**Task:** designing a protocol which brings the system in finite time to a configuration such that


1. all agents support the same opinion (**AGREEMENT**)
2. the final opinion is among the initial ones (**VALIDITY**)
3. the agreement keeps on unless external events occur (**STABILITY**)

time  $t = 0$   $\longrightarrow$  time  $t > 0$



valid consensus


time  $t = 0$   $\longrightarrow$  time  $t > 0$



non valid consensus

# The majority consensus problem

1. AGREEMENT
2. ~~VALIDITY~~
3. ~~STABILITY~~





1. AGREEMENT
2. **MAJORITY**
3. STABILITY

2. **MAJORITY** property: the **final opinion** is the **initial majority** one

time  $t = 0$



time  $t > 0$



majority consensus

# Opinion dynamics for the consensus problem

**Opinion dynamics:** class of simple, lightweight parallel protocols for the consensus problems

Many have been investigated, including:

- Voter Model [[Hassin and Peleg, Inf. Comput. 2001](#)]
  - Averaging dynamics [[Becchetti et al., SODA 2017](#)]
  - 3-Majority [[Becchetti et al., SODA 2016](#)]
  - 2-Choices [[Berenbrink et al., PODC 2017](#)]
  - Undecided-State [[Becchetti et al., SODA 2015](#)]
- ) linear dynamics
- ) non-linear dynamics



# Opinion dynamics for the consensus problem

**Opinion dynamics:** class of simple, lightweight parallel protocols for the consensus problems

Many have been investigated, including:

- Voter Model [[Hassin and Peleg, Inf. Comput. 2001](#)]
  - Averaging dynamics [[Becchetti et al., SODA 2017](#)]
  - 3-Majority [[Becchetti et al., SODA 2016](#)]
  - 2-Choices [[Berenbrink et al., PODC 2017](#)]
  - Undecided-State [[Becchetti et al., SODA 2015](#)]
- ) linear dynamics
- ) non-linear dynamics

Majority update-rules and the undecided state dynamics have **biological inspirations** [[Reina et al., Physical Review 2017](#)] [[Condon et al., Nat. Computing 2020](#)] [[Chaouiya et al., PLOS ONE 2013](#)]

# Opinion dynamics for the consensus problem

**Opinion dynamics**: class of simple, lightweight parallel protocols for the consensus problems

Many have been investigated, including:

- Voter Model [Hassin and Peleg, Inf. Comput. 2001]
  - Averaging dynamics [Becchetti et al., SODA 2017]
  - 3-Majority [Becchetti et al., SODA 2016]
  - 2-Choices [Berenbrink et al., PODC 2017]
  - Undecided-State [Becchetti et al., SODA 2015]
- ) linear dynamics
- ) non-linear dynamics

Majority update-rules and the undecided state dynamics have **biological inspirations** [Reina et al., Physical Review 2017] [Condon et al., Nat. Computing 2020] [Chaouiya et al., PLOS ONE 2013]

Often, settings with **adversarial Byzantine failures** are investigated

**Not realistic** in **biological scenarios**; rather, **uniform noise** [Feinerman et al., PODC 2014]

# Uniform communication noise

Inspired by [Feinerman et al., PODC 2014], [Freignaud and Natale, PODC 2016]

$\Sigma$  set of  $k$  opinions,  $p \in [0, 1/2]$  constant

When  $u$  looks at  $v$ 's opinion  $x$

- a) with probability  $1 - p$ ,  $u$  sees  $x$
- b) with probability  $p$ ,  $u$  sees  $y$  where  $y$  is chosen u.a.r. in  $\Sigma$

# Uniform communication noise


Inspired by [Feinerman et al., PODC 2014], [Freignaud and Natale, PODC 2016]

$\Sigma$  set of  $k$  opinions,  $p \in [0, 1/2]$  constant

When  $u$  looks at  $v$ 's **opinion**  $x$

- a) with **probability**  $1 - p$ ,  $u$  **sees**  $x$
- b) with **probability**  $p$ ,  $u$  **sees**  $y$  where  $y$  is **chosen u.a.r.** in  $\Sigma$

Example:  $k = 3$



# The dynamics

**3-Majority** dynamics: each node  $u$

1. samples 3 **neighbors** u.a.r.
2. **pulls** their **opinions**
3. **updates** its opinion to the **majority** one, if any

# The dynamics

**3-Majority** dynamics: each node  $u$

1. samples 3 **neighbors** u.a.r.
2. **pulls** their **opinions**
3. **updates** its opinion to the **majority** one, if any

**Undecided-State** dynamics: each node  $u$

1. samples a **neighbor**  $v$  u.a.r.
2. **pulls**  $v$ 's **opinion**
3. **updates** its opinion according to the following **table**

$u \backslash v$	opinion $i$	opinion $j$	undecided
opinion $i$	$i$	undecided	$i$
opinion $j$	undecided	$j$	$j$
undecided	$i$	$j$	undecided

# The dynamics

**3-Majority** dynamics: each node  $u$

1. samples 3 **neighbors** u.a.r.
2. **pulls** their **opinions**
3. **updates** its opinion to the **majority** one, if any

**Undecided-State** dynamics: each node  $u$

1. samples a **neighbor**  $v$  u.a.r.
2. **pulls**  $v$ 's **opinion**
3. **updates** its opinion according to the following **table**

$u \backslash v$	opinion $i$	opinion $j$	undecided
opinion $i$	$i$	undecided	$i$
opinion $j$	undecided	$j$	$j$
undecided	$i$	$j$	undecided

Overview of results in **noiseless** settings [Becchetti et al., SIGACT News 2020]

# Our contribution

Based on [d'Amore et al., SIROCCO 2020], [d'Amore et Ziccardi, SIROCCO 2022]

We study the **Undecided-State** dynamics and the **3-Majority** dynamics with  $k = 2$  **opinions** in the presence of **uniform noise** in the **complete graph**



# Our contribution

Based on [d'Amore et al., SIROCCO 2020], [d'Amore et Ziccardi, SIROCCO 2022]

We study the **Undecided-State** dynamics and the **3-Majority** dynamics with  $k = 2$  **opinions** in the presence of **uniform noise** in the **complete graph**

For the **3-Majority** dynamics: **phase-transition**

- $p < 1/3$ :
- a value  $\bar{s} = \Theta(n)$  exists such that the **bias** of the system reaches the **interval**  $I_\varepsilon = [(1 - \varepsilon)\bar{s}, (1 + \varepsilon)\bar{s}]$  in **time**  $\mathcal{O}(\log n)$  w.h.p., and **keeps** in  $I_\varepsilon$  for time  $\text{poly}(n)$  w.h.p.  $\longrightarrow$  **almost-consensus**
  - if the initial **bias** is  $\Omega(\sqrt{n \log n})$ , we have **almost-majority** consensus
- $p > 1/3$ :
- in **time**  $\mathcal{O}(\log n)$  the bias becomes **bounded** by  $\mathcal{O}(\sqrt{n \log n})$  and **keeps** bounded for time  $\text{poly}(n)$  wh.p.  $\longrightarrow$  **victory of noise**
  - there is **constant probability** to **switch majority** within **time**  $\mathcal{O}(\log n)$

# Our contribution

Based on [d'Amore et al., SIROCCO 2020], [d'Amore et Ziccardi, SIROCCO 2022]

We study the **Undecided-State** dynamics and the **3-Majority** dynamics with  $k = 2$  **opinions** in the presence of **uniform noise** in the **complete graph**

For the **3-Majority** dynamics: **phase-transition**

- $p < 1/3$ :
- a value  $\bar{s} = \Theta(n)$  exists such that the **bias** of the system reaches the **interval**  $I_\varepsilon = [(1 - \varepsilon)\bar{s}, (1 + \varepsilon)\bar{s}]$  in **time**  $\mathcal{O}(\log n)$  w.h.p., and **keeps** in  $I_\varepsilon$  for time  $\text{poly}(n)$  w.h.p.  $\longrightarrow$  **almost-consensus**
  - if the initial **bias** is  $\Omega(\sqrt{n \log n})$ , we have **almost-majority** consensus
- $p > 1/3$ :
- in **time**  $\mathcal{O}(\log n)$  the bias becomes **bounded** by  $\mathcal{O}(\sqrt{n \log n})$  and **keeps** bounded for time  $\text{poly}(n)$  wh.p.  $\longrightarrow$  **victory of noise**
  - there is **constant probability** to **switch majority** within **time**  $\mathcal{O}(\log n)$

For the **Undecided-State**: similar behavior

- **phase-transition** at  $p = 1/2$
- less characterized, more complex

# Techniques

For **consensus**:

- **symmetry breaking**: the bias has enough **standard deviation** to break symmetry (**drift analysis** results)
- applying **concentration inequalities** to construct a process  $M_t$  such that  $M_{t+1} \leq (1 - \delta)M_t$  w.h.p. as long as the **bias is outside**  $I_\varepsilon = [(1 - \varepsilon)\bar{s}, (1 + \varepsilon)\bar{s}]$  but at least  $\Omega(\sqrt{n \log n})$
- **chain rule** + **union bound**

# Techniques

For **consensus**:

- **symmetry breaking**: the bias has enough **standard deviation** to break symmetry (**drift analysis** results)
- applying **concentration inequalities** to construct a process  $M_t$  such that  $M_{t+1} \leq (1 - \delta)M_t$  w.h.p. as long as the **bias is outside**  $I_\varepsilon = [(1 - \varepsilon)\bar{s}, (1 + \varepsilon)\bar{s}]$  but at least  $\Omega(\sqrt{n \log n})$
- **chain rule + union bound**

For **victory of noise**:

- constructing a **super-martingale**  $N_t$  such that  $\mathbb{E}[N_{t+1} | \mathcal{F}_t] \leq (1 - \delta)N_t$  involving the bias
- **concentration arguments** for super-martingales [Lehre and Witt, ISAAC 2014] implying that the bias **reaches** 0

# Techniques


For **consensus**:

- **symmetry breaking**: the bias has enough **standard deviation** to break symmetry (**drift analysis** results)
- applying **concentration inequalities** to construct a process  $M_t$  such that  $M_{t+1} \leq (1 - \delta)M_t$  w.h.p. as long as the **bias is outside**  $I_\varepsilon = [(1 - \varepsilon)\bar{s}, (1 + \varepsilon)\bar{s}]$  but at least  $\Omega(\sqrt{n \log n})$
- **chain rule + union bound**

For **victory of noise**:

- constructing a **super-martingale**  $N_t$  such that  $\mathbb{E}[N_{t+1} | \mathcal{F}_t] \leq (1 - \delta)N_t$  involving the bias
- **concentration arguments** for super-martingales [Lehre and Witt, ISAAC 2014] implying that the bias **reaches** 0

**Example:** consensus



# Discussion

- **Undecided-State** dynamics and **3-Majority** dynamics **are not** implemented by biological systems
  - despite the bio-inspiration, highly abstract model
  - aiming to capture fundamental phenomena that (**very loosely**) relates to many biological systems

# Discussion

- **Undecided-State** dynamics and **3-Majority** dynamics **are not** implemented by **biological systems**
  - despite the **bio-inspiration**, **highly abstract model**
  - aiming to **capture** fundamental **phenomena** that (**very loosely**) relates to many biological systems
- **Undecided-State** dynamics **more resilient** to **noise** than **3-Majority** dynamics
  - **phase-transitions**:  $p = 1/2$  vs  $p = 1/3$ 
    - $p = 1/2$  (USD) means **half** of the **communications** are **non-noisy** on average
    - $p = 1/3$  (3-Maj) means 2 out of 3 **pulled opinions** are **non-noisy** on average
- Are noise-thresholds **independent** of  $k$ ?
- What about **sparser** topologies, e.g. **expanders**?

The End

Four decorative corner ornaments, each featuring a stylized scroll and leaf design, positioned at the corners of the text area.

THANK  
YOU