

# Causal Limits of Distributed Computation



**Francesco d'Amore**

Based on the works [\[Coiteux-Roy et al. STOC '24\]](#), [\[Akbari et al. STOC '25\]](#), [\[Balliu et al. STOC '25\]](#), [\[Balliu et al. '25\]](#).

**INdAM - RomaTre**

07 May 2025

# Table of content

## 1. **Intro**

- Distributed computation
- The LOCAL model of computation
- Locally checkable labeling (LCL) problems

## 2. **Quantum and causality-based models**

- The non-signaling model & bounded-dependence model
- State-of-the-art lower bounds & upper bounds

## 3. **From quantum back to classical**



- Simulation in weaker models

## 4. **Conclusions and open problems**

# Distributed computation

- **Synchronous distributed network**

- graph  $G = (V, E)$  with  $|V| = n$
- $E$ : communication links
- discrete communication rounds:  $t = 1, 2, \dots$
- each node in  $V$  runs the **same algorithm**
- each **round** = local **computation** + **communication**





# Distributed computation

- **Synchronous distributed network**

- graph  $G = (V, E)$  with  $|V| = n$
- $E$ : communication links
- discrete communication rounds:  $t = 1, 2, \dots$
- each node in  $V$  runs the **same algorithm**
- each **round** = local **computation** + **communication**

- **Problem examples**

- **Broadcast**: one node is **informed**, we want all nodes informed





# Distributed computation

- **Synchronous distributed network**

- graph  $G = (V, E)$  with  $|V| = n$
- $E$ : communication links
- discrete communication rounds:  $t = 1, 2, \dots$
- each node in  $V$  runs the **same algorithm**
- each **round** = local **computation** + **communication**

- **Problem examples**

- **Broadcast**: one node is **informed**, we want all nodes informed





# Distributed computation

- **Synchronous distributed network**

- graph  $G = (V, E)$  with  $|V| = n$
- $E$ : communication links
- discrete communication rounds:  $t = 1, 2, \dots$
- each node in  $V$  runs the **same algorithm**
- each **round** = local **computation** + **communication**

- **Problem examples**

- **Broadcast**: one node is **informed**, we want all nodes informed
  - algorithm: *in each round, send everything*





# Distributed computation

- **Synchronous distributed network**

- graph  $G = (V, E)$  with  $|V| = n$
- $E$ : communication links
- discrete communication rounds:  $t = 1, 2, \dots$
- each node in  $V$  runs the **same algorithm**
- each **round** = local **computation** + **communication**

- **Problem examples**

- **Broadcast**: one node is **informed**, we want all nodes informed
  - algorithm: *in each round, send everything*
- **3-coloring**: output a color so that neighbors have different colors





# Distributed computation

- **Synchronous distributed network**

- graph  $G = (V, E)$  with  $|V| = n$
- $E$ : communication links
- discrete communication rounds:  $t = 1, 2, \dots$
- each node in  $V$  runs the **same algorithm**
- each **round** = local **computation** + **communication**

- **Problem examples**

- **Broadcast**: one node is **informed**, we want all nodes informed
  - algorithm: *in each round, send everything*
- **3-coloring**: output a color so that neighbors have different colors
  - algorithm: ?? we need to break symmetry






# The LOCAL model

[Linial FOCS '87 & SICOMP '92]


- **Distributed network** of  $n$  processors/nodes
  - graph  $G = (V, E)$  with  $|V| = n$
  - $E$ : communication links
  - each node in  $V$  runs the same algorithm



# The LOCAL model

[Linial FOCS '87 & SICOMP '92]


- **Distributed network** of  $n$  processors/nodes
  - graph  $G = (V, E)$  with  $|V| = n$
  - $E$ : communication links
  - each node in  $V$  runs the same algorithm
- **Time is synchronous**: nodes alternate
  - arbitrary local computation & update of state variables
  - sending of messages to all neighbors
    - \* no bandwidth constraints



# The LOCAL model

[Linial FOCS '87 & SICOMP '92]


- **Distributed network** of  $n$  processors/nodes
  - graph  $G = (V, E)$  with  $|V| = n$
  - $E$ : communication links
  - each node in  $V$  runs the same algorithm
- **Time is synchronous**: nodes alternate
  - arbitrary local computation & update of state variables
  - sending of messages to all neighbors
    - \* no bandwidth constraints
- **Unique identifiers** to nodes in the set  $1, \dots, \text{poly}(n)$ 
  - \* adversarially chosen      \*  $n$  is known to the nodes
  - needed to solve even basic problems (**2**-coloring a **2**-path)



# The LOCAL model

[Linial FOCS '87 & SICOMP '92]


- **Distributed network** of  $n$  processors/nodes
  - graph  $G = (V, E)$  with  $|V| = n$
  - $E$ : communication links
  - each node in  $V$  runs the same algorithm
- **Time is synchronous**: nodes alternate
  - arbitrary local computation & update of state variables
  - sending of messages to all neighbors
    - \* no bandwidth constraints
- **Unique identifiers** to nodes in the set  $1, \dots, \text{poly}(n)$ 
  - \* adversarially chosen      \*  $n$  is known to the nodes
  - needed to solve even basic problems (**2**-coloring a **2**-path)



# The LOCAL model

[Linial FOCS '87 & SICOMP '92]

- **Distributed network** of  $n$  processors/nodes
  - graph  $G = (V, E)$  with  $|V| = n$
  - $E$ : communication links
  - each node in  $V$  runs the same algorithm
- **Time is synchronous**: nodes alternate
  - arbitrary local computation & update of state variables
  - sending of messages to all neighbors
    - \* no bandwidth constraints
- **Unique identifiers** to nodes in the set  $1, \dots, \text{poly}(n)$ 
  - \* adversarially chosen      \*  $n$  is known to the nodes
  - needed to solve even basic problems (**2**-coloring a **2**-path)
- **Complexity measure**: number of communication rounds




# Local view

**Complexity measure:** number of communication rounds

**Equivalence:**

- $A$ :  $T(n)$ -round LOCAL algorithm




# Local view

**Complexity measure:** number of communication rounds

**Equivalence:**

- $A$ :  $T(n)$ -round LOCAL algorithm




knowledge after **2** rounds of communication

# Local view

**Complexity measure:** number of communication rounds

**Equivalence:**

- $A$ :  $T(n)$ -round LOCAL algorithm
- $f$ : function mapping radius- $T(n)$  neighborhoods to node outputs



knowledge after 2 rounds of communication




# Local view

**Complexity measure:** number of communication rounds

**Equivalence:**

- $A$ :  $T(n)$ -round LOCAL algorithm
  - $f$ : function mapping radius- $T(n)$  neighborhoods to node outputs
- given a LOCAL algorithm  $A$ , we can construct the mapping  $f$
- given  $f$ , we can construct a LOCAL algorithm  $B$  that simulates  $f$




knowledge after **2** rounds of communication

# Local view

**Complexity measure:** number of communication rounds

**Equivalence:**

- $A$ :  $T(n)$ -round LOCAL algorithm
  - $f$ : function mapping radius- $T(n)$  neighborhoods to node outputs
- given a LOCAL algorithm  $A$ , we can construct the mapping  $f$
- given  $f$ , we can construct a LOCAL algorithm  $B$  that simulates  $f$




knowledge after **2** rounds of communication

- **Locality**  $T = \text{diam}(G) + 1$  is **always sufficient** to solve any problem: **gathering** algorithm


# Lower bound: indistinguishability argument

- **Problem:** 2-coloring even cycles. Assume we have a  $T$ -round LOCAL algorithm with  $T \leq \frac{n}{2} - 2$




# Lower bound: indistinguishability argument

- **Problem:** 2-coloring even cycles. Assume we have a  $T$ -round LOCAL algorithm with  $T \leq \frac{n}{2} - 2$




# Lower bound: indistinguishability argument

- **Problem:** 2-coloring even cycles. Assume we have a  $T$ -round LOCAL algorithm with  $T \leq \frac{n}{2} - 2$




# Lower bound: indistinguishability argument

- **Problem:** 2-coloring even cycles. Assume we have a  $T$ -round LOCAL algorithm with  $T \leq \frac{n}{2} - 2$




# Lower bound: indistinguishability argument

- **Problem:** 2-coloring even cycles. Assume we have a  $T$ -round LOCAL algorithm with  $T \leq \frac{n}{2} - 2$



# Lower bound: indistinguishability argument


- **Problem:** 2-coloring even cycles. Assume we have a  $T$ -round LOCAL algorithm with  $T \leq \frac{n}{2} - 2$





# Lower bound: indistinguishability argument


- **Problem:** 2-coloring even cycles. Assume we have a  $T$ -round LOCAL algorithm with  $T \leq \frac{n}{2} - 2$



existence of  $o(n)$ -round LOCAL algorithm that 2-colors even cycles  $\implies$  2-coloring of odd cycles

# Lower bound: indistinguishability argument

- **Problem:** 2-coloring even cycles requires locality  $\Omega(n)$




existence of  $o(n)$ -round LOCAL algorithm that 2-colors even cycles  $\implies$  2-coloring of odd cycles

# Locally checkable labeling (LCL) problems

[Naor and Stockmeyer STOC '93 & SICOMP '95]


- **Problems** whose solutions might be “hard to find” but are “easy to check”
  - “analogue” of NP in the distributed setting
  - coloring, maximal independent set, maximal matching, etc.



# Locally checkable labeling (LCL) problems

[Naor and Stockmeyer STOC '93 & SICOMP '95]

- **Problems** whose solutions might be “hard to find” but are “easy to check”
  - “analogue” of NP in the distributed setting
  - coloring, maximal independent set, maximal matching, etc.
- **“Easy to check”**
  - radius  $r = \Theta(1)$
  - each node can check its solution within its radius- $r$  neighborhood
  - a globally valid iff each node is locally happy



# Locally checkable labeling (LCL) problems


[Naor and Stockmeyer STOC '93 & SICOMP '95]

- **Problems** whose solutions might be “hard to find” but are “easy to check”

- “analogue” of NP in the distributed setting
- coloring, maximal independent set, maximal matching, etc.

- **“Easy to check”**

- radius  $r = \Theta(1)$
- each node can check its solution within its radius- $r$  neighborhood
- a globally valid iff each node is locally happy



**3-coloring:** the blue node checks if its color is different from those of its neighbors

valid LCL

# Locally checkable labeling (LCL) problems


[Naor and Stockmeyer STOC '93 & SICOMP '95]

- **Problems** whose solutions might be “hard to find” but are “easy to check”

- “analogue” of NP in the distributed setting
- coloring, maximal independent set, maximal matching, etc.

- **“Easy to check”**

- radius  $r = \Theta(1)$
- each node can check its solution within its radius- $r$  neighborhood
- a globally valid iff each node is locally happy



**Leader election:** the checking radius should be  $r = \text{diam}(G)$

not an LCL

# Locally checkable labeling (LCL) problems


[Naor and Stockmeyer STOC '93 & SICOMP '95]

- **Problems** whose solutions might be “hard to find” but are “easy to check”

- “analogue” of NP in the distributed setting
- coloring, maximal independent set, maximal matching, etc.

- **“Easy to check”**

- radius  $r = \Theta(1)$
- each node can check its solution within its radius- $r$  neighborhood
- a globally valid iff each node is locally happy



**3-coloring:** the blue node checks if its color is different from those of its neighbors

# Locally checkable labeling (LCL) problems

[Naor and Stockmeyer STOC '93 & SICOMP '95]

- **Problems** whose solutions might be “hard to find” but are “easy to check”


- “analogue” of NP in the distributed setting
- coloring, maximal independent set, maximal matching, etc.

- “Easy to check”

- radius  $r = \Theta(1)$
- each node can check its solution within its radius- $r$  neighborhood
- a globally valid iff each node is locally happy

- A lot of literature studying LCLs:

- classification of LCLs based on complexity (locality)
- e.g.: complexity  $T(n)$  in randomized-LOCAL  $\implies O(T(2^{n^2}))$  in deterministic-LOCAL [Chang et al. SICOMP '19]



**3-coloring:** the blue node checks if its color is different from those of its neighbors



# Locally checkable labeling (LCL) problems

[Naor and Stockmeyer STOC '93 & SICOMP '95]

- **Problems** whose solutions might be “hard to find” but are “easy to check”


- “analogue” of NP in the distributed setting
- coloring, maximal independent set, maximal matching, etc.

- “Easy to check”

- radius  $r = \Theta(1)$
- each node can check its solution within its radius- $r$  neighborhood
- a globally valid iff each node is locally happy

- A lot of literature studying LCLs:

- classification of LCLs based on complexity (locality)
- e.g.: complexity  $T(n)$  in randomized-LOCAL  $\implies O(T(2^{n^2}))$  in deterministic-LOCAL [Chang et al. SICOMP '19]
- [BFHKLRSU STOC '16; BHKLOPRSU PODC'17; GKM STOC '17; GHK FOCS '18; CP SICOMP '19; BHKLOS STOC '18; BBCORS PODC '19; BBOS PODC '20; BBHORS JACM '21; BBCOSS DISC '22; AELMSS ICALP '23; etc.]



**3-coloring:** the blue node checks if its color is different from those of its neighbors

# Complexity landscape of LCLs

- **Paths and cycles**

det-LOCAL	$O(1)$	$\Theta(\log^\star n)$	$\Theta(n)$
rand-LOCAL	$O(1)$	$\Theta(\log^\star n)$	$\Theta(n)$

- **Balanced  $d$ -dimensional toroidal grids**

det-LOCAL	$O(1)$	$\Theta(\log^\star n)$	$\Theta(n^{1/d})$
rand-LOCAL	$O(1)$	$\Theta(\log^\star n)$	$\Theta(n^{1/d})$

# Complexity landscape of LCLs

- **Paths and cycles**

det-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n)$
rand-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n)$

- **Balanced  $d$ -dimensional toroidal grids**

det-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n^{1/d})$
rand-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n^{1/d})$

randomness does not help

# Complexity landscape of LCLs

- **Paths and cycles**

det-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n)$
rand-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n)$

- **Balanced  $d$ -dimensional toroidal grids**

det-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n^{1/d})$
rand-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n^{1/d})$

- **Bounded-degree trees**

det-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(\log n)$		$\Theta(n^{1/k})$	$\Theta(n)$
rand-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(\log \log n)$	$\Theta(\log n)$	$\Theta(n^{1/k})$	$\Theta(n)$

randomness does not help

# Complexity landscape of LCLs

- **Paths and cycles**


det-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n)$
rand-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n)$

- **Balanced  $d$ -dimensional toroidal grids**

det-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n^{1/d})$
rand-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(n^{1/d})$

- **Bounded-degree trees**

det-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(\log n)$		$\Theta(n^{1/k})$	$\Theta(n)$
rand-LOCAL	$O(1)$	$\Theta(\log^{\star} n)$	$\Theta(\log \log n)$	$\Theta(\log n)$	$\Theta(n^{1/k})$	$\Theta(n)$



# Table of content

## 1. Intro

- The LOCAL model of computation
- Locally checkable labeling (LCL) problems

## 2. Quantum and causality-based models

- The non-signaling model & bounded-dependence model
- State-of-the-art lower bounds & upper bounds

## 3. Locality-based models

- The online-LOCAL model
- Relation with causality-based models
- Simulation in weaker models

## 4. Conclusions and open problems

# Quantum-LOCAL

[Gavoille et al. DISC '09]

- **Distributed system** of  $n$  quantum processors/nodes
  - quantum computation
  - quantum communication (qubits)
  - output: measurement of qubits
- **Complexity measure:** number of communication rounds


local computation +  
measurement

round 1: communication

local computation +  
measurement

round 2: communication


local computation +  
measurement



# Quantum-LOCAL

[Gavoille et al. DISC '09]

- **Distributed system** of  $n$  quantum processors/nodes
  - quantum computation
  - quantum communication (qubits)
  - output: measurement of qubits
- **Complexity measure:** number of communication rounds






# Quantum-LOCAL

[Gavoille et al. DISC '09]

- **Distributed system** of  $n$  quantum processors/nodes
  - quantum computation
  - quantum communication (qubits)
  - output: measurement of qubits
- **Complexity measure:** number of communication rounds



- **Question:** *is there any graph problem that admits quantum advantage?*

# Quantum-LOCAL

- **Question:** *is there any graph problem that admits quantum advantage?*
  - yes! [Le Gall et al. STACS '19]
  - problem with complexity  $\Omega(n)$  in randomized-LOCAL and  $\mathcal{O}(1)$  in quantum-LOCAL

# Quantum-LOCAL

- **Question:** *is there any graph problem that admits quantum advantage?*
  - yes! [Le Gall et al. STACS '19]
  - problem with complexity  $\Omega(n)$  in randomized-LOCAL and  $O(1)$  in quantum-LOCAL
- **Question:** *what about problems that actually interest the distributed computing community?*

# Quantum-LOCAL


- **Question:** *is there any graph problem that admits quantum advantage?*
  - yes! [Le Gall et al. STACS '19]
  - problem with complexity  $\Omega(n)$  in randomized-LOCAL and  $O(1)$  in quantum-LOCAL
- **Question:** *what about problems that actually interest the distributed computing community?*
  - Yes! But artificial LCLs [Balliu et al. STOC '25; Balliu et al. '25]
  - Otherwise we do not know

# Quantum-LOCAL

- **Question:** *is there any graph problem that admits quantum advantage?*
  - yes! [Le Gall et al. STACS '19]
  - problem with complexity  $\Omega(n)$  in randomized-LOCAL and  $O(1)$  in quantum-LOCAL
- **Question:** *what about problems that actually interest the distributed computing community?*
  - Yes! But artificial LCLs [Balliu et al. STOC '25; Balliu et al. '25]
  - Otherwise we do not know
- *What do we know?*
  - focus on LCLs
  - input **graph degree** is **bounded** by a constant  $\Delta$  [Naor and Stockmeyer SICOMP '95]

# Properties of distributed algorithms


- **Run** a **2**-round algorithm  $A$  in  $G$



# Properties of distributed algorithms

- **Run** a 2-round algorithm  $A$  in  $G$ 
  - output for the red and blue nodes is determined by their respective light cones

light cone for  
the blue nodes




light cone for  
the red nodes

# Properties of distributed algorithms

- **Run** a 2-round algorithm  $A$  in  $G$ 
  - output for the red and blue nodes is determined by their respective light cones
- **Output distributions** for red and blue nodes are *independent*
  - as long as their distance is at least 5

light cone for  
the blue nodes



light cone for  
the red nodes




# Properties of distributed algorithms

- **Run** a 2-round algorithm  $A$  in  $G$ 
  - output for the red and blue nodes is determined by their respective light cones
- **Output distributions** for red and blue nodes are **independent**
  - as long as their distance is at least 5

light cone for  
the blue nodes

$H$

light cone for  
the red nodes




# Properties of distributed algorithms

- **Run** a 2-round algorithm  $A$  in  $G$ 
  - output for the red and blue nodes is determined by their respective light cones
- **Output distributions** for red and blue nodes are **independent**
  - as long as their distance is at least 5
- **Output distributions** remains **the same** if **light cone is the same**
  - non-signaling property
  - changes that are beyond 2-hops away do not influence the output distribution
  - also known as causality

light cone for  
the blue nodes

$H$



light cone for  
the red nodes

# Abstracting output distributions

- A  $T$ -round distributed algorithm yields an **output distribution** with the following **properties**:
  - outputs of subsets of nodes at distance more than  $2T$  are **independent**
  - **non-signaling** beyond distance  $T$

# Abstracting output distributions

- A  $T$ -round distributed algorithm yields an **output distribution** with the following **properties**:
  - outputs of subsets of nodes at distance more than  $2T$  are **independent**
  - **non-signaling** beyond distance  $T$
- Then we can ***just think about output distributions!***
  - **computational models** that **produce** directly **distributions** with the aforementioned properties

# Abstracting output distributions

- A  $T$ -round distributed algorithm yields an **output distribution** with the following **properties**:
  - outputs of subsets of nodes at distance more than  $2T$  are **independent**
  - **non-signaling** beyond distance  $T$
- Then we can **just think about output distributions!**
  - **computational models** that **produce** directly **distributions** with the aforementioned properties



[Holroyd and Liggett Forum of Mathematics Pi '14]


[Gavoille et al. DISC '09]

[Akbari et al. STOC '24]\* finitely-dependent distributions if  $T = O(1)$

[Arfaoui and Fraigniaud PODC '12 & SIGACT News '14]

# Relations among models

- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$




# Relations among models

- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$



# Relations among models

- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$






# Relations among models

- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$


independence +  
non-signaling



# Relations among models

- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$


independence +  
non-signaling



# Relations among models

- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$


independence +  
non-signaling



# Relations among models


- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$

independence +  
non-signaling




# Relations among models

- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$



# Relations among models


- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$



- Is it possible to “**sandwich**” **quantum-LOCAL** between weaker and stronger models?

# Relations among models

- $X \rightarrow Y$  means that locality  $T$  in  $X$  becomes locality  $O(T)$  in  $Y$



- Is it possible to “**sandwich**” **quantum-LOCAL** between weaker and stronger models?
  - yes! *for some problems*

# Some results: non-signaling model

- **Graph-existential lower bound** arguments based on indistinguishability **hold!** [Coiteux-Roy et al. STOC '24]




# Some results: non-signaling model

- **Graph-existential lower bound** arguments based on indistinguishability **hold!** [Coiteux-Roy et al. STOC '24]
- Example: **3-coloring**  $\sqrt{n} \times \sqrt{n}$  **grids** is hard ( $T = \Theta(\sqrt{n})$ )


# Some results: non-signaling model

- **Graph-existential lower bound** arguments based on indistinguishability **hold!** [Coiteux-Roy et al. STOC '24]
- Example: **3-coloring  $\sqrt{n} \times \sqrt{n}$  grids** is hard ( $T = \Theta(\sqrt{n})$ )
  - find graph  $H$  that **locally is like a grid** but chromatic number  $\chi(H) \geq 4$




# Some results: non-signaling model

- **Graph-existential lower bound** arguments based on indistinguishability **hold!** [Coiteux-Roy et al. STOC '24]
- Example: **3-coloring  $\sqrt{n} \times \sqrt{n}$  grids** is hard ( $T = \Theta(\sqrt{n})$ )
  - find graph  $H$  that **locally is like a grid** but chromatic number  $\chi(H) \geq 4$
  - **by contradiction**: quantum-LOCAL algorithm with locality  $T \leq \lfloor \frac{\sqrt{n}-2}{4} \rfloor$  that 3-colors grids with high probability




# Some results: non-signaling model

- **Graph-existential lower bound** arguments based on indistinguishability **hold!** [Coiteux-Roy et al. STOC '24]
- Example: **3-coloring  $\sqrt{n} \times \sqrt{n}$  grids** is hard ( $T = \Theta(\sqrt{n})$ )
  - find graph  $H$  that **locally is like a grid** but chromatic number  $\chi(H) \geq 4$
  - **by contradiction**: quantum-LOCAL algorithm with locality  $T \leq \lfloor \frac{\sqrt{n}-2}{4} \rfloor$  that **3-colors** grids with high probability
  - failure with prob. **1** overall  $\implies$  failure with prob.  $\frac{1}{4}$  in at least one of the regions



# Some results: non-signaling model

- **Graph-existential lower bound** arguments based on indistinguishability **hold!** [Coiteux-Roy et al. STOC '24]
- Example: **3-coloring  $\sqrt{n} \times \sqrt{n}$  grids** is hard ( $T = \Theta(\sqrt{n})$ )
  - find graph  $H$  that **locally is like a grid** but chromatic number  $\chi(H) \geq 4$
  - **by contradiction**: quantum-LOCAL algorithm with locality  $T \leq \lfloor \frac{\sqrt{n}-2}{4} \rfloor$  that 3-colors grids with high probability
  - failure with prob. **1** overall  $\implies$  failure with prob.  $\frac{1}{4}$  in at least one of the regions
  - exploit **non-signaling principle**




# Some results: non-signaling model

- **Graph-existential lower bound** arguments based on indistinguishability **hold!** [Coiteux-Roy et al. STOC '24]
- Example: **3-coloring  $\sqrt{n} \times \sqrt{n}$  grids** is hard ( $T = \Theta(\sqrt{n})$ )
  - find graph  $H$  that **locally is like a grid** but chromatic number  $\chi(H) \geq 4$
  - **by contradiction**: quantum-LOCAL algorithm with locality  $T \leq \lfloor \frac{\sqrt{n}-2}{4} \rfloor$  that **3-colors** grids with high probability
  - failure with prob. **1** overall  $\implies$  failure with prob.  $\frac{1}{4}$  in at least one of the regions
  - exploit **non-signaling principle**

$H$ : odd **quadrangulation**  
of **Klein-bottle**  
- locally grid-like,  $\chi(H) = 4$   
[Mohar et al. Combinatorica '13]

- **Boosting failure prob.** is also possible



# Some results: non-signaling model

**Graph-existential lower bound arguments** based on indistinguishability

- **Graph coloring:**  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]
  - makes use of a “cheating graph” from [Bogdanov '13]
  - upper bound in deterministic LOCAL, lower bound in the non-signaling model
  - no quantum advantage

# Some results: non-signaling model

**Graph-existential lower bound arguments** based on indistinguishability

- **Graph coloring:**  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]
  - makes use of a “cheating graph” from [Bogdanov '13]
  - upper bound in deterministic LOCAL, lower bound in the non-signaling model
  - no quantum advantage
- **Tree coloring:**  $c$ -coloring trees has complexity  $\Omega(\log_c n)$  [Coiteux-Roy et al. STOC '24]



# Some results: non-signaling model

**Graph-existential lower bound arguments** based on indistinguishability

- **Graph coloring:**  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]
  - makes use of a “cheating graph” from [Bogdanov '13]
  - upper bound in deterministic LOCAL, lower bound in the non-signaling model
  - no quantum advantage
- **Tree coloring:**  $c$ -coloring trees has complexity  $\Omega(\log_c n)$  [Coiteux-Roy et al. STOC '24]
- **Grid coloring:** 3-coloring grids of size  $n_1 \times n_2$  has complexity  $\Omega(\min\{n_1, n_2\})$  [Coiteux-Roy et al. STOC '24]

# Some results: non-signaling model

**Graph-existential lower bound arguments** based on indistinguishability

- **Graph coloring:**  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]
  - makes use of a “cheating graph” from [Bogdanov '13]
  - upper bound in deterministic LOCAL, lower bound in the non-signaling model
  - no quantum advantage
- **Tree coloring:**  $c$ -coloring trees has complexity  $\Omega(\log_c n)$  [Coiteux-Roy et al. STOC '24]
- **Grid coloring:** 3-coloring grids of size  $n_1 \times n_2$  has complexity  $\Omega(\min\{n_1, n_2\})$  [Coiteux-Roy et al. STOC '24]

**What about other known lower bounds?** E.g., 3-coloring cycles has complexity  $\Theta(\log^\star n)$  [Linial FOCS '87]

# Some results: bounded-dependence model

- Can we similarly **rule out quantum advantage for 3-coloring cycles**? Classical complexity  $T = \Theta(\log^\star n)$

# Some results: bounded-dependence model

- Can we similarly **rule out quantum advantage for 3-coloring cycles**? Classical complexity  $T = \Theta(\log^{\star} n)$ 
  - **no!** *There is a bounded-dependent distribution that 3-colors paths and cycles ( $T = O(1)$ )*
  - [Holroyd and Liggett Forum of Mathematics Pi '14]
  - [Holroyd et al. Electronic Communications in Probability '18]

# Some results: bounded-dependence model

- Can we similarly **rule out quantum advantage for 3-coloring cycles**? Classical complexity  $T = \Theta(\log^\star n)$ 
  - **no!** *There is a bounded-dependent distribution that 3-colors paths and cycles ( $T = O(1)$ )*
  - [Holroyd and Liggett Forum of Mathematics Pi '14]
  - [Holroyd et al. Electronic Communications in Probability '18]
- Is there **any quantum-LOCAL algorithm that 3-colors paths and cycles with locality  $T = o(\log^\star n)$** ?
  - **major open question**

# Some results: bounded-dependence model

- Can we similarly **rule out quantum advantage for 3-coloring cycles**? Classical complexity  $T = \Theta(\log^\star n)$ 
  - **no!** *There is a bounded-dependent distribution that 3-colors paths and cycles ( $T = O(1)$ )*
  - [Holroyd and Liggett Forum of Mathematics Pi '14]
  - [Holroyd et al. Electronic Communications in Probability '18]
- Is there **any quantum-LOCAL algorithm that 3-colors paths and cycles with locality  $T = o(\log^\star n)$** ?
  - **major open question**
- Is there any hope to **rule out quantum advantage for LCLs of complexity  $\Theta(\log^\star n)$  in classical LOCAL**?
  - \* using stronger models

# Some results: bounded-dependence model

- Can we similarly **rule out quantum advantage for 3-coloring cycles**? Classical complexity  $T = \Theta(\log^\star n)$ 
  - **no!** *There is a bounded-dependent distribution that 3-colors paths and cycles ( $T = O(1)$ )*
  - [Holroyd and Liggett Forum of Mathematics Pi '14]
  - [Holroyd et al. Electronic Communications in Probability '18]
- Is there **any quantum-LOCAL algorithm that 3-colors paths and cycles with locality  $T = o(\log^\star n)$** ?
  - **major open question**
- Is there any hope to **rule out quantum advantage for LCLs of complexity  $\Theta(\log^\star n)$  in classical LOCAL**?
  - \* using stronger models
  - **no!**
  - For any  $\Theta(\log^\star n)$  LCL  $\Pi$  on bounded degree graphs, *there is a bounded-dependent distribution ( $T = O(1)$ ) solving  $\Pi$*   
[Akbari et al. STOC '24]

# Table of content

## 1. Intro

- Distributed computation
- The LOCAL model of computation
- Locally checkable labeling (LCL) problems

## 2. Quantum and causality-based models

- The non-signaling model & bounded-dependence model
- State-of-the-art lower bounds & upper bounds

## 3. From quantum back to classical

- Simulation in weaker models


## 4. Conclusions and open problems



# From bounded-dependence back to LOCAL

- Start with a **bounded-dependent distribution**  $\rho$  with locality  $T$  solving some LCL  $\Pi$ 
  - locality  $T$  = independence at distance  $2T + 1$  plus non-signaling beyond distance  $T$


$G$



# From bounded-dependence back to LOCAL

- Start with a **bounded-dependent distribution**  $\rho$  with locality  $T$  solving some LCL  $\Pi$ 
  - locality  $T$  = independence at distance  $2T + 1$  plus non-signaling beyond distance  $T$
- **Observation:** LOCAL algorithms  $A_1$  and  $A_2$  with localities  $T_1$  and  $T_2$ 
  - merged into a single LOCAL algorithm  $B$  with locality  $T = O(T_1 + T_2)$


$G$



# From bounded-dependence back to LOCAL


- Start with a **bounded-dependent distribution**  $\rho$  with locality  $T$  solving some LCL  $\Pi$ 
  - locality  $T$  = independence at distance  $2T + 1$  plus non-signaling beyond distance  $T$
- **Observation:** LOCAL algorithms  $A_1$  and  $A_2$  with localities  $T_1$  and  $T_2$ 
  - merged into a single LOCAL algorithm  $B$  with locality  $T = O(T_1 + T_2)$
- We can “nicely” **decompose** the graph with a LOCAL algorithm

$G$




# From bounded-dependence back to LOCAL

- Start with a **bounded-dependent distribution**  $\rho$  with locality  $T$  solving some LCL  $\Pi$ 
  - locality  $T$  = independence at distance  $2T + 1$  plus non-signaling beyond distance  $T$
- **Observation:** LOCAL algorithms  $A_1$  and  $A_2$  with localities  $T_1$  and  $T_2$ 
  - merged into a single LOCAL algorithm  $B$  with locality  $T = O(T_1 + T_2)$
- We can “nicely” **decompose** the graph with a LOCAL algorithm



# From bounded-dependence back to LOCAL

- Start with a **bounded-dependent distribution**  $\rho$  with locality  $T$  solving some LCL  $\Pi$ 
  - locality  $T$  = independence at distance  $2T + 1$  plus non-signaling beyond distance  $T$
- **Observation:** LOCAL algorithms  $A_1$  and  $A_2$  with localities  $T_1$  and  $T_2$ 
  - merged into a single LOCAL algorithm  $B$  with locality  $T = O(T_1 + T_2)$
- We can “nicely” **decompose** the graph with a LOCAL algorithm
  - locality  $T = \tilde{O}(\sqrt{nT})$




$$\text{diam}(C_i) = \tilde{O}(\sqrt{nT})$$

$$\text{dist}(C_i, C_j) > 2T + \Omega(1)$$

$$\# \text{ unclustered nodes} = O(\sqrt{n/T})$$

# From bounded-dependence back to LOCAL

- Start with a **bounded-dependent distribution**  $\rho$  with locality  $T$  solving some LCL  $\Pi$ 
  - locality  $T$  = independence at distance  $2T + 1$  plus non-signaling beyond distance  $T$
- **Observation:** LOCAL algorithms  $A_1$  and  $A_2$  with localities  $T_1$  and  $T_2$ 
  - merged into a single LOCAL algorithm  $B$  with locality  $T = O(T_1 + T_2)$
- We can “nicely” **decompose** the graph with a LOCAL algorithm
  - locality  $T = \tilde{O}(\sqrt{nT})$
  - **sample** from  $\rho$  in **unclustered nodes**
  - solution exists in each cluster because of LCL definition
  - **brute-force** a solution inside each **cluster**



$$\text{diam}(C_i) = \tilde{O}(\sqrt{nT})$$

$$\text{dist}(C_i, C_j) > 2T + \Omega(1)$$

$$\# \text{ unclustered nodes} = O(\sqrt{n/T})$$

# From bounded-dependence back to LOCAL


- Start with a **bounded-dependent distribution**  $\rho$  with locality  $T$  solving some LCL  $\Pi$ 
  - locality  $T$  = independence at distance  $2T + 1$  plus non-signaling beyond distance  $T$

- **Observation:** LOCAL algorithms  $A_1$  and  $A_2$  with localities  $T_1$  and  $T_2$ 
  - merged into a single LOCAL algorithm  $B$  with locality  $T = O(T_1 + T_2)$

- We can “nicely” **decompose** the graph with a LOCAL algorithm

- locality  $T = \tilde{O}(\sqrt{nT})$
- **sample** from  $\rho$  in **unclustered nodes**
- solution exists in each cluster because of LCL definition
- **brute-force** a solution inside each **cluster**

- **Bounded dependent distribution** with locality  $T \implies$  **LOCAL algorithm** with locality  $\tilde{O}(\sqrt{nT})$ 
  - LOCAL complexity is  $\Theta(n) \implies$  bounded-dependence complexity  $\tilde{\Omega}(n)$  (same for quantum-LOCAL)
  - bounded-dependence (or quantum-LOCAL) complexity  $O(1) \implies$  LOCAL complexity is  $\tilde{O}(\sqrt{n})$



$$\text{diam}(C_i) = \tilde{O}(\sqrt{nT})$$

$$\text{dist}(C_i, C_j) > 2T + \Omega(1)$$

$$\# \text{ unclustered nodes} = O(\sqrt{n/T})$$

# Table of content

## 1. Intro

- Distributed computation
- The LOCAL model of computation
- Locally checkable labeling (LCL) problems

## 2. Quantum and causality-based models

- The non-signaling model & bounded-dependence model
- State-of-the-art lower bounds & upper bounds

## 3. From quantum back to classical


- Simulation in weaker models

## 4. Conclusions and open problems




# Conclusions

- Possibility to derive **results** for quantum-LOCAL by “**sandwiching**” it between weaker and stronger models
  - *Graph coloring*:  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]




# Conclusions

- Possibility to derive **results** for quantum-LOCAL by “**sandwiching**” it between weaker and stronger models
  - Graph coloring:  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]
- $O(\log^\star n)$  LOCAL  $\rightarrow O(1)$  bounded-dependence. **Other complexities?**




# Conclusions

- Possibility to derive **results** for quantum-LOCAL by “**sandwiching**” it between weaker and stronger models
  - Graph coloring:  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]
- $O(\log^\star n)$  LOCAL  $\rightarrow O(1)$  bounded-dependence. **Other complexities?**
- How to **create bounded-dependent distributions** that do not rely on [Holroyd et al. Forum of Mathematics, Pi '14]?




# Conclusions

- Possibility to derive **results** for quantum-LOCAL by “**sandwiching**” it between weaker and stronger models
  - Graph coloring:  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]
- $O(\log^\star n)$  LOCAL  $\rightarrow O(1)$  bounded-dependence. **Other complexities?**
- How to **create bounded-dependent distributions** that do not rely on [Holroyd et al. Forum of Mathematics, Pi '14]?
- $T$  bounded-dependence  $\implies \tilde{O}(\sqrt{nT})$  LOCAL. **Better reduction?**




# Conclusions

- Possibility to derive **results** for quantum-LOCAL by “**sandwiching**” it between weaker and stronger models
  - Graph coloring:  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]
- $O(\log^* n)$  LOCAL  $\rightarrow O(1)$  bounded-dependence. **Other complexities?**
- How to **create bounded-dependent distributions** that do not rely on [Holroyd et al. Forum of Mathematics, Pi '14]?
- $T$  bounded-dependence  $\implies \tilde{O}(\sqrt{nT})$  LOCAL. **Better reduction?**
- How to get **lower bounds directly in quantum-LOCAL?**



# Conclusions

- Possibility to derive **results** for quantum-LOCAL by “**sandwiching**” it between weaker and stronger models
  - Graph coloring:  $c$ -coloring  $\chi$ -chromatic graphs has complexity  $\tilde{\Theta}(n^{1/\lfloor \frac{c-1}{\chi-1} \rfloor})$  [Coiteux-Roy et al. STOC '24]
- $O(\log^\star n)$  LOCAL  $\rightarrow O(1)$  bounded-dependence. **Other complexities?**
- How to **create bounded-dependent distributions** that do not rely on [Holroyd et al. Forum of Mathematics, Pi '14]?
- $T$  bounded-dependence  $\implies \tilde{O}(\sqrt{nT})$  LOCAL. **Better reduction?**
- How to get **lower bounds directly in quantum-LOCAL?**



THANKS! QUESTIONS?