

Causal limits of distributed computation



Francesco d'Amore

Based on joint work with the [Xavier Coiteux-Roy](#), [Rishikesh Gajjala](#),
[Fabian Kuhn](#), [François Le Gall](#), [Henrik Lievonen](#), [Augusto Modanese](#),
[Marc-Olivier Renou](#), [Gustav Schmid](#), [Jukka Suomela](#)


Bocconi University

05 December 2023

The LOCAL model

Introduced by [Linial, FOCS '87]


- **distributed systems** with n nodes/processors
 - **synchronous** rounds
 - **infinite** computational **power**
 - **unbounded** bandwidth



The LOCAL model

Introduced by [Linial, FOCS '87]


- **distributed systems** with n nodes/processors
 - **synchronous** rounds
 - **infinite** computational **power**
 - **unbounded bandwidth**
 - unique **ID**s in $\{1, \dots, n^{\Theta(1)}\}$



The LOCAL model

Introduced by [Linial, FOCS '87]


- **distributed systems** with n nodes/processors
 - **synchronous** rounds
 - **infinite** computational **power**
 - **unbounded bandwidth**
 - unique **ID**s in $\{1, \dots, n^{\Theta(1)}\}$
 - knowledge of n



The LOCAL model

Introduced by [Linial, FOCS '87]

- **distributed systems** with n nodes/processors
 - **synchronous** rounds
 - **infinite** computational **power**
 - **unbounded bandwidth**
 - unique **ID**s in $\{1, \dots, n^{\Theta(1)}\}$
 - knowledge of n
- **complexity** measure: **# of rounds**



The LOCAL model


Introduced by [Linial, FOCS '87]

- **distributed systems** with n nodes/processors

- **synchronous** rounds
- **infinite** computational **power**
- **unbounded bandwidth**
- unique **ID**s in $\{1, \dots, n^{\Theta(1)}\}$
- knowledge of n

- **complexity** measure: **# of rounds**

- E.g., T rounds of computation



The LOCAL model


Introduced by [Linial, FOCS '87]

- **distributed systems** with n nodes/processors

- **synchronous** rounds
- **infinite** computational **power**
- **unbounded bandwidth**
- unique **ID**s in $\{1, \dots, n^{\Theta(1)}\}$
- knowledge of n

- **complexity** measure: **# of rounds**

- E.g., T rounds of computation
- also called **locality**



The LOCAL model

Introduced by [Linial, FOCS '87]

- **distributed systems** with n nodes/processors


- **synchronous** rounds
- **infinite** computational **power**
- **unbounded bandwidth**
- unique **ID**s in $\{1, \dots, n^{\Theta(1)}\}$
- knowledge of n

- **complexity** measure: **# of rounds**

- E.g., T rounds of computation
- also called **locality**

- **randomized-LOCAL**

- infinite i.i.d. random bit strings
- error probability $\leq 1/n$



The LOCAL model

- **strongest lower bounds** for synchronous distributed computation
 - upper bounds \implies lower bounds cannot be moved forward

The LOCAL model

- **strongest lower bounds** for synchronous distributed computation
 - upper bounds \implies lower bounds cannot be moved forward
- modelling $\text{cost}(\text{message exchange}) \gg \text{cost}(\text{computation})$

The LOCAL model

- **strongest lower bounds** for synchronous distributed computation
 - upper bounds \implies lower bounds cannot be moved forward
- modelling cost(message exchange) \gg cost(computation)

Sample of **previous results**

- [Linial, SIAM J. of C. '92]
 - 3-coloring cycles: $\Omega(\log^* n)$
 - $\mathcal{O}(\sqrt{d})$ -coloring d -regular trees: $\Theta(\text{diameter})$

The LOCAL model

- **strongest lower bounds** for synchronous distributed computation
 - upper bounds \implies lower bounds cannot be moved forward
- modelling cost(message exchange) \gg cost(computation)

Sample of **previous results**

- [Linial, SIAM J. of C. '92]
 - 3-coloring cycles: $\Omega(\log^* n)$
 - $\mathcal{O}(\sqrt{d})$ -coloring d -regular trees: $\Theta(\text{diameter})$
- [Kuhn and Wattenhofer, PODC '06]
 - $(\Delta + 1)$ -coloring: $\mathcal{O}(\Delta \log \Delta + \log^* n)$

The LOCAL model

- **strongest lower bounds** for synchronous distributed computation
 - upper bounds \implies lower bounds cannot be moved forward
- modelling cost(message exchange) \gg cost(computation)

Sample of **previous results**

- [Linial, SIAM J. of C. '92]
 - 3-coloring cycles: $\Omega(\log^* n)$
 - $\mathcal{O}(\sqrt{d})$ -coloring d -regular trees: $\Theta(\text{diameter})$
- [Kuhn and Wattenhofer, PODC '06]
 - $(\Delta + 1)$ -coloring: $\mathcal{O}(\Delta \log \Delta + \log^* n)$
- [Chang and Pettie, FOCS '16]
 - $T(n)$ -round rand-algorithm $\implies T(2^{2^n})$ -round det-algorithm

The LOCAL model

- **strongest lower bounds** for synchronous distributed computation
 - upper bounds \implies lower bounds cannot be moved forward
- modelling cost(message exchange) \gg cost(computation)


Sample of **previous results**

- [Linial, SIAM J. of C. '92]
 - 3-coloring cycles: $\Omega(\log^* n)$
 - $\mathcal{O}(\sqrt{d})$ -coloring d -regular trees: $\Theta(\text{diameter})$
- [Kuhn and Wattenhofer, PODC '06]
 - $(\Delta + 1)$ -coloring: $\mathcal{O}(\Delta \log \Delta + \log^* n)$
- [Chang and Pettie, FOCS '16]
 - $T(n)$ -round rand-algorithm $\implies T(2^{2^n})$ -round det-algorithm
- [Balliu et al., FOCS '19]
 - MM and MIS cannot be solved in $o(\Delta) + \mathcal{O}(\log^* n)$

Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$
- maximal independent set: $r = 1$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$
- maximal independent set: $r = 1$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$
- maximal independent set: $r = 1$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$
- maximal independent set: $r = 1$
- maximal matching: $r = 2$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$
- maximal independent set: $r = 1$
- maximal matching: $r = 2$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$
- maximal independent set: $r = 1$
- maximal matching: $r = 2$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]


- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$
- maximal independent set: $r = 1$
- maximal matching: $r = 2$
- sinkless orientation: $r = 1$



Locally checkable labelling (LCL) problems

[Naor and Stockmeyer, STOC '93]

- problems that can be **locally checked**
 - $\Sigma_{\text{in}}, \Sigma_{\text{out}}$: finite input and output label sets
 - family \mathcal{F} of **admissible output neighborhoods** of radius $r = \Theta(1)$
 - input: labelled graph of degree Δ
 - output: labelled graph that is valid iff each node verifies positively
- 3-coloring: $r = 1$
- maximal independent set: $r = 1$
- maximal matching: $r = 2$
- sinkless orientation: $r = 1$
- minimal dominating set: $r = 1$
- many others...



Complexity of LCLs

- LCLs' complexity has been **characterized** in many graph families

Complexity of LCLs

- LCLs' complexity has been **characterized** in many graph families
 - paths & cycles

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$

Complexity of LCLs

- LCLs' complexity has been **characterized** in many graph families
 - paths & cycles

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$

- balanced d -dimensional toroidal grids

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$

Complexity of LCLs

- LCLs' complexity has been **characterized** in many graph families
 - paths & cycles

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$

- balanced d -dimensional toroidal grids

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$

- bounded-degree trees

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log n)$		$\Theta(n^{1/k})$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log \log n)$	$\Theta(\log n)$	$\Theta(n^{1/k})$	$\Theta(n)$

Complexity of LCLs

- LCLs' complexity has been **characterized** in many graph families
 - paths & cycles

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$

- balanced d -dimensional toroidal grids

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$

- bounded-degree trees

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log n)$		$\Theta(n^{1/k})$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log \log n)$	$\Theta(\log n)$	$\Theta(n^{1/k})$	$\Theta(n)$

- general graphs: much more complex

Complexity of LCLs

- LCLs' complexity has been **characterized** in many graph families
 - paths & cycles

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$

- balanced d -dimensional toroidal grids

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$

- bounded-degree trees

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log n)$		$\Theta(n^{1/k})$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log \log n)$	$\Theta(\log n)$	$\Theta(n^{1/k})$	$\Theta(n)$

- general graphs: much more complex
 - randomness does not help up to $\Theta(\log^* n)$ and for $\Theta(n)$

Complexity of LCLs

- LCLs' complexity has been **characterized** in many graph families
 - paths & cycles

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$

- balanced d -dimensional toroidal grids

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$

- bounded-degree trees

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log n)$		$\Theta(n^{1/k})$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log \log n)$	$\Theta(\log n)$	$\Theta(n^{1/k})$	$\Theta(n)$

- general graphs: much more complex
 - randomness does not help up to $\Theta(\log^* n)$ and for $\Theta(n)$
 - gap $\Theta(\log^* n) - \Theta(\log n)$ ($\Theta(\log \log n)$) for det- (rand-) LOCAL

Complexity of LCLs

- LCLs' complexity has been **characterized** in many graph families
 - paths & cycles

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n)$

- balanced d -dimensional toroidal grids

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(n^{1/d})$

- bounded-degree trees

det-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log n)$		$\Theta(n^{1/k})$	$\Theta(n)$
rand-LOCAL	$\mathcal{O}(1)$	$\Theta(\log^* n)$	$\Theta(\log \log n)$	$\Theta(\log n)$	$\Theta(n^{1/k})$	$\Theta(n)$

- general graphs: much more complex
 - randomness does not help up to $\Theta(\log^* n)$ and for $\Theta(n)$
 - gap $\Theta(\log^* n)$ - $\Theta(\log n)$ ($\Theta(\log \log n)$) for det- (rand-) LOCAL
 - in general, randomness helps both exponentially and polynomially

Some lower bound techniques

- **Round elimination**

- input: LCL problem of complexity T
- output 1: LCL problem of complexity $T - 1$

Some lower bound techniques

- **Round elimination**

- input: LCL problem of complexity T
- output 1: LCL problem of complexity $T - 1$
- ⋮
- output T : LCL problem of complexity 0

Some lower bound techniques

- **Round elimination**

- input: LCL problem of complexity T
- output 1: LCL problem of complexity $T - 1$
- ⋮
- output T : LCL problem of complexity 0

If output T is not 0-round solvable, then lower bound T for the input

Some lower bound techniques

- **Round elimination**

- input: LCL problem of complexity T
- output 1: LCL problem of complexity $T - 1$
- ⋮
- output T : LCL problem of complexity 0

If output T is not 0-round solvable, then lower bound T for the input

- **Indistinguishability argument**

- local algorithms cannot recognize “global” modifications
- “fool” the algorithm

Some lower bound techniques

- **Round elimination**

- input: LCL problem of complexity T
- output 1: LCL problem of complexity $T - 1$
- ⋮
- output T : LCL problem of complexity 0


If output T is not 0-round solvable, then lower bound T for the input

- **Indistinguishability argument**

- local algorithms cannot recognize “global” modifications
- “fool” the algorithm


Indistinguishability argument

- Example: 2-coloring cycles requires $\Theta(n)$



Indistinguishability argument

- Example: 2-coloring cycles requires $\Theta(n)$



- red nodes must output the same
- blue nodes must output the same
- more complex arguments show $T \geq \lfloor \frac{n}{2} \rfloor - 1$

Quantum advantage

- Natural questions
 - can **quantum communication** bring advantage?

Quantum advantage

- Natural questions
 - can **quantum communication** bring advantage?
 - can **pre-shared quantum states** bring advantage?

Quantum advantage

- Natural questions
 - can **quantum communication** bring advantage?
 - can **pre-shared quantum states** bring advantage?
- For non-LCLs, **yes**
 - complexity $\Theta(n)$ in LOCAL with shared randomness and $\Theta(1)$ in q-LOCAL with pre-shared quantum state [Gavoille et al., DISC '09]

Quantum advantage

- Natural questions
 - can **quantum communication** bring advantage?
 - can **pre-shared quantum states** bring advantage?
- For non-LCLs, **yes**
 - complexity $\Theta(n)$ in LOCAL with shared randomness and $\Theta(1)$ in q-LOCAL with pre-shared quantum state [Gavoille et al., DISC '09]
 - complexity $\Theta(n)$ in rand-LOCAL and $\Theta(1)$ in q-LOCAL [Le Gall et al., STACS '19]

Quantum advantage

- Natural questions
 - can **quantum communication** bring advantage?
 - can **pre-shared quantum states** bring advantage?
- For non-LCLs, **yes**
 - complexity $\Theta(n)$ in LOCAL with shared randomness and $\Theta(1)$ in q-LOCAL with pre-shared quantum state [Gavoille et al., DISC '09]
 - complexity $\Theta(n)$ in rand-LOCAL and $\Theta(1)$ in q-LOCAL [Le Gall et al., STACS '19]
- For LCLs, **unknown**
 - how to prove lower bounds for q-LOCAL?

Quantum advantage

- Natural questions
 - can **quantum communication** bring advantage?
 - can **pre-shared quantum states** bring advantage?
- For non-LCLs, **yes**
 - complexity $\Theta(n)$ in LOCAL with shared randomness and $\Theta(1)$ in q-LOCAL with pre-shared quantum state [Gavoille et al., DISC '09]
 - complexity $\Theta(n)$ in rand-LOCAL and $\Theta(1)$ in q-LOCAL [Le Gall et al., STACS '19]
- For LCLs, **unknown**
 - how to prove lower bounds for q-LOCAL?
 - some indistinguishability arguments works! [Gavoille et al., DISC '09]

The no-signaling principle

- Principle (informal): *no signal can be sent from the future to the past*

The no-signaling principle


- Principle (informal): *no signal can be sent from the future to the past*
- In distributed systems?

The no-signaling principle

- Principle (informal): *no signal can be sent from the future to the past*
- In distributed systems?

Some preliminary remarks ...

- Fix a set V of n processors




The no-signaling principle

- Principle (informal): *no signal can be sent from the future to the past*
- In distributed systems?

Some preliminary remarks ...

- Fix a set V of n processors
 - fix *any* **algorithm** \mathcal{A}




The no-signaling principle

- Principle (informal): *no signal can be sent from the future to the past*
- In distributed systems?

Some preliminary remarks . . .

- Fix a set V of n processors
 - fix *any* **algorithm** \mathcal{A}
 - **freedom** on how to set links (the *graph*)




The no-signaling principle

- Principle (informal): *no signal can be sent from the future to the past*
- In distributed systems?

Some preliminary remarks ...

- Fix a set V of n processors
 - fix *any* **algorithm** \mathcal{A}
 - **freedom** on how to set links (the *graph*)




The no-signaling principle

- Principle (informal): *no signal can be sent from the future to the past*
- In distributed systems?

Some preliminary remarks ...

- Fix a set V of n processors
 - fix *any* **algorithm** \mathcal{A}
 - **freedom** on how to set links (the *graph*)




The no-signaling principle

- Principle (informal): *no signal can be sent from the future to the past*
- In distributed systems?

Some preliminary remarks . . .

- Fix a set V of n processors
 - fix *any* **algorithm** \mathcal{A}
 - **freedom** on how to set links (the *graph*)
 - the algorithm **always outputs** something




The no-signaling principle

- Principle (informal): *no signal can be sent from the future to the past*
- In distributed systems?


Some preliminary remarks . . .

- Fix a set V of n processors
 - fix *any* **algorithm** \mathcal{A}
 - **freedom** on how to set links (the *graph*)
 - the algorithm **always outputs** something
- Wlog, we assume algorithms are defined over **all graphs** of n nodes




The no-signaling principle

- In distributed systems?
- Fix a **distributed system** with $|V| = n$ processors




The no-signaling principle

- In distributed systems?
- Fix a **distributed system** with $|V| = n$ processors
 - run algorithm \mathcal{A} for T rounds




The no-signaling principle

- In distributed systems?
- Fix a **distributed system** with $|V| = n$ processors
 - run algorithm \mathcal{A} for T rounds
 - fix $S \subseteq V$




The no-signaling principle

- In distributed systems?
- Fix a **distributed system** with $|V| = n$ processors
 - run algorithm \mathcal{A} for T rounds
 - fix $S \subseteq V$
 - consider $G[\mathcal{N}_T(S)]$ ($T = 2$)




The no-signaling principle

- In distributed systems?
- Fix a **distributed system** with $|V| = n$ processors
 - run algorithm \mathcal{A} for T rounds
 - fix $S \subseteq V$
 - consider $G[\mathcal{N}_T(S)]$ ($T = 2$)
 - modify G outside $G[\mathcal{N}_T(S)]$




The no-signaling principle

- In distributed systems?
- Fix a **distributed system** with $|V| = n$ processors
 - run algorithm \mathcal{A} for T rounds
 - fix $S \subseteq V$
 - consider $G[\mathcal{N}_T(S)]$ ($T = 2$)
 - modify G outside $G[\mathcal{N}_T(S)]$
 - the **output distribution** over $G[\mathcal{N}_T(S)]$ must be the **same no matter the structure outside**



The no-signaling principle

- In distributed systems?
- Fix a **distributed system** with $|V| = n$ processors
 - run algorithm \mathcal{A} for T rounds
 - fix $S \subseteq V$
 - consider $G[\mathcal{N}_T(S)]$ ($T = 2$)
 - modify G outside $G[\mathcal{N}_T(S)]$
 - the **output distribution** over $G[\mathcal{N}_T(S)]$ must be the **same no matter the structure outside**



Outcome: “generalization” of algorithm

- An **outcome** assigns to inputs (G, x) a distribution over outputs $\{(y_i, p_i)\}_{i \in I}$, $y_i : V \rightarrow \Sigma_{\text{out}}$

Non-signaling outcome

- An outcome is **non-signaling beyond distance T** if for all $S \subseteq V$, for all inputs $(G, x), (H, y)$ on V with $G[\mathcal{N}_T(S)] \sim H[\mathcal{N}_T(S)]$, the distributions restricted to $G[S]$ and $H[S]$ are the same

Non-signaling outcome

- An outcome is **non-signaling beyond distance T** if for all $S \subseteq V$, for all inputs $(G, x), (H, y)$ on V with $G[\mathcal{N}_T(S)] \sim H[\mathcal{N}_T(S)]$, the distributions restricted to $G[S]$ and $H[S]$ are the same

Example: 2-coloring cycles


- Outcome: sample uniformly at random a consistent 2-coloring

Non-signaling outcome

- An outcome is **non-signaling beyond distance T** if for all $S \subseteq V$, for all inputs $(G, x), (H, y)$ on V with $G[\mathcal{N}_T(S)] \sim H[\mathcal{N}_T(S)]$, the distributions restricted to $G[S]$ and $H[S]$ are the same

Example: 2-coloring cycles

- Outcome: sample uniformly at random a consistent 2-coloring




Non-signaling outcome

- An outcome is **non-signaling beyond distance T** if for all $S \subseteq V$, for all inputs $(G, x), (H, y)$ on V with $G[\mathcal{N}_T(S)] \sim H[\mathcal{N}_T(S)]$, the distributions restricted to $G[S]$ and $H[S]$ are the same

Example: 2-coloring cycles

- Outcome: sample uniformly at random a consistent 2-coloring




- non-signaling beyond distance $T = \lceil \frac{n-2}{4} \rceil$

Non-signaling outcome

- An outcome is **non-signaling beyond distance T** if for all $S \subseteq V$, for all inputs $(G, x), (H, y)$ on V with $G[\mathcal{N}_T(S)] \sim H[\mathcal{N}_T(S)]$, the distributions restricted to $G[S]$ and $H[S]$ are the same

Example: 2-coloring cycles

- Outcome: sample uniformly at random a consistent 2-coloring



- non-signaling beyond distance $T = \lceil \frac{n-2}{4} \rceil$

The φ -LOCAL and non-signaling LOCAL models

[Gavoille et al., DISC '09]

- The φ -**LOCAL** model is a computational model that produces non-signaling outcomes
 - class $\Phi[T]$ consists of problems solvable by outcomes that are non-signaling beyond distance T

The φ -LOCAL and non-signaling LOCAL models

[Gavoille et al., DISC '09]

- The φ -**LOCAL** model is a computational model that produces non-signaling outcomes
 - class $\Phi[T]$ consists of problems solvable by outcomes that are non-signaling beyond distance T

[Arfaoui and Fraigniaud, PODC '12]

- The **non-signaling** (NS) **LOCAL** model is a computational model that produces non-signaling outcomes defined for **every possible input graph**
 - class $\mathcal{NS}[T]$ defined analogously

The φ -LOCAL and non-signaling LOCAL models

[Gavoille et al., DISC '09]

- The φ -**LOCAL** model is a computational model that produces non-signaling outcomes
 - class $\Phi[T]$ consists of problems solvable by outcomes that are non-signaling beyond distance T

[Arfaoui and Fraigniaud, PODC '12]

- The **non-signaling** (NS) **LOCAL** model is a computational model that produces non-signaling outcomes defined for **every possible input graph**
 - class $\mathcal{NS}[T]$ defined analogously
- $\mathcal{P} \in \mathcal{NS}[T] \implies \mathcal{P} \in \Phi[T]$

Indistinguishability & graph-theory: det-LOCAL

- [Linial, FOCS '87] combines the indistinguishability argument with some graph-theoretic results

Problem: c -coloring trees: $T = \Omega(\log_c n)$

Indistinguishability & graph-theory: det-LOCAL

- [Linial, FOCS '87] combines the indistinguishability argument with some graph-theoretic results

Problem: c -coloring trees: $T = \Omega(\log_c n)$

- Ramanujan graphs of n nodes with the following properties
 - $2c^2$ -regular
 - girth $\Omega(\log_c n)$
 - chromatic number $> c$

Indistinguishability & graph-theory: det-LOCAL

- [Linial, FOCS '87] combines the indistinguishability argument with some graph-theoretic results

Problem: c -coloring trees: $T = \Omega(\log_c n)$

- Ramanujan graphs of n nodes with the following properties
 - $2c^2$ -regular
 - girth $\Omega(\log_c n)$
 - chromatic number $> c$
- **By contradiction:** det-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$

Indistinguishability & graph-theory: det-LOCAL

- [Linial, FOCS '87] combines the indistinguishability argument with some graph-theoretic results

Problem: c -coloring trees: $T = \Omega(\log_c n)$

- Ramanujan graphs of n nodes with the following properties
 - $2c^2$ -regular
 - girth $\Omega(\log_c n)$
 - chromatic number $> c$
- **By contradiction:** det-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R




Indistinguishability & graph-theory: det-LOCAL

- [Linial, FOCS '87] combines the indistinguishability argument with some graph-theoretic results

Problem: c -coloring trees: $T = \Omega(\log_c n)$

- Ramanujan graphs of n nodes with the following properties
 - $2c^2$ -regular
 - girth $\Omega(\log_c n)$
 - chromatic number $> c$
- **By contradiction:** det-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R
 - \mathcal{A} fails somewhere

R




Indistinguishability & graph-theory: det-LOCAL

- [Linial, FOCS '87] combines the indistinguishability argument with some graph-theoretic results

Problem: c -coloring trees: $T = \Omega(\log_c n)$

- Ramanujan graphs of n nodes with the following properties
 - $2c^2$ -regular
 - girth $\Omega(\log_c n)$
 - chromatic number $> c$
- **By contradiction:** det-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R
 - \mathcal{A} fails somewhere
 - T -radius neighborhood around the failing region




Indistinguishability & graph-theory: det-LOCAL

- [Linial, FOCS '87] combines the indistinguishability argument with some graph-theoretic results


Problem: c -coloring trees: $T = \Omega(\log_c n)$

- Ramanujan graphs of n nodes with the following properties
 - $2c^2$ -regular
 - girth $\Omega(\log_c n)$
 - chromatic number $> c$
- **By contradiction:** det-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R
 - \mathcal{A} **fails somewhere**
 - T -radius neighborhood around the failing region
 - it's a c -regular tree (completable to n nodes)




Indistinguishability & graph-theory: rand-LOCAL

- **By contradiction:** rand-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R




Indistinguishability & graph-theory: rand-LOCAL

- **By contradiction:** rand-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R
 - \mathcal{A} **fails somewhere**, but then?



Indistinguishability & graph-theory: rand-LOCAL


- **By contradiction:** rand-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R
 - \mathcal{A} **fails somewhere**, but then?



- Suppose R can admits a family of subgraphs $\{R_i\}_{i=1}^k$ such that
 - $\cup_{i=1}^k R_i = R$

Indistinguishability & graph-theory: rand-LOCAL


- **By contradiction:** rand-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R
 - \mathcal{A} **fails somewhere**, but then?



- Suppose R can admits a family of subgraphs $\{R_i\}_{i=1}^k$ such that
 - $\cup_{i=1}^k R_i = R$
 - $\implies \exists i^* \in [k]$ such that \mathcal{A} fails in R_{i^*} with probability at least $1/k$

Indistinguishability & graph-theory: rand-LOCAL


- **By contradiction:** rand-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R
 - \mathcal{A} **fails somewhere**, but then?




- Suppose R can admits a family of subgraphs $\{R_i\}_{i=1}^k$ such that
 - $\cup_{i=1}^k R_i = R$
 - $\implies \exists i^* \in [k]$ such that \mathcal{A} fails in R_{i^*} with probability at least $1/k$
 - $R[\mathcal{N}_T[R_{i^*}]]$ is a tree for each i

Indistinguishability & graph-theory: rand-LOCAL

- **By contradiction:** rand-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R
 - \mathcal{A} **fails somewhere**, but then?




- Suppose R can admits a family of subgraphs $\{R_i\}_{i=1}^k$ such that
 - $\cup_{i=1}^k R_i = R$
 - $\implies \exists i^* \in [k]$ such that \mathcal{A} fails in R_{i^*} with probability at least $1/k$
 - $R[\mathcal{N}_T[R_i]]$ is a tree for each i




Indistinguishability & graph-theory: rand-LOCAL

- **By contradiction:** rand-LOCAL algorithm \mathcal{A} with $T = \mathcal{O}(\log_c n)$
 - run \mathcal{A} in the Ramanujan graph R
 - \mathcal{A} **fails somewhere**, but then?



- Suppose R can admits a family of subgraphs $\{R_i\}_{i=1}^k$ such that
 - $\cup_{i=1}^k R_i = R$
 - $\implies \exists i^* \in [k]$ such that \mathcal{A} fails in R_{i^*} with probability at least $1/k$
 - $R[\mathcal{N}_T[R_i]]$ is a tree for each i



- Failing prob.: $1 - (1 - \frac{1}{k})^N$
 - lower bound $T_{\text{new}}(n) = T(n/N)$

Indistinguishability & graph-theory: NS-LOCAL

Issues

- **Possible dependencies:** output distributions for two subsets of nodes X and Y , then even if X and Y are far from each other, the outputs of these subsets might be dependent

Indistinguishability & graph-theory: NS-LOCAL

Issues

- **Possible dependencies:** output distributions for two subsets of nodes X and Y , then even if X and Y are far from each other, the outputs of these subsets might be dependent
- **No-cloning principle:** if two graphs G and H have different sizes, then even if they share two identical subgraphs G' and H' with isomorphic radius- T neighborhoods, the output distribution is not guaranteed to be identical over G' and H'

Indistinguishability & graph-theory: NS-LOCAL

Issues

- **Possible dependencies:** output distributions for two subsets of nodes X and Y , then even if X and Y are far from each other, the outputs of these subsets might be dependent
- **No-cloning principle:** if two graphs G and H have different sizes, then even if they share two identical subgraphs G' and H' with isomorphic radius- T neighborhoods, the output distribution is not guaranteed to be identical over G' and H'
- Can we do something similar?

Indistinguishability & graph-theory: NS-LOCAL

Issues

- **Possible dependencies:** output distributions for two subsets of nodes X and Y , then even if X and Y are far from each other, the outputs of these subsets might be dependent
- **No-cloning principle:** if two graphs G and H have different sizes, then even if they share two identical subgraphs G' and H' with isomorphic radius- T neighborhoods, the output distribution is not guaranteed to be identical over G' and H'
- Can we do something similar?
- We need to refine the definition of **cheating graph**

Cheating graph

Fix an LCL problem \mathcal{P} over some graph family \mathcal{F}

Cheating graph:

Cheating graph

Fix an LCL problem \mathcal{P} over some graph family \mathcal{F}

Cheating graph:

- For some n , there exist a value $T = T(n)$ and a graph G_n on n nodes with a **family of subgraphs** $\{G_n^{(i)}\}_{i=1}^k$ such that

Cheating graph

Fix an LCL problem \mathcal{P} over some graph family \mathcal{F}

Cheating graph:

- For some n , there exist a value $T = T(n)$ and a graph G_n on n nodes with a **family of subgraphs** $\{G_n^{(i)}\}_{i=1}^k$ such that
 - $\cup_{i=1}^k G_n^{(i)} = G_n$

Cheating graph

Fix an LCL problem \mathcal{P} over some graph family \mathcal{F}

Cheating graph:

- For some n , there exist a value $T = T(n)$ and a graph G_n on n nodes with a **family of subgraphs** $\{G_n^{(i)}\}_{i=1}^k$ such that
 - $\cup_{i=1}^k G_n^{(i)} = G_n$
 - \mathcal{P} is solvable on each $G_n[\mathcal{N}_T(G_n^{(i)})]$

Cheating graph

Fix an LCL problem \mathcal{P} over some graph family \mathcal{F}

Cheating graph:

- For some n , there exist a value $T = T(n)$ and a graph G_n on n nodes with a **family of subgraphs** $\{G_n^{(i)}\}_{i=1}^k$ such that
 - $\cup_{i=1}^k G_n^{(i)} = G_n$
 - \mathcal{P} is solvable on each $G_n[\mathcal{N}_T(G_n^{(i)})]$
 - for some $N > 0$, and all $\mathbf{x} \in \{1, \dots, k\}^N$, \mathcal{F} contains a graph $H_{\mathbf{x}}$ on $n \cdot N$ nodes which admits $\sqcup_{j=1}^N G_n^{(\mathbf{x}_j)}$ as induced subgraph $H'_{\mathbf{x}}$ so that $H_{\mathbf{x}}[\mathcal{N}_T(H'_{\mathbf{x}})]$ and $\sqcup_{j=1}^N G_n[\mathcal{N}_T(G_n^{(\mathbf{x}_j)})]$ are isomorphic

Cheating graph


Fix an LCL problem \mathcal{P} over some graph family \mathcal{F}

Cheating graph:


- For some n , there exist a value $T = T(n)$ and a graph G_n on n nodes with a **family of subgraphs** $\{G_n^{(i)}\}_{i=1}^k$ such that
 - $\cup_{i=1}^k G_n^{(i)} = G_n$
 - \mathcal{P} is solvable on each $G_n[\mathcal{N}_T(G_n^{(i)})]$
 - for some $N > 0$, and all $\mathbf{x} \in \{1, \dots, k\}^N$, \mathcal{F} contains a graph $H_{\mathbf{x}}$ on $n \cdot N$ nodes which admits $\sqcup_{j=1}^N G_n^{(\mathbf{x}_j)}$ as induced subgraph $H'_{\mathbf{x}}$ so that $H_{\mathbf{x}}[\mathcal{N}_T(H'_{\mathbf{x}})]$ and $\sqcup_{j=1}^N G_n[\mathcal{N}_T(G_n^{(\mathbf{x}_j)})]$ are isomorphic

Theorem: failing probability $\geq 1 - (1 - \frac{1}{k})^N$ and $T_{\text{new}}(n) = T(\frac{n}{N})$


Cheating graph



Cheating graph



N copies of the cheating graph G



Some applications

The following holds in NS-LOCAL

- **Result 1:** c -coloring trees with success probability ε requires locality
 $T = \Omega(\log_c n - \log_c \log \frac{1}{\varepsilon})$
 - Ramanujan graphs

Some applications

The following holds in NS-LOCAL

- **Result 1:** c -coloring trees with success probability ε requires locality $T = \Omega(\log_c n - \log_c \log \frac{1}{\varepsilon})$
 - Ramanujan graphs
- **Result 2:** 3-coloring $n \times n$ grids with success probability $\geq \varepsilon$ requires locality $T = \Omega(\frac{n}{\log \frac{1}{\varepsilon}})$

Some applications

The following holds in NS-LOCAL

- **Result 1:** c -coloring trees with success probability ε requires locality $T = \Omega(\log_c n - \log_c \log \frac{1}{\varepsilon})$
 - Ramanujan graphs
- **Result 2:** 3-coloring $n \times n$ grids with success probability $\geq \varepsilon$ requires locality $T = \Omega(\frac{n}{\log \frac{1}{\varepsilon}})$
 - quadrangulations of the Klein bottle

Some applications

The following holds in NS-LOCAL

- **Result 1:** c -coloring trees with success probability ε requires locality $T = \Omega(\log_c n - \log_c \log \frac{1}{\varepsilon})$
 - Ramanujan graphs
- **Result 2:** 3-coloring $n \times n$ grids with success probability $\geq \varepsilon$ requires locality $T = \Omega(\frac{n}{\log \frac{1}{\varepsilon}})$
 - quadrangulations of the Klein bottle
- **Result 3:** c -coloring χ -chromatic graphs with success probability $\geq \varepsilon$ requires locality $T = \Omega((\frac{n}{\log \frac{1}{\varepsilon}})^{1/\alpha})$ where $\alpha = \lfloor \frac{c-1}{\chi-1} \rfloor$

Some applications

The following holds in NS-LOCAL

- **Result 1:** c -coloring trees with success probability ε requires locality $T = \Omega(\log_c n - \log_c \log \frac{1}{\varepsilon})$
 - Ramanujan graphs
- **Result 2:** 3-coloring $n \times n$ grids with success probability $\geq \varepsilon$ requires locality $T = \Omega(\frac{n}{\log \frac{1}{\varepsilon}})$
 - quadrangulations of the Klein bottle
- **Result 3:** c -coloring χ -chromatic graphs with success probability $\geq \varepsilon$ requires locality $T = \Omega((\frac{n}{\log \frac{1}{\varepsilon}})^{1/\alpha})$ where $\alpha = \lfloor \frac{c-1}{\chi-1} \rfloor$
 - construction in [\[Bogdanov '13\]](#)

Some applications

The following holds in NS-LOCAL

- **Result 1:** c -coloring trees with success probability ε requires locality $T = \Omega(\log_c n - \log_c \log \frac{1}{\varepsilon})$
 - Ramanujan graphs
- **Result 2:** 3-coloring $n \times n$ grids with success probability $\geq \varepsilon$ requires locality $T = \Omega(\frac{n}{\log \frac{1}{\varepsilon}})$
 - quadrangulations of the Klein bottle
- **Result 3:** c -coloring χ -chromatic graphs with success probability $\geq \varepsilon$ requires locality $T = \Omega((\frac{n}{\log \frac{1}{\varepsilon}})^{1/\alpha})$ where $\alpha = \lfloor \frac{c-1}{\chi-1} \rfloor$
 - construction in [\[Bogdanov '13\]](#)
 - deterministic upper bound $T = \mathcal{O}(n^{\frac{1}{\alpha}} \text{polylog}(n))$

Some applications

The following holds in NS-LOCAL

- **Result 1:** c -coloring trees with success probability ε requires locality $T = \Omega(\log_c n - \log_c \log \frac{1}{\varepsilon})$
 - Ramanujan graphs
- **Result 2:** 3-coloring $n \times n$ grids with success probability $\geq \varepsilon$ requires locality $T = \Omega(\frac{n}{\log \frac{1}{\varepsilon}})$
 - quadrangulations of the Klein bottle
- **Result 3:** c -coloring χ -chromatic graphs with success probability $\geq \varepsilon$ requires locality $T = \Omega((\frac{n}{\log \frac{1}{\varepsilon}})^{1/\alpha})$ where $\alpha = \lfloor \frac{c-1}{\chi-1} \rfloor$
 - construction in [\[Bogdanov '13\]](#)
 - deterministic upper bound $T = \mathcal{O}(n^{\frac{1}{\alpha}} \text{polylog}(n))$

Approximate graph coloring

Problem: Let $2 \leq \chi \leq c$. The **approximate graph coloring** problem asks to c -color χ -chromatic graphs.

- **Previous results** (classical LOCAL model)
 - $c = 2, \chi = 2 \implies T = \Theta(n)$
 - $c = 3, \chi = 2 \implies T = \Omega(\sqrt{n})$ [Brandt et al., PODC '17]
 - $c \geq 4, \chi = 2 \implies T = \Omega(\log(n))$ [Linial, FOCS '87]
- **Our results** (All LOCAL models – from det. to non-signaling)
 - $\alpha = \lfloor \frac{c-1}{\chi-1} \rfloor \implies T = \Omega(n^{\frac{1}{\alpha}}), T = \mathcal{O}(n^{\frac{1}{\alpha}} \text{polylog}(n))$
 - \implies **no quantum advantage**

Bogdanov's construction

- **Theorem:** Let $\chi \geq 2$, $r \geq 1$, $\alpha \geq 0$ be integers. There exists a graph $G_{\alpha, \chi}$ such that
 - $\mathcal{LX}_r(G_{\alpha, \chi}) = \chi$

Bogdanov's construction

- **Theorem:** Let $\chi \geq 2$, $r \geq 1$, $\alpha \geq 0$ be integers. There exists a graph $G_{\alpha, \chi}$ such that
 - $\mathcal{LX}_r(G_{\alpha, \chi}) = \chi$
 - $\mathcal{X}(G_{\alpha, \chi}) = (\alpha + 1)(\chi - 1) + 1$

Bogdanov's construction

- **Theorem:** Let $\chi \geq 2$, $r \geq 1$, $\alpha \geq 0$ be integers. There exists a graph $G_{\alpha, \chi}$ such that
 - $\mathcal{LX}_r(G_{\alpha, \chi}) = \chi$
 - $\mathcal{X}(G_{\alpha, \chi}) = (\alpha + 1)(\chi - 1) + 1$
 - $|V(G_{\alpha, \chi})| = n = \frac{(2r\chi+1)^{\alpha+1}-1}{2r}$

Bogdanov's construction

- **Theorem:** Let $\chi \geq 2$, $r \geq 1$, $\alpha \geq 0$ be integers. There exists a graph $G_{\alpha, \chi}$ such that
 - $\mathcal{LX}_r(G_{\alpha, \chi}) = \chi$
 - $\mathcal{X}(G_{\alpha, \chi}) = (\alpha + 1)(\chi - 1) + 1$
 - $|V(G_{\alpha, \chi})| = n = \frac{(2r\chi + 1)^{\alpha + 1} - 1}{2r}$
- **Remark 1:** Let $c \geq \chi \geq 2$. If $\alpha = \lfloor \frac{c-1}{\chi-1} \rfloor$, then $\alpha(\chi - 1) + 1 \leq c < (\alpha + 1)(\chi - 1) + 1$

Bogdanov's construction

- **Theorem:** Let $\chi \geq 2$, $r \geq 1$, $\alpha \geq 0$ be integers. There exists a graph $G_{\alpha, \chi}$ such that
 - $\mathcal{LX}_r(G_{\alpha, \chi}) = \chi$
 - $\mathcal{X}(G_{\alpha, \chi}) = (\alpha + 1)(\chi - 1) + 1$
 - $|V(G_{\alpha, \chi})| = n = \frac{(2r\chi + 1)^{\alpha + 1} - 1}{2r}$
- **Remark 1:** Let $c \geq \chi \geq 2$. If $\alpha = \lfloor \frac{c-1}{\chi-1} \rfloor$, then $\alpha(\chi - 1) + 1 \leq c < (\alpha + 1)(\chi - 1) + 1$
- **Remark 2:** $r = \Theta(n^{\frac{1}{\alpha}} / \chi^{1 + \frac{1}{\alpha}})$


Bogdanov's construction

- **Theorem:** Let $\chi \geq 2$, $r \geq 1$, $\alpha \geq 0$ be integers. There exists a graph $G_{\alpha, \chi}$ such that
 - $\mathcal{LX}_r(G_{\alpha, \chi}) = \chi$
 - $\mathcal{X}(G_{\alpha, \chi}) = (\alpha + 1)(\chi - 1) + 1$
 - $|V(G_{\alpha, \chi})| = n = \frac{(2r\chi + 1)^{\alpha + 1} - 1}{2r}$
- **Remark 1:** Let $c \geq \chi \geq 2$. If $\alpha = \lfloor \frac{c-1}{\chi-1} \rfloor$, then $\alpha(\chi - 1) + 1 \leq c < (\alpha + 1)(\chi - 1) + 1$
- **Remark 2:** $r = \Theta(n^{\frac{1}{\alpha}} / \chi^{1 + \frac{1}{\alpha}})$

$G_{\alpha, \chi}$ is constructed recursively in α



Bogdanov's construction

- **Tensor product** of graphs





Bogdanov's construction

- Tensor product of graphs





Bogdanov's construction

- Tensor product of graphs





Bogdanov's construction

- Tensor product of graphs





Bogdanov's construction

- Tensor product of graphs



Bogdanov's construction

- Tensor product of graphs




r -join of graphs

- **r-join** of graphs ($r = 2$) $K_2^{(1)} \star_2 K_2^{(2)}$


r -join of graphs

- **r-join** of graphs ($r = 2$)

$$K_2^{(1)} \star_2 K_2^{(2)}$$



$$K_2^{(1)} \times K_2^{(2)} \times \{1\}$$




$$K_2^{(1)} \times K_3^{(2)} \times \{2\}$$

r -join of graphs

- **r-join** of graphs ($r = 2$)


$$K_2^{(1)} \star_2 K_2^{(2)}$$



r -join of graphs


- **r-join** of graphs ($r = 2$)

$$K_2^{(1)} \star_2 K_2^{(2)}$$



r -join of graphs


- **r-join** of graphs ($r = 2$)



r -join of graphs

- **r-join** of graphs ($r = 2$)

$$K_2^{(1)} \star_2 K_2^{(2)}$$




r -join of graphs

- **r-join** of graphs ($r = 2$)

$$K_2^{(1)} \star_2 K_2^{(2)}$$

$$- \chi(K_2^{(1)} \star_2 K_2^{(2)}) = 3$$




r -join of graphs

- **r -join** of graphs ($r = 2$)

$$K_2^{(1)} \star_2 K_2^{(2)}$$

- $\mathcal{X}(K_2^{(1)} \star_2 K_2^{(2)}) = 3$

- $G_{\alpha, \chi} = K_2^{(1)} \star_2 K_2^{(2)}$
for $(\alpha, \chi) = (1, 2)$



r -join of graphs


- **r -join** of graphs ($r = 2$)

$$K_2^{(1)} \star_2 K_2^{(2)}$$

- $\mathcal{X}(K_2^{(1)} \star_2 K_2^{(2)}) = 3$


- $G_{\alpha, \chi} = K_2^{(1)} \star_2 K_2^{(2)}$
for $(\alpha, \chi) = (1, 2)$

- $G_{\alpha, \chi} = G_{\alpha-1, \chi} \star_r K_{\chi}^{(\alpha)}$




Bogdanov's construction

- **r-join** of graphs ($r = 2$), example for $\chi = 3$



Bogdanov's construction

- **r-join** of graphs ($r = 2$), example for $\chi = 3$



- $\mathcal{X}(K_3^{(1)} \star_2 K_3^{(2)}) = 5$

Summary

- To date, **no quantum advantage** has been shown in the LOCAL model for LCLs

Summary

- To date, **no quantum advantage** has been shown in the LOCAL model for LCLs
- We prove that the following LCLs **cannot admit quantum advantage**
 - c -coloring trees
 - 3-coloring grids
 - c -coloring χ chromatic graphs
 - how? Extending indistinguishability and graph existential arguments all the way up to NS-LOCAL

Summary

- To date, **no quantum advantage** has been shown in the LOCAL model for LCLs
- We prove that the following LCLs **cannot admit quantum advantage**
 - c -coloring trees
 - 3-coloring grids
 - c -coloring χ chromatic graphs
 - how? Extending indistinguishability and graph existential arguments all the way up to NS-LOCAL
- Under development (spoiler alert)

Summary

- To date, **no quantum advantage** has been shown in the LOCAL model for LCLs
- We prove that the following LCLs **cannot admit quantum advantage**
 - c -coloring trees
 - 3-coloring grids
 - c -coloring χ chromatic graphs
 - how? Extending indistinguishability and graph existential arguments all the way up to NS-LOCAL
- Under development (spoiler alert)
 - all problems' complexities $\mathcal{O}(\log^* n)$ in classical LOCAL become $\mathcal{O}(1)$ in NS-LOCAL (**plus independence!**)

Summary

- To date, **no quantum advantage** has been shown in the LOCAL model for LCLs
- We prove that the following LCLs **cannot admit quantum advantage**
 - c -coloring trees
 - 3-coloring grids
 - c -coloring χ chromatic graphs
 - how? Extending indistinguishability and graph existential arguments all the way up to NS-LOCAL
- Under development (spoiler alert)
 - all problems' complexities $\mathcal{O}(\log^* n)$ in classical LOCAL become $\mathcal{O}(1)$ in NS-LOCAL (**plus independence!**)
 - (paths, cycles, trees): all problems' complexities $\mathcal{O}(1)$ in φ -LOCAL become $\mathcal{O}(\log^* n)$ in classical LOCAL

Summary

- To date, **no quantum advantage** has been shown in the LOCAL model for LCLs
- We prove that the following LCLs **cannot admit quantum advantage**
 - c -coloring trees
 - 3-coloring grids
 - c -coloring χ chromatic graphs
 - how? Extending indistinguishability and graph existential arguments all the way up to NS-LOCAL
- Under development (spoiler alert)
 - all problems' complexities $\mathcal{O}(\log^* n)$ in classical LOCAL become $\mathcal{O}(1)$ in NS-LOCAL (**plus independence!**)
 - (paths, cycles, trees): all problems' complexities $\mathcal{O}(1)$ in φ -LOCAL become $\mathcal{O}(\log^* n)$ in classical LOCAL
 - (paths, cycles, rooted trees): there **cannot be quantum advantage** beyond complexity $\mathcal{O}(\log^* n)$

Summary

- To date, **no quantum advantage** has been shown in the LOCAL model for LCLs
- We prove that the following LCLs **cannot admit quantum advantage**
 - c -coloring trees
 - 3-coloring grids
 - c -coloring χ chromatic graphs
 - how? Extending indistinguishability and graph existential arguments all the way up to NS-LOCAL
- Under development (spoiler alert)
 - all problems' complexities $\mathcal{O}(\log^* n)$ in classical LOCAL become $\mathcal{O}(1)$ in NS-LOCAL (**plus independence!**)
 - (paths, cycles, trees): all problems' complexities $\mathcal{O}(1)$ in φ -LOCAL become $\mathcal{O}(\log^* n)$ in classical LOCAL
 - (paths, cycles, rooted trees): there **cannot be quantum advantage** beyond complexity $\mathcal{O}(\log^* n)$

THANKS!