


Which members should Marketing protect before they drift, and is Q2 on track against the plan line?

Kalpa Retail's marketing lead wants each segment's top fifty members by Q2 revenue and a flag on falling monthly spend, and Meera Raghavan, the CEO, wants Q2 to date against the plan line. Q2 is July to September 2026; revenue is booked, every order at its amount: Rs 9,84,00,000 on 462 orders.

1 What does a window keep that GROUP BY throws away?



GROUP BY answers how much per group and keeps nothing below the group: four segments, four rows. A window function computes over related rows and keeps every row, adding one column: a place, a previous month, or a total so far. It is written `function() OVER (PARTITION BY ... ORDER BY ...)`: the partition says whose rows belong together and the order says which row comes before which. WHERE runs before any window exists, so a place is computed in a named step and filtered outside.

2 Is the top fifty a list of members or of orders?

The list	Rows	Members	Segments
The fifty biggest Q2 orders	50	28	1
Members ranked on summed Q2 revenue	50	50	3

`count(DISTINCT customer_id)` beside `count(*)` catches it. Ranked as members, the fifty are 35 Business, 11 Retail-Plus and 4 Retail-Core.

Crux. Say what one row of the list is before you rank it: fifty orders named only 28 members.

3 How does each segment get its own fifty?

Segment	Buyers	Book split	Partitioned
Business	35	35	35
Retail-Core	96	4	50
Retail-Plus	76	11	50
Student	20	0	20

```
row_number() OVER (PARTITION BY segment
                   ORDER BY q2_revenue DESC, customer_id)
```

Check each list against the smaller of 50 and its buyers.

Crux. "In each segment" is a PARTITION BY: fifty, or every buyer, in each segment.

4 When members tie at the line, how many does each rule ship?

Invented	A	B	C	D	E	F
Spend, Rs	7,500	7,500	6,000	5,200	5,200	4,100
ROW_NUMBER	1	2	3	4	5	6
RANK	1	1	3	4	4	6
DENSE_RANK	1	1	2	3	3	4

Ships	ROW_NUMBER	RANK	DENSE_RANK	Whole ties
Invented top 4	4	5	5	3
Retail-Core top 50	50	50	52	50

Two ties higher up leave DENSE_RANK two behind, so its 50 is Retail-Core's 52nd member.

Crux. RANK keeps a tie at the line and says the count; DENSE_RANK can run past the line with no tie at it.

5 Whose monthly spend fell two months running?

```
-- the quick flag, and the column that exposes it
lag(spend, 1) OVER (ORDER BY customer_id, month)
lag(customer_id, 1) OVER (ORDER BY customer_id, month)
-- the fix
lag(spend, 1) OVER (PARTITION BY customer_id ORDER BY month)
```

The quick flag names 20 members, 4 of them read from another member's months; the partition leaves 16.

Crux. Tell the window whose rows belong together, or LAG reads another member's month.

6 Did Q2 close on plan, and where was it at mid-quarter?

Booked to date	At the close	Against plan
Plan weeks LEFT JOIN weekly	Rs 9,68,60,180	Rs 15,39,810 short
1 to 5 July moved onto 6 July	Rs 9,84,00,000	Rs 10 ahead

The plan line has no week for 1 to 5 July. At mid-quarter Q2 stood Rs 1,57,51,980 ahead on one July week; six of seven full weeks since 10 August ran below plan. Add `order_id` to make it repeat.

Crux. A running total is done when its last value equals the quarter's total.

7 Does each flag hold up when a member skipped a month?

C-0216	May	Jun	Jul	Aug	Sep
Spend, Rs	6,440	none	4,300	none	2,540

LAG compared his September with July. Seven of the 16 flags step over an empty month, and checking that the two rows before September are August and July keeps 9. Zero-filling flags 26.

Crux. A month with no order is no reading: check that LAG read the calendar months before.

THE WORDS ON THIS SHEET

- Window function** Computes over related rows and keeps every row, adding one column
- PARTITION BY** Says whose rows belong together; the window restarts in each partition
- ROW_NUMBER** Numbers rows 1, 2, 3 with no repeats; a tiebreaker column decides ties
- RANK** Tied rows share a place, and the places they use up are skipped

- DENSE_RANK** Tied rows share a place and nothing is skipped; it numbers distinct values
- LAG** Reads a value from an earlier row in the window's order; NULL if none