

PHYC90045 Introduction to Quantum Computing

Week 12



Lecture 23
Quantum Computing architectures and quantum complexity classes

Lecture 24
Quantum Computing Review

Lab 12
HHL algorithm using the QUI

1

PHYC90045 Introduction to Quantum Computing



Quantum Computing Review

Physics 90045
Lecture 24

2

PHYC90045 Introduction to Quantum Computing



Review
(Selected Highlights)

3

PHYC90045 Introduction to Quantum Computing

Linear Algebra and Dirac notation

$|\psi\rangle = a|0\rangle + b|1\rangle$

For qubits we can use column vectors to represent a convenient basis for kets:

$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$
 $|1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$
 Computational basis states

$a|0\rangle + b|1\rangle = \begin{bmatrix} a \\ b \end{bmatrix}$
 $a, b \in \mathbb{C}$
 General qubit state
 a, b are "amplitudes"

4

PHYC90045 Introduction to Quantum Computing

The Bloch Sphere

A convenient geometric representation of single qubit states is the Bloch sphere:

5

PHYC90045 Introduction to Quantum Computing

Single Qubit Gates

Circuit symbol:

Matrix representation: $X = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$

Action on ket states: $\alpha|0\rangle + \beta|1\rangle \rightarrow \alpha|1\rangle + \beta|0\rangle$

QUI example:

$\frac{\sqrt{3}}{2}|0\rangle + \frac{-i}{2}|1\rangle$
 complex amplitudes

6

PHYC90045 Introduction to Quantum Computing

Multiple Qubit States

$$\begin{bmatrix} a \\ b \end{bmatrix} \otimes \begin{bmatrix} c \\ d \end{bmatrix} = \begin{bmatrix} ac \\ ad \\ bc \\ bd \end{bmatrix}$$

00 amplitude
01 amplitude
10 amplitude
11 amplitude

$|\psi\rangle = a|0\rangle + b|1\rangle$ $|\phi\rangle = c|0\rangle + d|1\rangle$

7

PHYC90045 Introduction to Quantum Computing

Two qubit operations

$\alpha|0\rangle + \beta|1\rangle$

$|0\rangle$

$|\psi\rangle$ $|\psi'\rangle$

Before the CNOT, the state is:

$$|\psi\rangle = (\alpha|0\rangle + \beta|1\rangle) \otimes |0\rangle = \alpha|00\rangle + \beta|10\rangle$$

After the CNOT, the state is:

$$|\psi'\rangle = \alpha|00\rangle + \beta|11\rangle$$

8

PHYC90045 Introduction to Quantum Computing

Using the QUI

In labs you will learn to use the “Quantum User Interface” (QUI) to construct circuits. Your first lab will be all about single qubit rotations.

Entanglement Probability: Min Max Phase

FILE 2 QUBITS DELETE GRAPHIC

Inspector Settings: PLOT RANGE (PERCENTILE), Lower: 0, Upper: 100, Gaps On:

MEASUREMENT PROBABILITY: 0.213

Inspector Settings: DROPPING (INDEX), V-AXIS STATE PROBABILITY, V-AXIS SCALE: LINEAR, COLOUR MAP: PHASE

9

PHYC90045 Introduction to Quantum Computing

THE UNIVERSITY OF
MELBOURNE

Entanglement

We can never find a, b, c, d, s.t.

$$\frac{|00\rangle + |11\rangle}{\sqrt{2}} \neq (a|0\rangle + b|1\rangle) \otimes (c|0\rangle + d|1\rangle)$$

A state which is not separable is called an **entangled** state.

Entanglement is a uniquely quantum mechanical property, with no direct classical analogue.

10

PHYC90045 Introduction to Quantum Computing

Dense Coding Circuit

Bob

Alice

Bell state preparation:

Bob's measurement

Alice encoding

Bell state preparation

Bob's measurement

Alice encoding

Bob's measurement

Bob's measurement

Alice's qubit: $|0\rangle$

Bob's qubit: $|0\rangle$

$|00\rangle \rightarrow \frac{|0\rangle + |1\rangle}{\sqrt{2}} |0\rangle$

$\rightarrow \frac{|00\rangle + |11\rangle}{\sqrt{2}}$

0, 0 $\frac{|00\rangle + |11\rangle}{\sqrt{2}} \rightarrow \frac{|00\rangle + |11\rangle}{\sqrt{2}}$

1, 0 $X_2 \frac{|00\rangle + |11\rangle}{\sqrt{2}} \rightarrow \frac{|01\rangle + |10\rangle}{\sqrt{2}}$

0, 1 $Z_2 \frac{|00\rangle + |11\rangle}{\sqrt{2}} \rightarrow \frac{|00\rangle - |11\rangle}{\sqrt{2}}$

1, 1 $X_2 Z_2 \frac{|00\rangle + |11\rangle}{\sqrt{2}} \rightarrow \frac{|01\rangle - |10\rangle}{\sqrt{2}}$

Alice applies one of four different operations to her qubit, based on the classical information she would like to send.


11

PHYC90045 Introduction to Quantum Computing

Teleportation



 THE UNIVERSITY OF
 MELBOURNE



Quantum circuit diagram for teleportation:

- Alice's qubit ($|\psi\rangle$) passes through a Hadamard (H) gate and then acts as the control for a CNOT gate on Bob's qubit.
- Bob's qubit ($|0\rangle_A$) passes through a Hadamard (H) gate and then acts as the control for a CNOT gate on Alice's qubit.
- Both qubits are measured (indicated by circles with diagonal lines).
- The measurement results are used to apply a Z gate on Bob's qubit.
- The final output is $|\psi\rangle$.

Alice measures	Bob's qubit	i.e. after correction Bob has successfully reconstructed Alice's original state.
0, 0	$ \alpha\rangle 0\rangle + \beta\rangle 1\rangle$	$ \alpha\rangle 0\rangle + \beta\rangle 1\rangle \rightarrow \alpha\rangle 0\rangle + \beta\rangle 1\rangle$
0, 1	$ \alpha\rangle 1\rangle + \beta\rangle 0\rangle$	$X(\alpha\rangle 1\rangle + \beta\rangle 0\rangle) \rightarrow \alpha\rangle 0\rangle + \beta\rangle 1\rangle$
1, 0	$ \alpha\rangle 0\rangle - \beta\rangle 1\rangle$	$Z(\alpha\rangle 0\rangle - \beta\rangle 1\rangle) \rightarrow \alpha\rangle 0\rangle + \beta\rangle 1\rangle$
1, 1	$ \alpha\rangle 1\rangle - \beta\rangle 0\rangle$	$ZX(\alpha\rangle 1\rangle - \beta\rangle 0\rangle) \rightarrow \alpha\rangle 0\rangle + \beta\rangle 1\rangle$


12

PHYC90045 Introduction to Quantum Computing

Deutsch-Josza algorithm



- Given a boolean function, f , determine if:
 - f is constant (always gives the same result), or
 - f is balanced (gives equal numbers of 0s and 1s)
- Classical algorithm** (worst case) needs $2^n/2+1$ queries
- Quantum algorithm** needs just 1 query.




13

PHYC90045 Introduction to Quantum Computing

Bernstein-Vazirani Algorithm





Given a Boolean function, f :

$$f(x) = x \cdot s \mod 2$$

find s .

$$x \cdot s = \sum_i x_i s_i$$


- Classical algorithm** needs n queries
- Quantum algorithm** needs just 1 query.

14

PHYC90045 Introduction to Quantum Computing

Simon's Algorithm





Given a 2-to-1 function, f , such that

$$f(x) = f(x \oplus a)$$

Find a .

Classical algorithm: $O(\sqrt{N})$ Queries to the oracle (probabilistically)

Quantum algorithm: $O(n)$ Queries to the oracle

15

PHYC90045 Introduction to Quantum Computing




 THE UNIVERSITY OF
 MELBOURNE

Grover's Algorithm

- Unordered search, find one marked item among many
- Classically, this requires $N/2$ uses of the oracle
- Quantum mechanically, requires only $O(\sqrt{N})$.



Lou Grover



The diagram illustrates a quantum circuit for Grover's algorithm. It consists of four main sections: an input register, an oracle, an inversion layer, and an output register.

- Input Register:** On the far left, there are four qubits, each initialized to $|0\rangle$. Each qubit passes through a Hadamard (H) gate before entering the circuit.
- Oracle:** The next section is labeled "Oracle". It contains four H gates stacked vertically. This is followed by a blue rectangular box labeled "Oracle", which represents the oracle function. The oracle acts on all four qubits simultaneously.
- Inversion Layer:** After the oracle, there is a grey rectangular box labeled "Inversion". It contains four $i\lvert - \rangle \langle - \rvert i$ terms, representing the inverse of the oracle. This is followed by another blue rectangular box labeled "Inversion", which contains four $\lvert - \rangle \langle - \rvert i$ terms, representing the inverse of the oracle again.
- Output Register:** The final section is an output register consisting of four qubits. Each qubit passes through a Hadamard (H) gate before being measured. The measurement results are shown as three curved arrows pointing to the right, indicating the three marked items found by the algorithm.

16

PHYC90045 Introduction to Quantum Computing

Shor's algorithm



- Efficient quantum algorithms for **factoring** semiprime numbers
- Best known classical algorithm is number field sieve (exponential in bit-length).
- Underpins the RSA cryptosystem
- Hidden Subgroup Problems (eg. Discrete logarithm) similar.




Peter Shor


17

The diagram illustrates a quantum optics experiment setup. A central grid of grey diagonal lines represents beam splitters. Blue vertical lines indicate the path of a single photon as it passes through the grid. One path is labeled "Path of a photon". The setup includes two vertical grey bars on the left and right labeled "Wall", and a blue arrow pointing from the text "Beamsplitter" to one of the diagonal lines.


18



19



20



21

PHYC90045 Introduction to Quantum Computing

Purity for one qubit

If the distance from the origin to the state is measured to be r , the purity is:

$$P = \frac{1 + r^2}{2}$$

Maximum purity of 1 for all pure states.

Minimum purity of $\frac{1}{2}$ for a completely mixed state.

Note: There's a more technical definition of purity in terms of density matrices, which we won't cover in this course.

22

PHYC90045 Introduction to Quantum Computing

Randomized Benchmarking

How good are our gates individual gate? We want a number for how much error doing each operation is. One way of determining this is to perform **randomized benchmarking**.

23

PHYC90045 Introduction to Quantum Computing

Quantum Error Correction

Similar to classical error correction codes, we can have a quantum repetition code:

$ 0\rangle \rightarrow 000\rangle$	"Logical 0"
$ 1\rangle \rightarrow 111\rangle$	"Logical 1"

In particular, a quantum superposition would be encoded as:

$$\alpha |0\rangle + \beta |1\rangle \rightarrow \alpha |000\rangle + \beta |111\rangle$$

Two key differences between quantum and classical error correction codes:

1. Cannot measure the codewords directly; would collapse the state
2. Phase errors

24

The Surface Code

Fig. 5. Circuits used to measure X-stabilizers (left) and Z-stabilizers (right).


25

PHYC90045 Introduction to Quantum Computing


THE UNIVERSITY OF
MELBOURNE

Optimization Problems

Given some cost-function or “objective function” we would like to maximize/minimize. Often the inputs/parameters are constrained.



26

PHYC90045 Introduction to Quantum Computing

Number partitioning as a QUBO problem

But if we square, we should get a positive solution (or zero). We want to find the assignment of spins which has the minimum energy (ie. closest to zero):

$$H = \left(\sum_i w_i Z_i \right)^2 = \sum_{i \neq j} 2w_i w_j Z_i Z_j + \sum_i w_i^2 I$$


Coupling is the product of numbers

Eg. For the set {1, 2, 3}:


$$H = 4Z_1Z_2 + 6Z_1Z_3 + 12Z_2Z_3 + 14I$$

Finding minimum energy state will solve the problem!


27




28




29




30



31



32



33

PHYC90045 Introduction to Quantum Computing

Week 12



Lecture 23
Quantum Computing architectures and quantum complexity classes

Lecture 24
Quantum Computing Review

Lab 12
HHL algorithm using the QUI

34