


PHYC90045 Introduction to Quantum Computing



Week 12


Lecture 23
Quantum Computing architectures and quantum complexity classes

Lecture 24
Quantum Computing Review

Lab 12
HHL algorithm using the QUI

1

PHYC90045 Introduction to Quantum Computing




Quantum Computing Implementations
and Complexity Classes

Physics 90045
Lecture 23

2


PHYC90045 Introduction to Quantum Computing



Implementations

3

PHYC90045 Introduction to Quantum Computing




Different Quantum Computing Hardware

Different ways to implement a quantum computer:

- Ion Traps
- Superconducting qubits
- NV centres
- Quantum Optics
- Semiconductors: Donors and Dots

4

PHYC90045 Introduction to Quantum Computing



Ion Traps





Image: Rainer Blatt (Innsbruck). Electrodes to trap six ⁴⁰Ca ions. Ions are laser cooled, and can remain in the trap for days once cooled. Qubit manipulation and readout via laser, CCD camera.

5

PHYC90045 Introduction to Quantum Computing



Ion Traps (2)

The Qubit: Quantum states of trapped ions (typically ⁴⁰Ca), interacting via coupling to collective degree of freedom.

Number of Qubits Demonstrated: ~20-50

Fidelity reported: 99.9%

Pros:

- Largest number of high fidelity qubits
- Extremely high fidelity
- Demonstrated error correction code (7 qubit) and largest “genuine” demonstration of Shor’s algorithm.

Challenges:

- Transport of qubits
- Comparatively large
- Heating

Corporate support
IonQ

6

PHYC90045 Introduction to Quantum Computing

THE UNIVERSITY OF
MELBOURNE

Paper on measured error rates for ion traps

PHYSICAL REVIEW LETTERS 123, 110503 (2019)

Probing Qubit Memory Errors at the Part-per-Million Level

M. A. Sepiol, A. C. Hughes, J. E. Turlion, D. P. Nadlinger, T. G. Ballance, C. J. Ballance, T. P. Harty, A. M. Steane, J. F. Goodwin, and D. M. Lucas
Department of Physics, University of Oxford, Clarendon Laboratory, Parks Road, Oxford OX1 3PU, United Kingdom

(Received 10 June 2019; published 13 September 2019)

Robust qubit memory is essential for quantum computing, both for near-term devices operating without error correction, and for the long-term goal of a fault-tolerant processor. We directly measure the memory error ϵ_m for a $^{40}\text{Ca}^+$ trapped-ion qubit in the small-error regime and find $\epsilon_m < 10^{-4}$ for storage times $t \leq 50$ ms. This exceeds gate or measurement times by three orders of magnitude. Using randomized benchmarking, at $t = 1$ ms we measure $\epsilon_m = 1.2(7) \times 10^{-4}$, around ten times smaller than that extrapolated from the T_2 time, and limited by instability of the atomic clock reference used to benchmark the qubit.

DOI: 10.1103/PhysRevLett.123.110503


Sepiol et al, PRL, 123, 110503, (2019)

7

PHYC90045 Introduction to Quantum Computing

THE UNIVERSITY OF
MELBOURNE

Superconducting Qubits



John Martinis (UCSB) Showing five (transmon or Xmon) superconducting qubits placed in a row, each coupled to their neighbour. Information is stored in the charge/phase degrees of freedom.

8

PHYC90045 Introduction to Quantum Computing

THE UNIVERSITY OF
MELBOURNE

Superconducting Qubits (2)

The Qubit: The charge or phase degrees of freedom of superconducting circuits. Modern designs (transmon qubits) minimize noise.

Number of Qubits Demonstrated: ~50+

Fidelity reported: 99.4%

Pros:

- Large number of qubits
- Demonstrated transport
- Demonstrated genuine error suppression in five and nine qubit error correction codes


Challenges:

- Comparatively fast decoherence times
- Currently comparately large

Corporate support
Google, IBM, Rigetti

9

PHYC90045 Introduction to Quantum Computing



Quantum supremacy

Quantum supremacy using a programmable superconducting processor

Google AI Quantum and collaborators¹

The tantalizing promise of quantum computers is that certain computational tasks might be executed exponentially faster on a quantum processor than on a classical processor. A fundamental challenge is to build a high-fidelity processor capable of running quantum algorithms in an exponentially large computational space. Here, we report using a processor with programmable superconducting qubits to create quantum states on 53 qubits, occupying a state space $2^{53} \sim 10^{16}$. Measurements from repeated experiments sample the corresponding probability distribution, which we verify using classical simulations. While our processor takes about 200 seconds to sample one instance of the quantum circuit 1 million times, a state-of-the-art supercomputer would require approximately 10,000 years to perform the equivalent task. This dramatic speedup relative to all known classical algorithms provides an experimental realization of quantum supremacy on a computational task and heralds the advent of a much-anticipated computing paradigm.

In the early 1980s, Richard Feynman proposed that a quantum computer would be an effective tool to solve problems in physics and chemistry, as it is exponentially costly to simulate large quantum systems with classical computers [1]. Realizing Feynman's vision poses simi-


A COMPUTATIONAL TASK TO DEMONSTRATE QUANTUM SUPREMACY

To demonstrate quantum supremacy, we compare our quantum processor against state-of-the-art classical computers in the task of sampling the output of a pseudo-random quantum circuit [24–26]. Pseudo-randomness is a

Google's leaked paper, Financial Times, September 20, 2019

10

PHYC90045 Introduction to Quantum Computing



Quantum Optics





Image from Pryde (Griffiths University). Quantum states of light are used to represent quantum information, and manipulated using linear optics. First proposed by KLM, using entanglement generated by non-linear crystals, and subsequent linear optical operation.

11

PHYC90045 Introduction to Quantum Computing



Linear Optics (2)

The Qubit: The optical quantum states of light, including continuous variables, squeezed states, polarization and presence or absence of photons.

Pros:

- Communications and telecommunication applications
- Qubits impervious to their environment
- May demonstrate quantum advantage with Boson sampling

Challenges:


- Interacting large numbers of qubits
- Creating large quantum states
- Single photon sources

12

© L. Hollenberg, C. Hill 2020

4

PHYC90045 introduction to Quantum Computing



Generation of multi-qubit cluster states

SHARE

REPORT

Generation of time-domain-multiplexed two-dimensional cluster state

Went Asavanant¹, Yu Shikuzawa¹, Shota Yokoyama¹, Baranek Chareonwutamon¹, Hiroki Emori¹, Rafael N. Alexander¹, S. ...
• See all authors and affiliations

Science 18 Oct 2019
DOI: 10.1126/science.aba2645

Article

Figures & Data

Info & Metrics

eLetters

PDF

You are currently viewing the abstract.

[View Full Text](#)

Generating large-scale cluster states

The development of a practical quantum computer requires universality, scalability, and fault tolerance. Although much progress is being made in circuit platforms in which arrays of qubits are addressed and manipulated individually, scale-up of such systems is experimentally challenging. Asavanant et al. and Larsen et al. explore an alternative route: measurement-based quantum computation, which is a platform based on the generation of large-scale cluster states. As these are optically prepared and easier to handle (one simply performs local measurements on each individual component of the cluster state), such a platform is readily scalable and fault tolerant. The topology of the cluster state ensures that the approach meets the requirements for quantum computation.

Science, this issue p. 373, p. 369

ARTICLE TOOLS

Email

Download Presentation

Print

Save to my folders

Request Permissions

Alerts

Citation tools

Share

Science

Vol 366, Issue 6463
18 October 2019

Table of Contents

Next Table of Contents

Advertising (PDF)


Copyright (PDF)

Masterfile (PDF)


Asavanant et al, Science, 366, 6463, p373-376, 2019

13

PHYC90045 introduction to Quantum Computing



NV Centres




Nitrogen Vacancy centre in diamond forms a room temperature, electronic spin-1 system which can be manipulated with microwave fields, and read out optically.

Image: Ahanovic et al Nature Photonics, 2011

14

PHYC90045 introduction to Quantum Computing



NV Centres (2)

The Qubit: The electronic spin-1 system of an NV defect in diamond. Can be coupled to nearby nuclear spins.

Number of Qubits Demonstrated: 10

Fidelity reported: 99.2%

Pros:

- Room temperature
- Biologically compatible
- First loophole-free violation of Bell's inequalities (Delft)

Challenges:

- Coupling two NVs is difficult
- Diamond difficult to work with, scale

15

© L. Hollenberg, C. Hill 2020

5

PHYC90045 Introduction to Quantum Computing

NV quantum memory

Featured in Physics

Open Access

A Ten-Qubit Solid-State Spin Register with Quantum Memory up to One Minute

C. E. Bradley, J. Randall, M. H. Abobeih, R. C. Bernevoets, M. J. Degen, M. A. Bakker, M. Markham, D. J. Twitchen, and T. H. Taminiau

Phys. Rev. X **9**, 031045 – Published 11 September 2019

Physics See Synopses: Diamond Qubits Take the Stage

Article

References

No Citing Articles

Supplemental Material

PDF

HTML

Export Citation

ABSTRACT

Spins associated with single defects in solids provide promising qubits for quantum-information processing and quantum networks. Recent experiments have demonstrated long coherence times, high-fidelity operations, and long-range entanglement. However, control has so far been limited to a few qubits, with entangled states of three spins demonstrated. Realizing larger multiparticle registers is challenging due to the need for quantum gates that avoid cross talk and protect the coherence of the complete register. In this paper, we present novel decoherence-protected gates that combine dynamical decoupling of an electron spin with selective phase-controlled driving of nuclear spins. We use these gates to realize a ten-qubit quantum register consisting of the electron spin of a nitrogen-vacancy center and nine nuclear spins in diamond. We show that the register is fully connected by generating entanglement between all 45 possible qubit pairs and realize genuine multiparticle entangled states with up to seven qubits. Finally, we investigate the register as a multiqubit memory. We demonstrate the protection of an arbitrary single-qubit state for over 75 s—the longest reported for a single solid-state qubit—and show that two-qubit entanglement can be preserved for over 10 s.

Issue

Vol. 9, Iss. 3 – July - September 2019

Subject Areas

Condensed Matter Physics

Quantum Physics


Quantum Information

Check for updates

16

PHYC90045 Introduction to Quantum Computing

Semiconductor Donors and Dots



UNSW. Qubits are the states of individual donors (either electron or nuclear spins) or the electronic levels of quantum dots (act as artificial atoms).

17

PHYC90045 Introduction to Quantum Computing

Donors and Dots (2)

The Qubit: The electrons spin or nuclear spin degrees of freedom of a donor or a dot.

Number of Qubits Demonstrated: 2+

Fidelity reported: > 99%

Pros:

- Intrinsically extremely long decoherence times (3s/minutes)
- Existing semiconductor industry at scale
- Comparatively small

Challenges:


- Need more qubits and coupling

Company support

Intel, Commonwealth Bank, Telstra

18

PHYC90045 introduction to Quantum Computing



Donors: A two qubit swap gate

MENUnature

Letter | Published: 17 July 2019

A two-qubit gate between phosphorus donor electrons in silicon

Y. He, S. K. Gorman, D. Keith, L. Kranz, J. G. Keizer & M. Y. Simmons

Nature 571, 371–375 (2019) | Download Citation & Metrics

9857 Accesses | 1 Citations | 136 Altmetric


He et al, Nature, 571, 371-375 (2019)

Abstract

Electron spin qubits formed by atoms in silicon have large (tens of millielectronvolts) orbital energies and weak spin-orbit coupling, giving rise to isolated electron spin ground states with coherence times of seconds^{1,2}. High-fidelity (more than 99.9 per cent) coherent control of such qubits has been demonstrated³, promising an attractive platform for quantum computing. However, inter-qubit coupling—which is essential for realizing large-scale circuits in atom-based qubits—has not yet been achieved. Exchange interactions between electron spins^{4,5} promise fast (gigahertz) gate operations with two-qubit gates, as recently demonstrated in gate-

19


PHYC90045 introduction to Quantum Computing




Quantum Complexity Classes

20

PHYC90045 introduction to Quantum Computing



Some classical complexity classes



P: Problems which can be solved in polynomial time


NP: Problems which can be checked in polynomial time (ie. they have an efficiently verifiable proof)

#P: Problems which count the number of solutions in NP

What are the equivalent for quantum computers?

21

PHYC90045 Introduction to Quantum Computing




Complexity classes with error

BPP is Bounded error Probabilistic Polynomial time. Polynomial time, but on a probabilistic computer allowing for an error of as much as 1/3.

- Can flip coin and make random decisions
- Guaranteed to run in polynomial time
- On any given run of the algorithm has a probability <1/3 of the wrong answer, whether the answer is TRUE or FALSE.

22

PHYC90045 Introduction to Quantum Computing




BQP

Bounded error Quantum Polynomial Time


BQP is the set of decision problems solvable by a quantum computer in polynomial time, with an error of at most 1/3.

23

PHYC90045 Introduction to Quantum Computing



Polynomial Time Algorithms



BQP

BPP


P

BPP = P?


So BQP is (roughly, including error) the quantum equivalent of P/BPP. What's the analogy to NP?

24

PHYC90045 Introduction to Quantum Computing



QMA and QMA Complete



Quantum Merlin-Arthur (QMA) is the analog of NP.

Informally:

NP is the set of problems you can verify in polynomial time.

QMA is the set of problems you can verify in polynomial time with a quantum "proof".


Example: Is does the lowest energy eigenstate of local Hamiltonian H have an energy less than E_ϵ or are all the energies greater than E_ϵ ?

Verification uses a quantum state as a "proof", and measure the energy!


QMA Complete: The hardest problems in QMA. Can map any problem in QMA onto these.

25

PHYC90045 Introduction to Quantum Computing



"Stoquastic" Hamiltonians



Not all Hamiltonians are equally hard to find the ground state of. In fact, those we have using for quantum annealing are easier in comparison to a general local Hamiltonian. These types of Hamiltonians are known as stoquastic Hamiltonians, and have their own complexity class:


StoqMA

Technically, a **Stoquastic matrix** is a Hermitian matrix, where all off-diagonal elements are real and non-positive.


Clearly, since we've been encoding NP-complete problems like MAX-CUT StoqMA includes NP.

26

PHYC90045 Introduction to Quantum Computing



Fitting it all together




Classical Complexity Classes

Quantum Complexity Classes

27

PHYC90045 introduction to Quantum Computing

Week 12



Lecture 23
Quantum Computing architectures and quantum complexity classes

Lecture 24
Quantum Computing Review

Lab 12
HHL algorithm using the QUI
