

Spanning Tree

Refer

Behrouz A Forouzan, "Data Communications and Networking", Tata McGraw Hill, 2013.

+

PPT

Spanning Tree Protocol (STP) is a network protocol used to prevent loops in Ethernet networks, ensuring a loop-free topology and improving network reliability.

Working of Spanning Tree Protocol:

Bridge Election: In a network with multiple interconnected switches, STP elects one switch as the "root bridge." The root bridge serves as the reference point for calculating the shortest path to reach all network segments.

Path Selection: Once the root bridge is elected, each switch in the network calculates the shortest path to reach the root bridge using a cost metric based on link speeds. This process determines the "root port" on each switch, which is the port that offers the shortest path to the root bridge.

Loop Elimination: After determining the root port, each switch identifies and blocks redundant paths (designated as "non-root ports") to prevent loops. These blocked ports remain inactive until a topology change occurs.

Topology Changes: STP continuously monitors the network for changes in topology, such as link failures or additions. When a change occurs, affected switches recalculate their paths to the root bridge and adjust port states accordingly to restore a loop-free topology.

Election of Root Bridge in STP

The primary criteria used to elect the root bridge in STP include the Bridge ID (BID) and the Path Cost. The BID consists of two components: the Priority and the MAC address. When switches boot up, they exchange Bridge Protocol Data Units (BPDUs) containing their BIDs. The switch with the lowest BID becomes the root bridge.

Election Process:

- Each switch initially assumes it is the root bridge and advertises its BID with itself as the root.

- Upon receiving BPDUs from neighboring switches, each switch compares the received BID with its own. If the received BID has a lower Priority or, in case of a tie, a lower MAC address, the switch adjusts its view of the root bridge accordingly.
- Eventually, the switch with the lowest BID becomes the root bridge. This switch then sends out BPDUs with its BID, and all other switches in the network update their forwarding tables accordingly.

Impact on network performance and stability:

- **Traffic Flow:** The root bridge determines the shortest paths to reach all other switches in the network. By electing the root bridge based on the lowest BID, STP ensures that traffic flows along the most efficient paths, minimizing latency and congestion.
- **Loop Prevention:** The root bridge serves as the reference point for constructing the spanning tree. By blocking redundant links and eliminating loops, STP prevents broadcast storms and ensures stable network operation.
- **Convergence Time:** The root bridge selection process influences the convergence time of the network. Rapidly converging to a stable topology reduces downtime and improves network responsiveness to topology changes.
- **Network Stability:** The stability of the network is enhanced by having a designated root bridge that all switches reference. This centralized control simplifies network management and troubleshooting.

Advantages:

Loop Prevention: The primary advantage of STP is its ability to prevent network loops, which can cause broadcast storms and network congestion. By selectively blocking redundant links, STP ensures a loop-free topology.

Automatic Redundancy: STP allows for the deployment of redundant links between switches without causing loops. This redundancy enhances network reliability and fault tolerance by providing alternate paths in case of link or switches failures.

Self-Configuration: STP operates autonomously without requiring manual configuration. It automatically elects a root bridge and calculates the shortest path to reach all network segments, simplifying network management.

Scalability: STP can scale to accommodate large and complex network topologies, including hierarchical designs with multiple switches and interconnected LAN segments.

Disadvantages:

Convergence Time: STP convergence time, the time taken for the network to stabilize after a topology change, can be relatively slow, especially in large networks. During this time, network traffic may experience delays or disruptions.

Resource Utilization: STP may lead to inefficient utilization of network resources because it relies on link blocking to prevent loops. Blocked links remain inactive, reducing available bandwidth and potentially causing congestion on active links.

Limited Bandwidth: In networks with high bandwidth requirements, the bandwidth available on active links may not be sufficient to handle peak traffic loads, leading to performance degradation.

Complex Configuration: While STP is designed to operate autonomously, configuring and troubleshooting STP can be complex, especially in environments with multiple VLANs or non-standard topologies. Misconfigurations can result in network instability or suboptimal performance.

Types of Spanning Tree Protocols:

Spanning Tree Protocol (STP): The original version of the protocol, standardized by IEEE 802.1D. It provides loop prevention but has relatively slow convergence times.

Rapid Spanning Tree Protocol (RSTP): An evolution of STP, standardized by IEEE 802.1w. RSTP offers faster convergence times by reducing the number of states a port passes through during topology changes.

Multiple Spanning Tree Protocol (MSTP): Also known as IEEE 802.1s, MSTP allows for the creation of multiple spanning tree instances, each corresponding to a specific VLAN. This improves scalability and resource utilization in networks with multiple VLANs.