

```

INSERT INTO Studente VALUES
    (1,'Luca','Rossi'), (2,'Marco','Bianchi'),
    (3,'Anna','Verdi'),
    (4,'Giulia','Neri'), (5,'Paolo','Galli'),
    (6,'Sara','Conti'),
    (7,'Davide','Greco'), (8,'Elena','Romano'),
    (9,'Andrea','Costa'),
    (10,'Marta','Fontana'), (11,'Simone','Marini'),
    (12,'Laura','Moretti'),
    (13,'Alessio','Ferri'), (14,'Chiara','Riva'),
    (15,'Matteo','Colombo'),
    (16,'Irene','Serra'), (17,'Nicola','De Luca'),
    (18,'Federica','Mancini'),
    (19,'Giorgio','Longo'), (20,'Valentina','Barbieri'),
    (21,'Stefano','Villa'), (22,'Francesca','Leoni'),
    (23,'Riccardo','Testa'), (24,'Beatrice','Pellegrini'),
    (25,'Emanuele','Sartori'), (26,'Alice','Fabbri'),
    (27,'Tommaso','Orlando'), (28,'Noemi','Caruso'),
    (29,'Daniele','Parisi'), (30,'Silvia','Amato')
;

```

```

INSERT INTO Linguaggio VALUES
    (1,'Python'),
    (2,'Java'),
    (3,'C'),
    (4,'C++'),
    (5,'JavaScript'),
    (6,'PHP'),
    (7,'Go'),
    (8,'Rust');

```

```

INSERT INTO Progetto VALUES
    (1,'Sistema gestione esami',1),
    (2,'App mobile università',2),
    (3,'Motore di ricerca',3),
    (4,'Gioco 2D',4),
    (5,'Sito e-commerce',5),
    (6,'Portale web PHP',6),
    (7,'Server distribuito',7),
    (8,'Sistema embedded',3),
    (9,'Chat real-time',5),
    (10,'Compiler base',4),
    (11,'API REST',1),
    (12,'Tool di sicurezza',8);

```

```

INSERT INTO Lavora VALUES
    (1,1,'backend'), (2,1,'frontend'), (3,1,'db'),

```

```
(4,2,'mobile'), (5,2,'tester'),  
(6,3,'algoritmi'),  
(7,4,'grafica'), (8,4,'logica'),  
(9,5,'frontend'), (10,5,'backend'), (11,5,'db'),  
(12,6,'web'),  
(13,7,'network'), (14,7,'security'), (15,7,'devops'),  
(16,8,'firmware'),  
(17,9,'realtime'), (18,9,'ui'),  
(19,10,'parser'),  
(20,11,'api'), (21,11,'auth'),  
(22,12,'crypto'),  
(23,3,'ottimizzazione'),  
(24,4,'audio'),  
(25,5,'pagamenti'),  
(26,6,'cms'),  
(27,7,'monitoring'),  
(28,8,'testing'),  
(29,9,'scaling'),  
(30,12,'analisi');
```

Per fare comparire null nella left join aggiungiamo uno studente senza progetto:

```
VALUES (31, 'Giovanni', 'Test');
```