



The ElGamal Cryptosystem

Gianluca Dini
Dept. of Ingegneria dell'Informazione
University of Pisa
Email: gianluca.dini@unipi.it
Version: 2022-05-01



1

The ElGamal Cryptosystem

INTRODUCTION

May-22

The ElGamal Cryptosystem

2

UNIVERSITÀ DI PISA

INTRODUZIONE

Introduction

- Taher ElGamal, 1985
- An “extension” of Diffie-Hellman Key Exchange
- One-way function: Discrete Logarithm
- Applicable in any cyclic group where DLP and DHP are intractable
 - We consider \mathbb{Z}_p^*

May-22

The ElGamal Cryptosystem

3

3

UNIVERSITÀ DI PISA

FROM DHKE TO ELGAMAL ENCRYPTION

Alice

(c) choose $i = \text{priv}K_A \in \{2, \dots, p - 2\}$

(d) compute $k_E = \text{pub}K_A \equiv \alpha^i \bmod p$

(e) compute $k_M \equiv \beta^i \bmod p$

(g) Encrypt $x \in \mathbb{Z}_p^*$
 $y \equiv x \cdot k_M \bmod p$

Bob

(a) choose $d = \text{priv}K_B \in \{2, \dots, p - 2\}$

(b) compute $\beta = \text{pub}K_B \equiv \alpha^d \bmod p$

(f) compute $k_M \equiv k_E^d \bmod p$

(g) decrypt $x \equiv y \cdot k_M^{-1} \bmod p$

May-22


The ElGamal Cryptosystem

4

4

Foundations of Cybersecurity

2




 UNIVERSITÀ DI PISA

From DHKE to ElGamal encryption

- On parameters and keys
 - Domain parameters
 - Large p and primitive element α
 - Keys
 - The public-private pair (d, β) does not change
 - The public-private pair (i, k_E) is generated for every new message
 - k_E is called *ephemeral key*
 - k_M is called the *masking key*

May-22
The ElGamal Cryptosystem
5

5



 UNIVERSITÀ DI PISA

From DHKE to ElGamal encryption

- Intuition
 - One property of cyclic groups is that, given $k_M \in \mathbb{Z}_p^*$, every message x maps to another ciphertext if the two values are multiplied
 - If every k_M is randomly chosen from \mathbb{Z}_p^* then every y in $\{1, 2, \dots, p-1\}$ is equally likely
- Remark
 - In the ElGamal encryption scheme we do not need a TTP which generates p and α

May-22
The ElGamal Cryptosystem
6

6

The ElGamal encryption scheme

THE ELGAMAL ENCRYPTION SCHEME


May-22

The ElGamal Cryptosystem

7

7

From DHKE to ElGamal encryption

UNIVERSITÀ DI PISA

Alice

choose $i = \text{priv}K_A \in \{2, \dots, p - 2\}$
compute ephemeral key: $k_E = \text{pub}K_A \equiv \alpha^i \text{ mod } p$
compute masking key: $k_M \equiv \beta^i \text{ mod } p$
encrypt $x \in \mathbb{Z}_p^*$: $y \equiv x \cdot k_M \text{ mod } p$

Bob

choose large prime p
choose primitive element α of (a subgroup of) \mathbb{Z}_p^*
choose $d = \text{priv}K_B \in \{2, \dots, p - 2\}$
compute $\beta = \text{pub}K_B \equiv \alpha^d \text{ mod } p$

<----- $\text{pub}K_B = (p, \alpha, \beta)$ ----->

----- (y, k_E) ----->

compute masking key: $k_M \equiv k_E^d \text{ mod } p$
decrypt $x \equiv y \cdot k_M^{-1} \text{ mod } p$

May-22

The ElGamal Cryptosystem


8

8

Foundations of Cybersecurity

4

Proof



UNIVERSITÀ DI PISA

- Prove that $x \equiv y \cdot k_M^{-1} \pmod p$
 - Proof
 - $y \cdot k_M^{-1} \equiv (x \cdot k_M) \cdot (k_E^d)^{-1} \equiv (x \cdot (\alpha^d)^i) \cdot ((\alpha^i)^d)^{-1} \equiv$
 - $x \cdot \alpha^{d \cdot i - d \cdot i} \equiv x \pmod p$


May-22

The ElGamal Cryptosystem

9

9

ElGamal is probabilistic



UNIVERSITÀ DI PISA


- ElGamal encryption scheme is probabilistic
 - Encrypting two identical messages x_1 and x_2 with the same public key $\text{pub}K_B = (p, \alpha, \beta)$ results in two different ciphertext y_1 and y_2 (with high probability)
 - Masking key k_M is chosen at random for every new message
 - Brute force against x is avoided a priori

May-22

The ElGamal Cryptosystem

10

10



Performance issues


- Communication issues
 - Cyphertext expansion factor is 2
 - The bit size of (y, kE) is twice as the bit size of x
- Computational issues
 - Key Generation
 - Generation of large prime p (at least 1024 bits)
 - $privK$ is generated by a RBG
 - $pubK$ requires a modular exponentiation

May-22

The ElGamal Cryptosystem

11

11



Performance issues


- Computational issues
 - Encryption
 - Two modular exponentiations and a modular multiplication
 - Exponentiations are independent of plaintext
 - Pre-computation of k_E and k_M
 - Decryption
 - A modular exponentiation, a modular inverse and a modular multiplication
 - EEA can be used for modular inverse, or
 - We may combine exponentiation and inverse together, so we just need an exponentiation and a multiplication (➔)

May-22

The ElGamal Cryptosystem

12

12


UNIVERSITÀ DI PISA

Computational issues

- How to combine exponentiation and inverse together
 - Proof
 - Recall Fermat’s Little Theorem: Let a be an integer and p be a prime, $a^{p-1} \equiv 1 \pmod p$
 - Merge the two steps of decryption: $k_M^{-1} \equiv (k_E^d)^{-1} \equiv (k_E^d)^{-1} k_E^{p-1} \equiv k_E^p$
 \pmod{p}

May-22

The ElGamal Cryptosystem

13

13

ElGamal Cryptosystem

SECURITY ISSUES

May-22

The ElGamal Cryptosystem

14

14

Security issues – passive attacks



- The ElGamal problem
 - Recovering x from (p, α, β) and (y, k_E) where $\beta \equiv \alpha^d \pmod{p}$; $k_E = \alpha^i \pmod{p}$, and $y = x \cdot \beta^i \pmod{p}$
- The ElGamal Problem relies on the hardness of DHP
 - Currently there is no other known method for solving the DHP than solving the DLP
 - The adversary needs to compute Bob's secret exponent d or Alice's secret random exponent i
 - The Index-calculus method can be applied therefore $|p| = 1024+$

May-22

The ElGamal Cryptosystem

15

15

Security issues – active attacks




- Active attacks
 - Bob's public key must be authentic
 - Secret exponent i must be not reused (→)
 - ElGamal is malleable (→)

May-22

The ElGamal Cryptosystem

16

16



Security issues - active attacks


- On reusing the secret exponent i
 - Alice uses the same i for x_1 and x_2 , then
 - both the masking keys and the ephemeral keys would be the same
 - $k_E = \alpha^i \equiv \text{mod } p$
 - $k_M = \beta^i \equiv \text{mod } p$
 - She transmits (y_1, k_E) and (y_2, k_E)
 - The adversary
 - Can easily identify the reuse of i
 - If (s)he can guess/know x_1 , then (s)he can compute $x_2 \equiv y_2 \cdot k_M^{-1} \text{ mod } p$ with $k_M \equiv y_1 \cdot x_1^{-1} \text{ mod } p$

May-22

The ElGamal Cryptosystem

17

17



Security issues – active attacks

- On malleability
 - The adversary replaces (k_E, y) by $(k_E, s \cdot y)$
 - The receiver decrypts $x' \equiv x \cdot s \text{ mod } p$
 - Schoolbook ElGamal is often not used in practice, but some padding is introduced

May-22

The ElGamal Cryptosystem

18

18

May-22The ElGamal Cryptosystem19