

# Perfect Cipher

Gianluca Dini  
Dept. of Ingegneria dell'Informazione  
University of Pisa  
gianluca.dini@unipi.it

1

## Towards a secure cipher



UNIVERSITÀ DI PISA


- Attacker's ability: (one) cipher-text only attack
- Security requirements
  - Attacker cannot recover the secret key
  - Attacker cannot recover the plaintext
- Intuition of perfectly secure cipher
  - Regardless of *any prior information* the attacker has about the plaintext, the cyphertext should leak *no additional information* about the plaintext

March 22

Perfect cipher

2

2



UNIVERSITÀ DI PISA

## Preliminaries


- Random variable, probability distribution
- Conditional probability
  - $\Pr[A|B] = \Pr[A \wedge B] / \Pr[B]$
- Law of total probability
  - $\{E_i\}$  are a *partition* of all possible events
    - For all  $i, j, i \neq j$ ,  $E_i$  and  $E_j$  are pairwise impossible
    - At least some  $E_i$  occurs
  - For any event  $A$ ,  $\Pr[A] = \sum_i \Pr[A \wedge E_i] = \sum_i \Pr[A|E_i] \times \Pr[E_i]$
- Bayes' Theorem
  - $\Pr[A|B] = \Pr[B|A] \times \Pr[A] / \Pr[B]$

March 22

Perfect cipher

3

3



UNIVERSITÀ DI PISA

## A probabilistic approach

- Message  $M$  is a random variable
  - Plaintext distribution
  - Example
    - $\Pr[M = \text{"attack today"}] = 0.7$
    - $\Pr[M = \text{"don't attack"}] = 0.3$
  - Prior knowledge of the attacker
- $\text{Gen}()$  defines a probability distribution over  $K$ 
  - $\Pr[K = k] = \Pr[k \leftarrow \text{Gen}()]$
- Random variables  $M$  and  $K$  are independent

March 22

Perfect cipher

4

4

## A probabilistic approach



UNIVERSITÀ DI PISA

- Ciphertext generation process
  - Choose a message  $m$
  - Generate a key  $k$ ,  $k \leftarrow \text{Gen}()$
  - Compute  $c \leftarrow E_k(m)$
- The ciphertext is a random variable  $C$
- Encryption defines a distribution over the ciphertext  $\mathbf{C}$

March 22

Perfect cipher

5

5

## Perfect secrecy (informal)



UNIVERSITÀ DI PISA

- We formalize «information about the plaintext» in terms of probability distribution
- The adversary's *a-priori* knowledge of the plaintext distribution, i.e. before observing a ciphertext, and the adversary's *a-posteriori* knowledge of the plaintext distribution, i.e. after observing the ciphertext, must be equal

March 22

Perfect cipher

6

6

## Perfect secrecy (Shannon, 1949)



UNIVERSITÀ DI PISA

- Definition of Perfect secrecy – For every distribution over  $\mathbf{M}$ , every  $p$  in  $\mathbf{M}$ , every  $c$  in  $\mathbf{C}$ , with  $\Pr[C = c] > 0$ , it holds  $\Pr[M = m \mid C = c] = \Pr[M = m]$

March 22

Perfect cipher

7

7

## Shannon's Theorem



UNIVERSITÀ DI PISA

- Shannon's Theorem – In a perfect cipher,  $|\mathbf{K}| \geq |\mathbf{M}|$ 
  - i.e., the number of keys cannot be smaller than the number of messages
  - Proof. By contradiction.
    - a) Let  $|\mathbf{K}| < |\mathbf{M}|$
    - b) It must be  $|\mathbf{C}| \geq |\mathbf{M}|$  or, otherwise, the cipher is not invertible
    - c) Therefore,  $|\mathbf{C}| > |\mathbf{K}|$
    - d) Select  $m$  in  $\mathbf{M}$ , s.t.,  $\Pr[M = m] \neq 0$ ;  $c_i \leftarrow E(k_i, m)$  for all  $k_i$  in  $\mathbf{K}$
    - e) Because of c), there exists at least one  $c$  s.t.  $c \neq c_i$ , for all  $i$
    - f) Therefore  $\Pr[M = m \mid C = c] = 0$ , that is different of  $\Pr[M = m]$

March 22

Perfect cipher

8

8

## Unconditional security



UNIVERSITÀ DI PISA

- Perfect secrecy is equivalent to unconditional security
  - An adversary is assumed to have infinite computing resources
  - Observation of the CT provides the adversary no information whatsoever
- Necessary conditions
  - Key bits are truly randomly chosen
  - Key len  $\geq$  msg len (Shannon theorem)

March 22

Perfect cipher

9

9

## Perfect indistinguishability



UNIVERSITÀ DI PISA

- Definition – An encryption scheme  $\Pi = (G, E, D)$  over  $(\mathbf{K}, \mathbf{M}, \mathbf{C})$  has perfect indistinguishability iff
  - For all  $m_1, m_2 \in \mathbf{P}$ ,  $|m_1| = |m_2|$
  - with  $k \leftarrow \text{Gen}()$  (uniform)
  - For all  $c \in \mathbf{C}$ ,  $\Pr[E(k, m_1) = c] = \Pr[E(k, m_2) = c]$
- Fact –  $\Pi$  has perfectly indistinguishability iff it is perfectly secure

March 22

Perfect cipher

10

10

Perfect Cipher

# ONE-TIME PAD


March 22

Perfect cipher

11

11

# One Time Pad



UNIVERSITÀ DI PISA

- Patented in 1917 by Vernam
  - Known 35 years earlier
- Proven perfect by Shannon in 1949
- Moscow-Washington “red telephone”
  - In reality a secure direct communication link
    - Teletype, fax machine, secure computer link (email)
  - Never a telephone (not even red)


March 22

Perfect cipher

12

12

## Preliminary



- Or-exclusive (xor)
  - Truth table

x	y	$z = x \oplus y$
0	0	0
0	1	1
1	0	1
1	1	0
  - Mathematically
    - $z = x \oplus y = (x + y) \bmod 2$


March 22

Perfect cipher

13

13

## One Time Pad



- Assumptions
  - Let  $x$  be a  $t$ -bit message, i.e.,  $x \in \{0,1\}^t$
  - Let  $k$  be a  $t$ -bit key stream,  $k \in \{0, 1\}^t$ , where each bit is truly random chosen
- Encryption
  - For all  $i$  in  $[1,...,t]$ ,  $y_i = m_i \oplus k_i$  i.e.,  $y_i = m_i + k_i \bmod 2$
- Decryption
  - For all  $i$  in  $[1,..., t]$ ,  $x_i = c_i \oplus k_i$ , i.e.,  $x_i = y_i + k_i \bmod 2$
- Consistency property can be easily proven


March 22

Perfect cipher

14

14

# One-Time Pad



The diagram illustrates the One-Time Pad encryption process. It features three rectangular boxes: 'key' at the top, 'plaintext' on the left, and 'ciphertext' on the right. A vertical arrow points from the 'key' box down to a circular node containing a plus sign (+). A horizontal arrow points from the 'plaintext' box to the same circular node. Another horizontal arrow points from the circular node to the 'ciphertext' box.


March 22

Perfect cipher

15

15

# Xor is a good encryption function



UNIVERSITÀ DI PISA

- Theorem – Let  $X$  be a random variable over  $\{0, 1\}^n$ , and  $K$  an independent uniform variable over  $\{0,1\}^n$ . Then,  $Y = X \oplus K$  is uniform over  $\{0,1\}^n$ .
  - Proof (for  $n = 1$ ).
    - Let  $\Pr[X = 0] = X_0$ ,  $\Pr[X = 1] = X_1$ ,  $X_0 + X_1 = 1$
    - $\Pr[Y = 0] =$   
 $= \Pr[(X = 0) \wedge (K = 0)] + \Pr[(X = 1) \wedge (K = 1)] =$   
 $= \Pr[X = 0] \times \Pr[K = 0] + \Pr[X = 1] \times \Pr[K = 1] =$   
 $= X_0 \times 0.5 + X_1 \times 0.5 = 0.5 \times (X_0 + X_1) =$   
 $= 0.5$

March 22

Perfect cipher

16

16



UNIVERSITÀ DI PISA

OTP has perfect secrecy

- Theorem – OTP has perfect secrecy
  - Proof
    - a)  $\Pr[M = m | C = c] = (\text{Bayes law})$   
 $= \Pr[C = c | M = m] \times \Pr[M = m] / \Pr[C = c]$
    - b)  $\Pr[C = c] = (\text{Total probability law})$   
 $= \sum_i \Pr[C = c | M = m_i] \times \Pr[M = m_i] =$   
 $= \sum_i \Pr[K = c \oplus m_i] \times \Pr[M = m_i] =$   
 $= \sum_i 2^{-k} \times \Pr[M = m_i] = 2^{-k}$
    - c) Put b) into a)  
 $\Pr[M = m | C = c] =$   
 $= \Pr[K = c \oplus m] \times \Pr[M = m] / 2^{-k} =$   
 $= 2^{-k} \times \Pr[M = m] / 2^{-k} =$   
 $\Pr[M = m]$

March 22

Perfect cipher

17


17

UNIVERSITÀ DI PISA

OTP has perfect secrecy: intuition

- $c[i] = m[i] + k[i] \bmod 26$
- $m = \text{"SUPPORT JAMES BOND"}$

$m$	S	U	P	P	O	R	T	J	A	M	E	S	B	O	N	D
$k$	W	C	L	N	B	T	D	E	F	J	A	Z	G	U	I	R
$c$	O	V	A	C	P	K	W	N	F	V	E	R	H	I	V	U



$c$	O	V	A	C	P	K	W	N	F	V	E	R	H	I	V	U
$k'$	M	W	L	J	V	T	S	E	F	J	A	Z	G	U	I	R
$m$	C	A	P	T	U	R	E	J	A	M	E	S	B	O	N	D

March 22

Perfect cipher

19

19

## Pros and Cons



UNIVERSITÀ DI PISA

- Pros
  - Unconditionally secure
    - A cryptosystem is unconditionally or information-theoretically secure if it cannot be broken even with infinite computational resources
  - Very fast enc/dec
  - Only one key maps  $m$  into  $c$

March 22

Perfect cipher

20

20

## Pros and Cons



UNIVERSITÀ DI PISA


- Cons
  - Long keys: unpractical!
    - Key len == msg len
  - Keys must be used once: avoid two-time pad!
    - Let  $C1 = M1 \text{ xor } K$  and  $C2 = M2 \text{ xor } K \Rightarrow$   
 $C1 \text{ xor } C2 = M1 \text{ xor } M2$
  - A Known-PlainText attack breaks OTP
    - Given  $(m, c) \Rightarrow k = m \text{ xor } c$
  - OTP is malleable
    - Modifications to cipher-text are undetected and have predictable impact on plain-text

March 22

Perfect cipher

21


21




UNIVERSITÀ DI PISA

# OTP is malleable


$m$	=	D	A	R	E	C	E	N	T	O	E	U	R	O	A	B	O	B
$k$	=	W	C	L	N	B	T	D	E	F	J	A	Z	G	U	I	R	X
$c$	=	Z	C	C	R	D	X	Q	X	T	N	U	Q	U	U	J	F	Y



ZCCRD...



ZCCRN...




$c'$	=	Z	C	C	R	N	B	O	P	J	N	U	Q	U	U	J	F	Y
$k$	=	W	C	L	N	B	T	D	E	F	J	A	Z	G	U	I	R	X
$m$	=	D	A	R	E	M	I	L	L	E	E	U	R	O	A	B	O	B

March 22

Perfect cipher

22

22



UNIVERSITÀ DI PISA

# Malleability

- Malleability
  - A crypto scheme is said to be malleable if the attacker is capable of transforming the ciphertext into another ciphertext which leads to a known transformation of the plaintext
    - The attacker does not decrypt the ciphertext but (s)he is able to manipulate the plaintext in a predictable manner


March 22

Perfect cipher

23

23

# On OTP malleability



UNIVERSITÀ DI PISA


- Attack against integrity
  - Alice sends Bob:  $c = p \oplus k$
  - The adversary
    - intercepts  $c$  and
    - transmits Bob  $c' = c \oplus r$ , with  $r$  called *perturbation*
  - Bob
    - receives  $c'$
    - Computes  $p' = c' \oplus k = c \oplus r \oplus k = p \oplus k \oplus r \oplus k$  so obtaining  $p' = p \oplus r$
    - The perturbation goes undetected and
    - The perturbation has a predictable impact on the plaintext

March 22

Perfect cipher

24

# Example 1



UNIVERSITÀ DI PISA

- Shift cipher
  - $K = \{0, \dots, 26\}$ ,  $\Pr[K = k] = 1/26$
  - $\Pr[M = 'a'] = 0.7$ ;  $\Pr[M = 'z'] < 0.3$  (a-priori distribution)
  - Compute  $\Pr[C = 'b']$ 
    - Result =  $1/26$

March 22

Perfect cipher

25

## Example 2



UNIVERSITÀ DI PISA

- Shift cipher
  - $K = \{0, \dots, 26\}$ ,  $\Pr[K = k] = 1/26$
  - $m1 = \text{«one»}$ ,  $m2 = \text{«ten»}$
  - $\Pr[M = m1] = \Pr[M = m2] = 0.5$  (a-priori distribution)
  - Compute  $\Pr[C = \text{«rqh»}]$ 
    - Result =  $1/52$

March 22

Perfect cipher

26

26

## Example 3



UNIVERSITÀ DI PISA


- Shift cipher
  - $K = \{0, \dots, 26\}$ ,  $\Pr[K = k] = 1/26$
  - $m1 = \text{«one»}$ ,  $m2 = \text{«ten»}$
  - $\Pr[M = m1] = \Pr[M = m2] = 0.5$  (a-priori distribution)
  - Compute  $\Pr[M = \text{«ten»} \mid C = \text{«rqh»}]$ 
    - Result = 0 that is different of  $\Pr[M = \text{«ten»}]$

March 22

Perfect cipher

27

27



UNIVERSITÀ DI PISA

## Example 4


- Shift cipher
- Message distribution
  - $\Pr[M = \text{«hi»}] = 0.3$
  - $\Pr[M = \text{«no»}] = 0.2$
  - $\Pr[M = \text{«in»}] = 0.5$
- Compute  $\Pr[M = \text{«hi»} \mid C = \text{«xy»}]$ 
  - $\Pr[M=\text{«hi»} \mid C=\text{«xy»}] = (\text{Bayes' law}) =$   
 $= \Pr[C = \text{«xy»} \mid M=\text{«hi»}] \cdot \Pr[M=\text{«hi»}] / \Pr[C=\text{«xy»}]$
  - $\Pr[C = \text{«xy»} \mid M=\text{«hi»}] = \Pr[K = 16] = 1/26$  (continue)

March 22

Perfect cipher

28

28



UNIVERSITÀ DI PISA

## Example 4 continued

- Compute  $\Pr[M = \text{«hi»} \mid C = \text{«xy»}]$ 
  - $\Pr[C = \text{«xy»}] =$   
 $= \Pr[C=\text{«xy»} \mid M=\text{«hi»}] \cdot \Pr[M=\text{«hi»}] +$   
 $\Pr[C=\text{«xy»} \mid M=\text{«no»}] \cdot \Pr[M=\text{«no»}] +$   
 $\Pr[C=\text{«xy»} \mid M=\text{«in»}] \cdot \Pr[M=\text{«in»}] =$   
 $= (1/26) \cdot 0.3 + (1/26) \cdot 0.2 + 0 \cdot 0.5 =$   
 $= 1/52$
  - $\Pr[M = \text{«hi»} \mid C = \text{«xy»}] = (1/26) \cdot 0.3 / (1/52) = 0.6$   
 $\neq \Pr[M = \text{«hi»}]$
- Shift cipher is not perfect

March 22

Perfect cipher

29

29