
Thesis Proposal:

The Role of Embeddings in Data-Driven Augmentation

Federico Dassereto

September 30, 2020

Abstract

Maecenas ipsum velit, consectetur eu, lobortis ut, dictum at, dui. In rutrum. Sed ac dolor sit amet purus malesuada congue. In laoreet, magna id viverra tincidunt, sem odio bibendum justo, vel imperdiet sapien wisi sed libero. Suspendisse sagittis ultrices augue. Mauris metus. Nunc dapibus tortor vel mi dapibus sollicitudin. Etiam posuere lacus quis dolor. Praesent id justo in neque elementum ultrices. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. In convallis. Fusce suscipit libero eget elit. Praesent vitae arcu tempor neque lacinia pretium. Morbi imperdiet, mauris ac auctor dictum, nisl ligula egestas nulla, et sollicitudin sem purus in lacus. Praesent in mauris eu tortor porttitor accumsan. Mauris suscipit, ligula sit amet pharetra semper, nibh ante cursus purus, vel sagittis velit mauris vel metus. Aenean fermentum risus id tortor. Integer imperdiet lectus quis justo. Integer tempor. Vivamus ac urna vel leo pretium faucibus. Mauris elementum mauris vitae tortor. In dapibus augue non sapien. Aliquam ante. Curabitur bibendum justo non orci.

Morbi a metus. Phasellus enim erat, vestibulum vel, aliquam a, posuere eu, velit. Nullam sapien sem, ornare ac, nonummy non, lobortis a, enim. Nunc tincidunt ante vitae massa. Duis ante orci, molestie vitae, vehicula venenatis, tincidunt ac, pede. Nulla accumsan, elit sit amet varius semper, nulla mauris mollis quam, tempor suscipit diam nulla vel leo. Etiam commodo dui eget wisi. Donec iaculis gravida nulla. Donec quis nibh at felis congue commodo. Etiam bibendum elit eget erat.

Maecenas ipsum velit, consectetur eu, lobortis ut, dictum at, dui. In rutrum. Sed ac dolor sit amet purus malesuada congue. In laoreet, magna id viverra tincidunt, sem odio bibendum justo, vel imperdiet sapien wisi sed libero. Suspendisse sagittis ultrices augue. Mauris metus. Nunc dapibus tortor vel mi dapibus sollicitudin. Etiam posuere lacus quis dolor. Praesent id justo in neque elementum

1 Motivation and Description

Since the rise of the World Wide Web, we have experienced an exponential growth in publicly available data. Data has become a crucial element in everyday life and many devices continuously produce and store them in a forest of different formats. This exponential growth has posed many challenges to scientists (even going so far as to create the figure of the *data scientist*) in every step in which data are traditionally used: from data collection to integration, from processing to visualization. The impact of *Big Data* has been

summarized in [5], where the key properties are **V**olume, **V**elocity, **V**ariety, **V**eracity and **V**alue.

In data science, it is increasingly the case that the main challenge is not in integrating known data, rather it is in finding the right data to solve a given data science problem. Today, data is a mass (uncountable) like dust, and data surrounds us like dust, even lovely structured data. Data is so cheap and easy to obtain that it is no longer important to always get the integration right and integrations are not static things (**V**elocity component). Data integration research has embraced and prospered by using approximation and machine learning. The uncontrolled nature of data manifests in large repositories of data (data lakes), in which both structured and unstructured data are stored. The peculiarity of data lakes lies in the fact that there is uncertainty about the presence of metadata describing the data themselves. Furthermore, it is common the situation in which there is a lack of schemas, making traditional database approaches to integrating or querying data difficult to pursue or even infeasible. Along with the uncertainty regarding the quality of the data, the amount of such data makes it infeasible also the traditional human-in-the-loop framework, since hand-labeling or manual rating of very large amounts of data is extremely expensive. It is easy to see that searching in data lakes is a complicated task, both in terms of time and methodology.

Following the path traced by Tim Berners-Lee et al. in [1] about Open Data publication and maintenance, many organizations are publishing data, augmenting tremendously the **V**olume and the **V**alue of such data. On the other hand, the explosion of sources providing data increases their **V**ariety, requiring new techniques to integrate data. At a processing level, the main difficulty arisen by the multiple sources and possibly unstructured data is given by the interpretation, i.e., the semantic layer. To extract semantics from unstructured data, in the last years the concept of embedding has been proposed. Embeddings are predominantly used in learning representations of texts [6] and graphs [7]. In the last year, an approach exploiting embedding to solve data integration task [2] has been published. This work can be seen as forerunner for the integration of embeddings in data management tasks, even if it works on tables from the same context.

A data scientist who is trying to solve machine learning tasks, frequently found herself in the situation in which there are not enough data to build a good model. Given the amount of data previously discussed, it would be very useful a framework which enables her to find automatically new features or samples to improve the model. Broadly, two main classes of augmentation can be distinguished: *Horizontal Augmentation*, in which new significant features are added to the dataset and *Vertical Augmentation*, in which new samples (tuples) are added to the dataset. Ideally, the two classes can be seen as the search for joinable (Horizontal) or unionable (Vertical) tables in the data lakes situation, and Knowledge Bases (KB) completion or extensions (vertical).

In this thesis, we focus on the problem of *using embeddings for automatic augmentation of data to improve machine learning tasks*. We believe that it is a crucial integration task that has not yet been explored, either as augmentation problem itself nor with the usage of embeddings. Few approaches that try to augment tables with respect to a repository have been proposed; the two closest approaches proposed until now show different problems: (i) a set of rules to decide if it is safe to avoid a join or not [4], restricted to a *pure relational* settings, i.e., the schemas of each table is known; and (ii) a feature selection algorithm working on a matrix in which the number of attributes is much larger than the number of tuples [3].

The goal of this thesis is to study how to stabilize the automatic increase and make it scalable to possibly huge tables or data lakes. The idea is to define indexing structures,

based on information theoretic measures, to make the search for joining tables fast and adapt to the variety of existing joining possibilities (one-to-one, one-to-many, many-to-one, many-to-many). More precisely, the thesis will propose and index for horizontal augmentation on the data lakes scenario, as well as the integration of embeddings in the augmentation of KBs. Eventually, an embedding algorithm for KBs will summarize unified framework the two previous results.

2 Reference Area and Relevance of Goals

3 State of the Art

4 Goals and Preliminaries

GOALS

- AGGIUNGI Embedding per ricerca in funzione di ML
- Studiare l'augmentation in termini di cosa esiste (entropia, FDs)
- Possibilità di augmenting verticale
- Introduzione delle KBs

5 Research Plan

Acknowledgements

So long, and thanks for all the fish.

References

- [1] Christian Bizer, Tom Heath, and Tim Berners-Lee. “Linked data: The story so far”. In: *Semantic services, interoperability and web applications: emerging concepts*. IGI Global, 2011, pp. 205–227.
- [2] Riccardo Cappuzzo, Paolo Papotti, and Saravanan Thirumuruganathan. “Creating embeddings of heterogeneous relational datasets for data integration tasks”. In: *Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data*. 2020, pp. 1335–1349.
- [3] Nadiia Chepurko et al. “ARDA: Automatic Relational Data Augmentation for Machine Learning”. In: *arXiv preprint arXiv:2003.09758* (2020).
- [4] Arun Kumar et al. “To join or not to join? thinking twice about joins before feature selection”. In: *Proceedings of the 2016 International Conference on Management of Data*. 2016, pp. 19–34.
- [5] Andrew McAfee et al. “Big data: the management revolution”. In: *Harvard business review* 90.10 (2012), pp. 60–68.
- [6] Tomas Mikolov et al. “Efficient estimation of word representations in vector space”. In: *arXiv preprint arXiv:1301.3781* (2013).

- [7] Maximillian Nickel and Douwe Kiela. “Poincaré embeddings for learning hierarchical representations”. In: *Advances in neural information processing systems*. 2017, pp. 6338–6347.