GRIDINTEL · UTILITY INTELLIGENCE

Daily operations brief

SAMPLE: SYNTHETIC DATA

This report is a sample. It shows the format and the methods GridIntel would deliver; it is not a report of real results. Every figure in it is calculated from a designed demonstration dataset, and none describes a real network, site, customer or organization.

A designed demonstration dataset for September 2026. It describes no real network, customer, meter reading, outage, bill or payment.

FOR
Control room; DisCo management

RECORDS OF
Savanna Electricity Distribution (synthetic)

PERIOD
30 September 2026

REPORT ID
GI-DOB-2026-09-30-44FDB02F

FIGURES COMPUTED
20 Oct 2026, 10:11 WAT, from data as of 1 Oct 2026, 00:00 WAT

DEFINITION
Version 1

DATA FINGERPRINT (SHA-256)
6b884e1c8bb65b5090d77370b0814a0d9be6442040bc35d6276f06e5d2ed4b46

IN BRIEF

SAIDI
8.4 h • C
OK · Calculated · gridintel.reliability.reference 0.3.0
Provisional: includes 1 open outage(s); duration counted to period end.

SAIFI
1.8 • C
OK · Calculated · gridintel.reliability.reference 0.3.0
Provisional: includes 1 open outage(s); duration counted to period end.

SAIDI ATTRIBUTED TO THE DISTRIBUTION NETWORK
0.7 h • C
OK · Calculated · gridintel.reliability.reference 0.3.0
Provisional: includes 1 open outage(s); duration counted to period end.

FEEDERS BELOW THEIR BAND MINIMUM
2 • C
OK · Calculated

INTERRUPTIONS IN PROGRESS AT THE END OF THE DAY
1 • C
OK · Calculated

SOURCE ALARMS STANDING AT THE END OF THE DAY
4 • C
OK · Calculated

Provisional: includes 1 open outage(s); duration counted to period end.

1 Supply on the day

Hours of supply, by feeder

Ranked by network-attributable SAIDI for the day, highest first.

	BAND	HOURS SUPPLIED	BAND MINIMUM	MET	NETWORK SAIDI (H)
Farm Road 11 kV feeder Hillcrest 33/11 kV injection substation	Band D	7.7 h/day • C	8.0 h/day • C	No	4.3 h • C
Government Avenue 11 kV feeder Hillcrest 33/11 kV injection substation	Band B	18.0 h/day • C	16.0 h/day • C	Yes	0.0 h • C
Market Road 11 kV feeder Riverside 33/11 kV injection substation	Band A	19.0 h/day • C	20.0 h/day • C	No	0.0 h • C
Old Town 11 kV feeder Riverside 33/11 kV injection substation	Band C	15.0 h/day • C	12.0 h/day • C	Yes	0.0 h • C

Method: GridIntel reference reliability indices (gridintel.reliability.reference 0.3.0); GridIntel reference hours of supply (gridintel.supply_hours.reference 0.2.0).

GridIntel reference calculation — not a regulatory figure. Band minimums are NERC Service-Based Tariff definitions.

2 Interruptions in progress at the end of the day

In progress

	CAUSE	INTERRUPTED	RESTORED	STILL OFF	CUSTOMERS STILL OFF
Farm Road 11 kV feeder Hillcrest 33/11 kV injection substation · Farm Road 11 kV feeder	Fault	30 Sep 2026, 23:20 WAT	*No restoration recorded*	10 transformers	1,015 • C

Restoration not recorded

No restoration time, and the source does not say the outage is open: a gap in the record, not a finding that supply is still off.

	CAUSE	INTERRUPTED	RESTORED	STILL OFF	CUSTOMERS STILL OFF
SP-MKT2-001 Riverside 33/11 kV injection substation · Market Road 11 kV feeder	Cause not known	21 Sep 2026, 09:15 WAT	*No restoration recorded*	1 service point	1 • M

3 Alarms and conditions at the end of the day

Source alarms standing

	ALARM	RAISED	ACKNOWLEDGED	ACCOUNTS BEHIND IT
Farm Road 11 kV feeder Feeder	high: 11 kV feeder breaker tripped on earth fault and locked out. (FDR-EF-TRIP)	30 Sep 2026, 23:20 WAT	30 Sep 2026, 23:24 WAT	1,015 • C
Hillcrest 33/11 kV injection substation Substation	high: 110 V DC supply low: battery charger failure. Protection will run on the battery alone. (DC-SUPPLY-LOW)	30 Sep 2026, 21:40 WAT	*Not acknowledged*	2,781 • C
Monitor on South Gate transformer Monitoring device	medium: Communications failure: remote unit SYN-DTM-OLD3 (transformer monitor) has not answered 2 consecutive polls. (RTU-COMMS-FAIL)	30 Sep 2026, 16:55 WAT	30 Sep 2026, 17:20 WAT	42 • C
Riverside T1 Power transformer	medium: Power transformer top-oil temperature above its alarm setting. (PT-OIL-TEMP-HIGH)	26 Sep 2026, 20:05 WAT	26 Sep 2026, 20:12 WAT	3,543 • C

1 alarm(s) have no recorded raise time, so whether they were standing cannot be told.

Derived conditions holding

Calculated by GridIntel under fixed rules; not alarms from any source system.

	RULE	FIGURE	SOURCE ALARM
Monitor on South Gate transformer Monitoring device	Monitor quiet	9.1 h • C	A source alarm agrees

Method: GridIntel reference derived conditions (gridintel.conditions.reference 0.3.0).

4 Loaded above rating in the day

Assets above rating

Highest peak first. Loading is apparent power against rating, from telemetry.

	PEAK LOADING	READINGS ABOVE RATING
Government Avenue transformer 3 Hillcrest 33/11 kV injection substation · Government Avenue 11 kV feeder	104.1% • C	6 • C
Riverbank transformer Riverside 33/11 kV injection substation · Old Town 11 kV feeder	106.5% • C	3 • C

Method: GridIntel reference equipment loading (gridintel.loading.reference 0.1.0).

5 Method, sources and how to reproduce this report

Methodologies

METHODOLOGY	VERSION	WHAT IT SAYS OF ITSELF
GridIntel reference derived conditions `gridintel.conditions.reference`	`0.3.0`	GridIntel derived condition, calculated from telemetry. It is not an alarm recorded by a source system.
GridIntel reference equipment loading `gridintel.loading.reference`	`0.1.0`	GridIntel reference calculation — not a regulatory figure.
GridIntel reference reliability indices `gridintel.reliability.reference`	`0.3.0`	GridIntel reference calculation — not a regulatory figure.
GridIntel reference hours of supply `gridintel.supply_hours.reference`	`0.2.0`	GridIntel reference calculation — not a regulatory figure. Band minimums are NERC Service-Based Tariff definitions.

Sources

- Synthetic alarm list (synthetic)
- Synthetic outage log (synthetic)
- Synthetic asset registry (synthetic)
- Synthetic telemetry (synthetic)

> Every source above is synthetic: designed demonstration data, not records of a real organization.

How to reproduce it

1. Build the report with definition version 1, for 30 September 2026, from the Savanna Electricity Distribution (synthetic) records.
2. The data fingerprint must be `6b884e1c8bb65b5090d77370b0814a0d9be6442040bc35d6276f06e5d2ed4b46`. SHA-256 over the sorted SHA-256 digests of every distinct result the report's services were given by the repositories, each written as JSON with its keys in order.
3. With the same definition, methodologies and fingerprint the report ID is the same: GI-DOB-2026-09-30-44FDB02F. A different ID means something above differs.
4. The figures with their status, origin, unit and method are in the CSV of the same report ID: gridintel-daily-brief-2026-09-30-SAMPLE-SYNTHETIC.csv.

6 Regulatory references

> How far this report carries the fields of the instruments below, as read from the instruments themselves. It is not a claim that the report conforms to any regulator's or programme's template: none has been checked against the template it would be filed on.

INSTRUMENT	REQUIREMENT	THIS REPORT
NERC June 2024 Supplementary Order to MYTO 2024 (e.g. ORDER/NERC/2024/068, YEDC), para. 9 and Appendix 1	9(c). Publish daily, by 09:00 the next day, a rolling seven-day average of daily hours of supply on each Band A feeder	**PARTLY** Section 1 gives each feeder's hours of supply for the day against its band; the rolling seven-day average is not calculated.
NERC June 2024 Supplementary Order to MYTO 2024 (e.g. ORDER/NERC/2024/068, YEDC), para. 9 and Appendix 1	9(d). Explain a Band A feeder below its committed level on two consecutive days	**PARTLY** Section 1 shows whether each feeder met its band on the day; runs of consecutive days are not counted, and no explanation is held.

7 Glossary and key

SAIDI — System Average Interruption Duration Index: the hours of interruption the average customer served had in the period. Customer-hours interrupted ÷ customers served.

SAIFI — System Average Interruption Frequency Index: the interruptions the average customer served had in the period. Customer interruptions ÷ customers served.

Network-attributable — The part of an index caused by interruptions that began on the distribution network (33 kV and 11 kV lines, distribution transformers, the low-voltage network), under the reference methodology.

Service band	NERC's Service-Based Tariff band of a feeder, with its minimum average hours of supply a day: A 20, B 16, C 12, D 8, E 4.
Provisional	A figure that includes an interruption still open at the end of the period, counted to its end. It is calculated, not estimated, and is final only when the restoration is recorded.
Source alarm	An alarm as a source system (SCADA, a relay, a monitor) recorded it. Observed; GridIntel does not decide whether it is true.
Derived condition	Something GridIntel worked out from telemetry under a fixed rule (loaded above rating, monitor quiet). Calculated; never shown as an alarm.
Accounts behind	Active customer accounts connected behind an asset, from the registry. It says who is connected there, not who is without supply.
Restoration not recorded	An outage with no restoration time whose source does not say it is open: a gap in the record, not a finding that supply is still off.
Measured	Read from a meter, a device or a source record.
Reported	A figure published by someone else, shown as they stated it. It is never altered.
Calculated	Computed by GridIntel from records, under a named and versioned methodology.
Estimated	An estimate, not a measurement; the method is named with it.
Derived	A residual: what is left when other figures are subtracted. It carries their uncertainty.
Insufficient data	An input the figure needs is missing. No value is given rather than a guess, and never a zero.
Not available	No source holds this figure, or the data does not cover the period.
Same basis	A reported figure and a calculation count the same things over the same period by the same rule. Only figures on the same basis are compared.
Data fingerprint	A SHA-256 digest of every record the report was built from. The same records give the same fingerprint; any change to them gives another.
Report ID	The report's code, its period and the first characters of a digest of its definition, methodologies and data fingerprint. The same report of the same data has the same ID.

The marks beside a figure

● **OK**	Every input is present and measured.
≈ **Estimated inputs**	Calculated; every input is present, but at least one was estimated rather than measured.
! **Insufficient data**	An input this figure needs is missing. No value is shown rather than a guess.
∅ **Not computable**	The inputs exist but the calculation is undefined for them.
– **Not available**	The platform has no source for this figure.
M **Measured**	Read from a meter, device or source record.
R **Reported**	Published by someone else; shown as stated.
C **Calculated**	Computed by GridIntel under a named methodology.
E **Estimated**	An estimate, not a measurement.
D **Derived**	A residual: what is left after subtracting other figures. It inherits their uncertainty.

SAMPLE: SYNTHETIC DATA. End of report GI-DOB-2026-09-30-44FDB02F.