| | |
|---|---|
| Acronym | Messer |
| Project | **ADS-B Message Server** |
| Doctype | **Requirements** |
| Author | **Hans-Gerhard Gross, Kai Warendorf** |
| Contact | hggross@hs-esslingen.de;<br>Kai.Warendorf@hs-esslingen.de |
| Client | Esslingen University |
| Contact | Faculty of Information Technology |
| Version | 1.0 |
| Date | March 2, 2015 |

# Contents

# Chapter 1

# Project Drivers

## 1.1 Purpose of the Project

### 1.1.1 Vision Statement

This project aims at developing a server that provides ADS-B messages locally in a Java application.

### 1.1.2 Project Outcomes

The Java application reads ADS-B sentences.

The Java application transforms each sentence into its respective message type.

The Java application prints a string representation of each message onto the screen.

### 1.1.3 Learning Objectives

After having completed this project, as student, you can ...

- develop and integrate Java classes and interfaces.
- apply the Java extension mechanism.
- perform advanced String transformation operations in Java.
- use Java's public inner classes.
- apply the Java observation/observable pattern.

## 1.2 Stakeholders

### 1.2.1 Project Team

Various members and roles.

### 1.2.2 Product Users

**Local Flight Control Engineer, User.** Priority: **Key User**.

# Chapter 2

# Functional Requirements

## 2.1 Data Model and Data Dictionary

### 2.1.1 Use Case Diagram




## 2.2 Messer Functional Requirements

**Messer.F.10 Observe ADS-B Messages** essential

**Feature** In order to get an overview of the local flight traffic, as a flight control engineer, I want to be able to observe each incoming ADS-B message.

**Messer.F.20 Fetch Messages** essential

**Feature** In order to provide ADS-B messages locally, the system shall fetch the corresponding sentences from the following web service:

`http://flugmon-it.hs-esslingen.de/subscribe/ads.sentence`

**Feature** In order to integrate seamlessly with other OS operations, the web service address shall be provided as input parameter upon application start.

# Chapter 3

# Non-Functional Requirements

## 3.1 Look and Feel Requirements

**Messer.NF.10 Text Output per ADS-B message** essential

**Feature** The system shall display each ADS-B message received in the following form (example):

```
484B91 Airborne Position Message
       Type:    12
       Alti:    30550
       Latlon:  15530 : 129595
       Format:  even

4B1621 Airborne Velocity Message
       Speed:   442
       Headng:  3
       Vertic:  -64

4B1621 Aircraft Identification and Category Message
       Ident:   SWR177Y
       Categ:   0

3C6424 Other Message
       Type:    29
```

The hexadecimal code represents the ICAO of the originator.

## 3.2 Implementation-Specific Requirements

### 3.2.1 Process

**Messer.NF.50 Test Driven Development** essential

In order to ascertain sufficient testing of the product, the implementation must be carried out following a test-driven development approach.

### 3.2.2 Architecture

**Messer.NF.60 Implementation of Messer** essential

**Feature** In order to serve several clients at the same time in terms of a publish/subscribe architecture, the module *Messer*, i.e. the ADS-B Message Server, must be realized following the Observer/Observable architectural pattern.

**Messer.NF.65 Use of Classes and Interfaces** essential

**Feature** The organization of the system implementation shall reflect the classes and interfaces shown in the following class diagrams:






## 3.3 Maintainability Requirements

### Messer.NF.70 Documentation essential

In order to ascertain high understandability, the source code must be self-explanatory.

### Messer.NF.80 Cohesion and Coupling essential

In order to support high maintainability, the modules of the system must be realized with high-cohesion and low coupling.

**Messer.NF.90 OO Design Principles** **essential**

In order to support high maintainability, the other well-known principles of good object-oriented design must also be applied.