

UF_DBC_MLD_ask_dbc_mld [\(view source\)](#)

Defined in: `uf_dbc_mld.h`

Overview

This function returns the `UF_DBC_MLD_id_t` that corresponds to the `UF_CAM_exit_id_t` passed to the User Exit from NX.

Environment

Internal and External

History

Originally released in V16.0

```
int UF_DBC_MLD_ask_dbc_mld
(
    UF_CAM_exit_id_t exit_id,
    UF_DBC_MLD_id_t * dbc_mld_id
)
```

<code>UF_CAM_exit_id_t</code>	exit_id	Input	- exit_id passed to exit from NX
<code>UF_DBC_MLD_id_t *</code>	dbc_mld_id	Output	- the dbc_mld of this exit_id

UF_DBC_MLD_ask_sheet [\(view source\)](#)

Defined in: `uf_dbc_mld.h`

Overview

Returns the sheet associated with the specified `UF_DBC_MLD_id_t`.

Environment

Internal and External

History

Originally released in V16.0

```
int UF_DBC_MLD_ask_sheet
(
    UF_DBC_MLD_id_t object,
    UF_DBC_MLD_sheet_t * sheet
)
```

<code>UF_DBC_MLD_id_t</code>	object	Input	- see above description
<code>UF_DBC_MLD_sheet_t *</code>	sheet	Output	- see above description

UF_DBC_MLD_create [\(view source\)](#)

Defined in: `uf_dbc_mld.h`

Overview

This function creates an UF_DBC_MLD object. The 'object' returned is used in the other public functions of UF_DBC_MLD to identify the object to process.

Environment

Internal and External

History

Originally released in V16.0

```
int UF_DBC_MLD_create
(
    UF_DBC_MLD_id_t * object
)
```

<code>UF_DBC_MLD_id_t *</code>	object	Output	- the id of the created object
--------------------------------	---------------	--------	--------------------------------

UF_DBC_MLD_delete [\(view source\)](#)

Defined in: `uf_dbc_mld.h`

Overview

Delete the specified UF_DBC_MLD object.

Environment

Internal and External

History

Originally released in V16.0

```
int UF_DBC_MLD_delete
(
    UF_DBC_MLD_id_t object
)
```

<code>UF_DBC_MLD_id_t</code>	object	Input	- the object to delete
------------------------------	---------------	-------	------------------------

UF_DBC_MLD_exec_command [\(view source\)](#)

Defined in: `uf_dbc_mld.h`

Overview

This function will execute the specified command in the interpreter associated with the specified UF_DBC_MLD object.

Environment

Internal and External

History

Originally released in V16.0

```
int UF_DBC_MLD_exec_command
(
    UF_DBC_MLD_id_t dbc_mld_id,
    const char * command
)
```

UF_DBC_MLD_id_t	dbc_mld_id	Input	- see above description
const char *	command	Input	- the command to execute

UF_DBC_MLD_set_interp_result (view source)

Defined in: uf_dbc_mld.h

Overview

Assign the specified string to the result in the interpreter associated with the specified UF_DBC_MLD_id_t. This will be the return value of the last TCL command executed in the interpreter.

Environment

Internal and External

History

Originally released in V16.0

```
int UF_DBC_MLD_set_interp_result
(
    UF_DBC_MLD_id_t object,
    const char * result
)
```

UF_DBC_MLD_id_t	object	Input	- see above description
const char *	result	Input	- see above description

UF_DBC_MLD_set_sheet (view source)

Defined in: uf_dbc_mld.h

Overview

Assign the specified sheet to the specified UF_DBC_MLD_id_t.

Environment

Internal and External

History

Originally released in V16.0

```
int UF_DBC_MLD_set_sheet
(
    UF_DBC_MLD_id_t object,
    UF_DBC_MLD_sheet_t sheet
)
```

UF_DBC_MLD_id_t	object	Input	- see above description
UF_DBC_MLD_sheet_t	sheet	Input	- see above description