

UF_WEB_author_html [\(view source\)](#)

Defined in: `uf_web.h`

Overview

Create an HTML document based on the contents of the NX HTML template. The template allows you to customize the NX contents of the HTML. See the NX Online Help for details of the contents of the NX HTML template file.
NOTE: When using this function the UGSPREADSHEET command is not functional.

Environment

Internal and External

History

Original release was in V13.0.

Required License(s)

ug_web_express

```
int UF_WEB_author_html
(
    char * output_filename,
    char * template_filename,
    int apply_to_each_component
)
```

char *	output_filename	Input	Output HTML file
char *	template_filename	Input	Template file to use
int	apply_to_each_component	Input	FALSE = Template is applied once to the assembly TRUE = Template is applied once to each component of the assembly with the work part being automatically changed.

UF_WEB_write_to_file [\(view source\)](#)

Defined in: `uf_web.h`

Overview

Writes text to the current HTML output file specified with UF_WEB_author_html. This function is generally used with the <@UGUF.> template command in order to write data into the output HTML file from an internal Open API program.

Environment

Internal and External

History

Original release was in V13.0.

Required License(s)

ug_web_express

```
int UF_WEB_write_to_file  
(  
    char * output_string  
)
```

char *	output_string	Input	Output HTML file
--------	----------------------	-------	------------------
