

UF_MB_action_type_e [\(view source\)](#)

Defined in: `uf_mb.h`

Also known as:

- `UF_MB_action_type_t`
- `UF_MB_action_type_p_t`

Overview

Each member of the `UF_MB_action_type_t` enumerated type represents one of the action types that can be specified for an action declared in a MenuScript menu file. This enumerated type is reserved for future use in the Open API; currently it is only used internally within MenuScript.

Data Members

UF_MB_FUNCTION_ACTION

Callback action registered via `UF_MB_add_actions`

UF_MB_PROGRAM_ACTION

Complete Open Program action

UF_MB_GRIP_ACTION

GRIP program action

UF_MB_JOURNAL_ACTION = UF_MB_GRIP_ACTION

Journal action is equivalent to GRIP but with different file extension

UF_MB_IMMEDIATE_ACTION

System Command Action enclosed in quotes

UF_MB_USER_TOOL_ACTION

User Tool Definition File to be opened by the action

UF_MB_STYLER_DIALOG_ACTION

Styler Dialog File to be opened by the the action

UF_MB_STYLER_TOP_DIALOG_ACTION

Styler Top Dialog File to be opened by the action

UF_MB_LEGACY_ACTION

Action defined via `UF_UI_append_menubar_menu`

UF_MB_cb_status_e [\(view source\)](#)

Defined in: `uf_mb.h`

Also known as:

- `UF_MB_cb_status_t`
- `UF_MB_cb_status_p_t`

Overview

Each member of the `UF_MB_cb_status_t` enumerated type represents one of the possible return values from a callback function that has been registered via `UF_MB_add_actions`.

To support possible future semantic differences between return codes, the five values shown below have been defined. The comments next to each member identify its nominal meaning. However, there are currently only two sets of semantics associated with these five values:

`UF_MB_CB_CONTINUE` - this value will cause execution of any additional actions for a menu item to be executed.

Any of the other four values will inhibit execution of the remaining actions.

Data Members

`UF_MB_CB_CONTINUE`

Continue performing the menu item's actions

`UF_MB_CB_CANCEL`

User interaction requested inhibiting the menu item's actions

`UF_MB_CB_OVERRIDE_STANDARD`

Inhibit further actions because a pre action took the place of the standard action for a standard NX menu item.

`UF_MB_CB_WARNING`

Inhibit further actions because a warning condition was raised.

`UF_MB_CB_ERROR`

Inhibit further actions because a error condition was raised.

`UF_MB_state_e` ([view source](#))

Defined in: `uf_mb.h`

Also known as:

- `UF_MB_state_t`
- `UF_MB_state_p_t`

Overview

The elements of the `UF_MB_state_t` enumerated type correspond to ask or set routine argument for a button's sensitivity or a toggle button's current state.

Data Members

`UF_MB_ON`

`UF_MB_OFF`

