

Q4 激进局部消融：一般场景 350 场；T/K 优先

每组清除 4611 个源；全场景清除与认证均通过；绿色为本表最低 T/K

策略	总耗时/场(s)	T/K(s/源)	行走/场(s)	探测/场
冻结基线	6565.8	513.19	4861.6	274.56
L+C	6352.2	496.93	4677.9	263.57
L+P+C	6337.7	495.88	4647.1	265.45
上一轮JSO紧凑D-optimal	6249.9	488.85	4561.5	270.63
E 预期光学比1	6399.8	500.60	4733.5	261.53
E 预期光学比2	6436.3	503.48	4757.8	260.85
B 两步20m	6404.8	500.30	4692.7	268.80
B 两步60m	6423.0	501.68	4705.3	269.18
G 动态补测0.75	6270.4	490.44	4577.7	265.81
G 动态补测1.5	6257.7	489.64	4572.2	263.73
R 专用探测2次后转光学	6343.8	496.20	4666.6	262.61
R 专用探测4次后转光学	6350.1	496.77	4676.3	263.43
H 乐观半径200	6364.8	497.80	4690.8	262.99
H 乐观半径400	6410.8	501.13	4726.7	264.28
N 路过试清除0.20	6352.1	496.92	4677.5	263.57
N 路过试清除0.50	6352.0	496.91	4677.5	263.57
G0.75+R2	6270.6	490.43	4572.5	265.62
G0.75+N0.20	6270.6	490.46	4577.8	265.81
G0.75+R2+N0.20	6270.8	490.45	4572.5	265.62