

Q4 激进局部消融：边界压力场景 50 场；T/K 优先

每组清除 664 个源；全场景清除与认证均通过；绿色为本表最低 T/K

策略	总耗时/场(s)	T/K(s/源)	行走/场(s)	探测/场
L+P+C	7151.7	549.70	4830.1	378.20
L+C	7172.5	551.56	4855.7	377.40
冻结基线	7680.7	589.34	5284.8	391.66
E 预期光学比1	7202.3	553.85	4881.5	376.44
E 预期光学比2	7222.9	555.47	4893.5	376.98
G 动态补测0.75	7102.9	546.02	4778.6	378.64
上一轮JSO紧凑D-optimal	7691.7	590.04	5298.9	392.26
G 动态补测1.5	7103.6	546.06	4779.4	378.58
R 专用探测2次后转光学	7165.4	551.11	4849.1	376.82
R 专用探测4次后转光学	7172.5	551.56	4855.7	377.40
H 乐观半径200	7168.7	551.28	4853.2	377.16
H 乐观半径400	7172.6	551.61	4857.2	377.10
N 路过试清除0.20	7172.5	551.56	4855.5	377.40
G0.75+R2	7095.8	545.49	4771.9	378.36
N 路过试清除0.50	7172.4	551.55	4855.5	377.40
G0.75+R2+N0.20	7095.7	545.49	4771.7	378.36
G0.75+N0.20	7102.9	546.02	4778.4	378.64
B 两步20m	7247.5	557.20	4891.9	384.66
B 两步60m	7225.3	555.61	4872.3	384.02