

Gap for services:
Copper 2.42%
Insulation (e.g. PUR or EPDM)
11.71%
Connector - Thermoplastic 1.04%
Stainless Steel 316 0.68%
Air 84.15%

1:10
On the flat

Inner and outer radius of each
layer can be found in:
EDMS 2504567

Blue line indicates
the envelope

Z	R
3188.5	1363.1

Z	R
3188.5	1275.5

Z	R
3145	1275.5

Z	R
2967.7	1241.7

ETL Envelope
coordinates
indicated in
orange

Z	R
3066.7	1197.2

See B-B

Z	R
3066.7	300

Z	R
2967.7	300

eta = 2.82
eta = 3
eta = 3.152
eta = 3.2

Beam pipe axis

eta = 1.52

eta = 2.02

Moderator
support
envelope

Thermal screen external
envelope indicated in pink

Z	R
2967.7	265

Z	R
2967.7	285

Z	R
3695.8	313.6

Z	R
3695.8	285

Z	R
4107.3	383.6

Z	R
4107.3	313.6

Z	R
4388	448.4

Z	R
4388	383.6

Z	R
4529	364.3

Z	R
4529	265

Z	Y
4573.8	-2.6

Center of Gravity
(the weight of all drawn components taken
into account, except weight of the services
and YE1 inner cylinder)

Z	R
3919	1776.6

Z	R
3839.7	1806.3

Z	R
3877.5	1735.2

Z	R
3621.8	1646.7

Z	R
3188.5	1580.9

Z	R
3210.5	1523.3

Z	R
4565.6	2624.6

Z	R
4525.6	2713

Z	R
5262	2713

More information
regarding MEO
chambers and
Shielding envelopes
can be found:

CDD Number:
CMSEG_0002
St Number:
ST1217856_01

Flexible ring
MEO Radiation shield
envelope

YE1 Inner Cylinder

Z	R
5235.9	448.4

(ON FLAT)

14 (ON FLAT)

SUPPORT (POLYGON)

STEP 1

STEP 2

STEP 3

B-B

1:1