
MODULE *TCommit*

CONSTANT *RM* The set of all Resource Managers (e.g. $\{r_{-1}, r_{-2}, r_{-3}\}$)
 VARIABLE *rmState* *rmState*[*rm*] is the state of the Resource Manager *rm*

TCTypeOK \triangleq *rmState* \in [*RM* \rightarrow {“working”, “prepared”, “committed”, “aborted”}]
TCInit \triangleq *rmState* = [*r* \in *RM* \mapsto “working”]

Prepare(*r*) \triangleq \wedge *rmState*[*r*] = “working”
 \wedge *rmState*' = [*rmState* EXCEPT ![*r*] = “prepared”]
 $[s \in RM \mapsto \text{IF } s = r \text{ THEN “prepared” ELSE } rmState[s]]$

canCommit \triangleq $\forall r \in RM : rmState[r] \in \{\text{“prepared”, “comitted”}\}$
notCommitted \triangleq $\forall r \in RM : rmState[r] \neq \text{“committed”}$

DecideToCommit(*r*) \triangleq \wedge *rmState*[*r*] = “prepared”
 \wedge *canCommit*
 \wedge *rmState*' = [*rmState* EXCEPT ![*r*] = “committed”]

DecideToAbort(*r*) \triangleq \wedge *rmState*[*r*] \in {“working”, “prepared”}
 \wedge *notCommitted*
 \wedge *rmState*' = [*rmState* EXCEPT ![*r*] = “aborted”]

Decide(*r*) \triangleq \vee *DecideToCommit*(*r*)
 \vee *DecideToAbort*(*r*)

TCNext \triangleq $\exists r \in RM : Prepare(r) \vee Decide(r)$

TCConsistent \triangleq $\forall r1, r2 \in RM : \neg \wedge rmState[r1] = \text{“aborted”}$
 $\wedge rmState[r2] = \text{“committed”}$

\ * Modification History
 \ * Last modified Sat Apr 03 14:19:20 BRT 2021 by felipe
 \ * Created Sat Apr 03 10:13:09 BRT 2021 by felipe