

**Why Risk it, When You Can {rix} it: A Tutorial for Computational Reproducibility Focused
on Simulation Studies**

Felipe Fontana Vieira¹, Jason Geller², and Bruno Rodrigues³

¹Department of Data Analysis, Ghent University

²Department of Psychology and Neuroscience, Boston College

³Statistics and Data Strategy Departments, Ministry of Research and Higher Education,
Luxembourg

Author Note

Correspondence concerning this article should be addressed to Felipe Fontana Vieira,
Email: felipe.fontanavieira@ugent.be

Abstract

Reproducibility remains limited in psychology, in part because reproducibility exists on a spectrum – from sharing isolated code fragments to providing fully executable pipelines that ensure identical results. This article introduces Nix and the {rix} R package as a way to provide a comprehensive solution for achieving full computational reproducibility in simulation studies. Building on this, we also demonstrate a tutorial on how to use {rix} to obtain a reproducible manuscript using the apaquarto extension.

Keywords: reproducibility, Nix, simulation studies, R, computational methods

Why Risk it, When You Can {rix} it: A Tutorial for Computational Reproducibility Focused on Simulation Studies

Psychological science is in the midst of a credibility revolution, which has prompted substantial progress in how research is conducted and evaluated ([Vazire, 2018](#)). Yet, despite notable progress, a key cornerstone of science, reproducibility (i.e., the ability to precisely reproduce the results of a study or studies based on provided data, code, materials, and software/hardware) remains limited ([Hardwicke et al., 2020](#)).

Addressing this gap is complicated by the fact that reproducibility is not a binary feature but instead exists along a continuum ([Peng, 2011](#)). At the lower end, researchers may share only their manuscript; further along, they might provide partial code, full analysis scripts, or publicly accessible datasets; at the highest level, they document a fully specified computational environment that allows others to recreate identical results (from raw data to final manuscript output) with minimal friction. Open-science initiatives have made considerable progress along this continuum. Journal incentives such as open-science badges ([Kidwell et al., 2016](#)), together with platforms like GitHub and the Open Science Framework, have made data and code sharing increasingly routine ([Levenstein & Lyle, 2018](#)). However, these efforts largely occupy the lower and middle portions of the spectrum, focusing on *what* is shared rather than *how* shared materials can be executed in practice.

This distinction matters because data and code are never self-sufficient. They depend on a hierarchy of software components—collectively known as dependencies—including the programming language version, the packages used, and the system libraries those packages require in order to function correctly. When these dependencies differ from those used in the original analysis, code may fail, behave differently across machines and time, or yield conflicting numerical results ([Baker et al., 2024](#); [Glatard et al., 2015](#); [Hodges et al., 2023](#); [Nosek et al., 2022](#)). These issues are particularly acute for simulation studies, which rely on complex codebases, versioned dependencies, and intricate software configurations ([Luijken et al., 2024](#); [Siepe et al., 2024](#)).

Researchers have identified several factors that support reproducibility, including literate programming, version control, dependency management, virtual machines, containerization, and thorough documentation (Peikert & Brandmaier, 2021; Wiebels & Moreau, 2021; Ziemann et al., 2023). Most of these practices presuppose a stable computational environment; virtual machines and containerization attempt to provide one. Therefore, we use *computational environment* to refer to this complete software context—the programming language version, package versions, system libraries, and operating system required for an analysis to run successfully (Rodrigues, 2023; Rodrigues & Baumann, 2026). *Computational environment reproducibility*, then, is the ability to reconstruct this entire software stack on any machine and at any future time, such that executing the same code yields the same numerical results.

Empirical assessments show that current practice falls short of this ideal. Siepe et al. (2024) report that nearly two-thirds of simulation studies in psychology provide no accompanying code, and among those that do, documentation of the computational environment is rarely included. This gap is consequential: simulation studies inform methodological recommendations, meaning that insufficient reproducibility undermines confidence in those recommendations (Luijken et al., 2024; White et al., 2024).

Arguably, these challenges persist, in part, because researchers must navigate a fragmented landscape of solutions, each addressing only part of the problem. Package-level managers such as {renv} (Ushey, 2024) and {groundhog} (Simonsohn, 2020) stabilize R package versions but do not manage the R interpreter itself or the system-level libraries those packages depend on. Workflow orchestration tools such as {targets} (Landau, 2021) and Make (Feldman, 1979) support reproducibility in a different sense: they specify the structure of an analysis by formalizing the order in which steps should run and by tracking dependencies among intermediate results. These tools clarify how an analysis proceeds, but they assume the software stack required to run each step is already stable. Virtual machines and containerization tools, such as Docker, offer more comprehensive approaches by bundling the full environment—operating system, system libraries, interpreter versions, and packages—into a single shareable unit. Virtual

machines, however, can be large and slow, making them impractical to share (Wiebels & Moreau, 2021). Containerization is more lightweight, and R-focused implementations like Rocker (Boettiger, 2015; Boettiger & Eddelbuettel, 2017) have made it more accessible. Yet building containers still requires familiarity with Linux system administration, and even containerization may suffer from temporal drift when Dockerfiles rely on mutable upstream repositories (Malka et al., 2024). For a detailed comparison of these tools and their limitations, see Rodrigues and Baumann (2026). Thus, researchers are left with options that are either accessible but incomplete or powerful but demanding of more technical expertise.

In response to that, we introduce Nix (Dolstra et al., 2004), a functional package manager designed to make software installation deterministic, and {rix} (Rodrigues & Baumann, 2025), an R interface that allows researchers to use Nix without needing deep knowledge of its underlying language or infrastructure. Our focus is specifically on computational environment reproducibility as the foundation upon which other reproducibility practices depend. We do not prescribe a particular workflow orchestration system or analytic structure. Instead, we aim to show how Nix and {rix} can establish a stable, cross-platform environment within which any analysis—whether organized in simple, documented script sequences (e.g., .R files that `source()` others), through more formal orchestration tools (e.g., Make, {targets} or {rixpress}) or embedded as code chunks in literate programming documents (e.g., .rmd or .qmd)—can be executed reliably.

We illustrate these ideas through a reproducible simulation study conducted in R, culminating in an automated APA-formatted manuscript generated with apaquarto (Schneider, 2024). Although the example centers on R because of its prominence in psychological methodology, the principles underlying environment reproducibility apply equally to other languages, including Python and Julia, and to different development environments such as RStudio, VS Code, Emacs, or Positron. Similarly, we use apaquarto because of its relevance to psychological journals, but Nix is agnostic to the manuscript template employed. Later in the article, we highlight additional considerations and briefly comment on {rixpress} (Rodrigues, 2025), which extends Nix-based reproducibility to workflows spanning multiple languages.

Throughout, our emphasis remains squarely on the reproducibility of computational environments as the essential basis for transparent, reliable, and durable scientific workflows.

A Practical Example: Setting up a Reproducible Simulation Study with {rix}

Before proceeding with the technical information and tutorial, we refer readers to the Appendix A, which presents a simulation study scenario designed to ground the subsequent discussion in a concrete example¹. The scenario mimics a typical methods manuscript, describing both the statistical design and the computational details one might encounter in practice. While readers can follow the tutorial without engaging with the specifics of the simulation, we include it to anchor the discussion in something more tangible. The code implementing this simulation follows a conventional format: multiple component files, each handling a distinct analytical phase.²: data generation (`Simulation_Scripts/01_data_generation.R`), statistical model specification (`Simulation_Scripts/02_models.R`), simulation execution (`Simulation_Scripts/03_run_simulation.R`), performance metric calculation (`Simulation_Scripts/04_performance_metrics.R`), and results visualization (`Simulation_Scripts/05_plots.R`).

Notably, the simulation study depends on several R packages (see Appendix A). Thus, let's pretend a researcher wants to reproduce our simulation and results reported in the article. What might prevent them from obtaining identical results? The most immediate concern may involve package versions. A researcher installing packages today may encounter errors if functions have been renamed or deprecated, or may obtain results that differ subtly due to changes in computational defaults. Beyond package versions, some R packages depend on system-level libraries that must be installed separately from R itself. Our simulation illustrates this directly: the {rvinecopulib} package provides an interface to a C++ library and links against Boost, Eigen, and RcppThread (Nagler & Vatter, 2025). Moreover, the R language itself introduces version

¹ Note that the rationale, programming-related choices, and results should not be used for substantial interpretation. For instance, the usage of {rvinecopulib} and the parallel set-up may be considered an overhead.

² Readers can find the files for these simulations here: <https://github.com/felipelfv/Why-risk-it-when-you-can-rix-it>

dependencies. Code written for a recent version of R may use syntax or functions unavailable in earlier versions (e.g., native pipe operator `|>`, introduced in R 4.1). More subtly, R's random number generator has changed across major versions, meaning that identical code with identical seeds can produce different random sequences depending on the R version ([Ottoboni & Stark, 2018](#)). For simulation studies where reproducibility of specific random draws matters, this version sensitivity is consequential. Moreover, if one also employs literate programming for the manuscript as in our case, additional dependencies arise: R Markdown or Quarto documents require pandoc, and PDF output requires a LaTeX distribution—each with its own versioning and platform-specific installation.

Nix and {rix}: A Comprehensive Solution

A potential solution to the above issue is Nix ([Dolstra et al., 2004](#)). Nix is a package manager [**Bruno you once used the analogy of Nix like the apple application store. I kind of like this because it is more than a package manger. (JG)**] built around declarative, isolated environments rather than ad hoc system-level installations. Unlike familiar tools such as `install.packages()` in R or `apt-get` on Linux, Nix manages language versions, package versions, system dependencies, and cross-platform consistency through a single framework ([Rodrigues & Baumann, 2025](#)). Rather than modifying shared directories, Nix builds each environment as an explicit, self-contained specification. This addresses the fragmented landscape described before: where researchers currently must coordinate separate tools for package management, interpreter versions, and system dependencies, Nix handles all three within a unified declarative model.

Core Principles

Rather than installing software into global directories (e.g., `/usr/lib`), Nix places every package in its own directory under `/nix/store`. Each package path contains a cryptographic hash representing its precise inputs—source code, dependencies, and build instructions. Because these paths are content-addressed, multiple versions of the same software can coexist without conflict. A researcher can, for example, maintain projects requiring R 4.1.0 and R 4.3.3 side by

side, or use different package versions across analyses, switching between them seamlessly (Rodrigues & Baumann, 2025).

The Nix ecosystem is built around nixpkgs, a version-controlled repository comprising more than 120,000 packages, including nearly all of CRAN and Bioconductor. By pinning a specific commit or date, researchers freeze the entire software stack—R itself, R packages, and all system libraries—at that point in time. This eliminates the system-dependency problems that tools like {renv} cannot address (Rodrigues & Baumann, 2025).

This architecture also ensures stability over time. Empirical work has shown strong rebuildability and reproducibility rates for historical nixpkgs snapshots (Rodrigues & Baumann, 2026). Combined with binary caches, which often allow environments to materialize in seconds, Nix becomes practical for interactive research workflows (Rodrigues & Baumann, 2025).

The {rix} Package: R Interface to Nix

Nix expressions are written in a dedicated functional language unfamiliar to most researchers. The {rix} package removes this barrier by providing an R-native interface. A single call to `rix()` generates complete Nix configurations from standard R syntax, specifying R versions, CRAN packages, system libraries, and even Python or Julia components when required. Users never need to read or write Nix code directly, as {rix} performs the translation automatically (Rodrigues & Baumann, 2025).

A key feature of {rix} is its integration with `rstats-on-nix`, a community-maintained fork offering daily CRAN snapshots and weekly tested environments on Linux and macOS. Researchers can request, for example, `rix(date = "2024-12-14")` to obtain a validated and reproducible environment without manually assessing compatibility. After the configuration is generated, `nix_build()` instantiates the environment, and binary caches typically allow this to complete within seconds (Rodrigues & Baumann, 2025).

Importantly, and we will come back to this later on, although Nix is capable of replacing tools like Docker for isolation or {renv} for package management, it does not require an all-or-nothing transition. Researchers can adopt it gradually and use it alongside those. For

instance, by building Docker images with Nix, converting existing `{renv}` lockfiles, or running `{targets}` pipelines within a Nix-defined environment (Rodrigues & Baumann, 2025). This allows Nix to strengthen reproducibility while preserving established workflows. For projects requiring more sophisticated pipeline management, `{rixpress}` extends Nix's guarantees to workflow orchestration, enabling step-level isolation across languages, though such capabilities lie beyond the present focus on environment reproducibility.

Step I: Installing Nix and `{rix}`

Before proceeding, both Nix and the `{rix}` R package need to be installed. Installation procedures differ across operating systems (Windows via WSL2, Linux, and macOS), and detailed, up-to-date instructions are maintained in the official `{rix}` documentation:

- **Linux and Windows (WSL2):** <https://docs.ropensci.org/rix/articles/b1-setting-up-and-using-rix-on-linux-and-windows.html>
- **macOS:** <https://docs.ropensci.org/rix/articles/b2-setting-up-and-using-rix-on-macos.html>

Once Nix is installed, `{rix}` can be installed from CRAN (Listing 1), or directly through Nix without requiring a pre-existing R installation (Listing 2; see the documentation links above for details).

Listing 1 Installing `{rix}` from CRAN

```
install.packages("rix")
```

Listing 2 Installing `{rix}` directly via Nix (no R required)

```
feligelfv@Felipes-MacBook-Pro Why-risk-it-when-you-can-rix-it %  
nix-shell --expr "$(curl -sL https://raw.githubusercontent.com/ropensci/rix/  
main/inst/extdata/default.nix)"
```

It is worth noting that `{rix}` can generate Nix expressions even without Nix installed on your system—you can write a `default.nix` file without Nix, but you cannot build or enter the resulting environment unless Nix is installed (Rodrigues & Baumann, 2025).

Step II: Specifying the Computational Environment

The initial step in establishing a reproducible environment is to create a script that will generate the environment specification. We recommend creating a file named `generate_env.R` (or similar) in the project directory. This script will use the `rix()` function from the `{rix}` package to produce a `default.nix` file—a declarative specification that precisely defines all software dependencies required for the project.

Our simulation requires several R packages, and because we generate the manuscript using `apaquarto`, we also need associated system and LaTeX dependencies. For our project, we specify the environment as follows (Listing 3; on the GitHub repository as a file named `generate_env.R`³):

Note that not all packages listed are required for the simulation and results themselves—packages like `{knitr}` and `{svglite}` are required because of `.qmd`. For the simulation and results alone, specifying `date` (see below) and the relevant `r_pkgs` (e.g., `{rvinecopulib}`, `{doParallel}`, `{doRNG}`, `{marginaleffects}`, etc) would suffice. Appendix B details the reasons for each package. For now, we focus on clarifying the `rix()` arguments.

The Environment Generation Script

The `rix()` function⁴ constructs this specification through a series of parameters that collectively describe the computational environment. Each parameter serves a distinct purpose in defining the environment’s characteristics.

Specifying the R version. Researchers must first determine which version of R to use. This can be accomplished in two ways: The `r_ver` argument accepts an exact version string (e.g., “4.3.3”) or special designations such as “latest-upstream” for the most recent stable release.

Alternatively, the `date` argument specifies a particular date (e.g., “2024-11-15”), which ensures

³ In the GitHub repository, the argument `r_pkgs` contains one extra package: `{rixpress}`. This is related to the fact we also attached extra information about `{rixpress}` for the interested reader as part of the additional considerations section.

⁴ For an overarching information on the function `rix()`, we suggest the following `{rix}` documentation: <https://docs.ropensci.org/rix/articles/c-using-rix-to-build-project-specific-environments.html>

Listing 3 Environment specification for the manuscript using `rix()`

```
library(rix)

rix(
  date = "2026-01-12",
  r_pkgs = c(
    "rix", "quarto", "knitr", "marginaleffects", "simhelpers",
    "ggplot2", "doParallel", "doRNG", "cowplot", "dplyr", "svglite",
    "rvinecopulib"
  ),
  system_pkgs = c("quarto"),
  tex_pkgs = c(
    "amsmath", "ninecolors", "apa7", "scalerel", "threeparttable",
    "threeparttablex", "endfloat", "environ", "multirow", "tcolorbox",
    "pdfcol", "tikzfill", "fontawesome5", "framed", "newtx",
    "fontaxes", "xstring", "wrapfig", "tabularray", "siunitx",
    "fvextra", "geometry", "setspace", "fancyvrb", "anyfontsize"
  ),
  ide = "rstudio",
  project_path = ".",
  overwrite = TRUE
)
```

that R and all packages correspond to the versions available on that date. The date-based approach is generally preferable for reproducibility, as it captures a complete snapshot of the R ecosystem at a single point in time. For this tutorial, as shown on top, we use the `date` parameter to ensure temporal consistency across all software components (Rodrigues & Baumann, 2025) (see `{rix}` documentation for more: <https://docs.ropensci.org/rix/articles/d2-installing-system-tools-and-texlive-packages-in-a-nix-environment.html>).

Declaring R package dependencies. The `r_pkgs` argument accepts a character vector listing all required R packages by their CRAN names. These packages will be installed from the version repository corresponding to the specified date or R version. It is important to list all packages that the analysis will load directly; dependencies of these packages are automatically resolved by Nix. For packages requiring specific versions not corresponding to the chosen date, researchers can specify exact versions using the syntax `"packagename@version"` (e.g.,

"ggplot2@2.2.1"). For packages available only on GitHub or other Git repositories, the `git_pkgs` argument accepts a list structure containing repository URLs and specific commit hashes. For example:

Listing 4 Example for the `git_pkgs` argument

```
git_pkgs = list(  
  package_name = "marginaleffects",  
  repo_url = "https://github.com/vincentarelbundock/marginaleffects",  
  commit = "304bff91dc31ae28b227a8485bfa4f7bdc86d625"  
)
```

This ensures that exact development versions are obtained (Rodrigues & Baumann, 2025). For our simulation study, all packages were used with their CRAN versions (see `{rix}` documentation for more details: <https://docs.ropensci.org/rix/articles/d2-installing-system-tools-and-texlive-packages-in-a-nix-environment.html>).

Including system-level dependencies. Many R-based workflows require tools beyond R packages. The `system_pkgs` parameter specifies system-level software such as Quarto for document generation, Git for version control, or Pandoc for document conversion. Critically, we include Quarto as a system package because this tutorial demonstrates full computational reproducibility—not merely of the simulation code, but of the complete manuscript itself. Our manuscript uses the `apaquarto` extension for APA formatting, stored in the project’s `_extensions/` directory (Rodrigues & Baumann, 2025) (see `{rix}` documentation for more: <https://docs.ropensci.org/rix/articles/d2-installing-system-tools-and-texlive-packages-in-a-nix-environment.html>).

Specifying LaTeX packages. The `tex_pkgs` parameter specifies LaTeX packages needed for PDF compilation. When any packages are listed, Nix automatically includes a minimal TeXLive distribution (`scheme-small`) as a base, to which the specified packages are added. Determining the required LaTeX packages typically involves some trial and error—Quarto’s error messages during, for example, the PDF rendering indicate which packages are missing, and these

can then be added to `tex_pkgs` (see `{rix}` documentation for more: <https://docs.ropensci.org/rix/articles/d2-installing-system-tools-and-texlive-packages-in-a-nix-environment.html>).

Configuring the development environment. The `ide` parameter determines whether an integrated development environment should be included in the Nix environment. Setting `ide = "rstudio"` installs a project-specific version of RStudio within the Nix environment. This is required for RStudio because, unlike other editors, RStudio cannot interact with Nix shells unless it is itself installed via Nix. Note that on macOS, RStudio is only available through Nix for R versions 4.4.3 or later (or dates after 2025-02-28); for earlier versions, alternative editors must be used. Other supported IDEs include Positron (`ide = "positron"`), Visual Studio Code (`ide = "code"`), and command-line tools such as Radian (`ide = "radian"`). These editors can either be installed within the Nix environment using the `ide` parameter, or researchers can use an already-installed version by setting `ide = "none"` (or `ide = "other"`) and configuring `direnv` to automatically load the Nix environment when opening the project folder. Each IDE installed via Nix is project-specific and will not interfere with system-wide installations. See the `{rix}` documentation for detailed configuration instructions:

<https://docs.ropensci.org/rix/articles/e-configuring-ide.html>.

Setting file output parameters. The `project_path` parameter indicates where the `default.nix` file should be written (“.” denotes the current directory), while `overwrite` controls whether an existing file should be replaced. Adding to this, setting `print = TRUE`, which is another argument, displays the generated specification in the console for immediate verification (Rodrigues & Baumann, 2025).

Multi-language environment support. While this tutorial focuses on R, researchers working across multiple programming languages can include Python or Julia in their environments. The `py_conf` parameter accepts a list specifying a Python version and required packages (e.g., `py_conf = list(py_version = "3.12", py_pkgs = c("polars", "pandas"))`). Similarly, `j1_conf` enables Julia package installation. This capability is particularly useful, for example, for projects requiring statistical computing in R

alongside machine learning pipelines in Python or numerical optimization in Julia (Rodrigues & Baumann, 2025) (see {rix} documentation for more:

<https://docs.ropensci.org/rix/articles/d1-installing-r-packages-in-a-nix-environment.html>).

Listing 5 Including Python packages

```
py_conf = list(py_version = "3.12",  
              py_pkgs = c("polars", "pandas"))
```

[We should include a code chunk like the github one above showing how to add python packages?JG]

Generating the Environment Specification

After defining the environment with `rix()`, the environment specification must be generated by executing the corresponding .R script. From the terminal, navigate to the study directory and execute (Listing 6):

Listing 6 Generate the environment specification

```
felipelfv@Felipes-MacBook-Pro Why-risk-it-when-you-can-rix-it %  
Rscript generate_env.R
```

Alternatively, the same script can be executed from within R:
`source("generate_env.R")` or `rix::rix()`. This step produces the `default.nix` file in the project directory, which serves as the formal, machine-readable specification of the computational environment. Importantly, `rix()` automatically invokes `rix_init()`, which creates a project-specific `.Rprofile` file that prevents package library conflicts and disables `install.packages()` to maintain environment integrity. There may be exemptions to this, which we comment briefly in the next section.

Step III: Building and Using the Reproducible Environment

Once the `default.nix` file has been generated, the next step is to build the environment and use it to reproduce the complete manuscript.

Building the Environment

From the terminal, navigate to the study directory containing the `default.nix` file and execute (Listing 7):

Listing 7 Building the Nix environment

```
felipelfv@Felipes-MacBook-Pro Why-risk-it-when-you-can-rix-it % nix-build
```

The expected output should look similar to (Listing 8):

Listing 8 Expected output from `nix-build`

```
unpacking 'https://github.com/rstats-on-nix/nixpkgs/archive/2025-08-25.tar.gz'
  into the Git cache...
warning: ignoring untrusted substituter...
warning: ignoring the client-specified setting...
/nix/store/qa7fq20m2f94szsnqzciwv8h4n81w43v-nix-shell
```

This command builds the environment according to the specification. The first execution will download and install all required packages, which may take a few minutes depending on network speed and system resources. Subsequent builds use cached packages and complete in seconds. Upon successful completion, a path to the constructed environment in the Nix store is printed (here, `/nix/store/qa7fq20m2f94szsnqzciwv8h4n81w43v-nix-shell`), and a symbolic link named `result` appears in the project directory pointing to this location.

Note that the warnings indicate that you are not configured as a trusted user, so Nix cannot use the `rstats-on-nix` binary cache and will instead compile packages from source, which is slower. To enable binary caching, install the `cachix` client and configure the `rstats-on-nix` cache. See https://docs.ropensci.org/rix/articles/z-binary_cache.html for instructions.

To activate the environment, run (Listing 9):

The expected output (if you have configured yourself as a trusted user, otherwise the same warnings will appear) should look similar to (Listing 10):

Listing 9 Activating the Nix environment

```
felipelfv@Felipes-MacBook-Pro Why-risk-it-when-you-can-rix-it % nix-shell
```

Listing 10 Expected output from `nix-shell`

```
unpacking 'https://flakehub.com/f/DeterminateSystems/nixpkgs-weekly/...'
into the Git cache...
[nix-shell:~/AMPPS/Why-risk-it-when-you-can-rix-it]$
```

This command drops the user into a shell where all specified packages and tools are available. The shell prompt changes to indicate that a Nix environment is active (here, `[nix-shell:~/AMPPS/Why-risk-it-when-you-can-rix-it]$`). To verify that R is being provided by Nix rather than a system installation, run `which R`. This should return a path within `/nix/store/`. Moreover, from within the Nix shell, users can launch their IDE by typing its name (e.g., `rstudio` or `positron`), which opens the IDE with the Nix environment active.

Reproducing the Complete Manuscript⁵

The manuscript source file (`article.qmd`) combines narrative text, executable code chunks, and references to simulation outputs. In our specific case, we integrate the simulation run itself in the manuscript as well as the reporting (i.e., performance metrics calculation and visualization). In other words, the code in the aforementioned separate `.R` files inside the folder `Simulation_Scripts` are included as code chunks (see `article.qmd` in the GitHub repository). This is not needed and most researchers would, in fact, probably not include the simulation run itself in the manuscript as many simulations take days to be completed.

To render the manuscript (Listing 11):

This command executes all code chunks in the manuscript, incorporates results and figures, and generates a formatted PDF following APA style guidelines via the `apaquarto` extension (Schneider, 2024). This extension is saved in the project repo already.

⁵ See the `{rix}` documentation for more:

<https://docs.ropensci.org/rix/articles/z-advanced-topic-building-an-environment-for-literate-programming.html>

Listing 11 Rendering the manuscript with Quarto

```
[nix-shell:~/Desktop/AMPPS/Why-risk-it-when-you-can-rix-it]$  
quarto render Manuscript/article.qmd
```

To download this extension for your own work you can install the extension by using the terminal (Listing 12):

Listing 12 Installing the apaquarto extension

```
quarto use template wjschne/apaquarto
```

or in the console (Listing 13):

Listing 13 Installing the apaquarto extension from R

```
quarto::quarto_use_template("wjschne/apaquarto")
```

The final document (.docx, .pdf, or .html) is saved directly in the project folder⁶. Because Quarto is installed as a system-level package in our Nix specification, the rendering occurs entirely within a fully reproducible environment, ensuring consistent output across machines regardless of local software configurations. If desired, the manuscript can also be reproduced interactively by opening the project folder in the user's preferred IDE and running the code chunks directly.

As mentioned, it is worth noting that Nix shells do not fully isolate you from your existing system by default. For R users, this has a practical implication: packages installed in your regular R library (outside of Nix) could potentially be loaded when running R from within the Nix environment. The {rix} package addresses this automatically—when you call `rix()`, it also executes `rix_init()`, which creates a project-specific `.Rprofile`. This file configures R to ignore external package libraries and also disables `install.packages()` within the

⁶ Although we use *apaquarto* in this example, many alternative manuscript templates are available, and Nix is agnostic to the specific template employed, provided the necessary extensions are installed.

environment. The rationale is straightforward: any new packages should be added to `default.nix` and the environment rebuilt, preserving full reproducibility (Rodrigues & Baumann, 2025). However, for stricter isolation⁷ that also prevents access to other system programs not specified in `default.nix`, use the `--pure` flag (Listing 14):

Listing 14 Activating the Nix environment with strict isolation

```
nix-shell --pure
```

Reproducing the Simulation and Results

As previously mentioned, and although we recommend it, researchers may not want or know how to use dynamic document generation. In this case, one could still follow the same steps shown thus far focusing only on the `.R` files while still benefiting from a reproducible computational environment.

To illustrate it, after following Steps I-III, without needing to define packages for the document rendering in Step I, the simulation study may be reproduced (Listing 15) as follows:

Listing 15 Running the complete simulation workflow

```
[nix-shell:~/Desktop/AMPPS/Why-risk-it-when-you-can-rix-it]$  
Rscript Simulation_Scripts/03_run_simulation.R
```

In this same way one may also execute the `.R` file associated with the performance criteria calculation and visualization. Therefore, the key advantage of executing within `nix-shell` is that all dependencies—R version, packages, and system tools—match exactly those specified in `default.nix`.

⁷ For example, when preparing this manuscript without the `--pure` flag, `quarto render` worked successfully. However, when using the `--pure` flag, the build failed. Running `quarto check` from within the Nix shell (i.e., `nix-shell --run "quarto check"`) revealed that Quarto was still accessing the system's LaTeX installation (`/Library/TeX/texbin`) rather than being restricted to only what was specified in `default.nix`.

Additional Considerations for Advanced Workflows

Workflow Orchestration: {targets} and {rixpress}

Complex simulation studies often benefit from workflow management systems that track dependencies between computational steps, cache intermediate results, and enable selective re-execution when inputs change. Two complementary approaches exist within the Nix ecosystem: using {targets} inside a Nix environment, or using {rixpress} to leverage Nix itself as the build automation tool.

Using {targets} Within Nix. As mentioned, the {targets} package (Landau, 2021) provides workflow orchestration for R-based projects. This combination ensures both computational reproducibility (via Nix controlling the environment) and computational efficiency (via targets' intelligent caching). To integrate {targets} with Nix, simply include “targets” in the `r_pkgs` parameter of `rix()`, [code listing? (JG)] and execute the pipeline within `nix-shell` using `Rscript -e 'targets::tar_make()'` . The {targets} metadata directory (`_targets/`) should be excluded from version control while the `_targets.R` configuration file should be committed alongside `default.nix` (Rodrigues & Baumann, 2025). This approach is ideal for projects that remain within the R ecosystem and do not require different computational environments for different pipeline steps (see {rix} documentation: <https://docs.ropensci.org/rix/articles/z-advanced-topic-reproducible-analytical-pipelines-with-nix.html>).

Using {rixpress} for Polyglot Pipelines. The {rixpress} package (Rodrigues, 2025), a sister package to {rix}, uses Nix itself as the build automation tool rather than operating within a Nix environment. Each pipeline step becomes a Nix derivation, providing hermetic builds with sandboxed execution and content-addressable caching. The key advantage of {rixpress} emerges in multi-language workflows: different steps can execute in different Nix-defined environments (e.g., one step using R 4.2.0 with specific packages, another using Python 3.12 with machine learning libraries, another using Julia for numerical optimization). The package interface, inspired by {targets}, uses functions like `rxp_r()`, `rxp_py()`, and `rxp_jl()` to define pipeline steps, with automatic serialization handling data transfer between languages. Objects are stored in the Nix

store and can be inspected interactively using helper functions like `rxp_read()` and `rxp_load()` (see `{rixpress}` documentation: <https://docs.ropensci.org/rixpress/articles/intro-concepts.html>).

For the interested reader, in the GitHub repository we included a folder in which the entire simulation and manuscript are produced using `{rixpress}`.

Converting Existing `{renv}` Projects

Many researchers have existing projects using `{renv}` for package management. The `renv2nix()` function facilitates migration by reading an `renv.lock` file and generating an equivalent Nix specification. This conversion is particularly valuable for projects where `{renv}` encountered system dependency issues or where stricter reproducibility guarantees are desired. However, researchers should note that while `{renv}` snapshots R package versions, Nix additionally pins system libraries and compilers, potentially exposing previously hidden dependencies on system configuration (Rodrigues & Baumann, 2025) (see `{rix}` documentation: <https://docs.ropensci.org/rix/articles/f-renv2nix.html>).

Containerization with Docker

Projects with existing Docker-based infrastructure may wish to combine Nix with containers. While this might seem redundant—both technologies provide isolation—the combination offers complementary benefits: Nix ensures bit-reproducible builds across systems, while Docker provides a familiar deployment mechanism for non-Nix-aware computing environments. The approach is to use Nix as the base layer within a Docker container (Rodrigues & Baumann, 2025). This strategy may be particularly relevant, for example, for projects requiring deployment to cloud computing platforms or high-performance computing clusters where Docker is the standard containerization technology (see `{rix}` documentation: <https://docs.ropensci.org/rix/articles/z-advanced-topic-using-nix-inside-docker.html>).

Discussion

Reproducibility in computational research is often treated as a matter of transparency—making data and code available. This tutorial has argued that transparency alone is insufficient without the ability to reliably reconstruct the computational environments in which

analyses are executed. For simulation studies in particular, where results depend critically on software versions, system libraries, and random number generation, environment-level reproducibility is not optional but essential.

By introducing Nix and the `{rix}` package, we demonstrated a practical and accessible approach to fully specifying and rebuilding computational environments for simulation-based research. This approach enables analyses and manuscripts to be rerun identically across machines and over time, transforming reproducibility from an aspirational goal into a verifiable property of the research workflow.

Importantly, adopting environment reproducibility does not require abandoning existing analytic practices. Nix is agnostic to programming language, editor, workflow structure, and manuscript template, allowing researchers to retain familiar tools while strengthening the reliability of their work. In this sense, reproducible environments serve as enabling infrastructure—supporting, rather than replacing, other best practices such as version control, workflow orchestration, and transparent reporting.

If reproducibility is to function as a cornerstone of cumulative science, then the ability to reconstruct computational environments must become a routine part of methodological practice. Tools such as Nix and `{rix}` lower the barrier to achieving this goal, making fully reproducible simulation research feasible without requiring deep systems expertise. We hope this tutorial helps normalize environment-level reproducibility as a standard component of rigorous computational research in psychology and beyond.

References

- Baker, D. H., Berg, M., Hansford, K., Quinn, B., Segala, F., & Warden-English, E. (2024). ReproduceMe: Lessons from a pilot project on computational reproducibility. *Meta-Psychology*, 8, MP.2023.4021. <https://doi.org/10.15626/MP.2023.4021>
- Boettiger, C. (2015). An introduction to Docker for reproducible research. *ACM SIGOPS Operating Systems Review*, 49(1), 71–79. <https://doi.org/10.1145/2723872.2723882>
- Boettiger, C., & Eddelbuettel, D. (2017). An introduction to Rocker: Docker containers for R. *The R Journal*, 9(2), 527–536. <https://doi.org/10.32614/RJ-2017-065>
- Dolstra, E., De Jonge, M., & Visser, E. (2004). Nix: A safe and policy-free system for software deployment. *18th Large Installation System Administration Conference*, 79–92.
- Feldman, S. I. (1979). Make — a program for maintaining computer programs. *Software: Practice and Experience*, 9(4), 255–265. <https://doi.org/10.1002/spe.4380090402>
- Glatard, T., Lewis, L. B., Ferreira da Silva, R., Adalat, R., Beck, N., Lepage, C., Rioux, P., Rousseau, M.-É., Sherif, T., Deelman, E., Khalili-Mahani, N., & Evans, A. C. (2015). Reproducibility of neuroimaging analyses across operating systems. *Frontiers in Neuroinformatics*, 9, 12. <https://doi.org/10.3389/fninf.2015.00012>
- Hardwicke, T. E., Wallach, J. D., Kidwell, M. C., Bendixen, T., Crüwell, S., & Ioannidis, J. P. A. (2020). An empirical assessment of transparency and reproducibility-related research practices in the social sciences (2014–2017). *Royal Society Open Science*, 7(2), 190806. <https://doi.org/10.1098/rsos.190806>
- Hodges, C. B., Stone, B. M., Johnson, P. K., Carter, J. H., III, Sawyers, C. K., Roby, P. R., & Lindsey, H. M. (2023). Researcher degrees of freedom in statistical software contribute to unreliable results: A comparison of nonparametric analyses conducted in SPSS, SAS, Stata, and R. *Behavior Research Methods*, 55(6), 2813–2837. <https://doi.org/10.3758/s13428-022-01932-2>
- Kidwell, M. C., Lazarević, L. B., Baranski, E., Hardwicke, T. E., Piechowski, S., Falkenberg, L.-S., Kennett, C., Slowik, A., Sonnleitner, C., Hess-Holden, C., Errington, T. M., Fiedler, S.,

- & Nosek, B. A. (2016). Badges to acknowledge open practices: A simple, low-cost, effective method for increasing transparency. *PLOS Biology*, *14*(5), e1002456.
<https://doi.org/10.1371/journal.pbio.1002456>
- Landau, W. M. (2021). *Targets: Dynamic function-oriented make-like declarative workflows*.
- Levenstein, M. C., & Lyle, J. A. (2018). Data: Sharing is caring. *Advances in Methods and Practices in Psychological Science*, *1*(1), 95–103.
- Luijken, K., Lohmann, A., Alter, U., Claramunt Gonzalez, J., Clouth, F. J., Fossum, J. L., Heslen, L., Huizing, A. H. J., Ketelaar, J., Montoya, A. K., Nab, L., Nijman, R. C. C., Penning de Vries, B. B. L., Tibbe, T. D., Wang, Y. A., & Groenwold, R. H. H. (2024). Replicability of simulation studies for the investigation of statistical methods: The RepliSims project. *Royal Society Open Science*, *11*(1), 231003. <https://doi.org/10.1098/rsos.231003>
- Malka, J., Zacchiroli, S., & Zimmermann, T. (2024). Reproducibility of build environments through space and time. *Proceedings of the 2024 ACM/IEEE 44th International Conference on Software Engineering: New Ideas and Emerging Results*, 97–101.
<https://doi.org/10.1145/3639476.3639767>
- Morris, T. P., White, I. R., & Crowther, M. J. (2019). Using simulation studies to evaluate statistical methods. *Statistics in Medicine*, *38*(11), 2074–2102.
<https://doi.org/10.1002/sim.8086>
- Nagler, T., & Vatter, T. (2025). *Rvinecopulib: High performance algorithms for vine copula modeling*. <https://CRAN.R-project.org/package=rvinecopulib>
- Nosek, B. A., Hardwicke, T. E., Moshontz, H., Allard, A., Corker, K. S., Dreber, A., Fidler, F., Hilgard, J., Kline Struhl, M., Nuijten, M. B., Rohrer, J. M., Romero, F., Scheel, A. M., Scherer, L. D., Schönbrodt, F. D., & Vazire, S. (2022). Replicability, robustness, and reproducibility in psychological science. *Annual Review of Psychology*, *73*, 719–748.
<https://doi.org/10.1146/annurev-psych-020821-114157>
- Ottoboni, K., & Stark, P. B. (2018). *Random problems with r*. <https://arxiv.org/abs/1809.06520>
- Pawel, S., Bartoš, F., Siepe, B. S., & Lohmann, A. (2025). Handling missingness, failures, and

non-convergence in simulation studies: A review of current practices and recommendations.

The American Statistician, 1–18. <https://doi.org/10.1080/00031305.2025.2540002>

Peikert, A., & Brandmaier, A. M. (2021). A reproducible data analysis workflow. *Quantitative and Computational Methods in Behavioral Sciences*, 1, e3763. <https://doi.org/10.5964/qcmb.3763>

Peng, R. D. (2011). Reproducible research in computational science. *Science*, 334(6060), 1226–1227.

Rodrigues, B. (2023). *Building reproducible analytical pipelines with R*. <https://raps-with-r.dev>

Rodrigues, B. (2025). *Rixpress: Build reproducible analytical pipelines with 'nix'*.
<https://CRAN.R-project.org/package=rixpress>

Rodrigues, B., & Baumann, P. (2025). *Rix: Reproducible data science environments with 'nix'*.
<https://CRAN.R-project.org/package=rix>

Rodrigues, B., & Baumann, P. (2026). *Nix for polyglot, reproducible data science workflows* (Version v0.0.1). Zenodo. <https://doi.org/10.5281/zenodo.18138618>

Schneider, W. J. (2024). *Apaquarto* [Computer software]. <https://github.com/wjschne/apaquarto>

Siepe, B. S., Bartoš, F., Morris, T. P., Boulesteix, A.-L., Heck, D. W., & Pawel, S. (2024).

Simulation studies for methodological research in psychology: A standardized template for planning, preregistration, and reporting. *Psychological Methods*.

<https://doi.org/10.1037/met0000695>

Simonsohn, U. (2020). *Groundhog: Version-control for CRAN, github, and gitlab packages*.

Ushey, K. (2024). *Renv: Project environments*.

Vazire, S. (2018). Implications of the credibility revolution for productivity, creativity, and progress. *Perspectives on Psychological Science*, 13(4), 411–417.

<https://doi.org/10.1177/1745691617751884>

White, I. R., Pham, T. M., Quartagno, M., & Morris, T. P. (2024). How to check a simulation study. *International Journal of Epidemiology*, 53(1), dyad134.

<https://doi.org/10.1093/ije/dyad134>

Wiebels, K., & Moreau, D. (2021). Leveraging containers for reproducible psychological

research. *Advances in Methods and Practices in Psychological Science*, 4(2).

<https://doi.org/10.1177/25152459211017853>

Ziemann, M., Poulain, P., & Bora, A. (2023). The five pillars of computational reproducibility:

Bioinformatics and beyond. *Briefings in Bioinformatics*, 24(6), bbad375.


<https://doi.org/10.1093/bib/bbad375>

Table 1*Performance metrics for ACE estimator across simulation conditions*

Sample Size	Confounding	Relative Bias	Relative RMSE	Coverage	CI Width
50	none	0.957	0.422	0.910	0.224
100	none	1.013	0.256	0.930	0.159
2000	none	0.997	0.059	0.960	0.036
50	mild	1.173	0.395	0.890	0.222
100	mild	1.157	0.318	0.870	0.154
2000	mild	1.114	0.130	0.510	0.035
50	severe	1.200	0.482	0.870	0.223
100	severe	1.235	0.379	0.830	0.157
2000	severe	1.257	0.266	0.020	0.035

Figure 1

Performance of ACE estimator across sample sizes and confounding severity. Panel A shows relative bias, Panel B shows relative RMSE, Panel C shows coverage probability of 95% confidence intervals (dashed line at nominal 0.95 level), and Panel D shows average confidence interval width. Results demonstrate that model misspecification induces systematic bias that persists across sample sizes, while increasing sample size improves precision but not accuracy under misspecification.



Appendix A

Simulation Study Design

Here we present a rather short description following recommendations from previous research, but ideally even more may be reported ([Morris et al., 2019](#); [Pawel et al., 2025](#); [Siepe et al., 2024](#); [White et al., 2024](#)). This mimics a methods or similar section in articles.

Factorial Design. The simulation employs a full factorial design with two factors: sample size ($n \in \{50, 100, 2000\}$) and degree of confounding non-linearity ($\gamma_2 \in \{0, 0.3, 0.8\}$, labeled as none, mild, and severe). The parameter γ_2 controls the strength of the quadratic confounder effect on the outcome (see Data Generation). This yields nine conditions, each replicated $K = 1000$ times.

Data Generation. For each replication, data are generated following a causal structure where a confounder X_2 affects both treatment assignment and the outcome. The confounder and treatment error term are generated using the `{rvinecopulib}` package: pairs (U_1, U_2) are drawn from an independence copula via `rbicop()`, then transformed to standard normals via $X_2 = \Phi^{-1}(U_1)$ and $\epsilon = \Phi^{-1}(U_2)$. The independence copula is simply $C(u, v) = uv$, meaning the resulting uniforms are independent—mathematically equivalent to calling `rnorm()` directly. We use `{rvinecopulib}` intentionally because it depends on C++ libraries.

Treatment assignment follows $X_1 = \alpha_0 + \alpha_1 X_2 + \alpha_2 X_2^2 + \epsilon$ where $\alpha_0 = 0$, $\alpha_1 = 0.5$, and $\alpha_2 = 0.2$. This creates confounding because X_2 influences treatment assignment through both linear and quadratic terms. The binary outcome is generated from the true logistic regression model:

$$\text{logit}(P(Y = 1 \mid X_1, X_2)) = \beta_0 + \beta_1 X_1 + \gamma_1 X_2 + \gamma_2 X_2^2$$

with parameters $\beta_0 = -0.5$, $\beta_1 = 0.7$ (the causal effect of interest), $\gamma_1 = -0.4$, and γ_2 varying by condition. The analyst misspecifies the outcome model by omitting the quadratic confounder term, fitting instead:

$$\text{logit}(P(Y = 1 \mid X_1, X_2)) = \beta_0 + \beta_1 X_1 + \gamma_1 X_2$$

This misspecification creates residual confounding because the omitted term $\gamma_2 X_2^2$ is correlated with X_1 (since X_1 depends on both X_2 and X_2^2), violating the conditional exchangeability assumption given linear adjustment alone.

Estimand. The target estimand is the average causal effect (ACE) of X_1 on Y , properly adjusted for confounding:

$$\text{ACE}(X_1) = \mathbb{E} \left[\frac{\partial P(Y = 1 \mid X_1, X_2)}{\partial X_1} \right] = \mathbb{E} \left[\beta_1 \cdot \frac{\exp(\eta)}{(1 + \exp(\eta))^2} \right]$$

where $\eta = \beta_0 + \beta_1 X_1 + \gamma_1 X_2 + \gamma_2 X_2^2$ is the correctly specified linear predictor, and the expectation is taken over the joint distribution of (X_1, X_2) . For each γ_2 condition, the “true” ACE (denoted θ) is approximated once using a very large sample ($N = 200,000$) with the correctly specified model including X_2^2 .

Estimator. The causal effect is estimated from the misspecified model (omitting X_2^2) as:

$$\widehat{\text{ACE}}(X_1) = \frac{1}{n} \sum_{i=1}^n \tilde{\beta}_1 \cdot \frac{\exp(\tilde{\eta}_i)}{(1 + \exp(\tilde{\eta}_i))^2}$$

where $\tilde{\eta}_i = \tilde{\beta}_0 + \tilde{\beta}_1 X_{i1} + \tilde{\gamma}_1 X_{i2}$ and $\tilde{\beta} = (\tilde{\beta}_0, \tilde{\beta}_1, \tilde{\gamma}_1)$ are maximum likelihood estimates from the misspecified logistic regression.

Performance Criteria. Table 1 presents the performance criteria used to evaluate the ACE estimator across simulation conditions.

Computational Details. The simulation was conducted on a MacBook Pro (...), running macOS Sequoia 15.6.1. All analyses were performed in R (version 4.5.2). Parallel processing was implemented through the `{doParallel}` package (version 1.0.17), with `{doRNG}` (version 1.8.6.2) to ensure independent and reproducible random number streams. For data generation we used the `{rvinecopulib}` package (version 0.7.3.1.0). The estimator was implemented using the `{marginaleffects}` package (version 0.31.0). Data wrangling was performed with `{dplyr}` (version 1.1.4). Method performance was assessed through multiple metrics following the formulas from the `{simhelpers}` package (version 0.3.1). Figures were produced with `{ggplot2}` (version 4.0.1).

and `{cowplot}` (version 1.2.0).

Appendix B

Clarifying the packages used

Table B1

Performance criteria for evaluating the ACE estimator. $\hat{\theta}_k$ denotes the ACE estimate from replication k (for $k = 1, \dots, K$), where $K = 1000$ is the number of replications, and θ denotes the true ACE for a given condition. For coverage and width criteria, A_k and B_k denote the lower and upper endpoints of the 95% confidence interval from replication k , $W_k = B_k - A_k$ is the interval width, c_β is the estimated coverage probability, and $I(\cdot)$ is an indicator function equaling 1 if the condition is true and 0 otherwise. The Monte Carlo standard error (MCSE) quantifies the simulation uncertainty in each performance measure estimate

Criterion	Estimate	MCSE
Bias	$\frac{1}{K} \sum_{k=1}^K \hat{\theta}_k - \theta$	$\sqrt{\frac{1}{K(K-1)} \sum_{k=1}^K (\hat{\theta}_k - \bar{\hat{\theta}})^2}$
Variance	$\frac{1}{K-1} \sum_{k=1}^K (\hat{\theta}_k - \bar{\hat{\theta}})^2$	$\sqrt{\frac{K-1}{K} \cdot \frac{1}{K-1} \sum_{k=1}^K (\hat{\theta}_k - \bar{\hat{\theta}})^2}$
RMSE	$\sqrt{\frac{1}{K} \sum_{k=1}^K (\hat{\theta}_k - \theta)^2}$	$\sqrt{\frac{K-1}{K} \sum_{j=1}^K \left(\sqrt{(\hat{\theta}_j - \theta)^2} - \overline{RMSE} \right)^2}$
Relative Bias	$\frac{1}{\theta K} \sum_{k=1}^K \hat{\theta}_k$	$\frac{1}{\theta} \sqrt{\frac{1}{K(K-1)} \sum_{k=1}^K (\hat{\theta}_k - \bar{\hat{\theta}})^2}$
Relative RMSE	$\frac{1}{\theta} \sqrt{\frac{1}{K} \sum_{k=1}^K (\hat{\theta}_k - \theta)^2}$	$\frac{1}{\theta} \sqrt{\frac{K-1}{K} \sum_{j=1}^K \left(\sqrt{(\hat{\theta}_j - \theta)^2} - \overline{RMSE} \right)^2}$
Coverage	$\frac{1}{K} \sum_{k=1}^K I(A_k \leq \theta \leq B_k)$	$\sqrt{\frac{c_\beta(1-c_\beta)}{K}}$
Width	$\frac{1}{K} \sum_{k=1}^K (B_k - A_k)$	$\sqrt{\frac{1}{K(K-1)} \sum_{k=1}^K (W_k - \bar{W})^2}$