

**Why Risk it, When You Can {rix} it: A Tutorial for Computational Reproducibility Focused
on Simulation Studies**

Felipe Fontana Vieira¹, Jason Geller², and Bruno Rodrigues³

¹Department of Data Analysis, Ghent University

²Department of Psychology and Neuroscience, Boston College

³Statistics and Data Strategy Departments, Ministry of Research and Higher Education,
Luxembourg

Author Note

Felipe Fontana Vieira  <https://orcid.org/0009-0006-0949-6569>

Jason Geller  <https://orcid.org/0000-0002-7459-4505>

Bruno Rodrigues  <https://orcid.org/0000-0002-3211-3689>

Data and materials from this study can be accessed at <https://github.com/felipelfv/Why-risk-it-when-you-can-rix-it>. Bruno Rodrigues is the author and maintainer of the {rix} package presented in this tutorial. The authors have no other conflicts of interest to declare. We would like to thank Julia Rohrer and Ole Schacht for their helpful feedback on earlier versions of this manuscript. During the first round of revision, Claude Sonnet 4.6 (Anthropic) was used to improve the grammar and coherence of the Introduction and Discussion. Author roles were classified using the Contributor Role Taxonomy (CRediT; <https://credit.niso.org/>) as follows: Felipe Fontana Vieira: Conceptualization, Methodology, Software, Data curation, Formal analysis, Visualization, Writing - original draft, Writing - review & editing; Jason Geller: Conceptualization, Supervision, Validation, Writing - review & editing; Bruno Rodrigues: Conceptualization, Software, Writing - review & editing

Correspondence concerning this article should be addressed to Felipe Fontana Vieira,
Email: felipe.fontanavieira@ugent.be

Abstract

Computational reproducibility remains limited in psychological research, despite widespread norms for sharing data and analysis code. One reason is that reproducibility exists on a continuum, ranging from partial transparency—such as providing scripts or software version numbers—to fully executable research compendia that regenerate all results from raw code. In this article, we introduce Nix and the {rix} R package as a practical framework for achieving full computational reproducibility in simulation-based research. We provide a step-by-step tutorial demonstrating how {rix} can be used to define, build, and share isolated, project-specific software environments that precisely capture R versions, package dependencies, system libraries, and integrated development environments. We further illustrate this workflow by reproducing a complete manuscript using Quarto and the {apaquarto} extension, showing how analyses, figures, and text can be regenerated in a single, executable pipeline. Together, these tools lower the technical barrier to robust, end-to-end reproducibility and offer a scalable solution for simulation studies and methodological research in psychology and related fields.

Keywords: reproducibility, Nix, simulation studies, R, computational methods

Why Risk it, When You Can {rix} it: A Tutorial for Computational Reproducibility Focused on Simulation Studies

Psychological science is in the midst of a credibility revolution ([Vazire, 2018](#)), yet much of that scrutiny has focused on empirical studies. Monte Carlo simulation studies (hereafter referred to as simulation studies) have received far less ([Siepe et al., 2024](#)), even though they are a primary tool for evaluating the statistical methods ([Morris et al., 2019](#)) and may suffer from selective reporting ([Bouma et al., 2026](#); [Pawel et al., 2024, 2025](#)). One aspect of credibility that remains especially underexamined for simulations is reproducibility (i.e., the ability to exactly reproduce the results of a study based on provided data, code, materials, and software/hardware) ([Hardwicke et al., 2020](#)). In a simulation study, this involves more than reanalyzing a fixed dataset, because the code also generates the data. Reproducing such a study therefore entails reproducing the data generation process, the analysis, and the summary of results. Montoya and Anderson ([2026](#)) conceptually address each of these stages separately.

Reproducibility in this sense is not all-or-nothing but occupies a continuum ([Peng, 2011](#)), on which a study is positioned according to the extent of the materials that are publicly available. This ranges from publication alone at the low end to code and data that are linked and directly executable at the high end. Reaching that executable end is often treated as *full* reproducibility ([Peikert et al., 2021](#); [Peikert & Brandmaier, 2021](#)), and open science initiatives have pushed work toward it ([Kidwell et al., 2016](#); [Levenstein & Lyle, 2018](#); [Nosek et al., 2015](#)). Yet code and data are never fully sufficient ([Brodeur et al., 2026](#); [Epskamp, 2019](#); [Wiebels & Moreau, 2021](#); [Ziemann et al., 2023](#)). Even error-free code depends on a hierarchy of software components, including the programming language version, the packages used in the analysis, and the system-level libraries those packages rely on. We define these and related terms used before the tutorial section in Table 1. When these differ from the originals, code may fail, behave inconsistently across machines, or yield conflicting numerical results ([Baker et al., 2024](#); [Glatard et al., 2015](#); [Hodges et al., 2023](#); [Nosek et al., 2022](#)). These problems are particularly acute for simulation studies, which typically rely on a large amount of interconnected code, packages

versions, and the underlying system itself to generate their data and produce the results of interest (Luijken et al., 2024; Siepe et al., 2024).

To make this concrete, we use the *computational environment* to refer to the complete software context required for an analysis to run successfully. This entails the programming language version, package versions, system-level libraries, and operating system (Figure 1) (Rodrigues, 2023; Rodrigues & Baumann, 2026). We define *computational environment reproducibility* as the ability to reconstruct these dependencies on top of whatever operating system a machine runs, at any future time, such that executing the same code yields the same numerical results¹. Empirical assessments show that current practice falls short of this ideal. Indeed, Siepe et al. (2024) report that, among the 100 simulation studies they identified in psychology journals in 2021 and 2022, nearly two-thirds provide no accompanying code, and among those that do, documentation of the computational environment is rarely included. This gap is consequential, as simulation studies inform methodological recommendations, meaning that insufficient reproducibility may undermine confidence in those recommendations (Luijken et al., 2024; White et al., 2024).

These challenges may persist for several reasons. Arguably, one is that even researchers aware of these demands face a fragmented landscape of solutions, each addressing only part of the problem. Package-level managers such as {renv} (Ushey, 2024) and {groundhog} (Simonsohn, 2020) stabilize R package versions but do not manage the R interpreter itself or the system-level libraries those packages depend on. Workflow orchestration tools such as {targets} (Landau, 2021) and Make (Feldman, 1979) support reproducibility in a different sense: they specify the structure of an analysis by formalizing the order in which steps should run and by tracking dependencies among intermediate results. These tools clarify *how* an analysis proceeds, but they assume that the software stack required to run each step is already stable. Containerization tools such as Docker, including R-focused implementations like Rocker (Boettiger, 2015; Boettiger &

¹ We note that the definition of computational environment reproducibility in this context may be considered rather loose. For the interested reader, we refer to Malka et al. (2026) (p. 3) and Lamb and Zacchiroli (2022).

[Eddelbuettel, 2017](#)) offer a more comprehensive approach by bundling nearly the entire environment into a single executable image. Yet their use requires familiarity with Linux system administration, and even containerization may suffer from temporal drift when Dockerfiles rely on mutable upstream repositories ([Malka et al., 2026](#)). For a detailed comparison of these tools and their limitations, see [Rodrigues and Baumann \(2026\)](#). Researchers thus face a difficult choice between solutions that are accessible but incomplete or approaches that are powerful but demand technical expertise.

In this article, we focus specifically on computational environment reproducibility as the foundation upon which other reproducibility practices depend. For that, we introduce Nix ([Dolstra et al., 2004](#)), a software ecosystem designed to make software installation deterministic, and {rix} ([Rodrigues & Baumann, 2025](#)), an R interface that allows researchers to use Nix without needing deep knowledge of its underlying language or infrastructure. Our main objective with the tutorial is not to introduce a specific workflow orchestration system or to prescribe a particular analytic structure.² Instead, we aim to show what Nix and {rix} are and how they can establish a stable, cross-platform environment within which any simulation study—whether organized in simple, documented script sequences (e.g., .R files that `source()` others), through more formal orchestration tools (e.g., {targets}) or embedded as code chunks in .Rmd or .qmd files—can be executed reliably. We illustrate these ideas through a reproducible simulation study conducted in R, culminating in this automated APA-formatted manuscript generated with `apaquarto` ([Schneider, 2024](#)). Although the example centers on R because of its prominence, the principles underlying environment reproducibility with {rix} apply equally to other languages, including Python and Julia, and to different development environments such as RStudio, VS Code, Emacs, or Positron. At the end of the article, we also briefly introduce {rixpress} ([Rodrigues, 2025](#)), a

² We leave workflow orchestration aside for two reasons. First, many tools address it, each with its own conventions, and doing them justice would require a more tailored treatment than a single tutorial allows. Second, although formal orchestration may be necessary for full reproducibility, it rests on a stable computational environment: orchestrating analyses is only meaningful when the software they run on is itself reproducible. Moreover, arguably, a study whose scripts are well documented, whose file dependencies are explained, and whose environment is stable therefore already sits high on the reproducibility spectrum, and that foundation is what we focus on here. For readers interested in the workflow side, we suggest [Peikert et al. \(2021\)](#), [van Lissa et al. \(2021\)](#), and [Rodrigues \(2023\)](#).

workflow orchestration tool that builds on Nix to coordinate pipelines across R, Python, and Julia.

Setting the Stage: A Simulation Study and Its Reproducibility Risks

Imagine you have just been awarded a grant to conduct a large-scale simulation study, where you want to evaluate the performance of a statistical estimator under varying data-generating conditions (see Appendix A for full technical details). This tutorial is organized around this example to ground our discussion in a typical methods section, but readers can follow the tutorial without engaging deeply with the simulation itself. In practice, simulation studies are typically organized into multiple component files. To mimic this practice, our simulation is organized into five sequential scripts: data generation (`01_data_generation.R`), model specification (`02_models.R`), simulation execution (`03_run_simulation.R`), performance metric calculation (`04_performance_metrics.R`), and results visualization (`05_plots.R`)³.

Now suppose a researcher attempts to reproduce the simulation run and results reported in this article. What might prevent them from obtaining identical outcomes, assuming error-free code? The natural first concern is the version of packages. Installing R packages at a later time may lead to errors if functions have been renamed or deprecated (e.g., `dplyr::cur_data()` changed to `pick()`), or, although usually discouraged, internal functions, such as `lavaan:::lav_utils_get_ancestors`, renamed to `lavaan:::lav_graph_get_ancestors`), or to subtle differences in the results due to changes in default settings (e.g., `stringsAsFactors` defaulting to `FALSE` as of R 4.0). Beyond package versioning, many packages rely on system-level libraries that must be installed separately from R. Our simulation illustrates this dependency structure directly: the `{rvinecopulib}` package interfaces with a C++ backend ([Nagler & Vatter, 2025](#)).

The R language version introduces another layer of dependency. Code written for a recent version of R may rely on syntax or functionality that is unavailable in earlier versions (e.g., the

³ We note that, for the sake of simplicity, we included all code directly within this document as executable chunks in a single `.qmd` file. This entails that the simulation runs from start to finish (i.e., generating data, producing results and figures automatically). This approach would be impractical for many real-world simulation studies, which are often too computationally intensive. We return to this trade-off later in the tutorial as the solution is quite simple: one may simply run the simulation outside the `.qmd` file and load the results for the analyses in the same file.

native pipe `|>` introduced in R 4.1). More subtly, changes to R's random number generation across versions mean that identical code executed with the same seed can nevertheless produce different random sequences (Ottoboni & Stark, 2018). This is especially consequential for simulation studies, because the random draws are not incidental to the analysis but constitute the data itself. Therefore, the random number generator is part of the computational environment: reproducing the data requires not only the same seed but also the same R version. Moreover, generating data and reproducing every statistical estimate *exactly* can depend on lower-level components still, such as the system-level libraries R uses for matrix computations (e.g., BLAS/LAPACK). With respect to the latter, we do not claim that this exact level of identity must be met. How much reproducibility is required is ultimately for the scientific community to decide (e.g., through journals and disciplinary norms), and reproducing the broader pattern of results is arguably enough. Regardless, the solution we propose increases the chances of reaching such a level of reproducibility, consistent with empirical findings (Malka et al., 2026).

Finally, analyses embedded in a literate programming workflow add further dependencies. Rendering R Markdown (`.Rmd`) or Quarto (`.qmd`) documents, for example, requires a document conversion tool (such as Pandoc) and a typesetting system (such as LaTeX or Typst), each with its own version and installation requirements.

Nix and {rix}: A Comprehensive Solution

A potential solution is Nix (Dolstra et al., 2004), a software ecosystem built so that installing software gives the same result every time. Nix is a functional programming language, a build tool, and a package manager wrapped in one. This article focuses on the latter. Most package managers (think of Apple's or Android's app stores) are imperative: they modify a system's state as they install or update software. Nix instead builds each environment from an explicit description and never alters it afterward, so the same description produces the same self-contained environment on other machines. Researchers state exactly which versions of their language and packages they need, and Nix works out the underlying system-level libraries automatically.

Core Principles

Rather than installing software into shared system folders (e.g., `/usr/lib`), Nix gives every package its own folder under `/nix/store`. The folder's name includes a short fingerprint (a *cryptographic hash*) computed from everything that went into the package, its source code, dependencies, and build instructions, so any change to those inputs yields a different folder. Because each package is identified by its exact contents this way, several versions of the same software can sit side by side without conflict: a researcher can, for example, keep R 4.1.0 and R 4.3.3 on the same machine, or use different package versions across analyses ([Rodrigues & Baumann, 2025](#)).

The Nix ecosystem is built around `nixpkgs`, a version-controlled repository comprising more than 120,000 packages, including nearly all of CRAN and Bioconductor. By pinning a specific commit or date, researchers freeze the entire software stack (i.e., R itself, R packages, and all system-level libraries). This eliminates the system-dependency problems that tools like `{renv}` cannot address ([Rodrigues & Baumann, 2025](#)). Empirical studies of historical `nixpkgs` snapshots report that old environments can still be rebuilt years later, and largely reproduce their original results ([Malka et al., 2026](#); [Rodrigues & Baumann, 2026](#)). Moreover, because prebuilt binaries can be downloaded from a shared binary cache instead of compiled from scratch, these environments are often ready in seconds, which keeps Nix practical for everyday interactive work ([Rodrigues & Baumann, 2025](#)).

The {rix} Package: R Interface to Nix

Because the Nix package manager is declarative, installing software requires writing expressions in its language. Since this language is unfamiliar to most researchers, we recommend and focus on using `{rix}` to lower this barrier. The `{rix}` package provides an R-native interface: a single call to `rix()` generates complete Nix configurations from standard R syntax, specifying R versions, CRAN packages, system-level libraries, and even Python or Julia components when required. Users never need to read or write Nix code directly, as `{rix}` translates automatically. For more on `{rix}`, including its integration with `rstats-on-nix` (a curated fork of the Nix package

collection whose dated snapshots let users request the exact R and package versions available on a chosen day), see Rodrigues and Baumann (2025) and Rodrigues and Baumann (2026).

A Practical Example: Setting up a Reproducible Simulation Study with {rix}

We take the perspective of a researcher (e.g., on macOS) beginning a simulation study who wants it reproducible from the outset. Rather than writing the analysis first and reproducing it later, we set up the computational environment with {rix} first, then create and run the scripts and manuscript inside it. We then show how another researcher could reproduce it.

Step 1: Installing Nix and {rix}

Before proceeding, both Nix and the {rix} R package need to be installed. The quick start below covers the common case, but the complete, up-to-date instructions for each operating system are maintained in the {rix} documentation: Linux and Windows (WSL2) (<https://docs.ropensci.org/rix/articles/setting-up-linux-windows.html>) and macOS (<https://docs.ropensci.org/rix/articles/setting-up-macos.html>).

The installation is the same across operating systems, with one prerequisite on Windows: Nix runs inside the Windows Subsystem for Linux 2 (WSL2), which must be installed and configured first (see the {rix} documentation above). On all systems, install Nix by running the Determinate Systems installer in a terminal⁴. To open it, on macOS, go to Applications → Utilities → Terminal. For Windows, launch your WSL2 (Ubuntu) shell from the Start menu. For Linux, open your distribution's terminal application. Then run (Listing 1):

Listing 1 Installing Nix

```
curl --proto '=https' --tlsv1.2 -sSf \  
-L https://install.determinate.systems/nix | \  
sh -s -- install
```

⁴ A terminal is a text-based way to give your computer instructions. Readers new to the command line may find the following link a useful primer: <https://swcarpentry.github.io/shell-novice/>. This was also suggested in Wiebels and Moreau (2021)

Once Nix is installed⁵, there are two ways to access {rix}, depending on whether R is already installed on your system. In this tutorial, we proceed as if R was already installed⁶, as that most likely will be the case for most readers (Listing 2):

Listing 2 Installing {rix} from CRAN or developmental version

```
# CRAN version
install.packages("rix")
# Development version
install.packages(
  "rix",
  repos = c(
    "https://ropensci.r-universe.dev"
  )
)
```

Step 2: Specifying the Computational Environment

We then begin with a folder for this project (here named `Why-risk-it-when-you-can-rix-it`) that contains only two empty subfolders, `Simulation` and `Manuscript`. We have not written any simulation scripts or the manuscript yet. The only file we write by hand for now is `gen-env.R` (or similar), which uses the `rix()` function from the {rix} package to produce a `default.nix` file: a declarative specification of all software dependencies the project needs.

We establish the full environment the simulation needs up front: the R version, an IDE, and the R packages the scripts will use. You can always add more later, but doing so means editing `gen-env.R` and following the steps we are about to illustrate. The simulation specification is shown in Listing 3 (the complete version, which also covers the manuscript, is on the GitHub

⁵ It is worth noting that {rix} can generate Nix expressions even without Nix installed on your system: you can write a `default.nix` file without Nix, but you cannot build or enter the resulting environment unless Nix is installed (Rodrigues & Baumann, 2025).

⁶ We, however, recommend uninstalling your local R and letting Nix manage R, R packages, and other tools entirely. This approach avoids potential conflicts between system-installed and Nix-managed software, an issue we will illustrate later in this tutorial. See <https://docs.ropensci.org/rix/articles/setting-up-linux-windows.html#case-1-you-dont-have-r-installed-and-wish-to-install-it-using-nix-as-well> for more details.

repository, <https://github.com/felipelfv/Why-risk-it-when-you-can-rix-it>, as `gen-env.R`):

Listing 3 Simulation environment: R, RStudio, and the packages the scripts need

```
library(rix)

# choose the path to your project
project_directory <- "." # here, the "Why-risk-it-when-you-can-rix-it" folder (root)

rix(
  date = "2026-01-14", # recommendation: pin a date
  r_pkgs = c( # all R packages the simulation scripts need
    "rix", "marginaleffects", "simhelpers", "rvinecopulib",
    "doParallel", "doRNG", "ggplot2", "cowplot", "dplyr", "svglite"
  ),
  ide = "rstudio", # editor to include
  project_path = project_directory,
  overwrite = TRUE
)
```

Environment Specification

The `rix()` function⁷ constructs the specification through a series of parameters that collectively describe the computational environment. Each parameter serves a distinct purpose in defining the environment’s characteristics, and we will clarify those throughout this tutorial section.

Specifying the R version. Researchers must first determine which version of R to use. This can be accomplished in two ways: The `r_ver` argument accepts an exact version string (e.g., “4.3.3”) or special designations such as “latest-upstream” for the most recent stable release. Alternatively, the `date` argument specifies a particular date (e.g., “2024-11-15”), which ensures that R and all packages correspond to the versions available on that date. The date-based approach is generally preferable for reproducibility, as it captures a complete snapshot of the R ecosystem at a single point in time. For this tutorial, as shown on top, we use the `date` parameter to ensure

⁷ For an overarching information on the function `rix()`, we suggest the following {rix} documentation: <https://docs.ropensci.org/rix/articles/project-environments.html>

temporal consistency across all software components (Rodrigues & Baumann, 2025) (see {rix} documentation for more: <https://docs.ropensci.org/rix/articles/project-environments.html>).

Declaring R package dependencies. The `r_pkgs` argument accepts a character vector listing all required R packages by their CRAN names. These packages will be installed from the version repository corresponding to the specified date or R version. It is important to list all packages that the analysis will load directly; dependencies of these packages are automatically resolved by Nix. For packages requiring specific versions not corresponding to the chosen date, researchers can specify exact versions using the syntax "packagename@version" (e.g., "ggplot2@2.2.1"). For packages available only on GitHub or other Git repositories, the `git_pkgs` argument accepts a list structure containing repository URLs and specific commit hashes. For example:

Listing 4 Example for the `git_pkgs` argument

```
git_pkgs = list(  
  package_name = "marginaleffects",  
  repo_url = "https://github.com/vincentarelbundock/marginaleffects",  
  commit = "304bff91dc31ae28b227a8485bfa4f7bdc86d625"  
)
```

This ensures that exact development versions are obtained (Rodrigues & Baumann, 2025). For our simulation study, all packages were used with their CRAN versions (see {rix} documentation for more details: <https://docs.ropensci.org/rix/articles/installing-r-packages.html>). Appendix B gives the reasons for adding each package in `r_pkgs`.

Configuring the development environment. The `ide` parameter controls whether an integrated development environment (IDE) is included in the Nix environment, allowing users to interactively develop and run code within their editor of choice. When `ide` is specified, the project can be opened directly in the corresponding IDE, with all dependencies provided by the Nix environment. Most readers likely already have an IDE installed locally. Here we instead show how to open RStudio from the rix specification, which does not require RStudio to be installed on

your system. For example, setting `ide = "rstudio"` installs a project-specific version of RStudio inside the Nix environment. This is required for RStudio because, unlike most other editors, it cannot attach to an external Nix shell unless it is itself installed via Nix. On macOS, RStudio is only available through Nix for R versions 4.4.3 or later (or environments dated 2025-02-28 or later). For earlier R versions, alternative editors must be used. Other supported IDEs include Positron (`ide = "positron"`), Visual Studio Code (`ide = "code"`), and command-line interfaces such as Radian (`ide = "radian"`). These tools may either be installed directly within the Nix environment using the `ide` parameter, or users may rely on an existing system installation by setting `ide = "none"` (or `ide = "other"`) and configuring `direnv` to automatically load the Nix environment when the project directory is opened⁸. All IDEs installed via Nix are project-specific and do not interfere with system-wide installations. Detailed configuration instructions are provided in the {rix} documentation:

<https://docs.ropensci.org/rix/articles/configuring-ide.html>

Setting file output parameters. The `project_path` parameter indicates where the `default.nix` file should be written (“.” denotes the current directory), while `overwrite` controls whether an existing file should be replaced. Adding to this, setting `print = TRUE`, which is another argument, displays the generated specification in the console for immediate verification (Rodrigues & Baumann, 2025).

Step 3: Generating the Environment Specification

After defining the computational environment, the `rix()` function must be executed to generate the `default.nix` file. This can be done interactively by running `rix()` (Listing 3). The file is written to the folder given in `project_path`, so you can confirm it succeeded by checking that this folder now contains `default.nix`.

⁸ `direnv` is a lightweight utility that integrates with the user’s shell and automatically loads project-specific environment settings when navigating into a directory (via a `.envrc` file), and unloads them when leaving. This makes environment activation implicit and reduces the risk of running analyses in the wrong software context.

Step 4: Building and Using the Reproducible Environment

Once Step 3 is complete, we build the reproducible environment by navigating to the project directory in the terminal. In our case, this is the `Why-risk-it-when-you-can-rix-it` folder. From there, run the following command (Listing 5):

Listing 5 Building the Nix environment

```
# in the terminal, from the project directory:  
nix-build
```

The expected output should look similar to (Listing 6):

Listing 6 Expected output from `nix-build`

```
unpacking 'https://github.com/rstats-on-nix/nixpkgs/archive/2025-08-25.tar.gz'  
into the Git cache...  
warning: ignoring untrusted substituter...  
warning: ignoring the client-specified setting...  
/nix/store/qa7fq20m2f94szsnqzciwv8h4n81w43v-nix-shell
```

This command builds the environment according to the specification. The first execution will download and install all required packages, which may take a few minutes depending on network speed and system resources. Subsequent builds use cached packages and complete in seconds. Upon successful completion, a path to the constructed environment in the Nix store is printed (here, `/nix/store/qa7fq20m2f94szsnqzciwv8h4n81w43v-nix-shell`), and a symbolic link named `result` appears in the project directory pointing to this location. In our illustration, this build already includes the R packages declared for the simulation (Listing 3).

Note that the warnings indicate that you are not configured as a trusted user, so Nix cannot use the `rstats-on-nix` binary cache and will instead compile packages from source, which is slower. To enable binary caching, see the `{rix}` documentation:

<https://docs.ropensci.org/rix/articles/binary-cache.html>.

To activate the environment, run (Listing 7):

Listing 7 Activating the Nix environment

```
# in the terminal, from the project directory:
nix-shell
```

The expected output (if you have configured yourself as a trusted user, otherwise the same warnings will appear) should look similar to (Listing 8):

Listing 8 Expected output from nix-shell

```
unpacking 'https://flakehub.com/f/DeterminateSystems/nixpkgs-weekly/...'
into the Git cache...
[nix-shell:~/Why-risk-it-when-you-can-rix-it]$
```

This command drops the user into a shell where all specified packages and tools are available. The shell prompt changes to indicate that a Nix environment is active (here, `[nix-shell:~/Why-risk-it-when-you-can-rix-it]$`). To verify that R is being provided by Nix rather than a system installation, run `which R`. This should return a path within `/nix/store/`. Moreover, from within the Nix shell, users can launch their IDE by typing its name (e.g., `rstudio` or `positron`), which opens the IDE with the Nix environment active (Listing 9)⁹:

Listing 9 Activating RStudio

```
[nix-shell:~/Why-risk-it-when-you-can-rix-it]$ rstudio
```

Step 5: Developing and Making the Simulation Reproducible

With RStudio open from the Nix environment, we write the five simulation `.R` scripts inside the `Simulation` subfolder. For the sake of clarity, one does not need to use RStudio, but we illustrate it as most readers probably make use of an IDE. Because we declared the simulation packages up front (Listing 3), they are already available in the shell, and the scripts run against

⁹ Please note that activating an RStudio instance via Nix does **not** automatically open the specific project directory you are working in. We therefore recommend creating an **RStudio project file** (`.Rproj`) and opening that file when using Nix to ensure that RStudio is correctly associated with the intended project and environment.

exactly those versions. One is rarely aware of every package a project will need in advance, but, as highlighted before, packages can be added “on-the-go”: as the code takes shape and calls for another package, we add it to `r_pkgs` in `gen-env.R` and rerun `rix()`. It is crucial that, after editing `gen-env.R`, we rebuild with `nix-build` and re-enter with `nix-shell` so the new packages become available.

Running the Simulation and Results

With the environment built, we run the simulation from inside the Nix shell so that it uses exactly the R version and packages declared in `default.nix`. This is how the results and plots reported in this manuscript were produced. For example, `03_run_simulation.R` begins by loading the required packages and sourcing the other scripts it needs:

Listing 10 Code for running the simulation

```
library(marginaleffects)
...

# Source helper functions
source("Simulation/01_data_generation.R")
...
```

The simulation needs nothing beyond the environment built above (Listing 3). From within the Nix shell, the simulation runs (Listing 11) as follows:

Listing 11 Running the complete simulation workflow

```
[nix-shell:~/Why-risk-it-when-you-can-rix-it]$
Rscript Simulation/03_run_simulation.R
```

In the same way, we run `04_performance_metrics.R` (Listing 12), which loads the simulation results (in `sim_results.rds`) and calculates the performance metrics:

Similarly, `05_plots.R` (Listing 13) uses those saved metrics (in `performance_summary.rds`) to create the plots:

Listing 12 Running the performance metrics calculation

```
[nix-shell:~/Why-risk-it-when-you-can-rix-it]$  
Rscript Simulation/04_performance_metrics.R
```

Listing 13 Generating the visualization plots

```
[nix-shell:~/Why-risk-it-when-you-can-rix-it]$  
Rscript Simulation/05_plots.R
```

Because these results and plots come entirely from running the scripts inside the Nix environment, they are reproducible. This approach does, however, rely on running the scripts in sequence by hand. It therefore guarantees a reproducible environment but does not formalize the workflow itself, leaving the dependencies between scripts implicit in the code rather than explicitly declared.

Step 6: Developing and Making the Complete Manuscript Reproducible

To also build the manuscript, we extend the simulation environment (Listing 3) with the literate-programming tools it lacks¹⁰: Quarto, {knitr}, and a set of LaTeX packages. We add these arguments to `gen-env.R` and `rebuild`. Listing 14 shows only what is added:

Including system-level dependencies. The `system_pkgs` parameter is for software the project needs that is not an R package. It accepts any of the programs available through Nix (the same large collection mentioned earlier), so beyond Git, Pandoc, and, here, Quarto, it can be essentially any command-line tool a project depends on. Not every system-level dependency needs listing, though: when an R package itself relies on compiled libraries, Nix installs them automatically. The {rvinecopulib} package, for example, links against the C++ libraries Boost and Eigen, which we never list. The `apaquarto` extension we use for APA formatting is a separate case: it is a Quarto extension stored in the project's `_extensions/` directory rather than a Nix package (Rodrigues & Baumann, 2025) (see the {rix} documentation for more:

¹⁰ See the {rix} documentation for more: <https://docs.ropensci.org/rix/articles/literate-programming.html>

Listing 14 Manuscript tools added to the simulation environment

```
rix(
  # ...all simulation arguments from @lst-rix-env-sim, plus:
  r_pkgs = c(..., "quarto", "knitr"), # add to the existing vector
  system_pkgs = c("quarto"), # command-line Quarto
  tex_pkgs = c("amsmath", "ninecolors", "apa7", "scalereel",
    "threeparttable", "threeparttablex", "endfloat", "environ",
    "multirow", "tcolorbox", "pdfcol", "tikzfill", "fontawesome5",
    "framed", "newtx", "fontaxes", "xstring", "wrapfig", "tabularray",
    "siunitx", "fvextra", "geometry", "setspace", "fancyvrb",
    "anyfontsize"
  )
)
```

<https://docs.ropensci.org/rix/articles/installing-system-tools.html>).

Specifying LaTeX packages. The `tex_pkgs` parameter lists the LaTeX packages needed for PDF compilation. When any are listed, Nix includes a minimal TeXLive distribution (`scheme-small`) and adds the requested packages on top. Finding the exact set often takes some trial and error, since Quarto's error messages during rendering indicate which packages are missing. Appendix B gives also the reasons for adding each package in `tex_pkgs`.

After rebuilding with `nix-build` and re-entering with `nix-shell`, Quarto is available. We write the manuscript (`article.qmd`) in a Manuscript subfolder, and render it from the terminal (Listing 15):

Listing 15 Rendering the manuscript with Quarto

```
[nix-shell:~/Why-risk-it-when-you-can-rix-it]$
quarto render Manuscript/article.qmd
```

This command executes all code chunks in the manuscript (i.e., loads the R packages, runs the data generation and estimation), calculates and incorporates results (e.g., Table 2) and figures (e.g., Figure 1), and generates a formatted PDF following APA style guidelines via the `apaquarto` extension (Schneider, 2024). This extension is saved in the project directory already. To add it to a

project of your own, run the following inside the Nix shell, where Quarto is provided by the environment and therefore needs no separate installation (Listing 16):

Listing 16 Adding the `apaquarto` extension

```
[nix-shell:~/Why-risk-it-when-you-can-rix-it]$  
quarto add wjschne/apaquarto
```

The final document (which can be saved as a `.docx`, `.pdf`, or `.html`) is saved directly in the project subfolder¹¹. Because Quarto is installed as a system-level package in our Nix specification, the rendering occurs entirely within a fully reproducible environment, ensuring consistent output across machines regardless of local software configurations. If desired, the manuscript can also be reproduced interactively by opening the project folder in the user’s preferred IDE.

As highlighted before, we included the simulation code as code chunks for this manuscript. This was done simply for illustration purposes. In a real-world simulation study, users could simply run the simulation as in the previous sections and then load the needed results (produced within the Nix shell) in the manuscript. However, the same remark holds with respect to the formalized workflow.

At this point, it is also worth noting that Nix shells do not fully isolate you from your existing system by default. For R users, this has a practical implication: packages installed in your regular R library (outside of Nix) could potentially be loaded when running R from within the Nix environment. The `{rix}` package addresses this automatically—when you call `rix()`, it also executes `rix_init()`, which creates a project-specific `.Rprofile`. This file configures R to ignore external package libraries and also disables `install.packages()` within the environment. The rationale is straightforward: any new packages should be added to `default.nix` and the environment rebuilt, preserving full reproducibility (Rodrigues & Baumann, 2025). However, for stricter isolation¹² that also prevents access to other system

¹¹ Although we use `apaquarto` in this example, many alternative manuscript templates are available, and Nix is agnostic to the specific template employed, provided the necessary extensions are installed.

¹² For example, when preparing this manuscript without the `--pure` flag, `quarto render` worked successfully.

programs not specified in `default.nix`, use the `--pure` flag (Listing 17):

Listing 17 Activating the Nix environment with strict isolation

```
nix-shell --pure
```

Reproducing the Simulation Study and Manuscript

Having built the project as its authors, we now switch to the perspective of a reader who wants to reproduce it. Because the environment is bundled with the project, reproduction requires almost nothing beyond the project folder itself.

A reader can download the entire project from its GitHub repository (<https://github.com/felipelfv/Why-risk-it-when-you-can-rix-it>). Because the folder already contains `default.nix`, they do not need the authoring steps (Steps 1 to 3). With Nix installed, they need only build and enter the environment as in Step 4 (`nix-build`, then `nix-shell`), which guarantees that all dependencies (the R version, packages, and system tools) match exactly those specified in `default.nix`.

From within that environment, reproduction proceeds on two levels. The simulation can be reproduced by running its scripts in order, regenerating the results and figures. The complete manuscript (its text together with the embedded results, tables, and figures) can be reproduced in the same environment as in Listing 15, which re-executes every code chunk and regenerates the formatted PDF end to end.

Additional Considerations for Simulation Studies

In this section, we turn to considerations that matter especially for simulation studies but fall outside this tutorial's scope, since they depend on the details of each study. The first concerns random draws and reproducibility. The second concerns workflow orchestration, environment for multiple programming languages environment, and integration with tools researchers may already

However, when using the `--pure` flag, the build failed. Running `quarto check` from within the Nix shell (i.e., `nix-shell --run "quarto check"`) revealed that Quarto was still accessing the system's LaTeX installation (`/Library/TeX/texbin`) rather than being restricted to only what was specified in `default.nix`.

use. We do not cover these topics in depth. Our goal is to clarify how they relate to {rix} and to point readers toward resources for more advanced use cases.

Reproducible Randomness and Parallel Execution for Data Generation

A simulation regenerates its data from a pseudo-random number generator, so its reproducibility depends on controlling that generator. The standard advice is to set the seed once and store it, so the same code reproduces the same sequence of draws ([Morris et al., 2019](#)). Simulation studies are typically organized as a set of conditions, each run for many repetitions, so the unit one wants to reproduce is a single repetition within a given condition. Storing the generator's state at the start of each condition-repetition cell, rather than only the initial seed, additionally allows any single cell to be reproduced in isolation, which is convenient for debugging ([Morris et al., 2019](#)). In R, the state lives in the variable `.Random.seed`, and such a procedure would look as follows (Listing 18):

With a sufficient number of repetitions the particular seed does not affect the conclusions. However, parallel processing complicates this ([Morris et al., 2019](#); [Siepe et al., 2024](#)). In this case, a single seed may no longer be sufficient, because each worker would advance its own copy of the generator and could draw overlapping sequences. In practice, many researchers assign a distinct seed to each condition, for example `set.seed(123 + i)` for condition `i`, and let the repetitions within that condition draw sequentially from it. This keeps every condition reproducible and might not be a problem for most studies (given the properties of the default algorithm, i.e., Mersenne-Twister), but it does not by itself *guarantee* that the random sequences of different conditions never overlap. The recommended solution is to assign separate, non-overlapping random number streams ([Morris et al., 2019](#); [Siepe et al., 2024](#)). R offers several packages for this ([Gaujoux, 2025](#); [Leydold, 2022](#); [R Core Team, 2023](#)), and we illustrate the approach with {doRNG}, which implements streams for {foreach} through the `%dorng%` operator (Listing 10). From a single master seed set before the loop, {doRNG} derives one independent stream per iteration in advance, before any work is dispatched. Each stream is bound to the iteration index rather than to a worker, so iteration seven always draws from stream seven no

Listing 18 Storing and restoring the generator state to reproduce one condition-repetition cell

```

# fix the starting position once
set.seed(123)

# 4 conditions, 1000 repetitions per condition
conditions <- expand.grid(n = c(50, 100), gamma2 = c(0, 0.3))
nsim <- 1000

# one slot per condition-repetition cell
states <- matrix(list(), nrow(conditions), nsim)
results <- matrix(NA_real_, nrow(conditions), nsim)

# nested loops shown for illustration
for (cond in seq_len(nrow(conditions))) {
  for (r in seq_len(nsim)) {
    # state at the start of cell (cond, r)
    states[[cond, r]] <- .Random.seed
    # data generation advances the state
    x <- rnorm(conditions$n[cond])
    results[cond, r] <- mean(x)
  }
}

# later, reproduce repetition 3 of condition 2 on its own
.Random.seed <- states[[2, 3]]
identical(mean(rnorm(conditions$n[2])), results[2, 3]) # TRUE

```

matter which core executes it. The number of cores (`ncore` in our script) changes only how iterations are scheduled in time, never which stream each one receives. A collaborator who reruns the study on four cores therefore reproduces data generated on twenty cores exactly. Moreover, because `{doRNG}` records the stream it assigned to each iteration in the `rng` attribute of the result, these states can be stored and later restored to reproduce the data of any single repetition within a condition in isolation, which the per-condition seed alone cannot do (Listing 19).

Because R's random-number generation can change across versions, pinning the R version with `{rix}` keeps it fixed, so the same seed reproduces the same draws across machines and over time.

Listing 19 Reproducible parallel streams with {doRNG}

```

library(doRNG)

# makes the streams below reproducible
set.seed(123)

# one slot per condition
rng_states <- vector("list", nrow(designs))

# nested loop over conditions
for (k in seq_len(nrow(designs))) {
  res <- foreach(
    i = seq_len(nsim),
    .packages = c("marginaleffects", "rvinecopulib")
  ) %dorng% {
    run_one_rep(designs$n[k], designs$gamma2[k])
  }
  # per-repetition stream states for this condition
  rng_states[[k]] <- attr(res, "rng")
  all_results[[k]] <- do.call(rbind, res)
}

# later, reproduce repetition 10 of condition 3 on its own
RNGkind("L'Ecuyer-CMRG")
.Random.seed <- rng_states[[3]][[10]]
rep10 <- run_one_rep(designs$n[3], designs$gamma2[3])

```

Workflow Orchestration: {targets} and {rixpress}

Complex simulation studies often benefit from workflow orchestration that track dependencies between computational steps, cache intermediate results, and enable selective re-execution when inputs change. Two complementary approaches exist within the Nix ecosystem.

Using {targets} Within Nix. The {targets} package ([Landau, 2021](#)) provides workflow orchestration for R-based projects. To integrate {targets} with Nix, include targets in the `r_pkgs` parameter of `rix()` and execute the pipeline within `nix-shell` using `Rscript -e 'targets::tar_make()'`. A shell hook can also be added via the `shell_hook` argument to run the pipeline automatically when entering the Nix shell. This approach is ideal for projects that

remain within R and do not require different environments for different pipeline steps (see {rix} documentation: <https://docs.ropensci.org/rix/articles/reproducible-pipelines.html>).

Using {rixpress} for Multi-Language Pipelines. The {rixpress} package (Rodrigues, 2025), a sister package to {rix}, uses Nix itself as the build automation tool rather than operating within a Nix environment. Each pipeline step becomes a Nix derivation, built in isolation with automatic caching based on content. The key advantage emerges in multi-language workflows: different steps can execute in different Nix-defined environments (e.g., one step using a specific version of R, another using Python, another using Julia). The interface, inspired by {targets}, uses functions like `rxp_r()`, `rxp_py()`, and `rxp_jl()` to define pipeline steps (see {rixpress} documentation: <https://docs.ropensci.org/rixpress/articles/intro-concepts.html>). The GitHub repository for this article directs interested readers to a demonstration of {rixpress} applied to this entire project.

Multi-Language Environment Support

While this tutorial focuses on R, researchers working across multiple programming languages can include Python or Julia in their environments. The `py_conf` parameter accepts a list specifying a Python version and required packages (Listing 20). Similarly, `jl_conf` enables Julia package installation. This capability is particularly useful, for example, for projects requiring statistical computing in R alongside machine learning pipelines in Python or numerical optimization in Julia (Rodrigues & Baumann, 2025) (see {rix} documentation for more: <https://docs.ropensci.org/rix/articles/installing-r-packages.html>).

Listing 20 Including Python packages

```
py_conf = list(py_version = "3.12", py_pkgs = c("polars", "pandas"))
```

Converting Existing {renv} Projects

Researchers with existing {renv} projects can migrate using the `renv2nix()` function, which reads an `renv.lock` file and generates an equivalent Nix expression. This is particularly

valuable for projects where {renv} encountered system dependency issues or where stricter reproducibility guarantees are desired. Unlike {renv}, which captures R package versions but not the R interpreter or system-level libraries, Nix manages all layers of the software stack (see {rix} documentation: <https://docs.ropensci.org/rix/articles/renv2nix.html>).

Containerization with Docker

Nix and Docker are not necessarily mutually exclusive (Rodrigues & Baumann, 2026). Researchers already using Docker do not need to abandon it to benefit from Nix, as the two can be combined by using Nix inside Docker containers to handle environment setup (Rodrigues & Baumann, 2025). This is particularly useful for deployment to cloud platforms or high-performance computing clusters where Docker is standard but Nix may not be available. In that case, the environment is built with Nix but shipped inside a Docker image, so it can be run with Docker alone on machines where Nix is not installed (see {rix} documentation: <https://docs.ropensci.org/rix/articles/nix-inside-docker.html>).

Discussion

Reproducibility in computational research is often treated as a matter of transparency: making data and code available. This tutorial has argued that transparency alone is insufficient without the ability to reliably reconstruct the computational environments in which analyses are executed. For simulation studies in particular, where results depend critically on software versions, system-level libraries, and random number generation, environment-level reproducibility is not optional but essential.

By introducing Nix and the {rix} package, we demonstrated a practical and accessible approach to fully specifying and rebuilding computational environments for simulation-based research. This approach greatly increases the chances that analyses and manuscripts can be reproduced across machines and over time, moving reproducibility from an aspirational goal toward a verifiable property of the research workflow.

Importantly, adopting environment reproducibility does not require abandoning existing analytic practices. Nix is agnostic to programming language, editor, workflow structure, and

manuscript template, allowing researchers to retain familiar tools while strengthening the reliability of their work. In this sense, reproducible environments serve as enabling infrastructure—supporting, rather than replacing, other best practices such as version control, workflow orchestration, and transparent reporting.

If reproducibility is to function as a cornerstone of cumulative science, then the ability to reconstruct computational environments must become a routine part of methodological practice. Tools such as Nix and {rix} lower the barrier to achieving this goal, making fully reproducible simulation research feasible without requiring deep systems expertise. We hope this tutorial helps normalize environment-level reproducibility as a standard component of rigorous computational research in psychology and beyond.

References

- Adler, J. (2012). *R in a nutshell* (2nd ed.). O'Reilly Media.
- Arel-Bundock, V., Greifer, N., & Heiss, A. (2024). How to interpret statistical models using `marginalEffects` for R and Python. *Journal of Statistical Software*, 111(9), 1–32.
<https://doi.org/10.18637/jss.v111.i09>
- Baker, D. H., Berg, M., Hansford, K., Quinn, B., Segala, F., & Warden-English, E. (2024). ReproduceMe: Lessons from a pilot project on computational reproducibility. *Meta-Psychology*, 8, MP.2023.4021. <https://doi.org/10.15626/MP.2023.4021>
- Boettiger, C. (2015). An introduction to Docker for reproducible research. *ACM SIGOPS Operating Systems Review*, 49(1), 71–79. <https://doi.org/10.1145/2723872.2723882>
- Boettiger, C., & Eddelbuettel, D. (2017). An introduction to Rocker: Docker containers for R. *The R Journal*, 9(2), 527–536. <https://doi.org/10.32614/RJ-2017-065>
- Bouma, A., Assen, M. A. L. M. van, Aert, R. C. M. van, & Voncken, L. (2026). Reporting practices, open science practices, and trustworthiness of simulation studies in psychology: A questionnaire study. *Advances in Methods and Practices in Psychological Science*.
- Brodeur, A., Mikola, D., Cook, N., Fiala, L., Brailey, T., Briggs, R., Gendre, A. de, Dupraz, Y., Gabani, J., Gauriot, R., Haddad, J., Lima, G., Ankel-Peters, J., Dreber, A., Campbell, D., Kattan, L., Marino Fages, D., Mierisch, F., Sun, P., ... Strobel, S. (2026). Reproducibility and robustness of economics and political science research. *Nature*, 652(8108), 151–156.
<https://doi.org/10.1038/s41586-026-10251-x>
- Corporation, M., & Weston, S. (2022). *doParallel: Foreach parallel adaptor for the 'parallel' package*. <https://CRAN.R-project.org/package=doParallel>
- Dolstra, E., De Jonge, M., & Visser, E. (2004). Nix: A safe and policy-free system for software deployment. *18th Large Installation System Administration Conference*, 79–92.
- Epskamp, S. (2019). Reproducibility and replicability in a fast-paced methodological world. *Advances in Methods and Practices in Psychological Science*, 2(2), 145–155.
<https://doi.org/10.1177/2515245919847421>

Feldman, S. I. (1979). Make — a program for maintaining computer programs. *Software:*

Practice and Experience, 9(4), 255–265. <https://doi.org/10.1002/spe.4380090402>

Gaujoux, R. (2025). *doRNG: Generic reproducible parallel backend for 'foreach' loops*.

<https://CRAN.R-project.org/package=doRNG>

Glatard, T., Lewis, L. B., Ferreira da Silva, R., Adalat, R., Beck, N., Lepage, C., Rioux, P.,

Rousseau, M.-É., Sherif, T., Deelman, E., Khalili-Mahani, N., & Evans, A. C. (2015).

Reproducibility of neuroimaging analyses across operating systems. *Frontiers in*

Neuroinformatics, 9, 12. <https://doi.org/10.3389/fninf.2015.00012>

Hardwicke, T. E., Wallach, J. D., Kidwell, M. C., Bendixen, T., Crüwell, S., & Ioannidis, J. P. A.

(2020). An empirical assessment of transparency and reproducibility-related research

practices in the social sciences (2014–2017). *Royal Society Open Science*, 7(2), 190806.

<https://doi.org/10.1098/rsos.190806>

Hodges, C. B., Stone, B. M., Johnson, P. K., Carter, J. H., III, Sawyers, C. K., Roby, P. R., &

Lindsey, H. M. (2023). Researcher degrees of freedom in statistical software contribute to

unreliable results: A comparison of nonparametric analyses conducted in SPSS, SAS, Stata,

and R. *Behavior Research Methods*, 55(6), 2813–2837.

<https://doi.org/10.3758/s13428-022-01932-2>

Joshi, M., & Pustejovsky, J. (2025). *Simhelpers: Helper functions for simulation studies*.

<https://CRAN.R-project.org/package=simhelpers>

Kidwell, M. C., Lazarević, L. B., Baranski, E., Hardwicke, T. E., Piechowski, S., Falkenberg,

L.-S., Kennett, C., Slowik, A., Sonnleitner, C., Hess-Holden, C., Errington, T. M., Fiedler, S.,

& Nosek, B. A. (2016). Badges to acknowledge open practices: A simple, low-cost, effective

method for increasing transparency. *PLOS Biology*, 14(5), e1002456.

<https://doi.org/10.1371/journal.pbio.1002456>

Lamb, C., & Zacchiroli, S. (2022). Reproducible builds: Increasing the integrity of software

supply chains. *IEEE Software*, 39(2), 62–70. <https://doi.org/10.1109/ms.2021.3073045>

Landau, W. M. (2021). *Targets: Dynamic function-oriented make-like declarative workflows*.

- Levenstein, M. C., & Lyle, J. A. (2018). Data: Sharing is caring. *Advances in Methods and Practices in Psychological Science*, 1(1), 95–103.
- Leydold, J. (2022). *Rstream: Streams of random numbers*.
<https://CRAN.R-project.org/package=rstream>
- Luijken, K., Lohmann, A., Alter, U., Claramunt Gonzalez, J., Clouth, F. J., Fossum, J. L., Heslen, L., Huizing, A. H. J., Ketelaar, J., Montoya, A. K., Nab, L., Nijman, R. C. C., Penning de Vries, B. B. L., Tibbe, T. D., Wang, Y. A., & Groenwold, R. H. H. (2024). Replicability of simulation studies for the investigation of statistical methods: The RepliSims project. *Royal Society Open Science*, 11(1), 231003. <https://doi.org/10.1098/rsos.231003>
- Malka, J., Zacchiroli, S., & Zimmermann, T. (2026). Docker does not guarantee reproducibility. *arXiv Preprint arXiv:2601.12811*. <https://arxiv.org/abs/2601.12811>
- Montoya, A. K., & Anderson, S. F. (2026). Repeatability in monte carlo simulation studies. *Advances in Methods and Practices in Psychological Science*.
- Morris, T. P., White, I. R., & Crowther, M. J. (2019). Using simulation studies to evaluate statistical methods. *Statistics in Medicine*, 38(11), 2074–2102.
<https://doi.org/10.1002/sim.8086>
- Nagler, T., & Vatter, T. (2025). *Rvinecopulib: High performance algorithms for vine copula modeling*. <https://CRAN.R-project.org/package=rvinecopulib>
- Nosek, B. A., Alter, G., Banks, G. C., Borsboom, D., Bowman, S. D., Breckler, S. J., Buck, S., Chambers, C. D., Chin, G., Christensen, G., Contestabile, M., Dafoe, A., Eich, E., Freese, J., Glennerster, R., Goroff, D., Green, D. P., Hesse, B., Humphreys, M., ... Yarkoni, T. (2015). Promoting an open research culture. *Science*, 348(6242), 1422–1425.
<https://doi.org/10.1126/science.aab2374>
- Nosek, B. A., Hardwicke, T. E., Moshontz, H., Allard, A., Corker, K. S., Dreber, A., Fidler, F., Hilgard, J., Kline Struhl, M., Nuijten, M. B., Rohrer, J. M., Romero, F., Scheel, A. M., Scherer, L. D., Schönbrodt, F. D., & Vazire, S. (2022). Replicability, robustness, and reproducibility in psychological science. *Annual Review of Psychology*, 73, 719–748.

<https://doi.org/10.1146/annurev-psych-020821-114157>

Ottoboni, K., & Stark, P. B. (2018). *Random problems with r*. <https://arxiv.org/abs/1809.06520>

Pawel, S., Bartoš, F., Siepe, B. S., & Lohmann, A. (2025). Handling missingness, failures, and non-convergence in simulation studies: A review of current practices and recommendations. *The American Statistician*, 1–18. <https://doi.org/10.1080/00031305.2025.2540002>

Pawel, S., Kook, L., & Reeve, K. (2024). Pitfalls and potentials in simulation studies: Questionable research practices in comparative simulation studies allow for spurious claims of superiority of any method. *Biometrical Journal*, 66(1), 2200091. <https://doi.org/10.1002/bimj.202200091>

Peikert, A., & Brandmaier, A. M. (2021). A reproducible data analysis workflow. *Quantitative and Computational Methods in Behavioral Sciences*, 1, e3763. <https://doi.org/10.5964/qcmb.3763>

Peikert, A., van Lissa, C. J., & Brandmaier, A. M. (2021). Reproducible research in R: A tutorial on how to do the same thing more than once. *Psych*, 3(4), 836–867. <https://doi.org/10.3390/psych3040053>

Peng, R. D. (2011). Reproducible research in computational science. *Science*, 334(6060), 1226–1227.

R Core Team. (2023). *R: A language and environment for statistical computing*. R Foundation for Statistical Computing. <https://www.R-project.org/>

R Core Team. (2025). *R installation and administration*. R Foundation for Statistical Computing. <https://cran.r-project.org/doc/manuals/r-release/R-admin.html>

Rodrigues, B. (2023). *Building reproducible analytical pipelines with R*. <https://raps-with-r.dev>

Rodrigues, B. (2025). *Rixpress: Build reproducible analytical pipelines with 'nix'*. <https://CRAN.R-project.org/package=rixpress>

Rodrigues, B., & Baumann, P. (2025). *Rix: Reproducible data science environments with 'nix'*. <https://CRAN.R-project.org/package=rix>

Rodrigues, B., & Baumann, P. (2026). *Nix for polyglot, reproducible data science workflows* (Version v0.0.1). Zenodo. <https://doi.org/10.5281/zenodo.18138618>

Schneider, W. J. (2024). *Apaquarto* [Computer software]. <https://github.com/wjschne/apaquarto>

Siepe, B. S., Bartoš, F., Morris, T. P., Boulesteix, A.-L., Heck, D. W., & Pawel, S. (2024).

Simulation studies for methodological research in psychology: A standardized template for planning, preregistration, and reporting. *Psychological Methods*.

<https://doi.org/10.1037/met0000695>

Simonsohn, U. (2020). *Groundhog: Version-control for CRAN, github, and gitlab packages*.

Ushey, K. (2024). *Renv: Project environments*.

van Lissa, C. J., Brandmaier, A. M., Brinkman, L., Lamprecht, A.-L., Peikert, A., Struiksma, M.

E., & Vreede, B. M. I. (2021). WORCS: A workflow for open reproducible code in science.

Data Science, 4(1), 29–49. <https://doi.org/10.3233/DS-210031>

Vazire, S. (2018). Implications of the credibility revolution for productivity, creativity, and progress. *Perspectives on Psychological Science*, 13(4), 411–417.

<https://doi.org/10.1177/1745691617751884>

White, I. R., Pham, T. M., Quartagno, M., & Morris, T. P. (2024). How to check a simulation study. *International Journal of Epidemiology*, 53(1), dyad134.

<https://doi.org/10.1093/ije/dyad134>

Wickham, H. (2016). *ggplot2: Elegant graphics for data analysis*. Springer-Verlag New York.

<https://ggplot2.tidyverse.org>

Wickham, H., François, R., Henry, L., Müller, K., & Vaughan, D. (2023). *Dplyr: A grammar of data manipulation*. <https://CRAN.R-project.org/package=dplyr>

Wiebels, K., & Moreau, D. (2021). Leveraging containers for reproducible psychological research. *Advances in Methods and Practices in Psychological Science*, 4(2).

<https://doi.org/10.1177/25152459211017853>

Wilke, C. O. (2025). *Cowplot: Streamlined plot theme and plot annotations for 'ggplot2'*.

<https://wilkelab.org/cowplot/>

Ziemann, M., Poulain, P., & Bora, A. (2023). The five pillars of computational reproducibility: Bioinformatics and beyond. *Briefings in Bioinformatics*, 24(6), bbad375.

<https://doi.org/10.1093/bib/bbad375>

Table 1*Glossary of computing terms used in the main text.*

Term	Definition
Operating system	The base software (e.g., Windows, macOS, Linux) that manages a computer's hardware and on which every other program runs. R, its packages, and system-level libraries all sit on top of it.
System-level libraries	Shared operating-system software that R packages depend on (e.g., BLAS/LAPACK, C++ backends). These are not installed by <code>install.packages()</code> .
Software stack	The complete set of software layers an analysis depends on: the operating system, system-level libraries, the R interpreter, and the R packages built on top of them.
R interpreter	The R program that reads and runs your R code (Adler, 2012). Two machines can report the same R version yet have interpreters compiled differently or linked against different system-level libraries (see R Core Team, 2025, Section A.3).
Workflow orchestration	Automating the order of analysis steps and re-running only those affected by a change.
Literate programming	Writing an analysis as a single document that combines narrative text and executable code (e.g., R Markdown or Quarto), so the report and the code that produces it stay together.
Containerization	An isolated, lightweight, shareable bundle of software and its dependencies (e.g., Docker) (Wiebels & Moreau, 2021).
Mutable upstream repositories	The external sources a build pulls from (e.g., base images or package repositories) can change, or even disappear, over time without the build instructions changing, so the same instructions may later produce a different result or fail to build (Malka et al., 2026).
Functional programming language	A language built around pure functions, immutability, and explicit inputs, so the same inputs always produce the same output.
Binary cache	A server that stores prebuilt packages, so Nix can download a finished copy instead of compiling it from source.

Table 2

Performance metrics for ACE estimator across simulation conditions. Values in parentheses are Monte Carlo standard errors (MCSE).

Sample Size	Confounding	Relative Bias	Relative RMSE	Coverage	CI Width
50	none	0.957 (0.042)	0.422 (0.035)	0.910 (0.029)	0.224 (0.004)
100	none	1.013 (0.026)	0.256 (0.020)	0.930 (0.026)	0.159 (0.002)
2000	none	0.997 (0.006)	0.059 (0.005)	0.960 (0.020)	0.036 (0.000)
50	mild	1.173 (0.036)	0.395 (0.034)	0.890 (0.031)	0.222 (0.004)
100	mild	1.157 (0.028)	0.318 (0.026)	0.870 (0.034)	0.154 (0.002)
2000	mild	1.114 (0.006)	0.130 (0.006)	0.510 (0.050)	0.035 (0.000)
50	severe	1.200 (0.044)	0.482 (0.054)	0.870 (0.034)	0.223 (0.005)
100	severe	1.235 (0.030)	0.379 (0.027)	0.830 (0.038)	0.157 (0.002)
2000	severe	1.257 (0.007)	0.266 (0.007)	0.020 (0.014)	0.035 (0.000)

Figure 1

The computational environment as a set of nested layers, based on Peikert & Brandmaier (2021).





Figure 2

Performance of ACE estimator across sample sizes and confounding severity. Panel A shows relative bias, Panel B shows relative RMSE, Panel C shows coverage probability of 95% confidence intervals (dashed line at nominal 0.95 level), and Panel D shows average confidence interval width. Results demonstrate that model misspecification induces systematic bias that persists across sample sizes, while increasing sample size improves precision but not accuracy under misspecification.



Appendix A

Simulation Study Design

Here we present a rather short description following recommendations from previous research, but ideally even more may be reported (Morris et al., 2019; Pawel et al., 2025; Siepe et al., 2024; White et al., 2024). This mimics a methods or similar section in articles.

Factorial Design. The simulation employs a full factorial design with two factors: sample size ($n \in \{50, 100, 2000\}$) and degree of confounding non-linearity ($\gamma_2 \in \{0, 0.3, 0.8\}$, labeled as none, mild, and severe). The parameter γ_2 controls the strength of the quadratic confounder effect on the outcome (see Data Generation). This yields nine conditions, each replicated $K = 100$ times.

Data Generation. For each replication, data are generated following a causal structure where a confounder X_2 affects both treatment assignment and the outcome. The confounder and treatment error term are generated using the {rvinecopulib} package: pairs (U_1, U_2) are drawn from an independence copula via `rbicop()`, then transformed to standard normals via $X_2 = \Phi^{-1}(U_1)$ and $\epsilon = \Phi^{-1}(U_2)$. The independence copula is simply $C(u, v) = uv$, meaning the resulting uniforms are independent—mathematically equivalent to calling `rnorm()` directly. We use {rvinecopulib} intentionally because it depends on C++ libraries.

Treatment assignment follows $X_1 = \alpha_0 + \alpha_1 X_2 + \alpha_2 X_2^2 + \epsilon$ where $\alpha_0 = 0$, $\alpha_1 = 0.5$, and $\alpha_2 = 0.2$. This creates confounding because X_2 influences treatment assignment through both linear and quadratic terms. The binary outcome is generated from the true logistic regression model:

$$\text{logit}(P(Y = 1 \mid X_1, X_2)) = \beta_0 + \beta_1 X_1 + \gamma_1 X_2 + \gamma_2 X_2^2$$

with parameters $\beta_0 = -0.5$, $\beta_1 = 0.7$ (the causal effect of interest), $\gamma_1 = -0.4$, and γ_2 varying by condition. The analyst misspecifies the outcome model by omitting the quadratic confounder term, fitting instead:

$$\text{logit}(P(Y = 1 \mid X_1, X_2)) = \beta_0 + \beta_1 X_1 + \gamma_1 X_2$$

This misspecification creates residual confounding because the omitted term $\gamma_2 X_2^2$ is

correlated with X_1 (since X_1 depends on both X_2 and X_2^2), violating the conditional exchangeability assumption given linear adjustment alone.

Estimand. The target estimand is the average causal effect (ACE) of X_1 on Y , properly adjusted for confounding:

$$\text{ACE}(X_1) = \mathbb{E} \left[\frac{\partial P(Y = 1 \mid X_1, X_2)}{\partial X_1} \right] = \mathbb{E} \left[\beta_1 \cdot \frac{\exp(\eta)}{(1 + \exp(\eta))^2} \right]$$

where $\eta = \beta_0 + \beta_1 X_1 + \gamma_1 X_2 + \gamma_2 X_2^2$ is the correctly specified linear predictor, and the expectation is taken over the joint distribution of (X_1, X_2) . For each γ_2 condition, the “true” ACE (denoted θ) is approximated once using a very large sample ($N = 200,000$) with the correctly specified model including X_2^2 .

Estimator. The causal effect is estimated from the misspecified model (omitting X_2^2) as:

$$\widehat{\text{ACE}}(X_1) = \frac{1}{n} \sum_{i=1}^n \tilde{\beta}_1 \cdot \frac{\exp(\tilde{\eta}_i)}{(1 + \exp(\tilde{\eta}_i))^2}$$

where $\tilde{\eta}_i = \tilde{\beta}_0 + \tilde{\beta}_1 X_{i1} + \tilde{\gamma}_1 X_{i2}$ and $\tilde{\beta} = (\tilde{\beta}_0, \tilde{\beta}_1, \tilde{\gamma}_1)$ are maximum likelihood estimates from the misspecified logistic regression.

Performance Criteria. Table B1 presents the performance criteria used to evaluate the ACE estimator across simulation conditions.

Computational Details. The simulation was conducted on a MacBook Pro (Apple M4 Pro Chip), running macOS Sequoia 15.7.3. All analyses were performed in R (version 4.5.2). Parallel processing was implemented through the {doParallel} package [version 1.0.17; Corporation and Weston (2022)], with {doRNG} [version 1.8.6.2; Gaujoux (2025)] to ensure independent and reproducible random number streams. For data generation we used the {rvinecopulib} package [version 0.7.3.1.0; Nagler and Vatter (2025)]. The estimator was implemented using the {marginaleffects} package [version 0.31.0; Arel-Bundock et al. (2024)]. Data wrangling was performed with {dplyr} [version 1.1.4; Wickham et al. (2023)]. Method performance was assessed through multiple metrics following the formulas from the {simhelpers}

package [version 0.3.1; Joshi and Pustejovsky (2025)]. Figures were produced with {ggplot2} [version 4.0.1; Wickham (2016)] and {cowplot} [version 1.2.0; Wilke (2025)].

Appendix B

Clarifying the packages used

R Packages

Reproducibility Infrastructure

rix: Generates the Nix expression (`default.nix`) for reproducible environments.

Simulation Study

These packages are used in the `Simulation/` folder:

rvinecopulib (used in `01_data_generation.R`): Generates correlated data via copulas using the `rbicop()` function.

marginaleffects (used in `02_models.R`): Computes average causal effects via the `avg_slopes()` function.

doParallel (used in `03_run_simulation.R`): Enables parallel foreach loops across CPU cores.

doRNG (used in `03_run_simulation.R`): Makes parallel RNG reproducible.

simhelpers (used in `04_performance_metrics.R`): Calculates bias, RMSE, and coverage metrics.

ggplot2 (used in `05_plots.R`): Creates simulation result visualizations.

cowplot (used in `05_plots.R`): Combines plots with `plot_grid()` and extracts legends.

dplyr (used in `article.qmd`): Data wrangling for results reported in [Table 2](#).

Dynamic Document Generation

quarto: R interface to invoke Quarto rendering.

knitr: Executes R code chunks in `.qmd` files.

svglite: SVG graphics device; `apaquarto` sets `dev: svglite` for HTML output.

LaTeX Packages

Required by apaquarto Extension

These are loaded in `apaquarto's header.tex` or `apatemplate.tex`:

amsmath: Math environments (align, equation, etc.).

threeparttablex: Tables with notes below (APA table format).

tcolorbox: Callout boxes (note, warning, tip blocks).

fontawesome5: Icons in callouts.

multirow: Table cells spanning multiple rows.

newtx: Times-like fonts (default when no custom mainfont).

geometry: Page margins.

Dependencies of apaquarto Packages

environ: Dependency of tcolorbox.

pdfcol: Dependency of tcolorbox.

tikzfill: Dependency of tcolorbox.

fontaxes: Dependency of newtx.

xstring: Template conditionals.

scalerel: Dependency of apa7 class.

Required by apa7 Document Class

apa7: The document class itself (\documentclass{apa7}).

endfloat: Moves floats to end of document in manuscript mode.

threeparttable: Dependency for threeparttablex.

Required by Quarto PDF Rendering

framed: Shaded/framed regions for callouts.

fvextra: Enhanced verbatim for syntax-highlighted code blocks.

fancyvrb: Verbatim environments for code display.

setspace: Line spacing; also used in article.qmd for single-spaced code blocks.

anyfontsize: Arbitrary font sizes in code blocks.

Additional Packages

ninecolors: Extended color palettes.

wrapfig: Text wrapping around figures.

tabularray: Modern table typesetting.

siunitx: SI units and number formatting.

Table B1

Performance criteria for evaluating the ACE estimator. $\hat{\theta}_k$ denotes the ACE estimate from replication k (for $k = 1, \dots, K$), where $K = 1000$ is the number of replications, and θ denotes the true ACE for a given condition. For coverage and width criteria, A_k and B_k denote the lower and upper endpoints of the 95% confidence interval from replication k , $W_k = B_k - A_k$ is the interval width, c_β is the estimated coverage probability, and $I(\cdot)$ is an indicator function equaling 1 if the condition is true and 0 otherwise. The Monte Carlo standard error (MCSE) quantifies the simulation uncertainty in each performance measure estimate

Criterion	Estimate	MCSE
Bias	$\frac{1}{K} \sum_{k=1}^K \hat{\theta}_k - \theta$	$\sqrt{\frac{1}{K(K-1)} \sum_{k=1}^K (\hat{\theta}_k - \bar{\hat{\theta}})^2}$
Variance	$\frac{1}{K-1} \sum_{k=1}^K (\hat{\theta}_k - \bar{\hat{\theta}})^2$	$\sqrt{\frac{K-1}{K} \cdot \frac{1}{K-1} \sum_{k=1}^K (\hat{\theta}_k - \bar{\hat{\theta}})^2}$
RMSE	$\sqrt{\frac{1}{K} \sum_{k=1}^K (\hat{\theta}_k - \theta)^2}$	$\sqrt{\frac{K-1}{K} \sum_{j=1}^K \left(\sqrt{(\hat{\theta}_j - \theta)^2} - \overline{RMSE} \right)^2}$
Relative Bias	$\frac{1}{\theta K} \sum_{k=1}^K \hat{\theta}_k$	$\frac{1}{\theta} \sqrt{\frac{1}{K(K-1)} \sum_{k=1}^K (\hat{\theta}_k - \bar{\hat{\theta}})^2}$
Relative RMSE	$\frac{1}{\theta} \sqrt{\frac{1}{K} \sum_{k=1}^K (\hat{\theta}_k - \theta)^2}$	$\frac{1}{\theta} \sqrt{\frac{K-1}{K} \sum_{j=1}^K \left(\sqrt{(\hat{\theta}_j - \theta)^2} - \overline{RMSE} \right)^2}$
Coverage	$\frac{1}{K} \sum_{k=1}^K I(A_k \leq \theta \leq B_k)$	$\sqrt{\frac{c_\beta(1-c_\beta)}{K}}$
Width	$\frac{1}{K} \sum_{k=1}^K (B_k - A_k)$	$\sqrt{\frac{1}{K(K-1)} \sum_{k=1}^K (W_k - \bar{W})^2}$