




Reference & picture: Michael A Nielsen and Isaac Chuang. Quantum computation and quantum information, 2002.

**Step 1**. Use Hadamad gate to create superposition




**Step 2**. Use Controlled-U gate to move the eigenvalue from register2 to register1







- $\therefore$  The target qubit  $|u\rangle$  does not change, but the control qubit  $|1\rangle$  changes, which is contrary to the ordinary situation.
- : We move the eigenvalue  $e^{2\pi i \varphi}$  from the  $|u\rangle$  space to the  $|1\rangle$  space.
- $U^{2^n}$  denotes by the controlled-U gate, which can be implemented by:



PS. The gate on the right-hand side is the controlled phase gate, which is specified in **Step.3**.

**Step 3**. Use inverse quantum Fourier trasnform to move the phase information from the probability amplitude to the quantum bases






For inverse quantum Fourier trnasform 
$$(|j\rangle \to \frac{1}{2^{\frac{n}{2}}} \sum_{k=0}^{2^{n}-1} e^{-2\pi i j k/2^{n}} |k\rangle)$$
, the gate  $R_k^{-1}$  denotes the controlled phase gate  $R_k^{-1} \equiv \begin{bmatrix} 1 & 0 \\ 0 & e^{-\frac{2\pi i}{k}} \end{bmatrix}$ .

**Picture:** https://www.qtumist.com/info/PE-H5/index.html

### Introduction to quantum Fourier transform

This slide is not part of the quantum phase estimation algorithm, but just to compare iQFT and QFT.




Quantum Fourier transform circuit

PS. For quantum Fourier transform 
$$(|j\rangle \to \frac{1}{\frac{n}{2^2}} \sum_{k=0}^{2^{n}-1} e^{2\pi i j k/2^n} |k\rangle)$$
, the gate  $R_k$  denotes the controlled phase gate  $R_k \equiv \begin{bmatrix} 1 & 0 \\ 0 & e^{\frac{2\pi i}{k}} \end{bmatrix}$ ;

**Picture:** https://www.wikiwand.com/en/Quantum\_Fourier\_transform

#### **Step 4**. Measurement

If U is an exact binary fraction, we can measure its phase with probability 1; Otherwise, we can measure it with a very high probability close to 1.



After divide the measuring result of register1 (binary string  $\psi_1\psi_2\cdots\psi_t$ ) by  $2^t$ , we can get the phase  $\varphi=0.\psi_1\psi_2\cdots\psi_t$ . e.g. Our result for measuring the register1 is 0001 (t=4). After divided by  $2^4$ , we get the answer 0.0001, which in decimal is 1/16. Thus the phase is 1/16.