

ChatGPT 4o

ChatGPT

GPTs erkunden

Heute

GCD Calculation in R

GCD Calculation in R

GCD Calculation in R

Juli

Bedürfnisse in der Karriere

AI in Education Research Paper

Mai

Hectic Meeting with Youngsters

Masterarbeitsthema Diskussion Teil

Stay in Baril

StratDiag & Tech: Structuring

New Apollo Software Packages

Dictionary Encoding in Databases

April

Committees Relevant in Ambition

Update Dictionary and Vectors

SQL CRUD with Dictionary-Encoding

Neuer Chat

Team-Arbeitsbereich hinzufügen

Mit einem Teamtarif...

Consider the following programming problem:

Given two positive integers A and B,  
find GCD of A and B.

Please provide a solution for this problem in the R language.

Certainly! Here's a solution to find the Greatest Common Divisor (GCD) of two positive integers A and B using the Euclidean algorithm in R:

```
r
# Function to calculate GCD of two numbers
gcd <- function(A, B) {
  while (B != 0) {
    temp <- B
    B <- A %% B
    A <- temp
  }
  return(A)
}

# Example usage:
A <- 56
B <- 98

result <- gcd(A, B)
cat("The GCD of", A, "and", B, "is:", result, "\n")
```

Explanation:

- The function `gcd` takes two arguments `A` and `B`.
- It repeatedly applies the Euclidean algorithm, where the GCD of two numbers can be calculated by repeatedly replacing the larger number by the remainder of the division of the two numbers.
- The loop continues until `B` becomes zero, at which point `A` holds the GCD.
- The example usage shows how to use the function with two numbers, 56 and 98.

You can replace the values of `A` and `B` with any two positive integers to compute their GCD.

🔍 📄 🔄 🗑️ 🌟 ⌵

🗣️

ChatGPT kann Fehler machen. Überprüfe wichtige Informationen.

