

I'm trying to understand a given program for a Python programming problem. Can you help by explaining a specific part of this program? Below I first provide the problem description, then the program, and then a specific part of this program.

Given two positive integers A and B, find GCD of A and B.

Program:

```
def find_gcd(A, B):
    while B != 0:
        temp = B
        B = A % B
        A = temp
    return A

def main():
    A = 56
    B = 98

    gcd = find_gcd(A, B)

    print(f"GCD of {A} and {B} is: {gcd}")

if __name__ == "__main__":
    main()
```

Specific part:

```
while B != 0:
    temp = B
    B = A % B
    A = temp
```

Can you provide a detailed explanation about the specific part above in the context of the whole program?

Vorschläge anzeigen

I'd be glad to provide a detailed explanation of the specific part of the Python program you've shared:

Specific part:

```
Python

while B != 0:
    temp = B
    B = A % B
    A = temp
```

Verwende den Code [mit Vorsicht](#)

Explanation:

This code block implements the **Euclidean algorithm**, a classic method for finding the greatest common divisor (GCD) of two positive integers. Here's a breakdown of what each line does:

- `while B != 0:` : This loop continues as long as `B` is not equal to 0. It's the core of the algorithm.
- `temp = B:` : This line temporarily stores the value of `B` in a variable `temp`. This is crucial for the subsequent calculations.
- `B = A % B:` : This line calculates the remainder of `A` divided by `B` and assigns it to `B`. This remainder is essentially the "leftover" after dividing `A` by `B`.
- `A = temp:` : This line assigns the value stored in `temp` (which was originally `B`) to `A`. This effectively swaps the values of `A` and `B`.

Overall logic:

The Euclidean algorithm works based on the following principle:

- If `B` is 0, then `A` is the GCD.
- Otherwise, the GCD of `A` and `B` is the same as the GCD of `B` and the remainder of `A` divided by `B`.

The loop repeatedly calculates the remainder and swaps the values until `B` becomes 0. At that point, `A` holds the GCD.

In the context of the entire program:

This specific part is essential for calculating the GCD of the two input numbers `A` and `B`. The `find_gcd` function encapsulates this algorithm and returns the calculated GCD. The `main` function then calls this function with the given input values and prints the result.

👍 🗨️ ⚙️ ⏪ 🌐 ⋮

Prompt hier eingeben

📄 🔊