

 ChatGPT 88 GPTs erkunden

Python GCD Calculation GCD Calculation in Python

Python GCD Function

Bedürfnisse in der Karriere Al in Education Research Paper

Hectic Meeting with Youngsters Masterarbeitsthema Diskussion Ter Stay in Bari!

StratDiag & Tech: Structuring New Apollo Software Packages

Dictionary Encoding in Databases

Committees Relevant in Ambition. Update Dictionary and Vectors

SQL CRUD with Dictionary-Encodir

Neuer Chat

Consider the following programming problem: Given two positive integers A and B, find GCD of A and B. Please provide a solution for this problem in the Python language.

You can find the Greatest Common Divisor (GCD) of two positive integers using the Euclidean algorithm. Here's a Python function that implements this approach:

```
def gcd(a, b):
    while b:
       a, b = b, a % b
   return a
A = 60
B = 48
print("GCD of", A, "and", B, "is", gcd(A, B))
```

Explanation:

- The function `gcd(a, b)` computes the GCD of `a` and `b` using the Euclidean algorithm.
- The Euclidean algorithm works on the principle that the GCD of two numbers `a` and `b` is the same as the GCD of `b` and `a % b` (where `%` is the modulus operator).
- . The process is repeated until 'b' becomes 0. At this point, 'a' contains the GCD of the original pair of numbers.

Example:

For `A = 60` and `B = 48`:

- First iteration: `a = 60`, `b = 48`. `a % b = 60 % 48 = 12`
- Second iteration: `a = 48`, `b = 12`. `a % b = 48 % 12 = 0`
- Third iteration: `a = 12`, `b = 0`. The loop ends, and `a` (which is 12) is the GCD.

The output will be:



This function is efficient and works even for very large integers.

⊕ □ □ □ □ □ ▼ ∨

Team-Arbeitsbereich hinzufügen

Sende eine Nachricht an ChatGPT

ChatGPT kann Fehler machen. Überprüfe wichtige Informationen.