



# Backd contest Findings & Analysis Report

2022-06-02

## Table of contents

- [Overview](#)
  - [About C4](#)
  - [Wardens](#)
- [Summary](#)
- [Scope](#)
- [Severity Criteria](#)
- [High Risk Findings \(3\)](#)
  - [\[H-01\] User can steal all rewards due to checkpoint after transfer](#)
  - [\[H-02\] function `lockFunds` in `TopUpActionLibrary` can cause serious fund lose. fee and Capped bypass. It's not calling `stakerVault.increaseActionLockedBalance` when transfers stakes.](#)
  - [\[H-03\] Customers cannot be `topUp\(\)` ed a second time](#)
- [Medium Risk Findings \(15\)](#)
  - [\[M-01\] `call\(\)` should be used instead of `transfer\(\)` on an `address payable`](#)
  - [\[M-02\] Its possible to lose total governance control by mistake](#)

- [M-03] Lack of `safeApprove(0)` prevents some registrations, and the changing of stakers and LP tokens
- [M-04] `CvxCrvRewardsLocker` implements a swap without a slippage check that can result in a loss of funds through MEV
- [M-05] Chainlink's `latestRoundData` might return stale or incorrect results
- [M-06] ERC777 tokens can bypass `depositCap` guard
- [M-07] Inconsistency between constructor and setting method for `slippageTolerance`
- [M-08] `_decimalMultiplier` doesn't account for tokens with decimals higher than 18
- [M-09] `getNewCurrentFees` reverts when `minFeePercentage > feeRatio`
- [M-10] Griefer can extend period of higher withdrawal fees
- [M-11] Position owner should set allowed slippage
- [M-12] `CompoundHandler#topUp()` Using the wrong function selector makes native token `topUp()` always revert
- [M-13] `CEthInterface#repayBorrowBehalf()` reading non-existing returns makes `_repayAnyDebt()` with CEther always revert
- [M-14] `CEthInterface#mint()` reading non-existing returns makes `topUp()` with native token always revert
- [M-15] Malicious Stakers can grief Keepers
- Low Risk and Non-Critical Issues
  - L-01 The first withdrawal for each vault from the vault reserve has no delay
  - L-02 `AaveHandler` does not extend `BaseHandler`
  - L-03 Unused `receive()` function will lock Ether in contract
  - L-04 Front-runable initializer
  - L-05 `safeApprove()` is deprecated

- [L-06 Missing checks for `address\(0x0\)` when assigning values to `address` state variables](#)
- [L-07 `abi.encodePacked\(\)` should not be used with dynamic types when passing the result to a hash function such as `keccak256\(\)`](#)
- [L-08 `address.call{value:x}\(\)` should be used instead of `payable.transfer\(\)`](#)
- [L-09 Upgradeable contract is missing a `\_\_gap\[50\]` storage variable to allow for new storage variables in later versions](#)
- [L-10 Math library unnecessarily overflows during some operations](#)
- [N-01 `\_prepareDeadline\(\)`, `\_setConfig\(\)`, and `\_executeDeadline\(\)` should be `private`](#)
- [N-02 Open TODOs](#)
- [N-03 `payable` function does not reject payments to ERC20 tokens](#)
- [N-04 Adding a `return` statement when the function defines a named return variable, is redundant](#)
- [N-05 `public` functions not called by the contract should be declared `external` instead](#)
- [N-06 `constant` s should be defined rather than using magic numbers](#)
- [N-07 Large multiples of ten should use scientific notation \(e.g. `1e6`\) rather than decimal literals \(e.g. `1000000`\), for readability](#)
- [N-08 Use a more recent version of solidity](#)
- [N-09 Constant redefined elsewhere](#)
- [N-10 Inconsistent spacing in comments](#)
- [N-11 Typos](#)
- [N-12 File is missing `NatSpec`](#)
- [N-13 `NatSpec` is incomplete](#)
- [N-14 Event is missing `indexed` fields](#)
- [Gas Optimizations](#)
  - [G-01 Caching storage variables in memory to save gas](#)

- [G-02 Calldata instead of memory for RO function parameters](#)
- [G-03 Comparisons with zero for unsigned integers](#)
- [G-04 Comparison Operators](#)
- [G-05 Custom Errors](#)
- [G-06 Default value initialization](#)
- [G-07 Prefix increments](#)
- [G-08 Redundant code](#)
- [G-09 Require instead of &&](#)
- [G-10 Tight Variable Packing](#)
- [G-11 Unchecked arithmetic](#)
- [Disclosures](#)



## Overview



## About C4

Code4rena (C4) is an open organization consisting of security researchers, auditors, developers, and individuals with domain expertise in smart contracts.

A C4 audit contest is an event in which community participants, referred to as Wardens, review, audit, or analyze smart contract logic in exchange for a bounty provided by sponsoring projects.

During the audit contest outlined in this document, C4 conducted an analysis of the Backd smart contract system written in Solidity. The audit contest took place between April 21—April 27 2022.



## Wardens

62 Wardens contributed reports to the Backd contest:

1. unforgiven
2. llllllll
3. [WatchPug](#)

4. OxDjango
5. [shenwilly](#)
6. [sseefried](#)
7. Ox52
8. [Ruhum](#)
9. [fatherOfBlocks](#)
10. [wuwe1](#)
11. [defsec](#)
12. [Dravee](#)
13. horsefacts
14. joestakey
15. [pauliax](#)
16. StyxRave
17. [rayn](#)
18. hubble (ksk2345 and shri4net)
19. robee
20. [antonttc](#)
21. [Tomio](#)
22. [csanuragjain](#)
23. TrungOre
24. sorrynotsorry
25. [catchup](#)
26. Oxkatana
27. reassor
28. [berndartmueller](#)
29. kenta
30. [securerodd](#)
31. gs8nrv
32. hake

- 33. [z3s](#)
- 34. [Ov3rf10w](#)
- 35. [Funen](#)
- 36. TerrierLover
- 37. oyc\_109
- 38. simon135
- 39. [Tadashi](#)
- 40. dipp
- 41. kebabsec (okkothejawa and [FlameHorizon](#))
- 42. peritoflores
- 43. jayjonah8
- 44. [Kenshin](#)
- 45. [m4rio\\_eth](#)
- 46. remora
- 47. [MaratCerby](#)
- 48. 0x1f8b
- 49. cccz
- 50. hyh
- 51. slywaters
- 52. 0x4non
- 53. [0xNazgul](#)
- 54. NoamYakov
- 55. [rfa](#)
- 56. saian
- 57. 0xmint
- 58. tin537
- 59. [danb](#)
- 60. UnusualTurtle

This contest was judged by [gzeon](#). The judge also competed in the contest as a warden, but forfeited their winnings.

Final report assembled by [liveactionllama](#).



## Summary

The C4 analysis yielded an aggregated total of 18 unique vulnerabilities. Of these vulnerabilities, 3 received a risk rating in the category of HIGH severity and 15 received a risk rating in the category of MEDIUM severity.

Additionally, C4 analysis included 39 reports detailing issues with a risk rating of LOW severity or non-critical. There were also 35 reports recommending gas optimizations.

All of the issues presented here are linked back to their original finding.



## Scope

The code under review can be found within the [C4 Backd contest repository](#), and is composed of 38 smart contracts written in the Solidity programming language and includes 4,630 lines of Solidity code.



## Severity Criteria

C4 assesses the severity of disclosed vulnerabilities according to a methodology based on [OWASP standards](#).

Vulnerabilities are divided into three primary risk categories: high, medium, and low/non-critical.

High-level considerations for vulnerabilities span the following key areas when conducting assessments:

- Malicious Input Handling
- Escalation of privileges
- Arithmetic
- Gas use

Further information regarding the severity criteria referenced throughout the submission review process, please refer to the documentation provided on [the C4 website](#).



## High Risk Findings (3)



### [H-01] User can steal all rewards due to checkpoint after transfer

*Submitted by OxDjango, also found by unforgiven*

#### [StakerVault.sol#L112-L119](#)

I believe this to be a high severity vulnerability that is potentially included in the currently deployed `StakerVault.sol` contract also. The team will be contacted immediately following the submission of this report.

In `StakerVault.sol`, the user checkpoints occur AFTER the balances are updated in the `transfer()` function. The user checkpoints update the amount of rewards claimable by the user. Since their rewards will be updated after transfer, a user can send funds between their own accounts and repeatedly claim maximum rewards since the pool's inception.

In every actionable function except `transfer()` of `StakerVault.sol`, a call to `ILpGauge(lpGauge).userCheckpoint()` is correctly made BEFORE the action effects.



### Proof of Concept

Assume a certain period of time has passed since the pool's inception. For easy accounting, assume `poolStakedIntegral` of `LpGauge.sol` equals 1. The `poolStakedIntegral` is used to keep track of the current reward rate.

Steps:

- Account A stakes 1000 LP tokens. `balances[A] += 1000`



- In the same `stakeFor()` function, `userCheckpoint()` was already called so A will already have `perUserShare[A]` set correctly based on their previously O balance and the current `poolStakedIntegral`.
- Account A can immediately send all balance to Account B via `transfer()`.
- Since the checkpoint occurs after the transfer, B's balance will increase and then `perUserShare[B]` will be updated. The calculation for `perUserShare` looks as follows.

```
perUserShare[user] += (
    (stakerVault.stakedAndActionLockedBalanceOf(user)) *
    (poolStakedIntegral_ - perUserStakedIntegral[user]
    )
);
```

Assuming Account B is new to the protocol, their `perUserStakedIntegral[user]` will default to 0.

$$\text{perUserShare[B]} += 1000 * (1 - 0) = 1000$$

- B is able to call `claimRewards()` and mint all 1000 reward tokens.
- B then calls `transfer()` and sends all 1000 staked tokens to Account C.
- Same calculation occurs, and C can claim all 1000 reward tokens.
- This process can be repeated until the contract is drained of reward tokens.



## Recommended Mitigation Steps

In `StakerVault.transfer()`, move the call to

`ILpGauge(lpGauge).userCheckpoint()` to before the balances are updated.

[chase-manning \(Backd\) confirmed and resolved](#)



**[H-02] function `lockFunds` in `TopUpActionLibrary` can cause serious fund lose. fee and Capped bypass. It's not**

**calling** `stakerVault.increaseActionLockedBalance` **when**  
**transfers stakes.**

*Submitted by unforgiven*

### [TopUpAction.sol#L57-L65](#)

In function `TopUpActionLibrary.lockFunds` when transfers stakes from payer it doesn't call `stakerVault.increaseActionLockedBalance` for that payer so `stakerVault.actionLockedBalances[payer]` is not get updated for payer and `stakerVault.stakedAndActionLockedBalanceOf(payer)` is going to show wrong value and any calculation based on this function is gonna be wrong which will cause fund lose and theft and some restriction bypasses.



### Proof of Concept

When user wants to create a `TopUpAction`. so he deposit his funds to Pool and get LP token. then stake the LP token in `StakerVault` and use that stakes to create a `TopUp` position with function `TopUpAction.register`. This function transfer user stakes (locks user staks) and create his position.

For transferring and locking user stakes it uses `TopUpActionLibrary.lockFunds`. function `lockFunds` transfers user stakes but don't call `stakerVault.increaseActionLockedBalance` for the payer which cause that `stakerVault.actionLockedBalances[payer]` to get different values(not equal to `position.depositTokenBalance`).

Function `StakerVault.stakedAndActionLockedBalanceOf(account)` uses `stakerVault.actionLockedBalances[account]` so it will return wrong value and any where in code that uses `stakedAndActionLockedBalanceOf()` is going to cause problems.

three part of the codes uses `stakerVault.stakedAndActionLockedBalanceOf()`:

1. `LiquidityPool.depositFor()` for checking user total deposits to be less than `depositCap`.
2. `LiquidityPool._updateUserFeesOnDeposit()` for updating user fee on new deposits.

3. `userCheckpoint()` for calculating user rewards.

attacker can use #1 and #2 to bypass high fee payment and max depositCap and #3 will cause users to lose rewards.

The detail steps:

1- user deposit fund to Pool and get LP token.

2- user stakes LP token in StakerVault.

3- user approve `TopUpAction` address to transfer his staks in StakerVault.

3- user use all his stakes to create a position with `TopUpAction.register()` function.

3.1- `register()` will call `lockFunds` to transfer and lock user stakes.

3.2- `lockFunds()` will transfer user stakes with `stakerVault.transferFrom()` but don't call `stakerVault.increaseActionLockedBalance()` so

`StakerVault.actionLockedBalances[user]` will be zero.

3.3- `StakerVault.balance[user]` will be zero too because his stakes get transfers in 3.2

4- `StakerVault.stakedAndActionLockedBalanceOf(user)` will return zero (user has some locked stakes in `TopUpAction` but because of the bug calculation get out of sync)

In this moment user will lose all the rewards that are minted in `LpGauge`. because `userCheckpoint()` use `stakerVault.stakedAndActionLockedBalanceOf(user)` for calculating rewards which is zero and new rewards will be zero too.

Attacker can use this process to bypass "max deposit Cap" and deposit any amount of assets he wants. because `LiquidityPool.depositFor(address,uint256,uint256)` uses `stakedAndActionLockedBalanceOf` to check user deposits which is zero so Attacker can deposit & stake & register to make his balance zero and repeat this and in the end reset his `TopUp` positions to get back his large stakes which are multiple time bigger than "max deposit Cap"

Attacker can also use this process to bypass fee penalties for early withdraw. because `LiquidityPool._updateUserFeesOnDeposit()` to get user current balance use `stakedAndActionLockedBalanceOf()` which is zero. so the value of `shareExisting` variable become zero and `newFeeRatio` will be calculated based on `feeOnDeposit` which can be `minFee` if asset is already in wallet for some time.



Tools Used

VIM



## Recommended Mitigation Steps

Add this line to `TopUpActionLibrary.lockFunds()` after `stakerVault.transferFrom()`:

```
stakerVault.increaseActionLockedBalance(payer, amountLeft);
```

[chase-manning \(Backd\) confirmed and resolved](#)



**[H-03] Customers cannot be `topUp()` ed a second time**

*Submitted by llllll*

[CompoundHandler.sol#L71](#)

[CompoundHandler.sol#L120](#)

[AaveHandler.sol#L53](#)

[TopUpAction.sol#L847](#)

OpenZeppelin's `safeApprove()` will revert if the account already is approved and the new `safeApprove()` is done with a non-zero value.

```
function safeApprove(
    IERC20 token,
    address spender,
    uint256 value
) internal {
    // safeApprove should only be called when setting an initial
    // or when resetting it to zero. To increase and decrease it
    // 'safeIncreaseAllowance' and 'safeDecreaseAllowance'
    require(
        (value == 0) || (token.allowance(address(this), spender)
        "SafeERC20: approve from non-zero to non-zero allowance"
    );
    _callOptionalReturn(token, abi.encodeWithSelector(token.appro
}
```

[OpenZeppelin/SafeERC20.sol#L45-L58](#)



Impact

Customers cannot be topped up a second time, which will cause them to be liquidated even though they think they're protected.



## Proof of Concept

There are multiple places where `safeApprove()` is called a second time without setting the value to zero first. The instances below are all related to topping up.

Compound-specific top-ups will fail the second time around when approving the `ctoken` again:

File: `backd/contracts/actions/topup/handlers/CompoundHandler.sol`

```
50     function topUp(  
51         bytes32 account,  
52         address underlying,  
53         uint256 amount,  
54         bytes memory extra  
55     ) external override returns (bool) {  
56         bool repayDebt = abi.decode(extra, (bool));  
57         CToken ctoken = cTokenRegistry.fetchCToken(underlying);  
58         uint256 initialTokens = ctoken.balanceOf(address(this));  
59  
60         address addr = account.addr();  
61  
62         if (repayDebt) {  
63             amount -= _repayAnyDebt(addr, underlying, amount);  
64             if (amount == 0) return true;  
65         }  
66  
67         uint256 err;  
68         if (underlying == address(0)) {  
69             err = ctoken.mint{value: amount}(amount);  
70         } else {  
71             IERC20(underlying).safeApprove(address(ctoken),
```

## [CompoundHandler.sol#L50-L71](#)

Compound-specific top-ups will also fail when trying to repay debt:

File: `backd/contracts/actions/topup/handlers/CompoundHandler.sol`

```

62         if (repayDebt) {
63             amount -= _repayAnyDebt(addr, underlying, amount)
64             if (amount == 0) return true;
65         }

```

## [CompoundHandler.sol#L62-L65](#)

Aave-specific top-ups will fail for the `lendingPool` :

File: `backd/contracts/actions/topup/handlers/AaveHandler.sol` #

```

36     function topUp(
37         bytes32 account,
38         address underlying,
39         uint256 amount,
40         bytes memory extra
41     ) external override returns (bool) {
42         bool repayDebt = abi.decode(extra, (bool));
43         if (underlying == address(0)) {
44             weth.deposit{value: amount}();
45             underlying = address(weth);
46         }
47
48         address addr = account.addr();
49
50         DataTypes.ReserveData memory reserve = lendingPool.
51             require(reserve.aTokenAddress != address(0), Error.
52
53         IERC20(underlying).safeApprove(address(lendingPool)

```

## [AaveHandler.sol#L36-L53](#)

The `TopUpAction` itself fails for the `feeHandler` :

File: `backd/contracts/actions/topup/TopUpAction.sol` #4

```

840     function _payFees(
841         address payer,
842         address beneficiary,
843         uint256 feeAmount,

```

```

844         address depositToken
845     ) internal {
846         address feeHandler = getFeeHandler();
847         IERC20(depositToken).safeApprove(feeHandler, feeAn

```

## [TopUpAction.sol#L840-L847](#)

I've filed the other less-severe instances as a separate medium-severity issue, and flagged the remaining low-severity instances in my QA report.



### Recommended Mitigation Steps

Always do `safeApprove(0)` if the allowance is being changed, or use `safeIncreaseAllowance()`.

## [chase-manning \(Backd\) confirmed and resolved](#)



### Medium Risk Findings (15)



**[M-01]** `call()` should be used instead of `transfer()` on an address payable

*Submitted by Dravee, also found by antonttc, berndartmueller, cccz, danb, horsefacts, hyh, llllll, MaratCerby, pauliax, rayn, UnusualTurtle, WatchPug, and wuwe1*

This is a classic Code4rena issue:

- <https://github.com/code-423n4/2021-04-meebits-findings/issues/2>
- <https://github.com/code-423n4/2021-10-tally-findings/issues/20>
- <https://github.com/code-423n4/2022-01-openleverage-findings/issues/75>



### Impact

The use of the deprecated `transfer()` function for an address will inevitably make the transaction fail when:

1. The claimer smart contract does not implement a payable function.
2. The claimer smart contract does implement a payable fallback which uses more than 2300 gas unit.
3. The claimer smart contract implements a payable fallback function that needs less than 2300 gas units but is called through proxy, raising the call's gas usage above 2300.

Additionally, using higher than 2300 gas might be mandatory for some multisig wallets.



### Impacted lines:

```
backd/contracts/pool/EthPool.sol:
30:         to.transfer(amount);
```

```
backd/contracts/strategies/BkdEthCvx.sol:
77:         payable(vault).transfer(amount);
93:         payable(vault).transfer(amount);
117:        payable(vault).transfer(underlyingBalance);
```

```
backd/contracts/vault/EthVault.sol:
29:         payable(to).transfer(amount);
37:         payable(addressProvider.getTreasury()).transfer(an
```

```
backd/contracts/vault/VaultReserve.sol:
81:         payable(msg.sender).transfer(amount);
```



### Recommended Mitigation

I recommend using `call()` instead of `transfer()`.

[chase-manning \(Backd\) confirmed and resolved](#)

[gzeon \(judge\) commented:](#)

| Sponsor confirmed. Judging this as Medium Risk.





# [M-02] Its possible to lose total governance control by mistake

*Submitted by hubble, also found by antonttc, csanuragjain, gs8nrv, rayn, reassor, and TrungOre*

[RoleManager.sol#L43-L46](#)

[RoleManager.sol#L115-L128](#)

The impact of this vulnerability, i.e., losing all governance control is very High. There is a possibility, due to a corner case as described below.



## Proof of Concept

Contract : RoleManager.sol

Function : renounceGovernance()

Step 0:

Let current governance role given to = CURRENT\_GOV\_ADDRESS  
so, getRoleMemberCount() for "governance" role will return

Step 1: Add a new address say ALICE to governance role, by ac  
now, ALICE also has governace role, and getRoleMemberCount()

Step 2: Assume that ALICE renounces governance role, by renou  
now, ALICE does not have governance role, but getRoleMember

Step 3: In some distant future, if there is a compromise of C  
its decided to revoke governance role for CURRENT\_GOV\_ADDRE  
It can be assumed that since getRoleMemberCount() for "gove  
But now, CURRENT\_GOV\_ADDRESS does not have governance role,



## Recommended Mitigation Steps

getRoleMemberCount() currently returns \_roleMembers[role].length();

It should return the count only for \_roles[role].members[account] = true;

Its recommended to add a new function to know who are the active members for any role,

like getRoleMembers(bytes32 role) returning address account.

[chase-manning \(Backd\) confirmed](#)

[gzeon \(judge\) decreased severity to Medium](#)



[M-03] Lack of `safeApprove(0)` prevents some registrations, and the changing of stakers and LP tokens

*Submitted by llllll, also found by defsec and Dravee*

[TopUpAction.sol#L50](#)

[LiquidityPool.sol#L721](#)

OpenZeppelin's `safeApprove()` will revert if the account already is approved and the new `safeApprove()` is done with a non-zero value

```
function safeApprove(
    IERC20 token,
    address spender,
    uint256 value
) internal {
    // safeApprove should only be called when setting an initial allowance
    // or when resetting it to zero. To increase and decrease allowance
    // 'safeIncreaseAllowance' and 'safeDecreaseAllowance'
    require(
        (value == 0) || (token.allowance(address(this), spender) < value),
        "SafeERC20: approve from non-zero to non-zero allowance"
    );
    _callOptionalReturn(token, abi.encodeWithSelector(token.approve.selector,
    spender, value));
}
```

[OpenZeppelin/SafeERC20.sol#L45-L58](#)



## Impact

Customers can be prevented from `register()` ing the same

`token / stakerVaultAddress` as another customer; and once changed away from, stakers and lptokens can't be used in the future.



## Proof of Concept

There are multiple places where `safeApprove()` is called a second time without setting the value to zero first.

`register()` calls `lockFunds()` for each user registration, and since users will use the same tokens and staker vaults, the second user's `register()` call will fail:

```
File: backd/contracts/actions/topup/TopUpAction.sol    #1

36     function lockFunds(
37         address stakerVaultAddress,
38         address payer,
39         address token,
40         uint256 lockAmount,
41         uint256 depositAmount
42     ) external {
43         uint256 amountLeft = lockAmount;
44         IStakerVault stakerVault = IStakerVault(stakerVault
45
46         // stake deposit amount
47         if (depositAmount > 0) {
48             depositAmount = depositAmount > amountLeft ? an
49             IERC20(token).safeTransferFrom(payer, address(t
50             IERC20(token).safeApprove(stakerVaultAddress, c
```

### [TopUpAction.sol#L36-L50](#)

The changing of either the staker or an lp token is behind a time-lock, and once the time has passed, the changed variables rely on this function:

```
File: backd/contracts/pool/LiquidityPool.sol    #2

717     function _approveStakerVaultSpendingLpTokens() interna
718         address staker_ = address(staker);
719         address lpToken_ = address(lpToken);
720         if (staker_ == address(0) || lpToken_ == address(0
721             IERC20(lpToken_).safeApprove(staker_, type(uint256
722     }
```

If a bug is found in a new `staker` or `lpToken` and the governor wishes to change back to the old one(s), the governor will have to wait for the time-lock delay only to find out that the old value(s) cause the code to revert.

I've filed the other more-severe instances as a separate high-severity issue, and flagged the remaining low-severity instances in my QA report.



### Recommended Mitigation Steps

Always do `safeApprove(0)` if the allowance is being changed, or use `safeIncreaseAllowance()`.

[chase-manning \(Backd\) confirmed](#)

[samwerner \(Backd\) commented:](#)

It should be noted that the second example referring to `_approveStakerVaultSpendingLpTokens()` is not an issue. This is neither a member variable that can be updated nor is it behind a time lock. Both the `staker` and `lpToken` can only be set once and hence the `safeApprove` in the aforementioned function can only be called once.

[chase-manning \(Backd\) resolved](#) resolved



**[M-04]** `CvxCrvRewardsLocker` implements a swap without a slippage check that can result in a loss of funds through MEV

*Submitted by Ruhum*

The `CvxCrvRewardsLocker` contract swaps tokens through the CRV `cvxCRV` pool. But, it doesn't use any slippage checks. The swap is at risk of being frontrun / sandwiched which will result in a loss of funds.

Since MEV is very prominent I think the chance of that happening is pretty high.



## Proof of Concept

Here's the swap: [CvxCrvRewardsLocker.sol#L247-L252](#).



## Recommended Mitigation Steps

Use a proper value for `minOut` instead of `0`.

[chase-manning \(Backd\) confirmed](#)

[gzeon \(judge\) decreased severity to Medium and commented:](#)

According to [C4 Judging criteria](#):

Unless there is something uniquely novel created by combining vectors, most submissions regarding vulnerabilities that are inherent to a particular system or the Ethereum network as a whole should be considered QA. Examples of such vulnerabilities include front running, sandwich attacks, and MEV.

However since there is a configurable `minOut` that is deliberately set to 0, this seems to be a valid issue. I am judging this as Medium Risk.



## [M-05] Chainlink's `latestRoundData` might return stale or incorrect results

*Submitted by cccz, also found by 0x1f8b, 0xDjango, Oxxatana, berndartmueller, defsec, Dravee, horsefacts, hyh, llllll, kenta, rayn, reassor, sorrynotsorry, and WatchPug*

On `ChainlinkOracleProvider.sol` and `ChainlinkUsdWrapper.sol`, we are using `latestRoundData`, but there is no check if the return value indicates stale data.

```
function _ethPrice() private view returns (int256) {
    (, int256 answer, , , ) = _ethOracle.latestRoundData();
    return answer;
}
```

...

```
function getPriceUSD(address asset) public view override returns (int256) {
    address feed = feeds[asset];
```

```

require(feed != address(0), Error.ASSET_NOT_SUPPORTED);

(, int256 answer, , uint256 updatedAt, ) = AggregatorV2V3Interface(feed).latestRoundData();

require(block.timestamp <= updatedAt + stalePriceDelay,
require(answer >= 0, Error.NEGATIVE_PRICE);

uint256 price = uint256(answer);
uint8 decimals = AggregatorV2V3Interface(feed).decimals;
return price.scaleFrom(decimals);
}

```

This could lead to stale prices according to the Chainlink documentation:

<https://docs.chain.link/docs/historical-price-data/#historical-rounds>

<https://docs.chain.link/docs/faq/#how-can-i-check-if-the-answer-to-a-round-is-being-carried-over-from-a-previous-round>



## Proof of Concept

[ChainlinkOracleProvider.sol#L55](#)

[ChainlinkUsdWrapper.sol#L64](#)



## Recommended Mitigation Steps

```

function _ethPrice() private view returns (int256) {
    (uint80 roundID, int256 answer, , uint256 timestamp, uint8 decimals) = AggregatorV2V3Interface(feed).latestRoundData();
    require(answeredInRound >= roundID, "Stale price");
    require(timestamp != 0, "Round not complete");
    require(answer > 0, "Chainlink answer reporting 0");
    return answer;
}

```

...

```

function getPriceUSD(address asset) public view override returns (int256) {
    address feed = feeds[asset];
    require(feed != address(0), Error.ASSET_NOT_SUPPORTED);
    (uint80 roundID, int256 answer, , uint256 updatedAt, uint8 decimals) = AggregatorV2V3Interface(feed).latestRoundData();
    require(answeredInRound >= roundID, "Stale price");
    require(answer > 0, "Error.NEGATIVE_PRICE");
    require(block.timestamp <= updatedAt + stalePriceDelay, "Stale price");

    uint256 price = uint256(answer);
    return price.scaleFrom(decimals);
}

```

```
uint8 decimals = AggregatorV2V3Interface(feed).decimals;  
return price.scaleFrom(decimals);  
}
```

[chase-manning \(Backd\) confirmed and resolved](#)



## [M-06] ERC777 tokens can bypass `depositCap` guard

*Submitted by shenwilly, also found by wuwe1*

[LiquidityPool.sol#L523](#)

When ERC777 token is used as the underlying token for a `LiquidityPool`, a depositor can reenter `depositFor` and bypass the `depositCap` requirement check, resulting in higher total deposit than intended by governance.



### Proof of Concept

- An empty ERC777 liquidity pool is capped at 1.000 token.
- Alice deposits 1.000 token. Before the token is actually sent to the contract, `tokensToSend` ERC777 hook is called and Alice reenters `depositFor`.
- As the previous deposit hasn't been taken into account, the reentrancy passes the `depositCap` check.
- Pool has 2.000 token now, despite the 1.000 deposit cap.



### Recommended Mitigation Steps

Add reentrancy guards to `depositFor`.

[chase-manning \(Backd\) confirmed and resolved](#)



## [M-07] Inconsistency between constructor and setting method for `slippageTolerance`

*Submitted by fatherOfBlocks, also found by shenwilly*

[StrategySwapper.sol#L38-L43](#)

[StrategySwapper.sol#L109-L114](#)

In the `setSlippageTolerance(L119)` method you have certain requirements to set `slippageTolerance`, but in the constructor you don't.



### Recommended Mitigation Steps

I would add the corresponding validations to the constructor.

[chase-manning \(Backd\) confirmed and resolved](#)



## [M-08] `_decimalMultiplier` doesn't account for tokens with decimals higher than 18

*Submitted by shenwilly, also found by pauliax, StyxRave, and WatchPug*

[StrategySwapper.sol#L287-L289](#)

[StrategySwapper.sol#L318-L320](#)

[StrategySwapper.sol#L335-L337](#)

In `StrategySwapper`, swapping from or to tokens with decimals higher than 18 will always revert. This will cause inabilities for strategies to harvest rewards.



### Proof of Concept

[L288](#) will revert when `token_` has higher than 18 decimals.

```
return 10**(18 - IERC20Full(token_).decimals());
```



### Recommended Mitigation Steps

Consider modifying how `_decimalMultiplier` works so it could handle tokens with higher than 18 decimals.

Update the calculation of `_minTokenAmountOut` and `_minWethAmountOut` to account when decimals are higher/lower than 18.





## [M-09] `getNewCurrentFees` reverts when

`minFeePercentage > feeRatio`

*Submitted by shenwilly*

### [LiquidityPool.sol#L694](#)

Depositors won't be able to transfer or redeem funds temporarily.

The problem is caused by the implementation of

`LiquidityPool.getNewCurrentFees`:

```
function getNewCurrentFees(
    uint256 timeToWait,
    uint256 lastActionTimestamp,
    uint256 feeRatio
) public view returns (uint256) {
    uint256 timeElapsed = _getTime() - lastActionTimestamp;
    uint256 minFeePercentage = getMinWithdrawalFee();
    if (timeElapsed >= timeToWait) {
        return minFeePercentage;
    }
    uint256 elapsedShare = timeElapsed.scaledDiv(timeToWait);
    return feeRatio - (feeRatio - minFeePercentage).scaledMul(el
```

The last line requires the current `feeRatio` to be higher than `minFeePercentage` or the function will revert. When this condition is broken, some critical functions such as transferring tokens and redeeming will be unusable. Affected users need to wait until enough time has elapsed and `getNewCurrentFees` returns `minFeePercentage` on [L691](#).

This could happen if governance changes the `MinWithdrawalFee` to be higher than a user's `feeRatio`.



## Proof of Concept

- Initial `MinWithdrawalFee` is set to 0, `MaxWithdrawalFee` is set to `0.03e18`.
- Alice deposits fund and receives LP token. Alice's `feeRatio` is now set to `0.03e18` (the current `MaxWithdrawalFee`).
- Governance changes `MaxWithdrawalFee` to `0.05e18` and `MinWithdrawalFee` to `0.04e18`.
- `minFeePercentage` is now higher than Alice's `feeRatio` and she can't transfer nor redeem the LP token until `timeElapsed >= timeToWait`.



## Recommended Mitigation Steps

Add a new condition in `getNewCurrentFees` [L690](#) to account for this case:

```
if (timeElapsed >= timeToWait || minFeePercentage > feeRatio) {  
    return minFeePercentage;  
}
```

[chase-manning \(Backd\) confirmed and resolved](#)



## [M-10] Griefer can extend period of higher withdrawal fees

*Submitted by OxDjango*

### [LiquidityPool.sol#L790-L792](#)

The `_updateUserFeesOnDeposit()` function in `LiquidityPool.sol` is used to update a user's withdrawal fees after an action such as deposit, transfer in, etc. The withdrawal fee decays toward a minimum withdrawal fee over a period of 1 or 2 weeks (discussed with developer). Since anyone can transfer lp tokens to any user, a griever can transfer 1 wei of lp tokens to another user to reset their `lastActionTimestamp` used in the withdrawal fee calculation.

The developers nicely weight the updated withdrawal fee by taking the original balance/original fee vs the added balance/added fee. The attacker will only be able

to extend the runway of the withdrawal fee cooldown by resetting the `lastActionTimestamp` for future calculations. Example below:



## Proof of Concept

Assumptions:

- `MinWithdrawalFee` = 0% //For easy math
- `MaxWithdrawalFee` = 10%
- `timeToWait` = 2 weeks



## Steps

- User A has `100 wei` of shares
- User A waits 1 week (Current withdrawal fee = 5%)
- User B deposits, receives `1 wei` of shares, current withdrawal fee = 10%
- User B immediately transfers `1 wei` of shares to User A

Based on the formula to calculated User A's new `feeRatio`:

```
uint256 newFeeRatio = shareExisting.scaledMul(newCurrentFeeRatio,
shareAdded.scaledMul(feeOnDeposit));
```

In reality, User A's withdrawal fee will only increase by a negligible amount since the shares added were very small in proportion to the original shares. We can assume user A's current withdrawal fee is still 5%.

The issue is that the function then reset's User A's `lastActionTimestamp` to the current time. This means that User A will have to wait the maximum 2 weeks for the withdrawal fee to reduce from 5% to 0%. Effectively the cooldown runway is the same length as the original runway length, so the decay down to 0% will take twice as long.

```
meta.lastActionTimestamp = uint64(_getTime());
```



## Recommended Mitigation Steps

Instead of resetting `lastActionTimestamp` to the current time, scale it the same way the `feeRatio` is scaled. I understand that this would technically not be the timestamp of the last action, so the variable would probably need to be renamed.

[chase-manning \(Backd\) confirmed and resolved](#)



## [M-11] Position owner should set allowed slippage

*Submitted by 0x52*

[TopUpAction.sol#L154](#)

[TopUpAction.sol#L187](#)

The default swap slippage of 5% allows malicious keepers to sandwich attack topup. Additionally, up to 40% (`_MINSWAPPERSLIPPAGE`) slippage allows malicious owner to sandwich huge amounts from topup



## Proof of Concept

Keeper can bundle swaps before and after topup to sandwich topup action, in fact it's actually in their best interest to do so.



## Recommended Mitigation Steps

Allow user to specify max swap slippage when creating topup similar to how it's specified on uniswap or sushiswap to block attacks from both keepers and owners.

[chase-manning \(Backd\) confirmed and resolved](#)

[gzeon \(judge\) commented:](#)

According to [C4 Judging criteria](#)

Unless there is something uniquely novel created by combining vectors, most submissions regarding vulnerabilities that are inherent to a particular system or the Ethereum network as a whole should be considered QA. Examples of such vulnerabilities include front running, sandwich attacks, and MEV.

However since Backd use keeper to run topup transactions, which presumably are bots and smart contracts that can fetch onchain price directly. A large (5% default, up to 40%) seems excessive and can lead to user losing fund. Judging this as Medium Risk.



## [M-12] CompoundHandler#topUp() Using the wrong function selector makes native token topUp() always revert

*Submitted by WatchPug*

### [compound-finance/CEther.sol#L44-L47](#)

```
function mint() external payable {
    (uint err,) = mintInternal(msg.value);
    requireNoError(err, "mint failed");
}
```

mint() for native cToken (CEther) does not have any parameters, as the Function Selector is based on the function name with the parenthesised list of parameter types, when you add a nonexisting parameter, the Function Selector will be incorrect.

### [CTokenInterfaces.sol#L316](#)

```
function mint(uint256 mintAmount) external payable virtual retur
```

The current implementation uses the same CToken interface for both CEther and CErc20 in topUp(), and function mint(uint256 mintAmount) is a nonexisting function for CEther.

As a result, the native token topUp() always revert.

### [CompoundHandler.sol#L57-L70](#)

```
CToken ctoken = cTokenRegistry.fetchCToken(underlying);
```

```

uint256 initialTokens = ctoken.balanceOf(address(this));

address addr = account.addr();

if (repayDebt) {
    amount -= _repayAnyDebt(addr, underlying, amount, ctoken);
    if (amount == 0) return true;
}

uint256 err;
if (underlying == address(0)) {
    err = ctoken.mint{value: amount}(amount);
}

```

See also:

- [Compound's cToken mint doc](#)

[samwerner \(Backd\) confirmed and resolved](#)

🔗

**[M-13] CEthInterface#repayBorrowBehalf() reading non-existing returns makes \_repayAnyDebt() with CEther always revert**

*Submitted by WatchPug*

[CTokenInterfaces.sol#L355-L358](#)

```

function repayBorrowBehalf(address borrower, uint256 repayAmount
    external
    payable
    returns (uint256);

```

`repayBorrowBehalf()` for native `cToken (CEther)` will return nothing, while the current `CEthInterface` interface defines the returns as `(uint256)`.

As a result, `ether.repayBorrowBehalf()` will always revert

## [CompoundHandler.sol#L117-L118](#)

```
CEther cether = CEther(address(ctoken));  
err = cether.repayBorrowBehalf{value: debt}(account);
```

Ref:

method	CEther	CErc20	
mint()	revert	error code	
redeem()	error code	error code	
repayBorrow()	revert	error code	
repayBorrowBehalf()	revert	error code	

- [Compound cToken Repay Borrow Behalf doc](#)
- [Compound CEther.repayBorrowBehalf\(\)](#)
- [Compound CErc20.repayBorrowBehalf\(\)](#)

[chase-manning \(Backd\) confirmed](#)



**[M-14]** CEthInterface#mint() reading non-existing returns  
makes topUp() with native token always revert

*Submitted by WatchPug*

## [CTokenInterfaces.sol#L345](#)

```
function mint() external payable returns (uint256);
```

mint() for native cToken (CEther) will return nothing, while the current  
CEthInterface interface defines the returns as (uint256) .

In the current implementation, the interface for CToken is used for both CEther  
and CErc20.

As a result, the transaction will revert with the error: `function returned an unexpected amount of data` when `topUp()` with the native token (ETH).

[CompoundHandler.sol#L57-L70](#)

```
CToken ctoken = cTokenRegistry.fetchCToken(underlying);
uint256 initialTokens = ctoken.balanceOf(address(this));

address addr = account.addr();

if (repayDebt) {
    amount -= _repayAnyDebt(addr, underlying, amount, ctoken);
    if (amount == 0) return true;
}

uint256 err;
if (underlying == address(0)) {
    err = ctoken.mint{value: amount}(amount);
}
```

Ref:

method	CEther	CErc20	
mint()	revert	error code	
redeem()	error code	error code	
repayBorrow()	revert	error code	
repayBorrowBehalf()	revert	error code	

- [Compound’s cToken mint doc](#)
- [Compound CEther.mint\(\)](#)
- [Compound CErc20.mint\(\)](#)

[chase-manning \(Backd\) confirmed](#)



A Staker — that has their top-up position removed after `execute` is called by a Keeper — can always cause the transaction to revert. They can do this by deploying a smart contract to the `payer` address that has implemented a `receive()` function that calls `revert()`. The revert will be triggered by the following [lines](#) in `execute`

```
if (vars.removePosition) {  
    gasBank.withdrawUnused(payer);  
}
```

This will consume some gas from the keeper while preventing them accruing any rewards for performing the top-up action.



## Proof of Concept

I have implemented a [PoC](#) in a fork of the contest repo. The attacker's contract can be found [here](#).



## Recommend Mitigation Steps

To prevent this denial of service attack some way of blacklisting badly behaved Stakers should be added.

[chase-manning \(Backd\) confirmed](#)



## Low Risk and Non-Critical Issues

For this contest, 39 reports were submitted by wardens detailing low risk and non-critical issues. The [report highlighted below](#) by `IIIIII` received the top score from the judge.

*The following wardens also submitted reports:* [horsefacts](#), [sseefried](#), [robee](#), [defsec](#), [hubble](#), [OxDjango](#), [sorrynotsorry](#), [berndartmueller](#), [Dravee](#), [joestakey](#), [StyxRave](#), [Oxkatana](#), [csanuragjain](#), [dipp](#), [hake](#), [kebabsec](#), [pauliax](#), [peritoflores](#), [securerodd](#), [z3s](#), [Ov3rf10w](#), [Ox52](#), [catchup](#), [fatherOfBlocks](#), [Funen](#), [jayjonah8](#), [Kenshin](#), [kenta](#), [m4rio\\_eth](#), [oyc\\_109](#), [rayn](#), [remora](#), [Ruhum](#), [simon135](#), [Tadashi](#), [TerrierLover](#), [TrungOre](#), and [antonttc](#).

## Vulnerability details:



### [L-01] The first withdrawal for each vault from the vault reserve has no delay

`_lastWithdrawal[vault]` will always be zero for new vaults, so the check is for `0 + minWithdrawalDelay` which will always be less than `block.timestamp`

```
File: backd/contracts/vault/VaultReserve.sol    #1

102     function canWithdraw(address vault) public view returns (
103         return block.timestamp >= _lastWithdrawal[vault] + mi
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/VaultReserve.sol#L102-L103>



### [L-02] AaveHandler **does not extend** BaseHandler

Unlike `CompoundHandler`, `AaveHandler` **does not extend** `BaseHandler`, which will cause storage problems in future versions

```
File: backd/contracts/actions/topup/handlers/AaveHandler.sol    #

15 contract AaveHandler is ITopUpHandler {
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/handlers/AaveHandler.sol#L15>



### [L-03] Unused `receive()` function will lock Ether in contract

If the intention is for the Ether to be used, the function should call another function, otherwise it should revert

```
File: contracts/actions/topup/TopUpAction.sol    #1
```

```
176     receive() external payable {  
177         // solhint-disable-previous-line no-empty-blocks  
178     }
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/TopUpAction.sol#L176-L178>

File: contracts/pool/EthPool.sol #2

```
10     receive() external payable {}
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/pool/EthPool.sol#L10>

File: contracts/strategies/BkdEthCvx.sol #3

```
46     receive() external payable {}
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/BkdEthCvx.sol#L46>

File: contracts/strategies/StrategySwapper.sol #4

```
45     receive() external payable {}
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/StrategySwapper.sol#L45>

File: contracts/vault/EthVault.sol #5

```
13         receive() external payable {}
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/EthVault.sol#L13>



## [L-04] Front-runnable initializer

If the initializer is not executed in the same transaction as the constructor, a malicious user can front-run the `initialize()` call, forcing the contract to be redeployed. Most other initializers in this project are protected, but this one appears not to be.

```
File: backd/contracts/AddressProvider.sol    #1

53     function initialize(address roleManager) external initiali
54         AddressProviderMeta.Meta memory meta = AddressProvider
55         _addressKeyMetas.set(AddressProviderKeys._ROLE_MANAGER
56         _setConfig(AddressProviderKeys._ROLE_MANAGER_KEY, role
57     }
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/AddressProvider.sol#L53-L57>



## [L-05] `safeApprove()` is deprecated

**Deprecated** in favor of `safeIncreaseAllowance()` and `safeDecreaseAllowance()`

See [original submission](#) for instances.



## [L-06] Missing checks for `address(0x0)` when assigning values to address state variables

```
File: contracts/actions/topup/TopUpActionFeeHandler.sol    #1
```

```
55         actionContract = _actionContract;
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/TopUpActionFeeHandler.sol#L55>

```
File: contracts/CvxCrvRewardsLocker.sol    #2
```

```
151         treasury = _treasury;
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/CvxCrvRewardsLocker.sol#L151>

```
File: contracts/StakerVault.sol    #3
```

```
66         token = _token;
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/StakerVault.sol#L66>

```
File: contracts/strategies/ConvexStrategyBase.sol    #4
```

```
100         vault = vault_;
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L100>

```
File: contracts/strategies/ConvexStrategyBase.sol    #5
```

```
101         _strategist = strategist_;
```

<https://github.com/code-423n4/2022-04->

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L101](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L101)

File: `contracts/strategies/ConvexStrategyBase.sol` #6

```
182         communityReserve = _communityReserve;
```

<https://github.com/code-423n4/2022-04->

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L182](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L182)

File: `contracts/strategies/ConvexStrategyBase.sol` #7

```
261         _strategist = strategist_;
```

<https://github.com/code-423n4/2022-04->

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L261](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L261)



**[L-07]** `abi.encodePacked()` should not be used with dynamic types when passing the result to a hash function such as `keccak256()`

Use `abi.encode()` instead which will pad items to 32 bytes, which will **prevent hash collisions** (e.g. `abi.encodePacked(0x123,0x456) ==> 0x123456 ==>`

`abi.encodePacked(0x1,0x23456)` , but `abi.encode(0x123,0x456) ==>`

`0x0...1230...456` ). “Unless there is a compelling reason, `abi.encode` should be preferred”. If there is only one argument to `abi.encodePacked()` it can often be cast to `bytes()` or `bytes32()` **instead**.

File: `contracts/actions/topup/handlers/CTokenRegistry.sol` #1

```
67         keccak256(abi.encodePacked(ctoken.symbol()))
```

<https://github.com/code-423n4/2022-04->

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/handlers/CTokenRegistry.sol#L67](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/handlers/CTokenRegistry.sol#L67)



**[L-08]** `address.call{value:x}()` should be used instead of `payable.transfer()`

The use of `payable.transfer()` is heavily frowned upon because it can lead to the locking of funds. The `transfer()` call requires that the recipient has a `payable` callback, only provides 2300 gas for its operation. This means the following cases can cause the transfer to fail:

- The contract does not have a `payable` callback
- The contract's `payable` callback spends more than 2300 gas (which is only enough to emit something)
- The contract is called through a proxy which itself uses up the 2300 gas

File: `backd/contracts/vault/VaultReserve.sol` #1

```
81 payable(msg.sender).transfer(amount);
```

uses the `onlyVault` modifier, and vaults currently have empty `payable` callbacks, so they don't currently revert <https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/VaultReserve.sol#L81>

File: `backd/contracts/vault/EthVault.sol` #2

```
29 payable(to).transfer(amount);
```

uses the `onlyPoolOrGovernance` modifier, and pools currently have an empty `payable` callback, so they don't currently revert. Governance is currently deployed and not seeing issues, so presumably it also has an empty `payable` callback <https://github.com/code-423n4/2022-04->

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/EthVault.sol#L29](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/EthVault.sol#L29)

```
File: backd/contracts/vault/EthVault.sol    #3
```

```
37         payable(addressProvider.getTreasury()).transfer(amount
```

the treasury is currently deployed and not seeing issues, so presumably it also has an empty payable callback <https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/EthVault.sol#L37>

```
File: backd/contracts/strategies/BkdEthCvx.sol    #4
```

```
77         payable(vault).transfer(amount);
```

vaults currently have an empty payable callback <https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/BkdEthCvx.sol#L77>

```
File: backd/contracts/strategies/BkdEthCvx.sol    #5
```

```
93         payable(vault).transfer(amount);
```

vaults currently have an empty payable callback <https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/BkdEthCvx.sol#L93>

```
File: backd/contracts/strategies/BkdEthCvx.sol    #6
```

```
117        payable(vault).transfer(underlyingBalance);
```



vaults currently have an empty payable callback [https://github.com/code-](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/BkdEthCvx.sol#L117)

[423n4/2022-04-](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/BkdEthCvx.sol#L117)

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/s](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/BkdEthCvx.sol#L117)  
[trategies/BkdEthCvx.sol#L117](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/BkdEthCvx.sol#L117)



## [L-09] Upgradeable contract is missing a `__gap[50]` storage variable to allow for new storage variables in later versions

See [this](#) link for a description of this storage variable. While some contracts may not currently be sub-classed, adding the variable now protects against forgetting to add it in the future.

```
File: contracts/LpToken.sol    #1
```

```
10 contract LpToken is ILpToken, ERC20Upgradeable {
```

[https://github.com/code-423n4/2022-04-](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/LpToken.sol#L10)

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/LpToken.sol#L10)  
[LpToken.sol#L10](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/LpToken.sol#L10)



## [L-10] Math library unnecessarily overflows during some operations

In the example below, `a + b` may overflow even though the division that comes later would prevent it. This particular case can be prevented by doing `(a & b) + (a ^ b) / b`. There are other functions with similar issues. See [this](#) library for ways of doing math without this sort of issue.

```
File: backd/libraries/ScaledMath.sol    #1
```

```
40     function divRoundUp(uint256 a, uint256 b) internal pure re
41         return (a + b - 1) / b;
42     }
```

[https://github.com/code-423n4/2022-04-](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/libraries/S)

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/libraries/S](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/libraries/S)



[N-01] `_prepareDeadline()` , `_setConfig()` , and `_executeDeadline()` **should be** `private`

These functions have the ability to bypass the timelocks of every setting. No contract besides the `Preparable` contract itself should need to call these functions, and having them available will lead to exploits. The contracts that currently call `_setConfig()` in their constructors should be given a new function `_initConfig()` for this purpose. The `Vault` [calls](#) some of these functions as well, and should be changed to manually inspect the deadline rather than mucking with the internals, which is error-prone. The mappings should also be made `private` , and there should be public getters to read their values

```
File: backd/contracts/utils/Preparable.sol    #1

115     /**
116      * @notice Execute uint256 config update (with time delay
117      * @dev Needs to be called after the update was prepared.
118      * @return New value.
119      */
120     function _executeUInt256(bytes32 key) internal returns (u
121         _executeDeadline(key);
122         uint256 newValue = pendingUints256[key];
123         _setConfig(key, newValue);
124         return newValue;
125     }
126
127     /**
128      * @notice Execute address config update (with time delay
129      * @dev Needs to be called after the update was prepared.
130      * @return New value.
131      */
132     function _executeAddress(bytes32 key) internal returns (a
133         _executeDeadline(key);
134         address newValue = pendingAddresses[key];
135         _setConfig(key, newValue);
136         return newValue;
137     }
```

<https://github.com/code-423n4/2022-04->

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/Utils/Preparable.sol#L115-L137](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/Utils/Preparable.sol#L115-L137)



## [N-02] Open TODOs

Code architecture, incentives, and error handling/reporting questions/issues should be resolved before deployment

```
File: contracts/actions/topup/TopUpAction.sol #1
```

```
713          // TODO: add constant gas consumed for transfer and
```

<https://github.com/code-423n4/2022-04->

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/TopUpAction.sol#L713](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/TopUpAction.sol#L713)

```
File: contracts/strategies/ConvexStrategyBase.sol #2
```

```
4 // TODO Add validation of curve pools
```

<https://github.com/code-423n4/2022-04->

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L4](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L4)

```
File: contracts/strategies/ConvexStrategyBase.sol #3
```

```
5 // TODO Test validation
```

<https://github.com/code-423n4/2022-04->

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L5](https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/strategies/ConvexStrategyBase.sol#L5)



## [N-03] payable function does not reject payments to ERC20 tokens

File: `backd/contracts/vault/VaultReserve.sol` #1

```
50         if (token == address(0)) {
51             require(msg.value == amount, Error.INVALID_AMOUNT)
52             _balances[msg.sender][token] += msg.value;
53             return true;
54         }
55         uint256 balance = IERC20(token).balanceOf(address(this));
```

After the if-statement there should be a `require(0 == msg.value)` to ensure no Ether is being used when updating ERC20 balances. This is non-critical since the function has the `onlyVault` modifier, and presumably vaults would be coded never to deposit Ether to ERC20 tokens <https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/VaultReserve.sol#L50-L55>



**[N-04]** Adding a `return` statement when the function defines a named return variable, is redundant

File: `contracts/pool/PoolFactory.sol` #1

```
216         return addrs;
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/pool/PoolFactory.sol#L216>



**[N-05]** `public` functions not called by the contract should be declared `external` instead

Contracts [are allowed](#) to override their parents' functions and change the visibility from `external` to `public`.

File: `contracts/actions/topup/TopUpAction.sol` #1

```
742     function prepareTopUpHandler(bytes32 protocol, address r
```

```
743         public
744         onlyGovernance
745         returns (bool)
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/TopUpAction.sol#L742-L745>

File: `contracts/CvxCrvRewardsLocker.sol` #2

```
222     function withdraw(address token, uint256 amount) public
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/CvxCrvRewardsLocker.sol#L222>



[N-06] `constant` `s` should be defined rather than using magic numbers

See [original submission](#) for instances.



[N-07] Large multiples of ten should use scientific notation (e.g. `1e6` ) rather than decimal literals (e.g. `1000000` ), for readability

File: `contracts/utils/CvxMintAmount.sol` #1

```
7     uint256 private constant _CLIFF_SIZE = 100000 * 1e18; //ne
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/utils/CvxMintAmount.sol#L7>

File: `contracts/utils/CvxMintAmount.sol` #2

```
9      uint256 private constant _MAX_SUPPLY = 100000000 * 1e18; /
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/utils/CvxMintAmount.sol#L9>



## [N-08] Use a more recent version of solidity

Use a solidity version of at least 0.8.12 to get `string.concat()` to be used instead of `abi.encodePacked(,)`

File: `contracts/actions/topup/handlers/CTokenRegistry.sol` #1

```
2 pragma solidity 0.8.9;
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/handlers/CTokenRegistry.sol#L2>

File: `contracts/actions/topup/TopUpActionFeeHandler.sol` #2

```
2 pragma solidity 0.8.9;
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/TopUpActionFeeHandler.sol#L2>

File: `contracts/actions/topup/TopUpAction.sol` #3

```
2 pragma solidity 0.8.9;
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/actions/topup/TopUpAction.sol#L2>



## [N-09] Constant redefined elsewhere

Consider defining in only one contract so that values cannot become out of sync when only one location is updated. A [cheap way](#) to store constants in a single location is to create an `internal constant` in a `library`. If the variable is a local cache of another contract's value, consider making the cache variable `internal` or `private`, which will require external users to query the contract with the source of truth, so that callers don't get out of sync.

See [original submission](#) for instances.



## [N-10] Inconsistent spacing in comments

Some lines use `// x` and some use `//x`. The instances below point out the usages that don't follow the majority, within each file

```
File: contracts/utils/CvxMintAmount.sol    #1
```

```
8      uint256 private constant _CLIFF_COUNT = 1000; // 1,000 cli
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/utils/CvxMintAmount.sol#L8>

```
File: contracts/utils/CvxMintAmount.sol    #2
```

```
11      IERC20(address(0x4e3FBD56CD56c3e72c1403e103b45Db9da5F
```

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/utils/CvxMintAmount.sol#L11>



## [N-11] Typos

See [original submission](#) for instances.



## [N-12] File is missing NatSpec

File: `contracts/access/Authorization.sol` (various lines) #1

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/access/Authorization.sol>

File: `contracts/access/RoleManager.sol` (various lines) #2

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/access/RoleManager.sol>

File: `contracts/oracles/ChainlinkUsdWrapper.sol` (various lines)

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/oracles/ChainlinkUsdWrapper.sol>

File: `contracts/oracles/OracleProviderExtensions.sol` (various li

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/oracles/OracleProviderExtensions.sol>

File: `contracts/pool/Erc20Pool.sol` (various lines) #5

<https://github.com/code-423n4/2022-04-backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/pool/Erc20Pool.sol>

File: `contracts/pool/EthPool.sol` (various lines) #6



<https://github.com/code-423n4/2022-04->

File: `contracts/utils/CvxMintAmount.sol` (various lines) #7

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/Utils/CvxMintAmount.sol](https://backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/Utils/CvxMintAmount.sol)

File: `contracts/vault/Erc20Vault.sol` (various lines) #8

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/Erc20Vault.sol](https://backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/Erc20Vault.sol)

File: `contracts/vault/EthVault.sol` (various lines) #9

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/EthVault.sol](https://backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/contracts/vault/EthVault.sol)

File: `libraries/AddressProviderMeta.sol` (various lines) #10

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/libraries/AddressProviderMeta.sol](https://backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/libraries/AddressProviderMeta.sol)

File: libraries/Errors.sol (various lines) #11

[backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/libraries/Errors.sol](https://backd/blob/c856714a50437cb33240a5964b63687c9876275b/backd/libraries/Errors.sol)



## [N-13] NatSpec is incomplete

See [original submission](#) for instances.



## [N-14] Event is missing indexed fields

Each `event` should use three `indexed` fields if there are three or more fields

See [original submission](#) for instances.

[chase-manning \(Backd\)](#) resolved and commented:



I consider this report to be of particularly high quality.

[gzeon \(judge\)](#) commented:



Nice submission, warden covered basically all the low risk and non-critical issues.  
Would be nice if there was an index.



## Gas Optimizations

For this contest, 35 reports were submitted by wardens detailing gas optimizations. The [report highlighted below](#) by [joestakey](#) received the top score from the judge.

*The following wardens also submitted reports:* [Tomio](#), [lllllll](#), [Dravee](#), [catchup](#), [defsec](#), [securerodd](#), [Oxkatana](#), [kenta](#), [robee](#), [slywaters](#), [sorrynotsorry](#), [Ov3rf10w](#), [Ox1f8b](#), [Ox4non](#), [OxNazgul](#), [fatherOfBlocks](#), [Funen](#), [NoamYakov](#), [pauliax](#), [rfa](#), [saian](#), [TerrierLover](#), [WatchPug](#), [MaratCerby](#), [OxDjango](#), [Oxmint](#), [hake](#), [horsefacts](#), [oyc\\_109](#), [rayn](#), [simon135](#), [Tadashi](#), [tin537](#), and [z3s](#).



## [G-01] Caching storage variables in memory to save gas



### PROBLEM

Anytime you are reading from storage more than once, it is cheaper in gas cost to cache the variable in memory: a `SLOAD` cost 100gas, while `MLOAD` and `MSTORE` cost 3 gas.

In particular, in `for` loops, when using the length of a storage array as the condition being checked after each loop, caching the array length in memory can yield significant gas savings if the array length is high.



## PROOF OF CONCEPT

Instances include:



### AaveHandler.sol

scope: `topUp()`

- `weth` is read twice

```
AaveHandler.sol:44
```

```
AaveHandler.sol:45
```

- `lendingPool` is read 4 times

```
AaveHandler.sol:50
```

```
AaveHandler.sol:53
```

```
AaveHandler.sol:60
```

```
AaveHandler.sol:65
```



### CompoundHandler.sol

scope: `_getAccountBorrowsAndSupply()`

- `comptroller` is read  $(2 + \text{assets.length})$  times. Number of read depends on the length of `assets` as it is in a for loop

```
CompoundHandler.sol:132
```

```
CompoundHandler.sol:134
```

```
CompoundHandler.sol:142
```



### CTokenRegistry.sol

**scope:** `_isCTokenUsable()`

- `comptroller` is read **3** times

`CTokenRegistry.sol:77`

`CTokenRegistry.sol:79`

`CTokenRegistry.sol:80`



## **TopUpAction.sol**

**scope:** `resetPosition()`

- `addressProvider` is read twice

`TopUpAction.sol:284`

`TopUpAction.sol:295`

**scope:** `execute()`

- `addressProvider` is read **3** times

`TopUpAction.sol:562`

`TopUpAction.sol:604`

`TopUpAction.sol:632`



## **BkdEthCvx.sol**

**scope:** `_withdraw()`

- `vault` is read twice

`BkdEthCvx.sol:77`

`BkdEthCvx.sol:93`



## BkdTriHopCvx.sol

scope: `_withdraw()`

- `vault` is read twice

BkdTriHopCvx.sol:175

BkdTriHopCvx.sol:201



## ConvexStrategyBase.sol

scope: `addRewardToken()`

- `_strategySwapper` is read twice

ConvexStrategyBase.sol:279

ConvexStrategyBase.sol:280

scope: `harvestable()`

- `crvCommunityReserveShare` is read twice

ConvexStrategyBase.sol:307

ConvexStrategyBase.sol:311

- `_rewardTokens.length()` is read `_rewardTokens.length()` times. Number of read depends on the length of `_rewardsTokens` as it is in a for loop

ConvexStrategyBase.sol:313

scope: `_harvest()`

- `_rewardTokens.length()` is read `_rewardTokens.length()` times. Number of read depends on the length of `_rewardsTokens` as it is in a for loop

ConvexStrategyBase.sol:380

**scope:** \_sendCommunityReserveShare()

- cvxCommunityReserveShare is read twice

ConvexStrategyBase.sol:398

ConvexStrategyBase.sol:409



## Vault.sol

**scope:** \_handleExcessDebt()

- reserve is read 3 times

Vault.sol:645

Vault.sol:648

Vault.sol:649

**scope:** \_handleExcessDebt()

- totalDebt is read twice

Vault.sol:657

Vault.sol:658



## Vault.sol

**scope:** stakeFor()

- token is read 4 times

Vault.sol:324

Vault.sol:331

```
Vault.sol:338
Vault.sol:339
```

**scope:** `unStakeFor()`

- `token` is read 4 times

```
Vault.sol:365
Vault.sol:376
Vault.sol:382
Vault.sol:384
```



## MITIGATION

cache these storage variables in memory



## [G-02] Calldata instead of memory for RO function parameters



## PROBLEM

If a reference type function parameter is read-only, it is cheaper in gas to use calldata instead of memory. Calldata is a non-modifiable, non-persistent area where function arguments are stored, and behaves mostly like memory.

Try to use calldata as a data location because it will avoid copies and also makes sure that the data cannot be modified.



## PROOF OF CONCEPT

Instances include:



## RoleManager.sol

**scope:** `hasAnyRole()`

```
RoleManager.sol:73: bytes32[] memory roles
```



## AaveHandler.sol

scope: topUp()

AaveHandler.sol:40: bytes memory extra



## CompoundHandler.sol

scope: topUp()

CompoundHandler.sol:54: bytes memory extra



## TopUpAction.sol

scope: getHealthFactor()

TopUpAction.sol:760: bytes memory extra



## TopUpKeeperHelper.sol

scope: canExecute()

TopUpKeeperHelper.sol:108: ITopUpAction.RecordKey memory key

scope: \_canExecute()

TopUpKeeperHelper.sol:131: ITopUpAction.RecordWithMeta memory pc

scope: \_positionToTopup()

TopUpKeeperHelper.sol:145: ITopUpAction.RecordWithMeta memory pc



**scope:** `_shortenTopups()`

```
TopUpKeeperHelper.sol:159: TopupData[] memory topups
```



## Erc20Pool.sol

**scope:** `initialize()`

```
Erc20Pool.sol:15: string memory name_
```



## EthPool.sol

**scope:** `initialize()`

```
EthPool.sol:13: string memory name_
```



## LiquidityPool.sol

**scope:** `initialize()`

```
LiquidityPool.sol:702: string memory name_
```



## LpToken.sol

**scope:** `initialize()`

```
LpToken.sol:29: string memory name_
```

```
LpToken.sol:30: string memory symbol_
```



## MITIGATION

**Replace** `memory` **with** `calldata`



# [G-03] Comparisons with zero for unsigned integers



## PROBLEM

`>0` is less gas efficient than `!=0` if you enable the optimizer at 10k AND you're in a require statement. Detailed explanation with the opcodes [here](#)



## PROOF OF CONCEPT

Instances include:



### TopUpAction.sol

**scope:** `register()`

```
TopUpAction.sol:210
```

**scope:** `execute()`

```
TopUpAction.sol:554
```



### TopUpActionFeeHandler.sol

**scope:** `claimKeeperFeesForPool()`

```
TopUpActionFeeHandler.sol:123
```



### LiquidityPool.sol

**scope:** `updateDepositCap()`

```
LiquidityPool.sol:401
```

**scope:** `calcRedeem()`

LiquidityPool.sol:471

LiquidityPool.sol:473

**scope:** redeem()

LiquidityPool.sol:549



## Vault.sol

**scope:** withdrawFromReserve()

Vault.sol:164



## BkdLocker.sol

**scope:** depositFees()

BkdLocker.sol:90

BkdLocker.sol:91

BkdLocker.sol:136



## MITIGATION

Replace `> 0` with `!0`



## [G-04] Comparison Operators



### PROBLEM

In the EVM, there is no opcode for `>=` or `<=`. When using greater than or equal, two operations are performed: `>` and `=`.

Using strict comparison operators hence saves gas



### PROOF OF CONCEPT

Instances include:



## TopUpAction.sol

```
TopUpAction.sol:61
TopUpAction.sol:212
TopUpAction.sol:224
TopUpAction.sol:328
TopUpAction.sol:360
TopUpAction.sol:361
TopUpAction.sol:500
TopUpAction.sol:501
TopUpAction.sol:576
TopUpAction.sol:584
TopUpAction.sol:724
```



## TopUpActionFeeHandler.sol

```
TopUpActionFeeHandler.sol:54
TopUpActionFeeHandler.sol:151
TopUpActionFeeHandler.sol:163
TopUpActionFeeHandler.sol:196
TopUpActionFeeHandler.sol:208
```



## ChainLinkOracleProvider.sol

```
ChainLinkOracleProvider.sol:41
ChainLinkOracleProvider.sol:57
```



## EthPool.sol

```
EthPool.sol:442
EthPool.sol:208
EthPool.sol:518
EthPool.sol:525
EthPool.sol:551
```

EthPool.sol:562  
EthPool.sol:690  
EthPool.sol:811  
EthPool.sol:812



## BkdEthCvx.sol

BkdEthCvx.sol:76



## BkdTriHopCvx.sol

BkdTriHopCvx.sol:174



## ConvexStrategyBase.sol

ConvexStrategyBase.sol:197  
ConvexStrategyBase.sol:214



## StrategySwapper.sol

StrategySwapper.sol:110



## CvxMintAmount.sol

CvxMintAmount.sol:21



## Preparable.sol

Preparable.sol:29

Preparable.sol:110



## Vault.sol

Vault.sol:88  
Vault.sol:89  
Vault.sol:90  
Vault.sol:167  
Vault.sol:264  
Vault.sol:323  
Vault.sol:392  
Vault.sol:437  
Vault.sol:482  
Vault.sol:712  
Vault.sol:763



## VaultReserve.sol

VaultReserve.sol:59  
VaultReserve.sol:75  
VaultReserve.sol:103



## BkdLocker.sol

BkdLocker.sol:119  
BkdLocker.sol:140  
BkdLocker.sol:281



## Controller.sol

Controller:98



## CvxCrvRewardsLocker.sol



## GasBank.sol

```
GasBank:68
```

```
GasBank:76
```



## StakerVault.sol

```
StakerVault:107
```

```
StakerVault:150
```

```
StakerVault:153
```

```
StakerVault:324
```

```
StakerVault:368
```

```
StakerVault:371
```



## MITIGATION

Replace `<=` with `<`, and `>=` with `>`. Do not forget to increment/decrement the compared variable

example:

```
-require(maxFee >= minFee, Error.INVALID_AMOUNT);
+require(maxFee > minFee - 1, Error.INVALID_AMOUNT);
```

When the comparison is with a constant storage variable, you can also do the increment in the storage variable declaration

example:

```
-require(maxFee <= _MAX_WITHDRAWAL_FEE, Error.INVALID_AMOUNT)
+require(maxFee < _MAX_WITHDRAWAL_FEE_PLUS_ONE, Error.INVALID_AM
```

However, when  $1$  is negligible compared to the variable (with is the case here as the variable is in the order of  $10^{16}$  ), it is not necessary to increment.



## [G-05] Custom Errors



### PROBLEM

Custom errors from Solidity 0.8.4 are cheaper than revert strings (cheaper deployment cost and runtime cost when the revert condition is met) while providing the same amount of information, as explained [here](#)

Custom errors are defined using the error statement



### PROOF OF CONCEPT

Instances include:



#### RoleManager.sol

```
RoleManager.sol:44
RoleManager.sol:110
RoleManager.sol:111
```



#### AaveHandler.sol

```
AaveHandler.sol:51
```



#### CompoundHandler.sol

```
CompoundHandler.sol:74
CompoundHandler.sol:80
CompoundHandler.sol:123
CompoundHandler.sol:141
CompoundHandler.sol:148
```





## TopUpAction.sol

TopUpAction.sol:67  
TopUpAction.sol:98  
TopUpAction.sol:185  
TopUpAction.sol:209  
TopUpAction.sol:210  
TopUpAction.sol:211  
TopUpAction.sol:212  
TopUpAction.sol:213  
TopUpAction.sol:217  
TopUpAction.sol:218  
TopUpAction.sol:224  
TopUpAction.sol:282  
TopUpAction.sol:328  
TopUpAction.sol:359  
TopUpAction.sol:546  
TopUpAction.sol:553  
TopUpAction.sol:554  
TopUpAction.sol:560  
TopUpAction.sol:575  
TopUpAction.sol:583  
TopUpAction.sol:676  
TopUpAction.sol:723  
TopUpAction.sol:928



## TopUpActionFeeHandler.sol

TopUpActionFeeHandler.sol:67  
TopUpActionFeeHandler.sol:68  
TopUpActionFeeHandler.sol:87  
TopUpActionFeeHandler.sol:123  
TopUpActionFeeHandler.sol:151  
TopUpActionFeeHandler.sol:161  
TopUpActionFeeHandler.sol:196  
TopUpActionFeeHandler.sol:206



## ChainLinkOracleProvider.sol

ChainLinkOracleProvider.sol:31  
ChainLinkOracleProvider.sol:41  
ChainLinkOracleProvider.sol:53  
ChainLinkOracleProvider.sol:57  
ChainLinkOracleProvider.sol:58



## Erc20Pool.sol

Erc20Pool.sol:20  
Erc20Pool.sol:30



## EthPool.sol

EthPool.sol:25  
EthPool.sol:26



## LiquidityPool.sol

LiquidityPool.sol:76  
LiquidityPool.sol:136  
LiquidityPool.sol:137  
LiquidityPool.sol:155  
LiquidityPool.sol:179  
LiquidityPool.sol:208  
LiquidityPool.sol:331  
LiquidityPool.sol:333  
LiquidityPool.sol:387  
LiquidityPool.sol:399  
LiquidityPool.sol:400  
LiquidityPool.sol:401  
LiquidityPool.sol:441  
LiquidityPool.sol:471  
LiquidityPool.sol:473  
LiquidityPool.sol:517  
LiquidityPool.sol:525  
LiquidityPool.sol:549  
LiquidityPool.sol:551

LiquidityPool.sol:562  
LiquidityPool.sol:811  
LiquidityPool.sol:812



## PoolFactory.sol

PoolFactory.sol:159  
PoolFactory.sol:162  
PoolFactory.sol:165  
PoolFactory.sol:170  
PoolFactory.sol:180  
PoolFactory.sol:184



## BkdTriHopCvx.sol

BkdTriHopCvx.sol:133  
BkdTriHopCvx.sol:147



## ConvexStrategyBase.sol

ConvexStrategyBase.sol:117  
ConvexStrategyBase.sol:144  
ConvexStrategyBase.sol:197  
ConvexStrategyBase.sol:198  
ConvexStrategyBase.sol:214  
ConvexStrategyBase.sol:215  
ConvexStrategyBase.sol:260  
ConvexStrategyBase.sol:273



## StrategySwapper.sol

StrategySwapper.sol:69  
StrategySwapper.sol:110  
StrategySwapper.sol:111  
StrategySwapper.sol:123

StrategySwapper.sol:124  
StrategySwapper.sol:139



## Preparable.sol

Preparable.sol:28  
Preparable.sol:29  
Preparable.sol:86  
Preparable.sol:98  
Preparable.sol:110  
Preparable.sol:111



## Erc20Vault.sol

Erc20Vault.sol:20



## Vault.sol

Vault.sol:88  
Vault.sol:89  
Vault.sol:90  
Vault.sol:164  
Vault.sol:165  
Vault.sol:167  
Vault.sol:194  
Vault.sol:195  
Vault.sol:198  
Vault.sol:264  
Vault.sol:392  
Vault.sol:429  
Vault.sol:762



## VaultReserve.sol

VaultReserve.sol:51

VaultReserve.sol:59  
VaultReserve.sol:73  
VaultReserve.sol:75



## AddressProvider.sol

AddressProvider.sol:64  
AddressProvider.sol:70  
AddressProvider.sol:96  
AddressProvider.sol:100  
AddressProvider.sol:170  
AddressProvider.sol:179  
AddressProvider.sol:188  
AddressProvider.sol:230  
AddressProvider.sol:231  
AddressProvider.sol:249  
AddressProvider.sol:259  
AddressProvider.sol:284  
AddressProvider.sol:285  
AddressProvider.sol:314  
AddressProvider.sol:417  
AddressProvider.sol:423



## BkdLocker.sol

BkdLocker.sol:58  
BkdLocker.sol:90  
BkdLocker.sol:91  
BkdLocker.sol:118  
BkdLocker.sol:136  
BkdLocker.sol:207



## Controller.sol

Controller:32  
Controller:33  
Controller:80



## CvxCrvRewardsLocker.sol

CvxCrvRewardsLocker:83  
CvxCrvRewardsLocker:135



## GasBank.sol

GasBank:42  
GasBank:68  
GasBank:69  
GasBank:76  
GasBank:91



## LpToken.sol

LpToken:34



## StakerVault.sol

StakerVault:70  
StakerVault:93  
StakerVault:106  
StakerVault:107  
StakerVault:139  
StakerVault:150  
StakerVault:153  
StakerVault:203  
StakerVault:224  
StakerVault:324  
StakerVault:340  
StakerVault:367  
StakerVault:371



## SwapperRegistry.sol



## MITIGATION

Replace require statements with custom errors.



## [G-06] Default value initialization



## PROBLEM

If a variable is not set/initialized, it is assumed to have the default value (0, false, 0x0 etc depending on the data type). Explicitly initializing it with its default value is an anti-pattern and wastes gas.



## PROOF OF CONCEPT

Instances include:



### RoleManager.sol

```
RoleManager.sol:80  
RoleManager.sol:110  
RoleManager.sol:111
```



### CompoundHandler.sol

```
CompoundHandler.sol:135
```



### CTokenRegistry.sol

```
CTokenRegistry.sol:61
```



### TopUpAction.sol

TopUpAction.sol:188  
TopUpAction.sol:452  
TopUpAction.sol:456  
TopUpAction.sol:479  
TopUpAction.sol:506  
TopUpAction.sol:891



## TopUpActionKeeperHandler.sol

TopUpActionKeeperHandler.sol:43  
TopUpActionKeeperHandler.sol:46  
TopUpActionKeeperHandler.sol:72  
TopUpActionKeeperHandler.sol:93  
TopUpActionKeeperHandler.sol:165



## LiquidityPool.sol

LiquidityPool.sol:483



## ConvexStrategyBase.sol

ConvexStrategyBase.sol:313  
ConvexStrategyBase.sol:380



## Vault.sol

Vault.sol:42  
Vault.sol:135  
Vault.sol:583



## BkdLocker.sol



BkdLocker.sol:133  
BkdLocker.sol:310



## Controller.sol

Controller:114  
Controller:117



## CvxCrvRewardsLocker.sol

CvxCrvRewardsLocker:43



## StakerVault.sol

StakerVault:144  
StakerVault:260



## MITIGATION

Remove explicit initialization for default values.



## [G-07] Prefix increments



## PROBLEM

Prefix increments are cheaper than postfix increments.



## PROOF OF CONCEPT

Instances include:



## RoleManager.sol

RoleManager.sol:80



## CompoundHandler.sol

CompoundHandler.sol:135



## CTokenRegistry.sol

CTokenRegistry.sol:61



## TopUpAction.sol

TopUpAction.sol:188

TopUpAction.sol:456

TopUpAction.sol:479

TopUpAction.sol:506

TopUpAction.sol:891



## TopUpActionKeeperHandler.sol

TopUpActionKeeperHandler.sol:43

TopUpActionKeeperHandler.sol:46

TopUpActionKeeperHandler.sol:50

TopUpActionKeeperHandler.sol:72

TopUpActionKeeperHandler.sol:93

TopUpActionKeeperHandler.sol:165



## ConvexStrategyBase.sol

ConvexStrategyBase.sol:313

ConvexStrategyBase.sol:380



## BkdLocker.sol

BkdLocker.sol:310



## Controller.sol

Controller:117



## StakerVault.sol

StakerVault:260



## MITIGATION

change `variable++` to `++variable`



## [G-08] Redundant code



## IMPACT

Redundant code should be avoided as it costs unnecessary gas



## PROOF OF CONCEPT

Instances include:



## Preparable.sol

```
Preparable.sol:140:
address oldValue = currentAddresses[key];
currentAddresses[key] = value;
pendingAddresses[key] = address(0);
deadlines[key] = 0;
emit ConfigUpdatedAddress(key, oldValue, value);
```

```
return value;
```

We can update `currentAddresses[key]` after emitting the event to save the gas of the declaration of `oldValue` :

```
+emit ConfigUpdatedAddress(key, currentAddresses[key], value);
pendingAddresses[key] = address(0);
deadlines[key] = 0;
currentAddresses[key] = value;
return value;
```



## MITIGATION

see Proof of Concept for mitigation steps.



## [G-09] Require instead of &&



## IMPACT

Require statements including conditions with the `&&` operator can be broken down in multiple require statements to save gas.



## PROOF OF CONCEPT

Instances include:



## TopUpAction.sol

```
TopUpAction:360:
require (
    newSwapperSlippage >= _MIN_SWAPPER_SLIPPAGE &&
        newSwapperSlippage <= _MAX_SWAPPER_SLIPPAGE,
    Error.INVALID_AMOUNT
);
```



## ConvexStrategyBase.sol

```
ConvexStrategyBase:274:
require(
    token_ != address(_CVX) && token_ != address(underly
    Error.INVALID_TOKEN_TO_ADD
);
```



## SwapperRegistry.sol

```
SwapperRegistry:35:
require(
    fromToken != toToken &&
    fromToken != address(0) &&
    toToken != address(0) &&
    newSwapper != address(0),
    Error.INVALID_TOKEN_PAIR
);
```



## MITIGATION

Breakdown each condition in a separate `require` statement (though `require` statements should be [replaced with custom errors](#))

```
require( newSwapperSlippage >= _MIN_SWAPPER_SLIPPAGE );
require( newSwapperSlippage <= _MAX_SWAPPER_SLIPPAGE,
    Error.INVALID_AMOUNT )
```



## [G-10] Tight Variable Packing



### PROBLEM

Solidity contracts have contiguous 32 bytes (256 bits) slots used in storage. By arranging the variables, it is possible to minimize the number of slots used within a contract's storage and therefore reduce deployment costs.

address type variables are each of 20 bytes size (way less than 32 bytes). However, they here take up a whole 32 bytes slot (they are contiguous).

As bool type variables are of size 1 byte, there's a slot here that can get saved by moving them closer to an address



## PROOF OF CONCEPT

Instances include:



### VaultStorage.sol

```
VaultStorage.sol:11:  
address public pool;  
uint256 public totalDebt;  
bool public strategyActive;
```



## MITIGATION

Place `strategyActive` **after** `pool` to save one storage slot

```
address public pool;  
+bool public strategyActive;  
uint256 public totalDebt;
```



## [G-11] Unchecked arithmetic



### PROBLEM

The default “checked” behavior costs more gas when adding/dividing/multiplying, because under-the-hood those checks are implemented as a series of opcodes that, prior to performing the actual arithmetic, check for under/overflow and revert if it is detected.

if it can statically be determined there is no possible way for your arithmetic to under/overflow (such as a condition in an if statement), surrounding the arithmetic in an `unchecked` block will save gas



## PROOF OF CONCEPT

Instances include:



## LiquidityPool.sol

```
LiquidityPool.sol:751: underlyingBalance - underlyingToWithdraw;
```



## BkdEthCvx.sol

```
BkdEthCvx.sol:83: uint256 requiredUnderlyingAmount = amount - ur
```



## BkdTriHopCvx.sol

```
BkdTriHopCvx.sol:181: uint256 requiredUnderlyingAmount = amount
```



## CvxMintAmount.sol

```
CvxMintAmount.sol:24: uint256 remaining = _CLIFF_COUNT - current
```



## Vault.sol

```
Vault.sol:24: uint256 remaining = _CLIFF_COUNT - currentCliff; /
```

```
Vault.sol:125: uint256 requiredWithdrawal = amount - availableUr
```

```
Vault.sol:130: uint256 newTarget = (allocated - requiredWithdraw
```

```
Vault.sol:141: uint256 totalUnderlyingAfterWithdraw = totalUnder
```

```
Vault.sol:440: waitingForRemovalAllocated = _waitingForRemovalAl
```

```
Vault.sol:444: uint256 profit = withdrawn - allocated; //because
```

```
Vault.sol:452: allocated -= withdrawn; //because of the conditic
```

```
Vault.sol:591: uint256 profit = allocatedUnderlying - amountAllocated;
Vault.sol:595: profit -= currentDebt; //because of the condition
Vault.sol:600: currentDebt -= profit; //because of the condition
Vault.sol:605: uint256 loss = amountAllocated - allocatedUnderlying;
Vault.sol:784: uint256 withdrawAmount = allocatedUnderlying - target;
Vault.sol:790: uint256 depositAmount = target - allocatedUnderlying;
```



## StakerVault.sol

```
StakerVault.sol:164: uint256 srcTokensNew = srcTokens - amount;
```



## MITIGATION

Place the arithmetic operations in an `unchecked` block

[chase-manning \(Backd\) resolved and commented:](#)

I consider this report to be of particularly high quality.



## Disclosures

C4 is an open organization governed by participants in the community.

C4 Contests incentivize the discovery of exploits, vulnerabilities, and bugs in smart contracts. Security researchers are rewarded at an increasing rate for finding higher-risk issues. Contest submissions are judged by a knowledgeable security researcher and solidity developer and disclosed to sponsoring developers. C4 does not conduct formal verification regarding the provided code but instead provides final verification.



C4 does not provide any guarantee or warranty regarding the security of this project. All smart contract software should be used at the sole risk and responsibility of users.

Top

An open organization | [Twitter](#) | [Discord](#) | [GitHub](#) | [Medium](#) | [Newsletter](#) | [Media kit](#) | [Careers](#) | [code4rena.eth](#)