



# Seascape – MSCP Token & Vesting

## Smart Contract Security Audit

Prepared by: Halborn

Date of Engagement: November 12th, 2021 – November 19th, 2021

Visit: [Halborn.com](https://Halborn.com)

DOCUMENT REVISION HISTORY	3
CONTACTS	3
1 EXECUTIVE OVERVIEW	4
1.1 INTRODUCTION	5
1.2 AUDIT SUMMARY	5
1.3 TEST APPROACH & METHODOLOGY	5
RISK METHODOLOGY	6
1.4 SCOPE	8
2 ASSESSMENT SUMMARY & FINDINGS OVERVIEW	9
3 FINDINGS & TECH DETAILS	9
3.1 (HAL-01) INVESTOR MULTI-WITHDRAW IF ADDED AGAIN - HIGH	11
Description	11
POC	11
Code Location	11
Risk Level	12
Recommendation	12
Remediation Plan	13
3.2 (HAL-02) UNUSED CODE - INFORMATIONAL	14
Description	14
Code Location	14
Risk Level	14
Recommendation	14
Remediation Plan	14
4 MANUAL TESTING	14
4.1 Introduction	16

4.2	Stateful testing	19
4.3	Manual checks	19
5	AUTOMATED TESTING	20
5.1	STATIC ANALYSIS REPORT	22
	Description	22
	Slither results	22

## DOCUMENT REVISION HISTORY

VERSION	MODIFICATION	DATE	AUTHOR
0.1	Document Creation	11/17/2021	Ferran.Celades
0.2	Document Edits	11/17/2021	Ferran.Celades
0.3	Draft Review	11/17/2021	Gabi Urrutia
1.0	Remediation Plan	11/18/2021	Gabi Urrutia

## CONTACTS

CONTACT	COMPANY	EMAIL
Rob Behnke	Halborn	<a href="mailto:Rob.Behnke@halborn.com">Rob.Behnke@halborn.com</a>
Steven Walbroehl	Halborn	<a href="mailto:Steven.Walbroehl@halborn.com">Steven.Walbroehl@halborn.com</a>
Gabi Urrutia	Halborn	<a href="mailto:Gabi.Urrutia@halborn.com">Gabi.Urrutia@halborn.com</a>
Ferran Celades	Halborn	<a href="mailto:Ferran.Celades@halborn.com">Ferran.Celades@halborn.com</a>



# EXECUTIVE OVERVIEW



## 1.1 INTRODUCTION

Seascope engaged Halborn to conduct a security audit on their [MSCP](#) Token and vesting contracts beginning on November 12th, 2021 and ending on November 19th, 2021. The security assessment was scoped to the smart contracts provided in the Github repository [blocklords/moonscape-smartcontracts/contracts/riverboat](#)

## 1.2 AUDIT SUMMARY

The team at Halborn was provided two weeks for the engagement and assigned a full time security engineer to audit the security of the smart contract. The security engineer is a blockchain and smart-contract security expert with advanced penetration testing, smart-contract hacking, and deep knowledge of multiple blockchain protocols.

The purpose of this audit is to:

- Ensure that smart contract functions operate as intended
- Identify potential security issues with the smart contracts

In summary, Halborn identified few security risks that were mostly addressed by the [Seascope team](#).

## 1.3 TEST APPROACH & METHODOLOGY

Halborn performed a combination of manual and automated security testing to balance efficiency, timeliness, practicality, and accuracy in regard to the scope of this audit. While manual testing is recommended to uncover flaws in logic, process, and implementation; automated testing techniques help enhance coverage of the bridge code and can quickly identify items that do not follow security best practices. The following phases and associated tools were used throughout the term of the audit:

- Research into architecture and purpose
- Smart contract manual code review and walkthrough
- Graphing out functionality and contract logic/connectivity/functions ([solgraph](#))
- Manual assessment of use and safety for the critical Solidity variables and functions in scope to identify any arithmetic related vulnerability classes
- Manual testing by custom scripts
- Static Analysis of security for scoped contract, and imported functions. ([Slither](#))
- Testnet deployment ([Brownie](#), [Remix IDE](#))

#### RISK METHODOLOGY:

Vulnerabilities or issues observed by Halborn are ranked based on the risk assessment methodology by measuring the **LIKELIHOOD** of a security incident, and the **IMPACT** should an incident occur. This framework works for communicating the characteristics and impacts of technology vulnerabilities. It's quantitative model ensures repeatable and accurate measurement while enabling users to see the underlying vulnerability characteristics that was used to generate the Risk scores. For every vulnerability, a risk level will be calculated on a scale of 5 to 1 with 5 being the highest likelihood or impact.

#### RISK SCALE - LIKELIHOOD

- 5 - Almost certain an incident will occur.
- 4 - High probability of an incident occurring.
- 3 - Potential of a security incident in the long term.
- 2 - Low probability of an incident occurring.
- 1 - Very unlikely issue will cause an incident.

#### RISK SCALE - IMPACT

- 5 - May cause devastating and unrecoverable impact or loss.
- 4 - May cause a significant level of impact or loss.
- 3 - May cause a partial impact or loss to many.
- 2 - May cause temporary impact or loss.

1 - May cause minimal or un-noticeable impact.

The risk level is then calculated using a sum of these two values, creating a value of 10 to 1 with 10 being the highest level of security risk.

CRITICAL	HIGH	MEDIUM	LOW	INFORMATIONAL
----------	------	--------	-----	---------------

10 - CRITICAL

9 - 8 - HIGH

7 - 6 - MEDIUM

5 - 4 - LOW

3 - 1 - VERY LOW AND INFORMATIONAL



## 1.4 SCOPE

The security assessment was scoped to the following  
[blocklords/moonscape-smartcontracts/contracts/riverboat](#)

- [MscpToken.sol](#)
- [MscpVesting.sol](#)
- All contracts inherited by these contracts

**Commit ID:** [9558f291d70c35828176823165316f128ccfb024](#)

## 2. ASSESSMENT SUMMARY & FINDINGS OVERVIEW

CRITICAL	HIGH	MEDIUM	LOW	INFORMATIONAL
0	1	0	0	1

### LIKELIHOOD

IMPACT

		(HAL-01)		
(HAL-02)				

SECURITY ANALYSIS	RISK LEVEL	REMEDIATION DATE
(HAL-01) INVESTOR MULTI-WITHDRAW IF ADDED AGAIN	High	SOLVED IN THE DEPLOYMENT
(HAL-02) UNUSED CODE	Informational	SOLVED - 11/18/2021



# FINDINGS & TECH DETAILS



### 3.1 (HAL-01) INVESTOR MULTI-WITHDRAW IF ADDED AGAIN – HIGH

#### Description:

The `addInvestor` function, called only by the owner, does not check if the investor does have claimed already the tokens. The only performed check is the `remainingCoins == 0` which will be true after the vesting period finishes (150 days for strategic and 300 days for private).

When the vesting period finishes, the owner can call `addInvestor`, this will reset the `remainingCoins` for the investor. Having the reset the amount of remaining tokens allows the investor to withdraw again the max amount of tokens. This is possible since the `getDuration` function will return the total duration (`startTime` did not change), allowing to re-claim the total tokens again. This process can be repeated.

#### POC:

- Add an investor with `addInvestor`
- Wait for the vesting period to finish (150/300 days)
- Withdraw the tokens using the investor account
- Owner can call again the `addInvestor` function
- Withdraw the tokens again

#### Code Location:

Listing 1: `contracts/MscpVesting` (Lines 51)

```
50 function addInvestor (address _investor, bool _strategicInvestor)
    external onlyOwner {
51     require(balances[_investor].remainingCoins == 0, "investor
        already has allocation");
52
53     if(_strategicInvestor){
```

```

>>> vesting.addInvestor(accounts[0], True)
Transaction sent: 0xfd38ab5ab26ed01d0ac4f010d861968b0754076fc6071ccb517836960e09881d
Gas price: 0.0 gwei Gas limit: 12000000 Nonce: 79
MscpVesting.addInvestor confirmed - Block: 98 Gas used: 66954 (0.56%)

<Transaction '0xfd38ab5ab26ed01d0ac4f010d861968b0754076fc6071ccb517836960e09881d'>
>>> chain.sleep(12960000 + 100)
>>> token.balanceOf(accounts[0]) / 10 ** 18
0.0
>>> t = vesting.withdraw()
Transaction sent: 0x3764937dcf16a0bf92370fcc33dd61289b1ed60c5d8221dc14ac44c585327c69
Gas price: 0.0 gwei Gas limit: 12000000 Nonce: 80
MscpVesting.withdraw confirmed - Block: 99 Gas used: 59542 (0.50%)

>>> token.balanceOf(accounts[0]) / 10 ** 18
10000000.0
>>> vesting.addInvestor(accounts[0], True)
Transaction sent: 0x346e2fbd984dacfc4f69dabe2a567ea3d48a95f501878cc82cceb957943618df
Gas price: 0.0 gwei Gas limit: 12000000 Nonce: 81
MscpVesting.addInvestor confirmed - Block: 100 Gas used: 47754 (0.40%)

<Transaction '0x346e2fbd984dacfc4f69dabe2a567ea3d48a95f501878cc82cceb957943618df'>
>>> t = vesting.withdraw()
Transaction sent: 0xea9d5981b24dd18f93197ddc46e1d11daea89c64da53c3e5103a2a10d26d5497
Gas price: 0.0 gwei Gas limit: 12000000 Nonce: 82
MscpVesting.withdraw confirmed - Block: 101 Gas used: 38623 (0.32%)

>>> token.balanceOf(accounts[0]) / 10 ** 18
18000000.0
>>>

```

Figure 1: PoC showing the double withdraw

```

54         balances[_investor].remainingCoins = TOTAL_STRATEGIC;
55         balances[_investor].strategicInvestor = true;
56     } else
57         balances[_investor].remainingCoins = TOTAL_PRIVATE;
58
59     emit InvestorModified(_investor, balances[_investor].
        remainingCoins);
60 }

```

**Risk Level:****Likelihood - 3****Impact - 5****Recommendation:**

Check if the investor already has `claimedBonus` tokens. If this value is different from zero, it means that the investor is already vested.

### Remediation Plan:

**SOLVED IN THE DEPLOYMENT:** The issue will be solved in the deployment implementing a multi-signature wallet.

## 3.2 (HAL-02) UNUSED CODE - INFORMATIONAL

### Description:

The `burn` function on the `MscpToken` does contain unnecessary code.

### Code Location:

Listing 2: `contracts/MscpToken.sol` (Lines 97)

```
96     function burn(uint256 amount) public onlyBridge {  
97         require(false, "Only burnFrom is allowed");  
98     }
```

### Risk Level:

**Likelihood - 1**

**Impact - 1**

### Recommendation:

It is recommended to remove the `onlyBridge` modifier and directly raise "Only burnFrom is allowed".

### Remediation Plan:

**SOLVED:** The code was removed by the `Seascape team`.



# MANUAL TESTING





## 4.1 Introduction

Halborn performed different manual tests in all the contracts, trying to find logic flaws and vulnerabilities that were not detected by the automatic tools.

During the manual testing, multiple questions were considered while evaluating each of the defined functions:

- Can it be re-called changing admin/roles and permissions?
- Can somehow an external controlled contract call again the function during the execution of it? (Re-entrancy)
- Can a function be called twice in the same block causing issues?
- Do we control sensitive or vulnerable parameters?
- Does the function check for boundaries on the parameters and internal values? Bigger than zero or equal? Argument count, array sizes, integer truncation. . .
- Are the function parameters and variables controlled by external contracts?
- Can extended contracts cause issues on the extender contract?

The following graph, Figure 2, displays the inheritance on both audited contracts.



Figure 2: MscpToken and MscpVesting inheritance graph

The Figure 3 and Figure 4 show the call flow present on the contracts.




Figure 3: MscpToken call graph




Figure 4: MscpVesting call graph

## 4.2 Stateful testing

The MscpToken was fully verified for being ERC20 compliant before the stateful testing.

[[attachments/token\_erc20\_compliant.png]]

The token was tested against stateful testing scripts made to verify current existing token implementations such as OpenZeppelin ERC20 tokens [ERC20-PBT](#)

The contract was executed against:

- StateMachine
- MintingStateMachine (since `mint` functionality exists)

The results showed no issues at all.

## 4.3 Manual checks

Both strategic and private should have the same amount at the end of the period. Checking for max withdrawal after the period finished for an strategic account, and a none strategic account (private):

```

>>> vesting.addInvestor(accounts[0], True)
Transaction sent: 0x5d55363e5f3486f1d5fc0a44189cdf00793e60b57e854f19540f0fb613ad9261
Gas price: 0.0 gwei Gas limit: 12000000 Nonce: 26
MscpVesting.addInvestor confirmed - Block: 27 Gas used: 66954 (0.56%)

<Transaction '0x5d55363e5f3486f1d5fc0a44189cdf00793e60b57e854f19540f0fb613ad9261'>
>>> chain.sleep(12960000 + 100)
>>> token.balanceOf(accounts[0]) / 10 ** 18
0.0
>>> t = vesting.withdraw()
Transaction sent: 0xf405ccacf991b648cead54fad5f8f9db40d37a91c106605636be5c9e21c7bee
Gas price: 0.0 gwei Gas limit: 12000000 Nonce: 27
MscpVesting.withdraw confirmed - Block: 28 Gas used: 59542 (0.50%)

>>> token.balanceOf(accounts[0]) / 10 ** 18
10000000.0
>>> 

```

```

>>> vesting.addInvestor(accounts[0], False)
Transaction sent: 0x758a0b3216ae237d8a6bdbe16b5074b4d7afd4537cdd258b16db57767788505c
Gas price: 0.0 gwei Gas limit: 12000000 Nonce: 31
MscpVesting.addInvestor confirmed - Block: 32 Gas used: 46096 (0.38%)

<Transaction '0x758a0b3216ae237d8a6bdbe16b5074b4d7afd4537cdd258b16db57767788505c'>
>>> chain.sleep(25920000 + 100)
>>> token.balanceOf(accounts[0]) / 10 ** 18
0.0
>>> t = vesting.withdraw()
Transaction sent: 0xab3661a2cb57b3c09ebfe890318e2f6855c79d1816c1d9a858f408019cddbd35b
Gas price: 0.0 gwei Gas limit: 12000000 Nonce: 32
MscpVesting.withdraw confirmed - Block: 33 Gas used: 74511 (0.62%)

>>> token.balanceOf(accounts[0]) / 10 ** 18
10000000.0
>>> 

```



# AUTOMATED TESTING



## 5.1 STATIC ANALYSIS REPORT

### Description:

Halborn used automated testing techniques to enhance the coverage of certain areas of the scoped contracts. Among the tools used was Slither, a Solidity static analysis framework. After Halborn verified all the contracts in the repository and was able to compile them correctly into their ABI and binary formats, Slither was run on the all-scoped contracts. This tool can statically verify mathematical relationships between Solidity variables to detect invalid or inconsistent usage of the contracts' APIs across the entire code-base.

### Slither results:

Slither did not reveal any security issue or concern.



THANK YOU FOR CHOOSING

 **HALBORN**

