



December 23rd 2021 — Quantstamp Verified

Rengo Labs

This audit report was prepared by Quantstamp, the leader in blockchain security.

Executive Summary

Source Code

Type DeFi protocol **Auditors** Kacper Bąk, Senior Research Engineer Souhail Mssassi, Research Engineer Timeline 2021-10-25 through 2021-12-15 Languages Rust Methods Architecture Review, Unit Testing, Manual Review Specification None **Documentation Quality** Low **Test Quality** Low

1 (1 Resolved)

Repository	Commit
casperswap-core	3069edd
casperswap-router	<u>9f464a6</u>

Total Issues

11 (10 Resolved)

High Risk Issues

4 (4 Resolved)

Medium Risk Issues

2 (2 Resolved)

Low Risk Issues

3 (2 Resolved)

Undetermined Risk Issues 1 (1 Resolved)

Informational Risk Issues

0 Unresolved 1 Acknowledged 10 Resolved

A High Risk	The issue puts a large number of users' sensitive information at risk, or is reasonably likely to lead to catastrophic impact for client's reputation or serious financial implications for client and users.
^ Medium Risk	The issue puts a subset of users' sensitive information at risk, would be detrimental for the client's reputation if exploited, or is reasonably likely to lead to moderate financial impact.
✓ Low Risk	The risk is relatively small and could not be exploited on a recurring basis, or is a risk that the client has indicated is low-impact in view of the client's business circumstances.
 Informational 	The issue does not post an immediate risk, but is relevant to security best practices or Defence in Depth.
? Undetermined	The impact of the issue is uncertain.
 Unresolved 	Acknowledged the existence of the risk, and decided to accept it without engaging in special efforts to control it.
 Unresolved Acknowledged 	and decided to accept it without
	and decided to accept it without engaging in special efforts to control it. The issue remains in the code but is a result of an intentional business or design decision. As such, it is supposed to be addressed outside the programmatic means, such as: 1) comments, documentation, README, FAQ; 2) business processes; 3) analyses showing that the issue shall have no negative consequences in practice (e.g., gas analysis, deployment

Summary of Findings

We have reviewed the code and evaluated it with respect to the following reference implementations:

- 1. Uniswap V2 Core,
- 2. <u>Uniswap V2 Periphery</u>, and
- 3. Uniswap Flash Swapper.

We have found a number of important issues which mostly caused by deviations from the original implementations. Half of the issues are of high and medium severity.

Furthermore, we believe that many of the vulnerabilities could have been caught if the project was accompanied by a high quality test suite. Therefore, we recommend addressing the issues and crafting an extensive test suite with positive and negative test cases. This task should be relatively easy since all of the reimplemented contracts have proper test suites coded in Solidity.

Update: the team has addressed all the issues in the following commits: 801eaae for Uniswap V2 Core, and 237cf3f for Uniswap V2 Router.

ID	Description	Severity	Status
QSP-1	Integer Overflow / Underflow	≈ High	Fixed
QSP-2	Unchecked Return Value	☆ High	Fixed
QSP-3	Incorrect Check for permissioned_pair_address	☆ High	Fixed
QSP-4	remove_liquidity_cspr() Differs from Uniswap's Implementation	☆ High	Fixed
QSP-5	mint_fee() Enables Fee Only When fee_to Is 0x0	^ Medium	Fixed
QSP-6	pair_for() Does Not Sort The Tokens Before Fetching a Pair	^ Medium	Fixed
QSP-7	Allowance Double-Spend Exploit	∨ Low	Fixed
QSP-8	Race Conditions / Front-Running	∨ Low	Acknowledged
QSP-9	Missing Verification on Some Variables	∨ Low	Fixed
QSP-10	set_nonce() Adds an Arbitrary amount To The Nonce	O Informational	Fixed
QSP-11	Functions skim() And sync() Are Re-entrant	? Undetermined	Fixed

Quantstamp Audit Breakdown

Quantstamp's objective was to evaluate the repository for security-related issues, code quality, and adherence to specification and best practices.

Possible issues we looked for included (but are not limited to):

- Transaction-ordering dependence
- Timestamp dependence
- Mishandled exceptions and call stack limits
- Unsafe external calls
- Integer overflow / underflow
- Number rounding errors
- Reentrancy and cross-function vulnerabilities
- Denial of service / logical oversights
- Access control
- Centralization of power
- Business logic contradicting the specification
- Code clones, functionality duplication
- Gas usage
- Arbitrary token minting

Methodology

The Quantstamp auditing process follows a routine series of steps:

- 1. Code review that includes the following
 - i. Review of the specifications, sources, and instructions provided to Quantstamp to make sure we understand the size, scope, and functionality of the smart contract.
 - ii. Manual review of code, which is the process of reading source code line-by-line in an attempt to identify potential vulnerabilities.
 - iii. Comparison to specification, which is the process of checking whether the code does what the specifications, sources, and instructions provided to Quantstamp describe.
- 2. Testing and automated analysis that includes the following:
 - i. Test coverage analysis, which is the process of determining whether the test cases are actually covering the code and how much code is exercised when we run those test cases.
 - ii. Symbolic execution, which is analyzing a program to determine what inputs cause each part of a program to execute.
- 3. Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.
- 4. Specific, itemized, and actionable recommendations to help you take steps to secure your smart contracts.

Findings

QSP-1 Integer Overflow / Underflow

Severity: High Risk

Status: Fixed

File(s) affected: erc20/erc20/src/erc20.rs, wcspr/wcspr/src/wcspr.rs, pair/pair/src/pair.rs,
uniswap_v2_library/uniswap_v2_library/src/uniswap_v2_library.rs, flash_swapper/src/flash_swapper.rs

Description: Integer overflow/underflow occur when an integer hits its bit-size limit. Every integer has a set range; when that range is passed, the value loops back around. A clock is a good analogy: at 11:59, the minute hand goes to 0, not 60, because 59 is the largest possible minute. Integer overflow and underflow may cause many unexpected kinds of behavior and was the core reason for the batch0verflow attack. Here's an example with uint8 variables, meaning unsigned integers with a range of 0..255.

Although Rust code compiled in debug mode (and ran in tests) catches the underflows and overflows, it is unclear how future-proof production code will be against these issues. We noticed potential underflows and/or overflows in the following:

```
1. erc20/erc20/src/erc20.rs in the function mint(),
```

- 2. erc20/erc20/src/erc20.rs in the function transfer_from(),
- 3. erc20/erc20/src/erc20.rs in the function make_transfer(),
- 4. wcspr/wcspr/src/wcspr.rs in the function mint(),
- 5. wcspr/wcspr/src/wcspr.rs in the function transfer_from(),
- 6. wcspr/wcspr/src/wcspr.rs in the function make_transfer(),
- 7. pair/pair/src/pair.rs in the function mint(),
- 8. pair/pair/src/pair.rs in the function transfer_from(),
- 9. pair/pair/src/pair.rs in the function make_transfer(),
- 10. uniswap_v2_library/uniswap_v2_library/src/uniswap_v2_library.rs in the function get_amount_out(),
- 11. uniswap_v2_library/uniswap_v2_library/src/uniswap_v2_library.rs in the function get_amount_in(),
- 12. flash_swapper/src/flash_swapper.rs, lines 264, 265, 469.

Recommendation: To protect against underflows we recommend using the function checked_sub(). To protect against overflows we recommend using the function checked_add().

Update: Fixed in 214c9cc (Uniswap v2 - Core) and in adfd626 (Uniswap v2 - Router).

QSP-2 Unchecked Return Value

Severity: High Risk

Status: Fixed

File(s) affected: pair/pair/src/pair.rs, flash_swapper/src/flash_swapper.rs, uniswap_v2_router/uniswap_v2_router/src/transfer_helper.rs, uniswap_v2_router/uniswap_v2_router/src/uniswap_v2_router.rs

Description: Most functions will return a true or false value upon success. Some functions, like send(), are more crucial to check than others. It's important to ensure that every necessary function is checked.

Specifically, the following code locations ignore return values:

- 1. pair/pair/src/pair.rs, lines 209, 222, 585, 590 ignore return values from transfer(), so a transfer may fail but swap() would still succeed,
- 2. flash_swapper/src/flash_swapper.rs, lines 301, 303, 510, 751, and 790,
- uniswap_v2_router/uniswap_v2_router/src/transfer_helper.rs, line 16,
- 4. uniswap_v2_router/uniswap_v2_router/src/uniswap_v2_router.rs, lines 239 and L626.

Recommendation: Check return values and revert where necessary.

Update: Fixed in 88c77bc, f6dc7de, 706ccea (Uniswap v2 - Core) and in 5a9b158 (Uniswap v2 - Router).

QSP-3 Incorrect Check for permissioned pair address

Severity: High Risk

Status: Fixed

File(s) affected: flash_swapper/src/flash_swapper.rs

 $\textbf{Description:} \ The \ function \ uniswap_v2_call() \ reverts \ if \ it's \ called \ by \ a \ permissioned_pair_address \ (line 98). \ This \ is \ likely \ incorrect.$

Recommendation: The function should revert if it's NOT called by permissioned_pair_address.

Update: Fixed in 00991ce (Uniswap v2 - Core).

Severity: High Risk

Status: Fixed

File(s) affected: uniswap_v2_router/uniswap_v2_router/src/uniswap_v2_router.rs

Description: The function remove_liquidity_cspr() calls transfer_from() in L294, whereas the original Uniswap implementation calls safeTransfer(). Consequently, the original implementation sends tokens from the contract whereas the new implementation sends tokens from the caller.

Recommendation: Use transfer() instead of transfer_from() or explain why the implementations differ.

Update: Fixed in 5a9b158 (Uniswap v2 - Router).

QSP-5 mint_fee() Enables Fee Only When fee_to Is 0x0

Severity: Medium Risk

Status: Fixed

File(s) affected: pair/pair/src/pair.rs

Description: It appears to be an error in implementation of mint_fee(); the fee would always be sent to 0x0.

Recommendation: Reverse the check so that the opposite happens, i.e., no fee if fee_to is 0x0, and fee otherwise.

Update: Fixed in f4e2742 (Uniswap v2 - Core).

QSP-6 pair_for() Does Not Sort The Tokens Before Fetching a Pair

Severity: Medium Risk

Status: Fixed

File(s) affected: uniswap_v2_library/uniswap_v2_library/src/uniswap_v2_library.rs

Description: pair_for() does not sort the tokens before fetching a pair. Consequently, it may contradict the assumptions that Uniswap users may have.

Recommendation: Sort the tokens before returning a pair.

Update: Fixed in adfd626 (Uniswap v2 - Router).

QSP-7 Allowance Double-Spend Exploit

Severity: Low Risk

Status: Fixed

File(s) affected: erc20/erc20/src/erc20.rs, wcspr/wcspr/src/wcspr.rs, pair/pair/src/pair.rs

Description: As it presently is constructed, the contract is vulnerable to the allowance double-spend exploit, as with other ERC20 tokens.

Exploit Scenario:

- 1. Alice allows Bob to transfer N amount of Alice's tokens (N>0) by calling the approve() method on Token smart contract (passing Bob's address and N as method arguments)
- 2. After some time, Alice decides to change from N to M (M>0) the number of Alice's tokens Bob is allowed to transfer, so she calls the approve() method again, this time passing Bob's address and M as method arguments
- 3. Bob notices Alice's second transaction before it was mined and quickly sends another transaction that calls the transferFrom() method to transfer N Alice's tokens somewhere
- 4. If Bob's transaction will be executed before Alice's transaction, then Bob will successfully transfer N Alice's tokens and will gain an ability to transfer another M tokens
- 5. Before Alice notices any irregularities, Bob calls transferFrom() method again, this time to transfer M Alice's tokens.

Recommendation: The exploit (as described above) is mitigated through use of functions that increase/decrease the allowance relative to its current value, such as increaseAllowance() and decreaseAllowance().

Pending community agreement on an ERC standard that would protect against this exploit, we recommend that developers of applications dependent on approve() / transferFrom() should keep in mind that they have to set allowance to 0 first and verify if it was used before setting the new value. Teams who decide to wait for such a standard should make these recommendations to app developers who work with their token contract.

Update: Fixed in 70274b8, 81e5d6e, 97508e1 (Uniswap v2 - Core).

QSP-8 Race Conditions / Front-Running

Severity: Low Risk

Status: Acknowledged

File(s) affected: pair/src/pair.rs

Description: A block is an ordered collection of transactions from all around the network. It's possible for the ordering of these transactions to manipulate the end result of a block. A producer attacker can take advantage of this by generating and moving transactions in a way that benefits themselves.

Specifically, in the mint_fee() function located in pair/src/pair.rs#L657, the treasury_fee is used in calculation for the liquidity, however these variable can also be changed from the set_treasury_fee() function which can cause a race condition and result a miscalculation in the liquidity.

Recommendation: Race condition issues are typically difficult to address and are of low severity. We describe it here mostly for informational purposes.

Severity: Low Risk

Status: Fixed

File(s) affected: uniswap_v2_router/src/uniswap_v2_router.rs, uniswap_v2_core/pair/pair.rs

Description: Some arguments are not checked for validity:

- 1. in the add_liquidity() function located in uniswap_v2_router/src/uniswap_v2_router.rs#L45, the amount_a_desired and amount_b_desired variables are not verified, in fact anyone can inject these parameters with the value 0.
- 2. in the add_liquidity_cspr() function located in uniswap_v2_router/src/uniswap_v2_router.rs#L214, the amount_token is not verified, in fact anyone can inject it with the value 0.
- 3. in the mint_fee() function located in uniswap_v2_core/pair/pair.rs#L658, we are dividing by denominator without verifying its value thus we can divide by 0.

Recommendation: Add the required checks.

Update: Fixed in 6f09359 (Uniswap v2 - Core) and in adfd626 (Uniswap v2 - Router).

QSP-10 set_nonce() Adds an Arbitrary amount To The Nonce

Severity: Informational

Status: Fixed

File(s) affected: erc20/erc20/src/erc20.rs, pair/pair/src/pair.rs

Description: The function set_nonce()may add an arbitrary amount to the nonce. It is unclear why amount is needed and why nonce isn't simply incremented.

Recommendation: Increment the nonce instead of adding an arbitrary value or provide an explanation why the current functionality is needed.

Update: Fixed in 6f09359 (Uniswap v2 - Core).

QSP-11 Functions skim() And sync() Are Re-entrant

Severity: Undetermined

Status: Fixed

File(s) affected: pair/pair/src/pair.rs

Description: Unlike in Uniswap, both functions are re-entrant.

Recommendation: Add a mutex to protect against re-entrancy.

Update: Fixed in d14fd07 (Uniswap v2 - Core).

Adherence to Specification

Assuming that the reference implementations act as specification, the provided implementation deviates from the specification in a few key locations (as indicated in the list of vulnerabilities).

Code Documentation

The code comes with very little inline documentation. We recommend documenting the code.

Adherence to Best Practices

- 1. erc20/utils/contract-utils/src/contract_context.rs#11: magic constant. The meaning of 2 is not immediately clear.
- 2. A lot of code clones, e.g., contract-utils in multiple locations.
- 3. Overall, a lot of boilerplate code and clones. We recommend improving code reusability by using macros and functions.
- 4. flash_swapper/src/flash_swapper.rs 74-88 code clones.

Test Results

Test Suite Results

All tests executed successfully. We reviewed the test suite, and given a number of important issues, we recommend expanding the test suite significantly to ensure that the code works as expected. Furthermore, a good test suite would contain both positive and negative test cases.

```
running 9 tests

test erc20_tests::test_calling_construction ... ok

test erc20_tests::test_erc20_approve ... ok

test erc20_tests::test_erc20_deploy ... ok

test erc20_tests::test_erc20_burn ... ok

test erc20_tests::test_erc20_mint ... ok

test erc20_tests::test_erc20_transfer ... ok

test erc20_tests::test_erc20_transfer_from ... ok

test erc20_tests::test_erc20_transfer_from_too_much ... ok

test erc20_tests::test_erc20_transfer_with_same_sender_and_recipient ... ok
```

```
test result: ok. 9 passed; 0 failed; 0 ignored; 0 measured; 0 filtered out; finished in 11.85s
running 7 tests
test factory_tests::test_calling_construction ... ok
test factory_tests::test_factory_create_pair ... ok
test factory_tests::test_factory_deploy ... ok
test factory_tests::test_factory_set_fee_to ... ok
test factory_tests::test_factory_set_fee_to_setter ... ok
test factory tests::test factory set white list ... ok
test factory tests::test factory set white list with non owner ... ok
test result: ok. 7 passed; 0 failed; 0 ignored; 0 measured; 0 filtered out; finished in 17.62s
running 2 tests
test flash_swapper_tests::test_flash_swapper_deploy ... ok
test flash swapper tests::test calling construction ... ok
test result: ok. 2 passed; 0 failed; 0 ignored; 0 measured; 0 filtered out; finished in 3.33s
running 15 tests
test pair_tests::test_calling_construction ... ok
test pair_tests::test_pair_approve ... ok
test pair_tests::test_pair_deploy ... ok
test pair tests::test pair burn ... ok
test pair_tests::test_pair_initialize ... ok
test pair tests::test pair set treasury fee percent ... ok
test pair_tests::test_pair_mint ... ok
test pair_tests::test_pair_skim ... ok
test pair_tests::test_pair_swap ... ok
test pair_tests::test_pair_sync ... ok
test pair_tests::test_pair_transfer ... ok
test pair_tests::test_pair_transfer_from ... ok
test pair_tests::test_pair_transfer_from_too_much ... ok
test pair_tests::test_pair_transfer_too_much ... ok
test pair_tests::test_pair_transfer_with_same_sender_and_recipient ... ok
test result: ok. 15 passed; 0 failed; 0 ignored; 0 measured; 0 filtered out; finished in 54.62s
running 10 tests
test wcspr_tests::test_calling_construction ... ok
test wcspr_tests::test_wcspr_approve ... ok
test wcspr_tests::test_wcspr_deploy ... ok
test wcspr_tests::test_wcspr_deposit ... ok
test wcspr_tests::test_wcspr_deposit_zero_amount ... ok
test wcspr_tests::test_wcspr_transfer ... ok
test wcspr_tests::test_wcspr_transfer_from ... ok
test wcspr_tests::test_wcspr_transfer_from_too_much ... ok
test wcspr_tests::test_wcspr_transfer_too_much ... ok
test wcspr_tests::test_wcspr_withdraw ... ok
test result: ok. 10 passed; 0 failed; 0 ignored; 0 measured; 0 filtered out; finished in 10.31s
running 7 tests
test uniswap_v2_library_tests::test_library_deploy ... ok
test uniswap_v2_library_tests::quote ... ok
test uniswap v2 library tests::test uniswap get amount in ... ok
test uniswap_v2_library_tests::test_uniswap_get_amount_out ... ok
test uniswap v2 library tests::test uniswap get amounts in ... ok
test uniswap_v2_library_tests::test_uniswap_get_amounts_out ... ok
test uniswap_v2_library_tests::test_uniswap_get_reserves ... ok
test result: ok. 7 passed; 0 failed; 0 ignored; 0 measured; 0 filtered out; finished in 62.44s
running 13 tests
test uniswap_tests::add_liquidity ... ok
test uniswap_tests::add_liquidity_cspr ... ok
test uniswap_tests::remove_liquidity ... ok
test uniswap_tests::remove_liquidity_cspr ... ok
test uniswap_tests::remove_liquidity_with_permit ... ok
test uniswap_tests::remove_liquidity_cspr_with_permit ... ok
test uniswap_tests::swap_exact_cspr_for_tokens ... ok
test uniswap_tests::swap_cspr_for_exact_tokens ... ok
test uniswap_tests::swap_exact_tokens_for_cspr ... ok
test uniswap_tests::swap_exact_tokens_for_tokens ... ok
test uniswap_tests::swap_tokens_for_exact_cspr ... ok
test uniswap_tests::swap_tokens_for_exact_tokens ... ok
test uniswap_tests::test_uniswap_deploy ... ok
test result: ok. 13 passed; 0 failed; 0 ignored; 0 measured; 0 filtered out; finished in 133.25s
```

Appendix

File Signatures

The following are the SHA-256 hashes of the reviewed files. A file with a different SHA-256 hash has been modified, intentionally or otherwise, after the security review. You are cautioned that a different SHA-256 hash could be (but is not necessarily) an indication of a changed condition or potential vulnerability that was not within the scope of the review.

Contracts

```
a5149e928e64e1c60b8d2280e5ef7e385ebe79dbd4d860eb1018250a81de4b55 ./transfer helper.rs
2e9656eef68ef9e5c3ff65c6f7c69787cc174c102b04fcf90c8a3300f5fb6ad5 ./uniswap_v2_router.rs
c290e2bb651bafcac76df9f453b926121199745caef32b257da137c234e9ab0d ./config.rs
7fe7addbc2228d1a6d5f56c310ce9b3a6e4f228363953242345e300d594fd027 ./lib.rs
9694b9ef58037ff7fe57297c15e6a50f220d4955ea8c0bc9fe55fe392c677727 ./data.rs
5eda941ac56416a358948d3672cdae6a28aba56c28e604f51acac5fa4f696fc0 ./uniswap_v2_library.rs
7866c91be8c0e4742b6a11b943c396eec1851a117581a07617880f6f5c82549a ./config.rs
2376ca113557de30a76708f6ca2041431394956d0459d28c6016ffc13c2a3dd2 ./lib.rs
a78dab169d46e8cd6bd9244141fd8bc76a62ece45ba5e937eed1efccb563986e ./data.rs
3dd28bf91238c14407769c8277f4373c9a01790352832e8f3d0c2c6729af6f60 ./wcspr.rs
4feeaec232d3507c7e85cc5773fb214cd1dc9dafeff34b2ee99a8ba590f03309 ./lib.rs
f9cf55a85196c1e2a8149a1443050a9439b3208830c4a7823c1f6215b0f4c9d6 ./data.rs
efc9db18db4c5e92e9435f9cc9c423086b47525a445ff5c26ed87fd479b4b0bd ./lib.rs
86414fd7a8814e4f161185f498b3ac395ee5bf940f69de89fb0691d89ac3065f ./pair.rs
2d28055fcc9918fe23f3ed823b26a8274c905299a312ee2f7309d8cc2b7331a9 ./data.rs
530620e8495b77380947115ee139cd03297535f188867dad1a0849a0b5a80cab ./lib.rs
614e8833fb9854027325bf6ddcda043b75bea98e676d617b54e3441cad9f03f8 ./data.rs
c7a87925d4c1111cf04fbacc84b6ef9547a77832b8cfb0500f7daa3f2a1f5042 ./flash_swapper.rs
bcdba8ffe4c2d2035258f0428ea24df55ad123fccf34e504b0fa9731906cb4c0 ./factory.rs
f1b82bc5fcd9691203a9e25b17b0bba5b292d9c2414c372196086715ddff49d4 ./lib.rs
a2f4d03faf859aa916de5e0b69c5462a018cf60ea3f7615da3593bc405afbb94 ./data.rs
fb93a2da65158adeb70491ef567079783f6ab59523adf4e57cc045d563d753da ./src/lib.rs
42c51dcf980e1fddd42ed29a7c16f4c36d5834d0bd92b32ddd38fe9bb2e71e0b ./src/data.rs
```

Tests

```
ae9c529ada29174c3ce9a186ad82b688ce8f36c2b507decd5eab77453cbccc40 ./build.rs
1bc17fbe996404962648bb4de45ce70b4906e526832449bd4a738e3160cb3d5b ./integration tests.rs
3a62e090dfbd5bb31f262f556fde6f512195703c2f50699edb4756fb413ea73e ./mappings.rs
36175ab23f09a91f47dfd62778864c7f2df26bd4bce1ba62802d59306825a75d ./main.rs
d1e7d7708d4bfb7206038d4db3f0f6cb4b749d1f12215bb2b61776f27d9b53c0 ./uniswap instance.rs
5e5c2e9e3f066d68170b540eeb44cc7e4ae4c16e87e3d27f587883ab4bd5c430 ./lib.rs
e811f3e60b6cf3ea41a540c198601107c83e55a37021a875e0da84b89097e432 ./uniswap tests.rs
0ab56c216f1bdf65320ad303c16a3da7f2d096dba9ce1a95410fc7986b0437ef ./lib.rs
11f329be098cc956197c2adcd143af9788dd4d1d478d43d6489b8c42fb85c19b ./uniswap v2 library instance.rs
f6a3ffd7492c565b6c7b951309dde5a7d74d3e38fe1ae2b213d394aca89467fb ./uniswap_v2_library_tests.rs
66fc76f380067e29f57d23869639cf7074fa6932aa8703fe3581280561816493 ./constants.rs
fccf68a46059fe37b6f168826a7c55a62cd5927eee17d2556b55882f8b3dbf7d ./main.rs
deef9945d03d01e6a9dd7b0c16c836b71a606aa15bde6065449b498e62384add ./utils.rs
4e2eb97a15065e7ca3a01a840b38df05b01ecf1fce6ca893c8d7a1b761143583 ./constants.rs
85de47863357d781fe9882d3eea1a2115c3654a033cc24f43e0d8a680f42c3d0 ./main.rs
deef9945d03d01e6a9dd7b0c16c836b71a606aa15bde6065449b498e62384add ./utils.rs
1ea35de660f6436b3476a89932fc34d579909ca453c5864e3ca37612e1682d7e ./constants.rs
96964f78b23149af6c2cedcc554f58dededa6a8ad3ceebc19eab8bbc9c1c347b ./wcspr_tests.rs
0ef78039a9ba9d18d1c67787dcc3185e57f24345c055c022021d8a5f73e1b9f5 ./lib.rs
455763e181f38b59b97fc0ce9252a831a5cdff5852347ae6c02309f379eb3bf9 ./wcspr_instance.rs
1a64509a720581e4986d42ebec5bb60c459888736b4de2f0a854f7083cd928df ./mappings.rs
b1b5afe87e1237306e2563c45ffa722943aec00d37aea73a29def0aa7e84c950 ./main.rs
1a64509a720581e4986d42ebec5bb60c459888736b4de2f0a854f7083cd928df ./mappings.rs
b1b5afe87e1237306e2563c45ffa722943aec00d37aea73a29def0aa7e84c950 ./main.rs
5be88be35cf46d79a195156ed3d148c381c7f81071b416d4c34a67fc59da1915 ./lib.rs
6cc28f108eab9f414293b58d0e6f67032bd466eb932034b36a9c83ebf171ef8a ./pair_instance.rs
69a95bd93b73d9831b0bf9205dabd87009ec865321ce571c7488a0a949696e29 ./pair_tests.rs
ee7121b3a06ef0f31b8ed231b1eddced36a135c7f1b7802bf0bddcd42a7f7eec ./test.rs
986e393ffeb206a88eec060c1ebd256dfbf85fadb5276066af419a7c48cb19ce ./lib.rs
027d6a14f50b41a81e677731e907c5161189620618066748e51f13f37e12a1c0 ./data.rs
b37eddcdb34db6d0369cd705a88f75f21dc2e9c7183c24a388ac577d646d3d0e ./test_instance.rs
a3c6456f9a39c2b91404b43b3081847ea06aa360df26e07be58ea717e4d5f031 ./flash_swapper_tests.rs
2eb68f1351ebb1e94739b084082559c91794f438c5c42cc2aa9d8a9251e377f9 ./lib.rs
bc7ac0717e6c168248ae1ee736dda2428be128d2e73d302bae45ae33409bfaac ./flash_swapper_instance.rs
20200946ba5e1192598b89f096b4567a10c0356a648333242802862a479528ef ./factory_instance.rs
3e6c8f8592465bcb17a2b1dd42f0aaef18acb479ad662e0e2b7185b6f403fcb4 ./lib.rs
7b87784042ef2a93beb0740c037718e8c9576ca7313ba8ac071a9a6cbdfc6219 ./factory_tests.rs
cc60afa7a35c2a57926666a36c3e8023f294c52ed53f63e2e7fdac92f5df613a ./mappings.rs
a27c3420502f6588f01e24a63b3c0d2b718a30a6c0648f74bccc312359a91dea ./main.rs
cc60afa7a35c2a57926666a36c3e8023f294c52ed53f63e2e7fdac92f5df613a ./mappings.rs
a27c3420502f6588f01e24a63b3c0d2b718a30a6c0648f74bccc312359a91dea ./main.rs
f3b918e51d57e362531b9e3cf16ba8d47b76d16e98c3b06cc3ec40c667ec439a ./src/lib.rs
7624764193e906681d3abffac75c3ae12bc6896877d98e3f54ebb97b5312bb95 ./src/erc20_tests.rs
ccb19dcea87585afb78fb41ce04bad5958a3d047845539fd93528a58c6f64420 ./src/erc20_instance.rs
```

Changelog

- 2021-11-05 Initial report
- 2021-12-07 Reaudit report

About Quantstamp

Quantstamp is a Y Combinator-backed company that helps to secure blockchain platforms at scale using computer-aided reasoning tools, with a mission to help boost the adoption of this exponentially growing technology.

With over 1000 Google scholar citations and numerous published papers, Quantstamp's team has decades of combined experience in formal verification, static analysis, and software verification. Quantstamp has also developed a protocol to help smart contract developers and projects worldwide to perform cost-effective smart contract security scans.

To date, Quantstamp has protected \$5B in digital asset risk from hackers and assisted dozens of blockchain projects globally through its white glove security assessment services. As an evangelist of the blockchain ecosystem, Quantstamp assists core infrastructure projects and leading community initiatives such as the Ethereum Community Fund to expedite the adoption of blockchain technology.

Quantstamp's collaborations with leading academic institutions such as the National University of Singapore and MIT (Massachusetts Institute of Technology) reflect our commitment to research, development, and enabling world-class blockchain security.

Timeliness of content

The content contained in the report is current as of the date appearing on the report and is subject to change without notice, unless indicated otherwise by Quantstamp; however, Quantstamp does not guarantee or warrant the accuracy, timeliness, or completeness of any report you access using the internet or other means, and assumes no obligation to update any information following publication.

Notice of confidentiality

This report, including the content, data, and underlying methodologies, are subject to the confidentiality and feedback provisions in your agreement with Quantstamp. These materials are not to be disclosed, extracted, copied, or distributed except to the extent expressly authorized by Quantstamp.

Links to other websites

You may, through hypertext or other computer links, gain access to web sites operated by persons other than Quantstamp, Inc. (Quantstamp). Such hyperlinks are provided for your reference and convenience only, and are the exclusive responsibility of such web sites' owners. You agree that Quantstamp are not responsible for the content or operation of such web sites, and that Quantstamp shall have no liability to you or any other person or entity for the use of third-party web sites. Except as described below, a hyperlink from this web site to another web site does not imply or mean that Quantstamp endorses the content on that web site or the operator or operations of that site. You are solely responsible for determining the extent to which you may use any content at any other web sites to which you link from the report. Quantstamp assumes no responsibility for the use of third-party software on the website and shall have no liability whatsoever to any person or entity for the accuracy or completeness of any outcome generated by such software.

Disclaimer

This report is based on the scope of materials and documentation provided for a limited review at the time provided. Results may not be complete nor inclusive of all vulnerabilities. The review and this report are provided on an as-is, where-is, and as-available basis. You agree that your access and/or use, including but not limited to any associated services, products, protocols, platforms, content, and materials, will be at your sole risk. Blockchain technology remains under development and is subject to unknown risks and flaws. The review does not extend to the compiler layer, or any other areas beyond the programming language, or other programming aspects that could present security risks. A report does not indicate the endorsement of any particular project or team, nor guarantee its security. No third party should rely on the reports in any way, including for the purpose of making any decisions to buy or sell a product, service or any other asset. To the fullest extent permitted by law, we disclaim all warranties, expressed or implied, in connection with this report, its content, and the related services and products and your use thereof, including, without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement. We do not warrant, endorse, guarantee, or assume responsibility for any product or service advertised or offered by a third party through the product, any open source or third-party software, code, libraries, materials, or information linked to, called by, referenced by or accessible through the report, its content, and the related services and products, any hyperlinked websites, any websites or mobile applications appearing on any advertising, and we will not be a party to or in any way be responsible for monitoring any transaction between you and any third-party providers of products or services. As with the purchase or use of a product or service through any medium or in any environment, you should use your best judgment and exercise caution

