



SMART CONTRACT AUDIT REPORT

for

Plena



Prepared By: Xiaomi Huang

PeckShield
July 13, 2023

Document Properties

Client	Plena
Title	Smart Contract Audit Report
Target	Plena
Version	1.0
Author	Patrick Lou
Auditors	Xuxian Jiang, Patrick Lou
Reviewed by	Xiaomi Huang
Approved by	Xuxian Jiang
Classification	Public

Version Info

Version	Date	Author(s)	Description
1.0	July 13, 2023	Patrick Lou	Final Release
1.0-rc	June 27, 2023	Patrick Lou	Release Candidate

Contact

For more information about this document and its contents, please contact PeckShield Inc.

Name	Xiaomi Huang
Phone	+86 183 5897 7782
Email	contact@peckshield.com

Contents

1	Introduction	4
1.1	About Plena	4
1.2	About PeckShield	5
1.3	Methodology	6
1.4	Disclaimer	9
2	Findings	10
2.1	Summary	10
2.2	Key Findings	11
3	Detailed Results	12
3.1	Accommodation Of Non-ERC20-Compliant Tokens	12
3.2	Trust Issue of Admin Keys	14
4	Conclusion	15
	References	16

1 | Introduction

Given the opportunity to review the design document and related smart contract source code of the Plena protocol, we outline in the report our systematic approach to evaluate potential security issues in the smart contract implementation, expose possible semantic inconsistencies between smart contract code and design document, and provide additional suggestions or recommendations for improvement. Our results show that the given version of smart contracts can be further improved due to the presence of several issues related to either security or performance. This document outlines our audit results.

1.1 About Plena

The Plena Finance protocol's Portfolio feature allows users to create multiple portfolios with different tokens. Users can select the tokens they want to invest in and begin their investment journey with any token of their choice. With a single tap, all the chosen tokens are bought simultaneously, streamlining the investment process. This feature offers flexibility and convenience for users to diversify their holdings and manage their investments efficiently. The basic information of the audited protocol is as follows:

Table 1.1: Basic Information of Plena

Item	Description
Target	Plena
Type	EVM Smart Contract
Language	Solidity
Audit Method	Whitebox
Latest Audit Report	July 13, 2023

In the following, we show the Git repository of reviewed files and the commit hash value used in this audit.

- <https://github.com/PlenaFinance/plenaPortfolioV3> (f73082d)

And this is the commit ID after all fixes for the issues found in the audit have been checked in:

- <https://github.com/PlenaFinance/plenaPortfolioV3> (54b9e33)

1.2 About PeckShield

PeckShield Inc. [7] is a leading blockchain security company with the goal of elevating the security, privacy, and usability of current blockchain ecosystems by offering top-notch, industry-leading services and products (including the service of smart contract auditing). We are reachable at Telegram (<https://t.me/peckshield>), Twitter (<http://twitter.com/peckshield>), or Email (contact@peckshield.com).

Table 1.2: Vulnerability Severity Classification

Impact	High	Critical	High	Medium
	Medium	High	Medium	Low
	Low	Medium	Low	Low
		High	Medium	Low
		Likelihood		

1.3 Methodology

To standardize the evaluation, we define the following terminology based on OWASP Risk Rating Methodology [6]:

- Likelihood represents how likely a particular vulnerability is to be uncovered and exploited in the wild;
- Impact measures the technical loss and business damage of a successful attack;
- Severity demonstrates the overall criticality of the risk.

Likelihood and impact are categorized into three ratings: *H*, *M* and *L*, i.e., *high*, *medium* and *low* respectively. Severity is determined by likelihood and impact and can be classified into four categories accordingly, i.e., *Critical*, *High*, *Medium*, *Low* shown in Table 1.2.

To evaluate the risk, we go through a list of check items and each would be labeled with a severity category. For one check item, if our tool or analysis does not identify any issue, the contract is considered safe regarding the check item. For any discovered issue, we might further deploy contracts on our private testnet and run tests to confirm the findings. If necessary, we would additionally build a PoC to demonstrate the possibility of exploitation. The concrete list of check items is shown in Table 1.3.

In particular, we perform the audit according to the following procedure:

- Basic Coding Bugs: We first statically analyze given smart contracts with our proprietary static code analyzer for known coding bugs, and then manually verify (reject or confirm) all the issues found by our tool.
- Semantic Consistency Checks: We then manually check the logic of implemented smart contracts and compare with the description in the white paper.
- Advanced DeFi Scrutiny: We further review business logics, examine system operations, and place DeFi-related aspects under scrutiny to uncover possible pitfalls and/or bugs.
- Additional Recommendations: We also provide additional suggestions regarding the coding and development of smart contracts from the perspective of proven programming practices.

To better describe each issue we identified, we categorize the findings with Common Weakness Enumeration (CWE-699) [5], which is a community-developed list of software weakness types to better delineate and organize weaknesses around concepts frequently encountered in software development. Though some categories used in CWE-699 may not be relevant in smart contracts, we use the CWE categories in Table 1.4 to classify our findings.

Table 1.3: The Full List of Check Items

Category	Check Item
Basic Coding Bugs	Constructor Mismatch
	Ownership Takeover
	Redundant Fallback Function
	Overflows & Underflows
	Reentrancy
	Money-Giving Bug
	Blackhole
	Unauthorized Self-Destruct
	Revert DoS
	Unchecked External Call
	Gasless Send
	Send Instead Of Transfer
	Costly Loop
	(Unsafe) Use Of Untrusted Libraries
	(Unsafe) Use Of Predictable Variables
	Transaction Ordering Dependence
	Deprecated Uses
Semantic Consistency Checks	Semantic Consistency Checks
Advanced DeFi Scrutiny	Business Logics Review
	Functionality Checks
	Authentication Management
	Access Control & Authorization
	Oracle Security
	Digital Asset Escrow
	Kill-Switch Mechanism
	Operation Trails & Event Generation
	ERC20 Idiosyncrasies Handling
	Frontend-Contract Integration
	Deployment Consistency
	Holistic Risk Management
Additional Recommendations	Avoiding Use of Variadic Byte Array
	Using Fixed Compiler Version
	Making Visibility Level Explicit
	Making Type Inference Explicit
	Adhering To Function Declaration Strictly
	Following Other Best Practices

Table 1.4: Common Weakness Enumeration (CWE) Classifications Used in This Audit

Category	Summary
Configuration	Weaknesses in this category are typically introduced during the configuration of the software.
Data Processing Issues	Weaknesses in this category are typically found in functionality that processes data.
Numeric Errors	Weaknesses in this category are related to improper calculation or conversion of numbers.
Security Features	Weaknesses in this category are concerned with topics like authentication, access control, confidentiality, cryptography, and privilege management. (Software security is not security software.)
Time and State	Weaknesses in this category are related to the improper management of time and state in an environment that supports simultaneous or near-simultaneous computation by multiple systems, processes, or threads.
Error Conditions, Return Values, Status Codes	Weaknesses in this category include weaknesses that occur if a function does not generate the correct return/status code, or if the application does not handle all possible return/status codes that could be generated by a function.
Resource Management	Weaknesses in this category are related to improper management of system resources.
Behavioral Issues	Weaknesses in this category are related to unexpected behaviors from code that an application uses.
Business Logics	Weaknesses in this category identify some of the underlying problems that commonly allow attackers to manipulate the business logic of an application. Errors in business logic can be devastating to an entire application.
Initialization and Cleanup	Weaknesses in this category occur in behaviors that are used for initialization and breakdown.
Arguments and Parameters	Weaknesses in this category are related to improper use of arguments or parameters within function calls.
Expression Issues	Weaknesses in this category are related to incorrectly written expressions within code.
Coding Practices	Weaknesses in this category are related to coding practices that are deemed unsafe and increase the chances that an exploitable vulnerability will be present in the application. They may not directly introduce a vulnerability, but indicate the product has not been carefully developed or maintained.

1.4 Disclaimer



Note that this security audit is not designed to replace functional tests required before any software release, and does not give any warranties on finding all possible security issues of the given smart contract(s) or blockchain software, i.e., the evaluation result does not guarantee the nonexistence of any further findings of security issues. As one audit-based assessment cannot be considered comprehensive, we always recommend proceeding with several independent audits and a public bug bounty program to ensure the security of smart contract(s). Last but not least, this security audit should not be used as investment advice.



2 | Findings

2.1 Summary

Here is a summary of our findings after analyzing the `plena` protocol. During the first phase of our audit, we study the smart contract source code and run our in-house static code analyzer through the codebase. The purpose here is to statically identify known coding bugs, and then manually verify (reject or confirm) issues reported by our tool. We further manually review business logic, examine system operations, and place DeFi-related aspects under scrutiny to uncover possible pitfalls and/or bugs.

Severity	# of Findings	
Critical	0	
High	0	
Medium	1	
Low	1	
Informational	0	
Total	2	

We have so far identified a list of potential issues: some of them involve subtle corner cases that might not be previously thought of, while others refer to unusual interactions among multiple contracts. For each uncovered issue, we have therefore developed test cases for reasoning, reproduction, and/or verification. After further analysis and internal discussion, we determined a few issues of varying severities that need to be brought up and paid more attention to, which are categorized in the above table. More information can be found in the next subsection, and the detailed discussions of each of them are in [Section 3](#).

2.2 Key Findings

Overall, these smart contracts are well-designed and engineered, though the implementation can be improved by resolving the identified issues (shown in Table 2.1), including 1 medium-severity vulnerability, and 1 low-severity vulnerability.

Table 2.1: Key Plena Audit Findings

ID	Severity	Title	Category	Status
PVE-001	Low	Accommodation Of Non-ERC20-Compliant Tokens	Coding Practices	Fixed
PVE-002	Medium	Trust Issue of Admin Keys	Security Features	Confirmed

Beside the identified issues, we emphasize that for any user-facing applications and services, it is always important to develop necessary risk-control mechanisms and make contingency plans, which may need to be exercised before the mainnet deployment. The risk-control mechanisms should kick in at the very moment when the contracts are being deployed on mainnet. Please refer to Section 3 for details.



3 | Detailed Results

3.1 Accommodation Of Non-ERC20-Compliant Tokens

- ID: PVE-001
- Severity: Low
- Likelihood: Low
- Impact: Low
- Target: FolioFactory
- Category: Coding Practices [4]
- CWE subcategory: CWE-1109 [1]

Description

Though there is a standardized ERC-20 specification, many token contracts may not strictly follow the specification or have additional functionalities beyond the specification. In this section, we examine the `transfer()` routine and possible idiosyncrasies from current widely-used token contracts.

In particular, we use the popular token, i.e., ZRX, as our example. We show the related code snippet below. On its entry of `transfer()`, there is a check, i.e., `if (balances[msg.sender] >= _value && balances[_to] + _value >= balances[_to])`. If the check fails, it returns `false`. However, the transaction still proceeds successfully without being reverted. This is not compliant with the ERC20 standard and may cause issues if not handled properly. Specifically, the ERC20 standard specifies the following: “Transfers `_value` amount of tokens to address `_to`, and **MUST** fire the Transfer event. The function **SHOULD** throw if the message caller’s account balance does not have enough tokens to spend.”

```

64     function transfer(address _to, uint _value) returns (bool) {
65         //Default assumes totalSupply can't be over max (2^256 - 1).
66         if (balances[msg.sender] >= _value && balances[_to] + _value >= balances[_to]) {
67             balances[msg.sender] -= _value;
68             balances[_to] += _value;
69             Transfer(msg.sender, _to, _value);
70             return true;
71         } else { return false; }
72     }
73     function transferFrom(address _from, address _to, uint _value) returns (bool) {

```

```

74     if (balances[_from] >= _value && allowed[_from][msg.sender] >= _value &&
        balances[_to] + _value >= balances[_to]) {
75         balances[_to] += _value;
76         balances[_from] -= _value;
77         allowed[_from][msg.sender] -= _value;
78         Transfer(_from, _to, _value);
79         return true;
80     } else { return false; }
81 }

```

Listing 3.1: ZRX.sol

Because of that, a normal call to `transfer()` is suggested to use the safe version, i.e., `safeTransfer()`. In essence, it is a wrapper around ERC20 operations that may either throw on failure or return false without reverts. Moreover, the safe version also supports tokens that return no value (and instead revert or throw on failure). Note that non-reverting calls are assumed to be successful.

In the following, we show the `FolioFactory::withdraw()` routine. The unsafe version of `IERC20(erc20).transfer(recipient, amount)`; (line 124) may return false on failure while not revert. We may intend to replace the `transferFrom()` with `safeTransferFrom()`.

```

118     function withdraw(
119         address erc20,
120         address recipient,
121         uint256 amount
122     ) external onlyOwner {
123         require(erc20 != address(0) && recipient != address(0), "ZERO ADDRESS");
124         IERC20(erc20).transfer(recipient, amount);
125     }

```

Listing 3.2: FolioFactory::withdraw()

Recommendation Accommodate the above-mentioned idiosyncrasy with safe-version implementation of ERC20-related `transfer()`.

Status The issue has been fixed by this commit: 54b9e33.

3.2 Trust Issue of Admin Keys

- ID: PVE-002
- Severity: Medium
- Likelihood: Medium
- Impact: Medium
- Target: FolioFactory
- Category: Security Features [3]
- CWE subcategory: CWE-287 [2]

Description

In the FolioFactory smart contract, there is a privileged `owner` account that plays a critical role in governing and regulating the protocol-wide operations (e.g., approve a module for use in the portfolio, withdraw ERC20 tokens). In the following, we show the representative functions potentially affected by the privilege of the `owner` account.

```

78     function approveModule(address _module) external onlyOwner {
79         _approvedModules[_module] = true;
80     }
81     ...
82     function withdraw(
83         address erc20,
84         address recipient,
85         uint256 amount
86     ) external onlyOwner {
87         require(erc20 != address(0) && recipient != address(0), "ZERO ADDRESS");
88         IERC20(erc20).transfer(recipient, amount);
89     }

```

Listing 3.3: Example Privileged Operations in FolioFactory

We emphasize that the privilege assignment may be necessary and consistent with the protocol design. However, it is worrisome if the `owner` is not governed by a DAO-like structure. Note that a compromised account would allow the attacker to modify a number of sensitive system parameters, which directly undermines the assumption of the protocol design.

Recommendation Promptly transfer the privileged account to the intended DAO-like governance contract. All changed to privileged operations may need to be mediated with necessary timelocks. Eventually, activate the normal on-chain community-based governance life-cycle and ensure the intended trustless nature and high-quality distributed governance.

Status The issue has been confirmed by the team.

4 | Conclusion

In this audit, we have analyzed the design and implementation of the `Plena` protocol which allows users to create multiple portfolios with different tokens. Users can select the tokens they want to invest in and begin their investment journey with any token of their choice. The current code base is well structured and neatly organized. Those identified issues are promptly confirmed and addressed.

Meanwhile, we need to emphasize that smart contracts as a whole are still in an early, but exciting stage of development. To improve this report, we greatly appreciate any constructive feedbacks or suggestions, on our methodology, audit findings, or potential gaps in scope/coverage.



References

- [1] MITRE. CWE-1126: Declaration of Variable with Unnecessarily Wide Scope. <https://cwe.mitre.org/data/definitions/1126.html>.
- [2] MITRE. CWE-287: Improper Authentication. <https://cwe.mitre.org/data/definitions/287.html>.
- [3] MITRE. CWE CATEGORY: 7PK - Security Features. <https://cwe.mitre.org/data/definitions/254.html>.
- [4] MITRE. CWE CATEGORY: Bad Coding Practices. <https://cwe.mitre.org/data/definitions/1006.html>.
- [5] MITRE. CWE VIEW: Development Concepts. <https://cwe.mitre.org/data/definitions/699.html>.
- [6] OWASP. Risk Rating Methodology. https://www.owasp.org/index.php/OWASP_Risk_Rating_Methodology.
- [7] PeckShield. PeckShield Inc. <https://www.peckshield.com>.