



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. B6

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839905.77
N 816498.75

DATE from 3/5/96 to 4/5/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.51 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	PX		100					PX		0.00			Concrete with red brick fragments and steel fragments. (FILL)
	PX 1.30m		92					HX		0.70			
	HX		86					T2-101	2.51	1.30			
2										2.00			Wash Boring. (No Recovery)
3										3.00			
4										4.00			
5										5.00			
6										6.00			
7										7.00			
8	HX 8.00m									8.00			
	NX									9.00			
9										10.00			
10										10.00			

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- SPT LINER SAMPLE
- U76 UNDISTURBED SAMPLE
- U100 UNDISTURBED SAMPLE
- MAZIER SAMPLE (70mm)
- PISTON SAMPLE
- WATER SAMPLE
- PIEZOMETER TIP
- STANDPIPE
- STANDARD PENETRATION TEST
- PERMEABILITY TEST
- IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 06/05/96

APPROVED C.LUN

DATE 07/05/96

REMARKS
Hole termination depth at 26.35m



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. B6

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839905.77

DATE from 3/5/96 to 4/5/96

N 816498.75

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.51 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11										11.00			Wash Boring. (No Recovery)
12										12.00			
13										13.00			
14										14.00			
15										15.00			
16										16.00			Moderately weak to moderately strong, brownish pink spotted black and white, moderately decomposed medium to coarse grained GRANITE with widely to medium spaced and occasionally closely spaced, very narrow to extremely narrow, rough planar, limonite and manganese
17										17.00			
18										18.00			
19			100	100	100	0.0		T-74	-13.79	18.30	+	III	
20			0	0	0	NR		T-74	-14.28	18.79	+	IV	
21			92	92	72	8.0		T-74	-14.79	19.30	+	III	
22										20.00	+		

• SMALL DISTURBED SAMPLE	Δ WATER SAMPLE
▬ LARGE DISTURBED SAMPLE	▲ PIEZOMETER TIP
▨ SPT LINER SAMPLE	□ STANDPIPE
▩ U76 UNDISTURBED SAMPLE	┆ STANDARD PENETRATION TEST
▩ U100 UNDISTURBED SAMPLE	┆ PERMEABILITY TEST
▩ MAZIER SAMPLE (70mm)	┆ IN-SITU VANE SHEAR TEST
▩ PISTON SAMPLE	

LOGGED FRANK CHAN

DATE 06/05/96

APPROVED C.LUN

DATE 07/05/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. B6

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839905.77

DATE from 3/5/96 to 4/5/96

N 816498.75

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.51 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21			92	92	72	8.0		↑ T-76	-15.69	20.20	+	III	stained, kaolin and chlorite coated joints, dipping 10°-20°, 30°-40°, 55°-70° and occasionally vertical joints. Weak to moderately weak, brownish pink spotted black and white, highly to moderately decomposed medium to coarse grained GRANITE at 20.20m to 20.70m. No Recovery at 18.79m to 19.30m and 20.70m to 20.82m.
						16.0		↓ T-76	-16.19	20.70	+	IV/III	
						NR		↓ T-76	-16.31	20.82	+	IV	
						20.0		↓ T-76			+	III	
22			100	100	86	2.2		↓ T-76			+		
						9.7		↓ T-76		22.06	+		
23			100	100	97	1.6		↓ T-76			+		
24						7.4		↓ T-76		23.61	+		
			100	100	97	1.2		↓ T-76			+		
25								↓ T-76		24.92	+		
26			100	100	94	5.6		↓ T-76			+		
								↓ T-76	-21.84	26.35	+		
27													End of hole at 26.35m.
28													
29													
30													

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- Δ WATER SAMPLE
- ▮ PIEZOMETER TIP
- Δ STANDPIPE
- ▮ STANDARD PENETRATION TEST
- ▮ PERMEABILITY TEST
- ▮ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 06/05/96

APPROVED C.LUN

DATE 07/05/96

REMARKS