



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. P64

SHEET 1 of 3

CONTRACT

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. D-17

E 839928.08
N 816490.56

DATE from 17/7/96 to 18/7/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.54 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1 17/07/96	PX							INSPECTION PIT					0.00-2.00m: wash boring
2									2.54	2.00			
3	PX 3.00m HX		60					PX	1.54	3.00			Rounded to subrounded COBBLES and fine to coarse GRAVEL. No recovery assumed, finer material washed out. (FILL)
4													3.00-11.70m: wash boring
5													
6													
7													
8													
9													
10													

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- SPT LINER SAMPLE
- U76 UNDISTURBED SAMPLE
- U100 UNDISTURBED SAMPLE
- MAZIER SAMPLE (70mm)
- PISTON SAMPLE
- WATER SAMPLE
- PIEZOMETER TIP
- STANDPIPE
- STANDARD PENETRATION TEST
- PERMEABILITY TEST
- IN-SITU VANE SHEAR TEST

LOGGED BENNY WONG

DATE 05/08/96

APPROVED C. LUN

DATE 06/08/96

REMARKS

Hole termination depth at 24.98m.
Inspection pit 0.00m to 2.00m.



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. P64

SHEET 2 of 3

CONTRACT

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. D-17

E 839928.08

DATE from 17/7/96 to 18/7/96

N 816490.56

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.54 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11													
12			40					T2-101	-7.16	11.70	+	IV/III	Moderately strong to moderately weak, brownish grey, spotted yellow, moderately to highly decomposed medium grained GRANITE with closely spaced, narrow to very narrow, rough undulating, limonite and stained joint, dipping 15° to 35°.
13									-7.66	12.20	+		12.20-16.00m: wash boring
14													
15													
16	HX 16.00m NX								-11.46	16.00	+	III	Moderately strong, pinkish grey, spotted black and white, moderately decomposed medium grained GRANITE with closely spaced, narrow to very narrow, rough undulating, limonite and manganese stained joints, dipping 5° to 25°.
17			100	98	72	10.5		TNW	-12.99	17.53	+		17.53-17.87m: wash boring
18	NX 17.87m								-13.33	17.87	+	III/II	Strong to moderately strong, pinkish grey, spotted black and white, slightly to moderately decomposed medium grained GRANITE with closely to medium spaced, very narrow, rough undulating, limonite and manganese stained joints, dipping 5° to 15°.
19			100	100	63	8.3		TNW	-14.66	19.20	+	II	Strong, pinkish grey, spotted black and white, slightly decomposed
20			100	100	98			TNW			+		

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- SPT LINER SAMPLE
- U76 UNDISTURBED SAMPLE
- U100 UNDISTURBED SAMPLE
- MAZIER SAMPLE (70mm)
- PISTON SAMPLE
- WATER SAMPLE
- PIEZOMETER TIP
- STANDPIPE
- STANDARD PENETRATION TEST
- PERMEABILITY TEST
- IN-SITU VANE SHEAR TEST

LOGGED BENNY WONG

DATE 05/08/96

APPROVED C. LUN

DATE 06/08/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. P64

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. D-17

E 839928.08

N 816490.56

DATE from 17/7/96 to 18/7/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.54 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21			100	97	97			TNW		20.09	+		medium grained GRANITE with closely to medium spaced, extremely narrow, rough undulating, clean joints, dipping 5° to 10°. 22.00-23.53m: moderately strong to strong, moderately to slightly decomposed zone.
			100	100	100			TNW		20.70	+		
								TNW		21.50	+		
22			100	100	95	4.0		TNW	-17.46	22.00	+	III/II	
23								TNW		23.03	+		
			100	100	85			TNW	-18.99	23.53	+	II	
24								TNW		24.13	+		End of hole at 24.98m.
			100	100	100			TNW		24.98	+		
25													
26													
27													
28													
29													
30													

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- SPT LINER SAMPLE
- U76 UNDISTURBED SAMPLE
- U100 UNDISTURBED SAMPLE
- MAZIER SAMPLE (70mm)
- PISTON SAMPLE
- WATER SAMPLE
- PIEZOMETER TIP
- STANDPIPE
- STANDARD PENETRATION TEST
- PERMEABILITY TEST
- IN-SITU VANE SHEAR TEST

LOGGED BENNY WONG

DATE 05/08/96

APPROVED C. LUN

DATE 06/08/96

REMARKS