



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. C5

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. CMC-57

E 839916.63
N 816512.00

DATE from 30/1/96 to 3/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.44 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	PX								4.24	0.00			Concrete Slab.
										0.20			
										0.30			
2	PX 1.50m NX		100					T2 -101		1.20			Concrete with Cobbles and Gravels of moderately decomposed granite with some steel bars and steel fragment. (FILL)
			100					T2 -101		2.00			
			100					T2 -101		2.24			
								T2 -101	1.94	2.50			
3													Wash boring. (No recovery)
4													
5													
6													
7													
8													
9													
10													

- SMALL DISTURBED SAMPLE
- ▬ LARGE DISTURBED SAMPLE
- ▬ SPT LINER SAMPLE
- ▬ U76 UNDISTURBED SAMPLE
- ▬ U100 UNDISTURBED SAMPLE
- ▬ MAZIER SAMPLE (70mm)
- ▬ PISTON SAMPLE
- △ WATER SAMPLE
- ▲ PIEZOMETER TIP
- STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ┃ PERMEABILITY TEST
- ∇ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 05/02/96

APPROVED C.LUN

DATE 06/02/96

REMARKS

Hole termination depth at 28.07m.
Inspection Pit from 0.00m to 0.30m.



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. C5

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. CMC-57

E 839916.63
N 816512.00

DATE from 30/1/96 to 3/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.44 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
31/01													AS SHEET 1 OF 3.
11													
12													
13													
14													
15													
01/02/96													
16													
	NX	16.45m							-12.01	16.45			
17			100	100	90	3.0		T-74		17.45		III/II	Strong, pinkish grey spotted black and white, slightly decomposed medium to coarse grained GRANITE with widely to medium spaced, extremely narrow, rough planar, limonite, manganese stained, kaolin coated joints, dipping 10°-20°.
18			100	100	100	1.7		T-74		17.81			16.45m-19.01m: moderately strong to strong, pinkish grey spotted black and white, moderately to slightly decomposed medium to coarse grained GRANITE.
19			100	100	96			T-74	-14.57	19.01		II	
20													

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- △ WATER SAMPLE
- ▲ PIEZOMETER TIP
- ▮ STANDPIPE
- ┆ STANDARD PENETRATION TEST
- ┆ PERMEABILITY TEST
- ∨ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 05/02/96

APPROVED C.LUN

DATE 06/02/96

REMARKS

		BACHY SOLETANCHE GROUP SOIL & FOUNDATIONS SPECIALISTS		DRILLHOLE RECORD		HOLE NO. C5							
				CONTRACT		SHEET 3 of 3							
PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY													
METHOD ROTARY				CO-ORDINATES E 839916.63 N 816512.00		W.O. W-518							
MACHINE & No. CMC-57						DATE from 30/1/96 to 3/2/96							
FLUSHING MEDIUM WATER				ORIENTATION Vertical		GROUND-LEVEL 4.44 mPD							
Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
01/02			100	100	96	1.7		T-76		20.35	+	II	AS SHEET 2 OF 3.
21			100	100	100	2.2		T-76		20.43	+		
22			100	100	100			T-76		21.78	+		
23			100	100	100			T-76		22.45	+		
24			100	100	100	0.9		T-76		22.66	+		
25			100	100	100			T-76		23.07	+		
26			100	100	100			T-76		23.81	+		
27			100	100	100	1.5		T-76		24.81	+		
28			100	100	100			T-76		25.11	+		
29			100	100	100			T-76		26.41	+		
30			100	100	100	0.0		T-76		26.81	+		
31			100	100	100			T-76		27.44	+		
32			100	100	100			T-76		28.07	+		
End of hole at 28.07m.													
▲ SMALL DISTURBED SAMPLE ■ LARGE DISTURBED SAMPLE ▨ SPT LINER SAMPLE ▩ U76 UNDISTURBED SAMPLE ▩ U100 UNDISTURBED SAMPLE ▩ MAZIER SAMPLE (70mm) ▩ PISTON SAMPLE ▲ WATER SAMPLE ▲ PIEZOMETER TIP □ STANDPIPE ↓ STANDARD PENETRATION TEST ⊥ PERMEABILITY TEST ∇ IN-SITU VANE SHEAR TEST LOGGED <u>FRANK CHAN</u> DATE <u>05/02/96</u> APPROVED <u>C.LUN</u> DATE <u>06/02/96</u>													
REMARKS													